```
No.      Time            Source                Destination           Protocol Length Info
   6786 3551.451519122  10.0.2.15             8.8.8.8               ICMP     61     Echo (ping) request  id=0x1200, seq=0/0,
ttl=64 (reply in 6787)
Frame 6786: 61 bytes on wire (488 bits), 61 bytes captured (488 bits) on interface enp0s3, id 0
    Interface id: 0 (enp0s3)
    Encapsulation type: Ethernet (1)
    Arrival Time: Jan 18, 2021 22:51:42.176431057 IST
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1611003102.176431057 seconds
    [Time delta from previous captured frame: 7.626996428 seconds]
    [Time delta from previous displayed frame: 0.000000000 seconds]
    [Time since reference or first frame: 3551.451519122 seconds]
    Frame Number: 6786
    Frame Length: 61 bytes (488 bits)
    Capture Length: 61 bytes (488 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:icmp:data]
    [Coloring Rule Name: ICMP]
    [Coloring Rule String: icmp || icmpv6]
Ethernet II, Src: PcsCompu_ea:50:a1 (08:00:27:ea:50:a1), Dst: RealtekU_12:35:02 (52:54:00:12:35:02)
    Destination: RealtekU_12:35:02 (52:54:00:12:35:02)
        Address: RealtekU_12:35:02 (52:54:00:12:35:02)
        .... ..1. .... .... .... .... = LG bit: Locally administered address (this is NOT the factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Source: PcsCompu_ea:50:a1 (08:00:27:ea:50:a1)
        Address: PcsCompu_ea:50:a1 (08:00:27:ea:50:a1)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 10.0.2.15, Dst: 8.8.8.8
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
    Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
        0000 00.. = Differentiated Services Codepoint: Default (0)
        .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
    Total Length: 47
    Identification: 0xf132 (61746)
    Flags: 0x4000, Don't fragment
        0... .... .... .... = Reserved bit: Not set
        .1.. .... .... .... = Don't fragment: Set
        ..0. .... .... .... = More fragments: Not set
    Fragment offset: 0
    Time to live: 64
    Protocol: ICMP (1)
    Header checksum: 0x2d7d [validation disabled]
    [Header checksum status: Unverified]
    Source: 10.0.2.15
    Destination: 8.8.8.8
Internet Control Message Protocol
    Type: 8 (Echo (ping) request)
    Code: 0
    Checksum: 0xae36 [correct]
    [Checksum Status: Good]
    Identifier (BE): 4608 (0x1200)
    Identifier (LE): 18 (0x0012)
    Sequence number (BE): 0 (0x0000)
    Sequence number (LE): 0 (0x0000)
    [Response frame: 6787]
    Data (19 bytes)
0000  54 68 69 73 20 69 73 20 74 68 65 20 70 69 6e 67   This is the ping
0010  2e 0a 00                                          ...
        Data: 54686973206973207468652070696e672e0a00
        [Length: 19]
No.      Time            Source                Destination           Protocol Length Info
   6787 3551.543987941  8.8.8.8               10.0.2.15             ICMP     61     Echo (ping) reply    id=0x1200, seq=0/0,
ttl=116 (request in 6786)
Frame 6787: 61 bytes on wire (488 bits), 61 bytes captured (488 bits) on interface enp0s3, id 0
    Interface id: 0 (enp0s3)
    Encapsulation type: Ethernet (1)
    Arrival Time: Jan 18, 2021 22:51:42.268899876 IST
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1611003102.268899876 seconds
    [Time delta from previous captured frame: 0.092468819 seconds]
    [Time delta from previous displayed frame: 0.092468819 seconds]
    [Time since reference or first frame: 3551.543987941 seconds]
    Frame Number: 6787
    Frame Length: 61 bytes (488 bits)
    Capture Length: 61 bytes (488 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:icmp:data]
    [Coloring Rule Name: ICMP]
    [Coloring Rule String: icmp || icmpv6]
Ethernet II, Src: RealtekU_12:35:02 (52:54:00:12:35:02), Dst: PcsCompu_ea:50:a1 (08:00:27:ea:50:a1)
    Destination: PcsCompu_ea:50:a1 (08:00:27:ea:50:a1)
        Address: PcsCompu_ea:50:a1 (08:00:27:ea:50:a1)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
```

```
        Source: RealtekU_12:35:02 (52:54:00:12:35:02)
            Address: RealtekU_12:35:02 (52:54:00:12:35:02)
            .... ..1. .... .... .... .... = LG bit: Locally administered address (this is NOT the factory default)
            .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
        Type: IPv4 (0x0800)
    Internet Protocol Version 4, Src: 8.8.8.8, Dst: 10.0.2.15
        0100 .... = Version: 4
        .... 0101 = Header Length: 20 bytes (5)
        Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
            0000 00.. = Differentiated Services Codepoint: Default (0)
            .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
        Total Length: 47
        Identification: 0x14a1 (5281)
        Flags: 0x0000
            0... .... .... .... = Reserved bit: Not set
            .0.. .... .... .... = Don't fragment: Not set
            ..0. .... .... .... = More fragments: Not set
        Fragment offset: 0
        Time to live: 116
        Protocol: ICMP (1)
        Header checksum: 0x160f [validation disabled]
        [Header checksum status: Unverified]
        Source: 8.8.8.8
        Destination: 10.0.2.15
    Internet Control Message Protocol
        Type: 0 (Echo (ping) reply)
        Code: 0
        Checksum: 0xb636 [correct]
        [Checksum Status: Good]
        Identifier (BE): 4608 (0x1200)
        Identifier (LE): 18 (0x0012)
        Sequence number (BE): 0 (0x0000)
        Sequence number (LE): 0 (0x0000)
        [Request frame: 6786]
        [Response time: 92.469 ms]
        Data (19 bytes)
0000  54 68 69 73 20 69 73 20 74 68 65 20 70 69 6e 67   This is the ping
0010  2e 0a 00                                          ...
            Data: 546869732069732074686520696e672e0a00
            [Length: 19]
```