Group 90 Progress Report:
Sleep Debt and Screen Time: Late Night Phone Habits

Nadeem Elsayed and Muhammad Ullah
Department of Computing and Software
McMaster University
{elsayn3, ullahm7}@mcmaster.ca

1 Introduction

Smartphones are an integral part of our lives due to benefits; such as easy accessibility to information, social connectivity, workplace/financial applications, and entertainment including watching videos or playing video games. Smartphones have been revolutionized the ease of information and has everyone connected. However, the smartphone - with many pros stated - has also many drawbacks that has disconnected everyone from reality. Spending too much time on the screen reduced personal socialization and significant sleep (CBC News, 2026). Sleep plays a crucial role in developing new memory and is essential for all stages of learning. With inadequate amounts of sleep, the body and mind experience rapid physical and cognitive decline, affecting overall long-term health. These include mood swings, (Shah et al., 2024). Over 3/4 of Americans lose sleep because of digital distractions (Newswise, 2026). The number might be different for different nations, but this is a severe problem that affects a lot of people.

The goal of this project is to analyze and predict the fatigue that people feel the following day based on their screentime usage.

There are a few challenges with trying to predict 'sleep fatigue' based on screentime. There are a lot of variables involved, they might not scale linearly with sleep loss, and there is a limit to the amount of sleep fatigue a person might experience (it could be different for different people).

The data type is tabular containing number and category features like screen time, type of screen use, device type, and the resulting sleep patterns during weekdays and weekends. The task type is regression since we are trying to figure out the exact amount of sleep loss in hours. The number of classes is not applicable for this task since we are using regression. Since we are predicting sleep loss for both weekdays and weekends, this is a multi-label problem where we will get 2 outputs per set of inputs.

2 Related Work

Similar studies have been done to show the effects of screen usage on sleep. A systematic review of school-aged children and adolescents (Hale and Guan, 2015) found that screen time is generally linked to worse sleep. A meta-analysis covering 125,198 children (mean age 14.5) reported that bedtime media-device use was associated with an odds ratio of 2.17 for inadequate sleep quantity (Carter et al., 2016). These studies report associations but do not predict an individual student's sleep loss. Their findings support using screen-use variables as inputs in this study, particularly the days per week each device is used at bedtime and the daily hours of each screen activity, and they suggest that higher screen use should be linked to greater sleep loss.

However, Alam et al. Alam et al. (2023) used objectively recorded smartphone usage from 269 participants aged 15–64 and found, with correlation and regression analyses, that more use was associated with shorter sleep and later bedtimes. This supports treating sleep duration as a numeric outcome that can be modelled from screen usage. It also highlights a limitation of the present dataset, where screen time is self-reported rather than measured. Simon et al. Simon et al. (2024) trained six algorithms, including SVM, XGBoost and random forest, to detect insomnia symptoms from smartphone usage and reported low sensitivity (0.05–0.27) on the test subsample, a warning that predicting sleep from behaviour is hard. This sets realistic expectations of only moderate performance and shows why every model must be compared against simple baselines on held-out data.

The most similar study that was found, a 2024 conference abstract in SLEEP (Machine Learning

Approach), used LASSO and random forest to rank factors associated with adolescent sleep outcomes, including sleep duration. It ranks factors rather than predicting hours of sleep loss. Its approach supports the modelling choices here: ridge regularization is applied to polynomial features to keep all inputs while shrinking noisy coefficients, which suits the many overlapping screen-use variables, and lasso regularization is planned as a next step to identify which variables are unnecessary. A public GitHub project (SOM-12211285, n.d.) classifies sleep quality from screen exposure with logistic regression, random forest and SVM but treats it as a classification problem. Its use of tree-based models indicates that non-linear models such as decision trees are a reasonable comparison, and these are also planned.

No study was found that predicts weekday and weekend sleep loss in hours for school-aged adolescents. The present study addresses this gap by combining the predictive framing of Alam et al. Alam et al. (2023) and Simon et al. Simon et al. (2024) with the screen-use variables identified by Hale and Guan Hale and Guan (2015) and Carter et al. Carter et al. (2016).

3 Dataset and Preprocessing

3.1 Data Source and Characteristics

We're using the research dataset by Perez-Lloret and Perez-Chada (2022), hosted on the Mendeley Data repository under a Creative Commons open-access license. The survey records data collected across 52 secondary schools in Argentina. The survey captures metrics such as demographic attributes like age and gender, device access, the types of digital screentime (gaming, social media, and video streaming), sleep timing, and clinical screening tools to look for narcolepsy and other disorders.

The raw archive (`repositorio.xlsx`) contains 4,115 raw respondent submissions with 123 distinct tabular variables recorded in Spanish.

3.2 Data Cleaning and Feature Harmonization

To establish a machine learning pipeline, we first implemented a data translation pipeline:

1. **Translation and Feature Extraction:** All feature headings and the responses were mapped from Spanish to English (ex: tpopantallatotalhs -> screen_total_hrs, tporedeshs -> screen_social_media_hrs, andtposueñosem -> sleep_weekday_hrs).

2. **Cohort Filtering and Missingness:** We isolated the participants from 11 to 20 years. Records with missing values for primary sleep durations or total screen hours were eliminated. Sub-activity values (such as gaming or console hours) where respondents indicated no use were set to 0 hours.

3. **Clinical Plausibility Bounding:** Outlier responses that did not make physical sense for humans were excluded (restricting sleep durations to $3.0 \leq \text{sleep} \leq 16.0$ hours/day and daily screen exposure to $0.0 \leq \text{screen} \leq 24.0$ hours/day).

After this preprocessing, our finalized dataset is composed of 2,496 student records, which have been exported to ̀/dataset_clean_english.csv.

3.3 Target Formulation: Sleep Debt

Consistent with pediatrician recommendations made by Paruthi et al. (2016), the target sleep duration for adolescents is set to $S_{\text{rec}} = 9.0$ hours. We define the target vector $\mathbf{y} = [y_{\text{weekday}}; y_{\text{weekend}}] \in \mathbb{R}^2$ as:

$$y_{\text{weekday}} = 9.0 - T_{\text{sleep, weekday}} \quad (1)$$

$$y_{\text{weekend}} = 9.0 - T_{\text{sleep, weekend}} \quad (2)$$

Under this formula, positive values represent severe sleep loss (sleep debt), whereas negative values represent sleep surplus. In our preprocessed data, adolescents experience an average weekday sleep loss of $\mu = 1.96$ hours ($\sigma = 1.36$ hours), contrasted with a weekend sleep surplus of $\mu = -0.42$ hours ($\sigma = 1.91$ hours), with a mean social jetlag of 2.38 hours of rebound sleep on weekends.

4 Features

Describe any features you used for your model, or how your data was input to your model. Are you doing feature engineering or feature selection? Are you learning embeddings? Is it all part of one neural network? Refer to item 2. This may range from 0.25 pages to 0.5 pages.

5 Model Implementation

We represent our task as a multi-target linear and non-linear regression problem where we learn a

parameter mapping $f : \mathbb{R}^{13} \to \mathbb{R}^2$ optimizing the Mean Squared Error (MSE):

$$MSE(W) = \frac{1}{N} \sum_{i=1}^{N} \|\mathbf{y}_i - \hat{\mathbf{y}}_i\|_2^2 \tag{3}$$

To establish benchmarks and evaluate model learning, we implemented three candidate solutions with scikit-learn:

5.1 Baseline 1: Empirical Mean Regressor

We construct a naive baseline predicting the training set mean vector for every test instance:

$$\hat{\mathbf{y}}_{\text{dummy}} = \bar{\mathbf{y}}_{\text{train}} = \frac{1}{N_{\text{train}}} \sum_{i=1}^{N_{\text{train}}} \mathbf{y}_i \tag{4}$$

This baseline represents the lower bound ($R^2 \approx 0.0$).

5.2 Baseline 2: Multiple Linear Regression (OLS)

We use a multi-output Ordinary Least Squares (OLS) solution:

$$\hat{\mathbf{y}} = \mathbf{W}^T \tilde{\mathbf{x}} + \mathbf{b} \tag{5}$$

5.3 Candidate Model: Polynomial Regression with Ridge Regularization

Recognizing that screen exposure exhibits non-linear effects, we construct a degree-2 polynomial feature mapping $\phi(\mathbf{x})$ encompassing all linear, quadratic, and pairwise interaction terms:

$$\phi(\mathbf{x}) = [1, x_1, \ldots, x_d, x_1^2, x_1 x_2, \ldots, x_d^2]^T \in \mathbb{R}^{104} \tag{6}$$

To prevent overfitting on the 104-dimensional space, we use the Ridge objective with penalty parameter $\alpha = 100.0$:

$$L_{\text{Ridge}} = \text{MSE} + \alpha \|\mathbf{w}\|_2^2 \tag{7}$$

6 Results and Evaluation

6.1 Evaluation Protocol

We split the preprocessed dataset N = 2,496 using an 80/20 train-test split with fixed random seed ($N_{\text{train}} = 1{,}996$, $N_{\text{test}} = 500$). Performance is measured across three standard regression metrics:

$$\text{MAE} = \frac{1}{N_{\text{test}}} \sum_{i=1}^{N_{\text{test}}} |y_i - \hat{y}_i| \tag{8}$$

$$\text{RMSE} = \sqrt{\frac{1}{N_{\text{test}}} \sum_{i=1}^{N_{\text{test}}} (y_i - \hat{y}_i)^2} \tag{9}$$

$$R^2 = 1 - \frac{\sum_i (y_i - \hat{y}_i)^2}{\sum_i (y_i - \bar{y})^2} \tag{10}$$

6.2 Preliminary Findings

The test results are detailed in Table 1. Multiple Linear Regression achieves a Mean Absolute Error of 0.971 hours on weekday sleep loss ($\hat{R2}$ = 0.103, RMSE = 1.332 hours), demonstrating that it's better than the baseline (MAE $= 1.043$ hours).

The degree-2 polynomial model with Ridge regularization ($\alpha = 100$) has a slightly higher test MAE (0.988 hours) than standard linear regression. This suggests that expanding to 104 quadratic and interaction features adds noise that outweighs non-linear gains when constrained to a linear regularizer.

Furthermore, all models showed lower predictive accuracy on weekend sleep loss ($R^2 \approx 0.027$) compared to weekday sleep loss ($R^2 \approx 0.103$). Weekend sleep schedules among teenagers show weirder behaviour and compensatory rebound sleeping, which is weakly correlated with isolated screen time.

7 Feedback and Plans

Write about your plans for the remainder of the project. This should include a discussion of the feedback you received from your TA, and how you plan to improve your approach. Reflect on your implementation and areas for improvement. Refer to item 6. This may be around 0.5 pages.

Team Contributions

Write in this section a few sentences describing the contributions of each team member. What did each member work on? Refer to item 7.

References

Aftab Alam, Sameha Alshakhsi, Dena Al-Thani, and Raian Ali. 2023. The role of objectively recorded smartphone usage and personality traits in sleep quality. *PeerJ Computer Science*, 9:e1261.

Model Architecture	Weekday Sleep Loss (Hours)			Weekend Sleep Loss (Hours)		
	MAE ↓	RMSE ↓	R^2 ↑	MAE ↓	RMSE ↓	R^2 ↑
Baseline 1: Mean Regressor	1.043	1.406	-0.000	1.549	1.949	-0.002
Baseline 2: Linear Regression (OLS)	**0.971**	**1.332**	**0.103**	**1.511**	**1.920**	**0.027**
Candidate: Polynomial Ridge (Deg 2, $\alpha = 100$)	0.988	1.360	0.065	1.535	1.967	-0.021

Table 1: Preliminary quantitative performance across 500 held-out test adolescents. Metrics report Mean Absolute Error (MAE in hours), Root Mean Squared Error (RMSE in hours), and Coefficient of Determination (R^2).

Ben Carter, Philippa Rees, Lauren Hale, Darsharna Bhattacharjee, and Mandar S. Paradkar. 2016. Association between portable screen-based media device access or use and sleep outcomes: A systematic review and meta-analysis. *JAMA Pediatrics*, 170(12):1202–1208.

CBC News. 2026. Kids and young adults are addicted to screens. New research argues it may be a public health concern. https://www.cbc.ca/news/health/youth-screen-time-tech-companies-9.7365434.

L. Hale and S. Guan. 2015. Screen time and sleep among school-aged children and adolescents: A systematic literature review. *Sleep Medicine Reviews*, 21:50–58.

Machine Learning Approach. 2024. A machine learning approach to identify factors associated with adolescent sleep outcomes. SLEEP (conference abstract).

Newswise. 2026. Over three-fourths of Americans lose sleep due to digital distractions – sleep experts urge a change. https://www.newswise.com/articles/over-three-fourths-of-americans-lose-sleep-due-to-digital-distractions-sleep-experts-urge-a-change.

Shalini Paruthi, Lee J. Brooks, Carolyn D'Ambrosio, Wendy A. Hall, Suresh Kotagal, Robin M. Lloyd, Beth A. Malow, Kiran Maski, Cynthia Nichols, Stuart F. Quan, and 1 others. 2016. Recommended amount of sleep for pediatric populations: A consensus statement of the American Academy of Sleep Medicine. *Journal of Clinical Sleep Medicine*, 12(6):785–786.

Santiago Perez-Lloret and Daniel Perez-Chada. 2022. Screen use, sleep duration, daytime somnolence, and academic failure in school-aged adolescents. *Mendeley Data, V1*.

A. S. Shah and 1 others. 2024. Effects of sleep deprivation on physical and mental health outcomes: An umbrella review. *American Journal of Lifestyle Medicine*.

Laura Simon, Yannik Terhorst, Caroline Cohrdes, Rüdiger Pryss, Lisa Steinmetz, and 1 others. 2024. The predictive value of supervised machine learning models for insomnia symptoms through smartphone usage behavior. *Sleep Medicine: X*, 7:100114.

SOM-12211285. n.d. Sleep-health-digital-screen-exposure-risk-prediction. GitHub repository. Accessed Oct. 8, 2026.