



WEB MODULE

Multiple Choice Question And Answer



1. **What does JSX stand for in React?**

- a) JavaScript XML
- b) Java XML
- c) JSON XML
- d) JavaScript Extension

Answer: a) JavaScript XML

2. **What function is used to change the state in React components?**

- a) `updateState()`
- b) `modifyState()`
- c) `setState()`
- d) `changeState()`

Answer: c) `setState()`

3. Which lifecycle method is called after a component is rendered for the first time?

- a) `componentWillMount()`
- b) `componentDidMount()`
- c) `componentWillRender()`
- d) `componentDidRender()`

Answer: b) `componentDidMount()`

4. What is the purpose of React Router in a React application?

- a) To manage HTTP requests
- b) To handle navigation and routing within the application
- c) To manage state in functional components
- d) To create UI components

Answer: b) To handle navigation and routing within the application

5. In React, which hook is used to perform side effects in functional components?

- a) `useEffect()`
- b) `useState()`
- c) `useReducer()`
- d) `useContext()`

Answer: a) `useEffect()`

6. What is the purpose of the key attribute in React lists?

- a) It specifies the data type of the list elements
- b) It helps identify list items and their changes efficiently
- c) It defines the style for list items
- d) It sets the position of list items

Answer: b) It helps identify list items and their changes efficiently

7. Which method is used to fetch data from an API in React?

- a) fetchData()
- b) retrieveData()
- c) get()
- d) fetch()

Answer: d) fetch()

8. What is the purpose of the props.children property in React?

- a) It contains all child components of a parent component
- b) It provides additional properties to child components
- c) It accesses the parent component's state
- d) It represents the inner content or components passed to a component

Answer: d) It represents the inner content or components passed to a component

9. **Which method is called when a component is about to be removed from the DOM in React?**

- a) `componentWillUnmount()`
- b) `componentDidUnmount()`
- c) `componentRemove()`
- d) `componentDidRemove()`

Answer: a) `componentWillUnmount()`

10. **What is the purpose of Redux in a React application?**

- a) To manage server-side rendering
- b) To handle asynchronous operations
- c) To manage application state
- d) To create reusable UI components

Answer: c) To manage application state

1. What does HTML stand for?

- a) Hyper Text Markup Language
- b) Hyperlinks and Text Markup Language
- c) Home Tool Markup Language
- d) Hyper Transfer Markup Language

Answer: a) Hyper Text Markup Language

2. Which HTML tag is used for creating an unordered list?

- a)
- b) <list>
- c)
- d)

**Answer: c) **

3. Which tag is used to create a hyperlink in HTML?

- a) <link>
- b) <href>
- c) <a>
- d) <hyperlink>

Answer: c) <a>

4. **What is the correct HTML tag for inserting a line break?**

- a) <break>
- b) <lb>
- c) <newline>
- d)

**Answer: d)
**

5. **What is the purpose of the HTML tag?**

- a) Defines an image map
- b) Embeds an image in the webpage
- c) Specifies an image as a button
- d) Inserts a background image

Answer: b) Embeds an image in the webpage

6. **Which attribute is used to specify an alternate text for an image in HTML?**

- a) alt
- b) title
- c) src
- d) href

Answer: a) alt

7. Which HTML element is used to define the structure of a table?

- a) <table>
- b) <tr>
- c) <td>
- d) <th>

Answer: a) <table>

8. In HTML, which tag is used to create an ordered list?

- a)
- b) <list>
- c)
- d)

**Answer: a) **

9. What is the correct HTML tag for creating a hyperlink that opens in a new tab?

- a)
- b)
- c)
- d)

**Answer: a) **

10. **Which HTML tag is used for creating a button?**

- a) <button>
- b) <input type="button">
- c) <btn>
- d) <submit>

Answer: a) <button>

1. **What does CSS stand for?**

- a) Cascading Style Sheets
- b) Creative Style Sheets
- c) Computer Style Sheets
- d) Colorful Style Sheets

Answer: a) Cascading Style Sheets

2. **Which CSS property is used to change the text color of an element?**

- a) text-color
- b) color
- c) font-color
- d) text-style

Answer: b) color

3. How can you link an external CSS file to an HTML document? a)

`<link rel="stylesheet" href="style.css">`

b) `<style src="style.css">`

c) `<css src="style.css">`

d) `<stylesheet>style.css</stylesheet>`

Answer: a) `<link rel="stylesheet" href="style.css">`

4. Which CSS property is used for controlling the spacing between lines of text within an element?

a) line-height

b) text-spacing

c) letter-spacing

d) line-spacing

Answer: a) line-height

5. What is the purpose of the z-index property in CSS?

a) It sets the width of the element

b) It controls the stacking order of elements

c) It changes the opacity of the element

d) It defines the font size of the element

Answer: b) It controls the stacking order of elements

6. **Which CSS property is used for adding rounded corners to an element?** a) border-radius

b) corner-radius

c) round-border

d) border-style

Answer: a) border-radius

7. **In CSS, what property is used for changing the background color of an element?**

a) color

b) background-color

c) bg-color

d) background

Answer: b) background-color

8. Which CSS display property value is used to make an element block-level?

- a) block
- b) inline
- c) inline-block
- d) flex

Answer: a) block

9. What does CSS specificity refer to?

- a) The importance of a stylesheet
- b) The order in which styles are written in a stylesheet
- c) The measurement of how specific a selector is
- d) The number of properties applied to an element

Answer: c) The measurement of how specific a selector is

10. **Which CSS property is used for controlling the order of flexible items in a flex container?**

- a) order
- b) flex-direction
- c) justify-content
- d) align-items

Answer: a) order

1. **What does JavaScript primarily enable you to do in web development?**

- a) Style web pages
- b) Create dynamic content
- c) Define page structure
- d) Manage databases

Answer: b) Create dynamic content

2. Which keyword is used to declare a variable in JavaScript?

- a) variable
- b) var
- c) v
- d) let

Answer: b) var

3. What is the purpose of the === operator in JavaScript?

- a) Assignment
- b) Equality comparison without type coercion
- c) Logical AND operation
- d) Conditional assignment

Answer: b) Equality comparison without type coercion

4. Which function is used to convert a string to an integer in JavaScript?

- a) parseInt()
- b) stringToInt()
- c) toInteger()
- d) parseInteger()

Answer: a) parseInt()

5. What does the typeof operator in JavaScript return?

- a) The data type of a variable
- b) The size of the variable
- c) The value of the variable
- d) The address of the variable

Answer: a) The data type of a variable

6. How can you comment on multiple lines in JavaScript?

- a) `/* ... */`
- b) `# ... #`
- c) `// ... //`
- d) `<!-- ... -->`

Answer: a) `/* ... */`

7. Which loop in JavaScript does not iterate over an array's elements? a)

- for
- b) while
- c) do-while
- d) for...in

Answer: b) while

8. What is the purpose of the `querySelector()` method in JavaScript?

- a) To query the browser's settings
- b) To select the first element that matches a CSS selector
- c) To query the user's input
- d) To find errors in the code

Answer: b) To select the first element that matches a CSS selector

9. Which event fires when a user clicks on an HTML element?

- a) mouseover
- b) click
- c) change
- d) keypress

Answer: b) click

10. **What does the NaN keyword represent in JavaScript?**

- a) Not a Node
- b) Not a Null
- c) Not a Number
- d) Not a Name

Answer: c) Not a Number

1. **Which character is used as a shortcut for jQuery?**

- a) &
- b) \$
- c) @
- d) #

Answer: b) \$

2. **What does `$(document).ready()` do in jQuery?**

- a) Waits for the document to be fully loaded before executing code inside it
- b) Selects all elements in the document
- c) Defines the document's structure
- d) Triggers an event when the document is ready to be modified

Answer: a) Waits for the document to be fully loaded before executing code inside it

3. Which jQuery method is used to add new HTML elements to the page?

- a) create()
- b) append()
- c) addToPage()
- d) insert()

Answer: b) append()

4. How do you select all elements with the class name "example" in jQuery?

- a) select("example")
- b) getElementByClass("example")
- c) \$("example")
- d) \$(".example")

Answer: d) \$(".example")

5. Which jQuery method is used to change the CSS property of an element?

- a) changeCSS()
- b) css()
- c) modifyCSS()
- d) setStyle()

Answer: b) css()

6. Which jQuery method is used to get the value of a form input element?

- a) inputValue()
- b) value()
- c) getInputValue()
- d) val()

Answer: d) val()

7. What does the fadeIn() method do in jQuery?

- a) Fades an element into view
- b) Fades an element out of view
- c) Adds a fade effect when hovering over an element
- d) Slides an element down

Answer: a) Fades an element into view

8. How do you stop an event from bubbling up the DOM tree in jQuery?

- a) preventDefault()
- b) stopPropagation()
- c) halt()
- d) cancelBubble()

Answer: b) stopPropagation()



9. Which jQuery method is used to make an Ajax request? a)

sendRequest()

b) ajax()

c) makeRequest()

d) request()

Answer: b) ajax()

10. Which method is used to remove all child nodes from the selected elements in jQuery?

a) empty()

b) remove()

c) detach()

d) purge()

Answer: a) empty()

1. What does AJAX stand for?

- a) Asynchronous JavaScript and XML
- b) Automated JavaScript and XML
- c) Advanced JavaScript and XML
- d) Asynchronous JavaScript and XHTML

Answer: a) Asynchronous JavaScript and XML

2. Which object is used to perform AJAX requests in JavaScript? a)

- HttpRequest
- b) XMLHttpRequest
- c) AjaxRequest
- d) HTTPHandler

Answer: b) XMLHttpRequest

3. Which method in XMLHttpRequest object is used to send an HTTP request?

- a) open()
- b) send()
- c) request()
- d) submit()

Answer: b) send()

4. What is the purpose of the onreadystatechange property in XMLHttpRequest?

- a) It holds the response status
- b) It defines the request headers
- c) It specifies the request method
- d) It defines a function to be called when the state changes

Answer: d) It defines a function to be called when the state changes

5. Which HTTP method is used by default in an AJAX request?

- a) GET
- b) POST
- c) PUT
- d) DELETE

Answer: a) GET

6. What is the role of the readyState property in AJAX?

- a) It stores the response data
- b) It holds the status of the AJAX request
- c) It specifies the request method
- d) It defines the request headers

Answer: b) It holds the status of the AJAX request

7. Which function is used to handle a successful AJAX response in JavaScript? a) handleSuccess()

- b) onSuccess()
- c) success()
- d) onreadystatechange()

Answer: d) onreadystatechange()

8. What does the XMLHttpRequest.responseText property contain?

- a) The response status
- b) The response headers
- c) The response data as a string
- d) The response XML

Answer: c) The response data as a string

9. Which method is used to handle errors in AJAX requests?

- a) `onError()`
- b) `handleError()`
- c) `onreadystatechange()` with error status check
- d) `onFailure()`

Answer: c) `onreadystatechange()` with error status check

10. What is the purpose of the `XMLHttpRequest.setRequestHeader()` method?

- a) To define the request body
- b) To specify the request method
- c) To set custom request headers
- d) To handle response headers

Answer: c) To set custom request headers

1. What is Node.js?

- a) A frontend JavaScript framework
- b) A server-side runtime environment for JavaScript
- c) A relational database system
- d) A browser-based development tool

Answer: b) A server-side runtime environment for JavaScript

2. **Which JavaScript engine is used by Node.js?**

- a) SpiderMonkey
- b) V8
- c) Rhino
- d) Chakra

Answer: b) V8

3. **What is the package manager used in Node.js?**

- a) npm (Node Package Manager)
- b) pip
- c) Maven
- d) NuGet

Answer: a) npm (Node Package Manager)

4. **Which command is used to initialise a Node.js project and create a package.json file?**

- a) node init
- b) npm init
- c) create-node
- d) node new

Answer: b) npm init

5. Which core module is used for handling file operations in Node.js?

- a) fs
- b) file
- c) io
- d) fileSystem

Answer: a) fs

6. Which module in Node.js allows you to create a web server?

- a) http
- b) web
- c) server
- d) network

Answer: a) http

7. What is the purpose of the `require()` function in Node.js?

- a) To include external modules in a Node.js application
- b) To define new variables
- c) To execute asynchronous functions
- d) To import CSS files

Answer: a) To include external modules in a Node.js application

8. **Which tool is used for managing multiple Node.js versions on the same machine?**

- a) Node Manager (NM)
- b) Node Version Manager (nvm)
- c) Node Control
- d) Node Env

Answer: b) Node Version Manager (nvm)

9. **Which event is emitted when an unhandled exception occurs in a Node.js application?**

- a) uncaughtException
- b) errorEvent
- c) exceptionThrown
- d) nodeError

Answer: a) uncaughtException

10. **Which Node.js method is used to perform asynchronous operations after a set period of time?**

- a) wait()
- b) setTimeout()
- c) delay()
- d) executeAfter()

Answer: b) setTimeout()

1. **What is Bootstrap?**

- a) A JavaScript library
- b) A CSS framework
- c) A server-side language
- d) A database management system

Answer: b) A CSS framework

2. **Which HTML element is commonly used to create a Bootstrap navigation bar?**

- a) <nav>
- b) <navbar>
- c) <navigation>
- d) <bar>

Answer: a) <nav>

3. **Which class is used in Bootstrap to create a responsive, two-column layout?**

- a) `.col-2`
- b) `.grid-two`
- c) `.row`
- d) `.col-md-6`

Answer: d) `.col-md-6`

4. **What is the purpose of the Bootstrap grid system?**

- a) To style text elements
- b) To create navigation menus
- c) To design responsive layouts using rows and columns
- d) To manage JavaScript components

Answer: c) To design responsive layouts using rows and columns

5. **Which class is used in Bootstrap to create a button?**

- a) `.btn`
- b) `.button`
- c) `.button-style`
- d) `.button-default`

Answer: a) `.btn`

6. In Bootstrap, which class is used to create a responsive image?

- a) `.img-responsive`
- b) `.responsive-img`
- c) `.image-fluid`
- d) `.fluid-img`

Answer: a) `.img-responsive`

7. Which file should be included to utilise Bootstrap in an HTML document?

- a) `bootstrap.js`
- b) `bootstrap.min.css`
- c) `bootstrap.min.js`
- d) `bootstrap.css`

Answer: b) `bootstrap.min.css`

8. What is the purpose of Bootstrap's container class?

- a) To create a full-width container
- b) To align elements to the left
- c) To add spacing inside the grid columns
- d) To make elements semi-transparent

Answer: c) To add spacing inside the grid columns

9. Which class in Bootstrap is used to create a responsive table?

- a) .table-responsive
- b) .responsive-table
- c) .table-fluid
- d) .fluid-table

Answer: a) .table-responsive

10. What is the purpose of the .jumbotron class in Bootstrap?

- a) To create a fluid container
- b) To style headings and titles
- c) To create a large showcase area or header
- d) To add animation effects

Answer: c) To create a large showcase area or header

1. What type of database is MongoDB considered to be?

- a) Relational database
- b) NoSQL database
- c) Graph database
- d) In-memory database

Answer: b) NoSQL database

2. In MongoDB, what is a document?

- a) A record in a table
- b) A collection of related tables
- c) A record in a collection
- d) A relational structure

Answer: c) A record in a collection

3. What is the primary language for interacting with MongoDB?

- a) SQL
- b) C++
- c) JavaScript
- d) Python

Answer: c) JavaScript

4. What is the default port number for MongoDB?

- a) 27017
- b) 3306
- c) 5432
- d) 1521

Answer: a) 27017

5. Which of the following is used to perform CRUD operations in MongoDB?

- a) Aggregate
- b) SQL
- c) ORM
- d) CRUD is native to MongoDB

Answer: d) CRUD is native to MongoDB

6. Which command is used to create a database in MongoDB if it doesn't exist?

- a) USE database_name
- b) CREATE DATABASE database_name
- c) db.createCollection('database_name')
- d) MongoDB automatically creates a database on insertion

Answer: d) MongoDB automatically creates a database on insertion

7. In MongoDB, what is the role of _id field in a document?

- a) It represents the name of the collection
- b) It serves as the primary key of the document
- c) It is used for indexing purposes
- d) It is not a mandatory field

Answer: b) It serves as the primary key of the document

8. Which aggregation stage is used to filter documents in MongoDB?

- a) \$project
- b) \$match
- c) \$filter
- d) \$group

Answer: b) \$match

9. Which command is used to drop a collection in MongoDB?

- a) DROP COLLECTION collection_name
- b) DELETE COLLECTION collection_name
- c) REMOVE COLLECTION collection_name
- d) db.collection_name.drop()

Answer: d) db.collection_name.drop()

10. What is the purpose of the findOne() method in MongoDB?

- a) To find all documents in a collection
- b) To find the first document that matches a query
- c) To retrieve multiple documents at once
- d) To find the last document in a collection

Answer: b) To find the first document that matches a query

1. What type of database is MySQL considered to be?

- a) Relational database
- b) NoSQL database
- c) Document-based database
- d) Graph database

Answer: a) Relational database

2. Which statement is used to create a new database in MySQL?

- a) CREATE DATABASE database_name
- b) NEW DATABASE database_name
- c) ADD DATABASE database_name
- d) MAKE DATABASE database_name

Answer: a) CREATE DATABASE database_name

3. Which command is used to retrieve data from a MySQL database?

- a) SELECT
- b) RETRIEVE
- c) FETCH
- d) GET

Answer: a) SELECT

4. **Which clause is used to filter the results of a MySQL query?**

- a) ORDER BY
- b) GROUP BY
- c) WHERE
- d) FILTER

Answer: c) WHERE

5. **What is the default port number for MySQL?**

- a) 3306
- b) 5432
- c) 27017
- d) 1521

Answer: a) 3306

6. **Which command is used to update data in a MySQL table?**

- a) MODIFY
- b) UPDATE
- c) CHANGE
- d) ALTER

Answer: b) UPDATE

7. What is the purpose of the JOIN clause in MySQL?

- a) To add new records to a table
- b) To modify table structure
- c) To retrieve data from multiple related tables
- d) To delete records from a table

Answer: c) To retrieve data from multiple related tables

8. Which function is used to count the number of rows in a MySQL table?

- a) COUNT (*)
- b) SUM ()
- c) ROWS ()
- d) TOTAL ()

Answer: a) COUNT (*)

9. Which command is used to delete a table in MySQL?

- a) DROP TABLE table_name
- b) DELETE TABLE table_name
- c) REMOVE TABLE table_name
- d) REMOVE TABLE IF EXISTS table_name

Answer: a) DROP TABLE table_name

10. **What is the purpose of the GROUP BY clause in MySQL?** a) To sort the result set in ascending or descending order
b) To combine rows into groups based on a given condition
c) To limit the number of rows returned by a query
d) To filter the result set

Answer: b) To combine rows into groups based on a given condition

1. What does HTML5 stand for?

- a) Hyper Text Markup Language 5
- b) High-Tech Markup Language 5
- c) Hyperlinks and Text Markup Language 5
- d) Home Tool Markup Language 5

Answer: a) Hyper Text Markup Language 5

2. Which element is used for embedding audio content in HTML5?

- a) <audio>
- b) <sound>
- c) <music>
- d) <media>

Answer: a) <audio>

3. Which attribute is used to specify the source of an image in HTML5?

- a) src
- b) source
- c) link
- d) href

Answer: a) src

4. Which input type in HTML5 is used for date selection?

- a) type="calendar"
- b) type="datetime"
- c) type="date"
- d) type="day"

Answer: c) type="date"

5. Which HTML5 tag is used to draw graphics on a web page?

- a) <draw>
- b) <graphic>
- c) <canvas>
- d) <paint>

Answer: c) <canvas>

6. Which HTML5 attribute is used for offline storage in the browser?

- a) offline-storage
- b) data-storage
- c) local-storage
- d) cache-storage

Answer: c) local-storage

7. Which element in HTML5 is used to define navigation links?

- a) <nav>
- b) <navbar>
- c) <navigation>
- d) <links>

Answer: a) <nav>

8. Which element in HTML5 is used to play video files?

- a) <media>
- b) <video>
- c) <mp4>
- d) <play>

Answer: b) <video>

9. What is the purpose of the HTML5 <footer> tag?

- a) To define a section for introductory content
- b) To define a section for main content
- c) To specify a section for contact information or author details
- d) To define a section for navigation links

Answer: c) To specify a section for contact information or author details

10. Which attribute is used in HTML5 to provide a brief hint or suggestion regarding the expected value of an input field?

- a) placeholder
- b) hint
- c) suggest
- d) valuehint

Answer: a) placeholder

1. **What does CSS3 stand for?**

- a) Cascading Style Sheets 3
- b) Creative Style Sheets 3
- c) Computer Style Sheets 3
- d) Colorful Style Sheets 3

Answer: a) Cascading Style Sheets 3

2. **Which property is used to create rounded corners in CSS3?**

- a) border-style
- b) corner-radius
- c) border-radius
- d) rounded-corners

Answer: c) border-radius

3. **Which CSS3 property is used to apply a gradient background to an element?**

- a) color-gradient
- b) background-gradient
- c) gradient
- d) background-image

Answer: d) background-image

4. **Which property in CSS3 is used to add shadows to text or elements?**

- a) shadow
- b) box-shadow
- c) text-shadow
- d) element-shadow

Answer: c) text-shadow

5. **Which CSS3 property is used for flexible sizing of elements in a layout?**

- a) flex
- b) size
- c) flexible
- d) box-sizing

Answer: a) flex

6. **Which value for the display property in CSS3 is used to make an element flexible?**

- a) inline
- b) block
- c) flex
- d) grid

Answer: c) flex

7. Which CSS3 property is used for creating animations?

- a) transition
- b) animate
- c) animation
- d) transform

Answer: c) animation

8. Which CSS3 property is used for applying 2D or 3D transformations to elements?

- a) transition
- b) transform
- c) translate
- d) rotate

Answer: b) transform

9. Which CSS3 property is used for adjusting the opacity of an element?

- a) alpha
- b) transparency
- c) opacity
- d) visibility

Answer: c) opacity

10. **Which CSS3 property is used to create multiple columns in a layout?**

- a) layout-columns
- b) multi-column
- c) column-count
- d) column-layout

Answer: c) column-count

1. **What is JSON?**

- a) JavaScript Object Notion
- b) JavaScript Object Notation
- c) JavaScript Object Naming
- d) JavaScript Object Nonconformity

Answer: b) JavaScript Object Notation

2. **Which data types can be represented in JSON?**

- a) Strings, numbers, booleans, arrays, objects, null
- b) Strings, integers, floats, arrays, booleans
- c) Strings, numbers, arrays, objects, undefined
- d) Strings, characters, arrays, objects, booleans

Answer: a) Strings, numbers, booleans, arrays, objects, null

3. What character is used to encapsulate data in a JSON string?

- a) () parentheses
- b) { } curly braces
- c) [] square brackets
- d) " " double quotes

Answer: d) " " double quotes

4. Which of the following is a valid JSON format?

- a) { "name": "John", "age": 30, "city": London }
- b) { name: "John", age: 30, city: "London" }
- c) { "name", "John", "age", 30, "city", "London" }
- d) { name: "John"; age: 30; city: "London" }

Answer: a) { "name": "John", "age": 30, "city": London }

5. How is a comment added in a JSON file?

- a) // This is a comment
- b) /* This is a comment */
- c) <!-- This is a comment -->
- d) Comments are not supported in JSON

Answer: d) Comments are not supported in JSON

6. **Which method is used to convert a JSON string to a JavaScript object?**

- a) `JSON.parse()`
- b) `JSON.stringify()`
- c) `JSON.toObject()`
- d) `JSON.convert()`

Answer: a) `JSON.parse()`

7. **What is the purpose of JSON schema?**

- a) To define the structure of JSON data
- b) To encrypt JSON data
- c) To compress JSON files
- d) To format JSON for output

Answer: a) To define the structure of JSON data

8. **Which character is used to separate multiple key-value pairs in a JSON object?**

- a) , comma
- b) : colon
- c) ; semi-colon
- d) . period

Answer: a) , comma

9. **In JSON, which data type is represented as an array?**

- a) Integer
- b) Boolean
- c) Object
- d) Array

Answer: d) Array

10. **Which method is used to convert a JavaScript object to a JSON string?**

- a) JSON.serialize()
- b) JSON.parse()
- c) JSON.stringify()
- d) JSON.format()

Answer: c) JSON.stringify()

1. **What is Redux?**

- a) A database management system
- b) A JavaScript library for managing application state
- c) A front-end framework
- d) A CSS preprocessor

Answer: b) A JavaScript library for managing application state

2. **In Redux, which function is used to dispatch actions?** a) commit()

- b) sendAction()
- c) dispatch()
- d) trigger()

Answer: c) dispatch()

3. **What is the purpose of an action in Redux?**

- a) To modify the state directly
- b) To represent an operation that will change the state
- c) To define the initial state
- d) To subscribe to state changes

Answer: b) To represent an operation that will change the state

4. **Which function is used to combine multiple reducers into a single reducer in Redux?**

- a) joinReducers()
- b) combineReducers()
- c) mergeReducers()
- d) concatReducers()

Answer: b) combineReducers()

5. **In Redux, what is the purpose of the store?**

- a) To manage middleware
- b) To define actions
- c) To manage the application's state
- d) To handle API requests

Answer: c) To manage the application's state

6. **What does the term "immutable state" mean in the context of Redux?**

- a) The state cannot be changed once set
- b) The state can only be changed using asynchronous actions
- c) The state can only be changed by the dispatch function
- d) The state can be changed freely at any time

Answer: a) The state cannot be changed once set

7. **Which method is used to subscribe to changes in the Redux store?** a)

subscribe()

b) watch()

c) onChange()

d) observe()

Answer: a) subscribe()

8. What does the term "action creator" refer to in Redux?

a) A function that creates action objects

b) A middleware responsible for API calls

c) A component that generates Redux actions

d) A reducer that initialises the store

Answer: a) A function that creates action objects

9. **In Redux, what is the role of a reducer?**

a) To dispatch actions

b) To handle asynchronous operations

c) To define the initial state of the application

d) To specify how the application's state changes in response to actions

Answer: d) To specify how the application's state changes in response to actions



10. **Which React-Redux function is used to connect React components to the Redux store?**

- a) `mapStateToProps()`
- b) `connect()`
- c) `reduxConnect()`
- d) `bindStore()`

Answer: b) `connect()`