

Exercise: Syntax, Functions and Statements

Problems for in-class lab for the ["JavaScript Advanced" course @ SoftUni](https://judge.softuni.org/Contests/1796/Exercise-Syntax-Functions-and-Statements). Submit your solutions in the SoftUni judge system at <https://judge.softuni.org/Contests/1796/Exercise-Syntax-Functions-and-Statements>

1. Fruit

Write a function that calculates how much money you need to buy fruit. You will receive a **string** for the type of fruit you want to buy, a **number** for weight in grams and another **number** for the price per kilogram.

Print the following text on the console:

`'I need ${money} to buy {weight} kilograms {fruit}.'`

Print the weight and the money **rounded** to two decimal places.

The **input** comes as **three arguments** passed to your function.

The **output** should be printed on the console.

Examples

Input	Output
'orange', 2500, 1.80	I need \$4.50 to buy 2.50 kilograms orange.

Input	Output
'apple', 1563, 2.35	I need \$3.67 to buy 1.56 kilograms apple.

2. Greatest Common Divisor - GCD

Write a function that takes **two positive numbers** as input and compute the greatest common divisor.

The **input** comes as **two positive integer numbers**.

The **output** should be printed on the console.

Examples

Input	Output
15, 5	5

Input	Output
2154, 458	2

3. Same Numbers

Write a function that takes **an integer number** as an input and check if all the digits in a given number are the same or not.

Print on the console **true** if all numbers are same and **false** if not. On the next line print the **sum of all digits**.

The **input** comes as an integer number.

The **output** should be printed on the console.

Examples

Input	Output
2222222	true 14

Input	Output
1234	false 10

4. Time to Walk

Write a function that **calculates** how long it takes a student to get to university.

The function takes **three numbers**:

- The **first** is the number of **steps** the student takes from their home to the university
- The **second** number is the length of the student's footprint in **meters**
- The **third** number is the student speed in **km/h**

Every 500 meters the student rests and takes a **1 minute break**.

Calculate how long the student walks from home to university and print on the console the result in the following format: '**hours:minutes:seconds**'.

The **input** comes as **three numbers**.

The **output** should be printed on the console.

Examples

Input	Output
4000, 0.60, 5	00:32:48

Input	Output
2564, 0.70, 5.5	00:22:35

5. Road Radar

Write a function that determines whether a driver is within the speed limit. You will receive the speed and the area. Each area has a different limit:

- On the **motorway** the limit is **130 km/h**
- On the **interstate** the limit is **90 km/h**
- In the **city** the limit is **50 km/h**
- Within a **residential** area the limit is **20 km/h**

If the driver is **within the limits**, there should not be any output. If the driver is **over the limit**, however, your function should print the severity of the infraction.

For speeding up to **20 km/h** over the limit, **speeding** should be printed

For speeding up to **40 km/h** over the limit, **excessive speeding** should be printed

For anything else, **reckless driving** should be printed

The **input** comes as an **array of elements**. The first element is the current speed (**number**), the second element is the area.

The **output** should be printed on the console. Note that in certain cases there isn't any output.

Examples

Input	Output
[40, 'city']	
[21, 'residential']	speeding
[120, 'interstate']	excessive speeding
[200, 'motorway']	reckless driving

6. Cooking by Numbers

Write a program that receives a **number** and a **list** of five operations. Perform the operations **sequentially** by starting with the **input number** and using the result of every operation as starting point for the next one. Print the result of every operation in order. The operations can be one of the following:

- **chop** - divide the number by two
- **dice** - square root of number
- **spice** - add 1 to number
- **bake** - multiply number by 3
- **fillet** - subtract 20% from number

The **input** comes as an **array of 6 string elements**. The first element is the starting point and must be **parsed** to a number. The remaining 5 elements are the names of the operations to be performed.

The **output** should be printed on the console.

Examples

Input	Output
['32', 'chop', 'chop', 'chop', 'chop', 'chop']	16 8 4 2 1

Input	Output
['9', 'dice', 'spice', 'chop', 'bake', 'fillet']	3 4 2 6 4.8

7. Validity Checker

Write a program that receives two points in the format **[x1, y1, x2, y2]**. Check if the distance between each point and the start of the cartesian coordinate system (0, 0) is **valid**. A distance between two points is considered **valid**, if it is an **integer value**.

In case a distance is valid, print "**{x1, y1} to {x2, y2} is valid**"

If the distance is invalid, print "**{x1, y1} to {x2, y2} is invalid**"

The order of comparisons should always be first **{x1, y1}** to **{0, 0}**, then **{x2, y2}** to **{0, 0}** and finally **{x1, y1}** to **{x2, y2}**.

The **input** consists of two points given as an **array of numbers**.

For each comparison print either "**{x1, y1} to {x2, y2} is valid**" if the distance is valid, or "**{x1, y1} to {x2, y2} is invalid**" if it is invalid.

Examples

Input	Output
[3, 0, 0, 4]	{3, 0} to {0, 0} is valid {0, 4} to {0, 0} is valid {3, 0} to {0, 4} is valid
[2, 1, 1, 1]	{2, 1} to {0, 0} is invalid {1, 1} to {0, 0} is invalid {2, 1} to {1, 1} is valid

8. * Calorie Object

Write a function that composes an object by given properties. The input comes as an **array of strings**. Every **even index** of the array represents the **name of the food**. Every **odd index** is a **number** that is equal to the **calories in 100 grams of the given product**. Assign each value to its corresponding property and print it on the console.

The **input** comes as an **array of string elements**.

The **output** should be printed on the console.

Examples

Input	Output
['Yoghurt', '48', 'Rise', '138', 'Apple', '52']	{ Yoghurt: 48, Rise: 138, Apple: 52 }
['Potato', '93', 'Skyr', '63', 'Cucumber', '18', 'Milk', '42']	{ Potato: 93, Skyr: 63, Cucumber: 18, Milk: 42 }