

Clustering

Hierarchical Clustering

- Agglomerative clustering
- Divisive clustering

Agglomerative Clustering Algorithm

Algorithm 1: Agglomerative Clustering Solution Algorithm

Input: Features from data

Output: k cluster labeling for each point

Initialize n clusters where every point is a cluster

while *cluster count reached greater than k* **do**

 Determine the two clusters closest to each other based on
 distance metric and linkage criteria





 Merge the two clusters into one

end

Linkage Criteria

- Complete linkage - $\max(\text{dist}(c_i, c_j))$
- Single linkage - $\min(\text{dist}(c_i, c_j))$
- Average linkage - $\text{mean}(\text{dist}(c_i, c_j))$
- Ward - $\text{variance}(\text{merge}(c_i, c_j))$


Dendrogram Examples



Complete Linkage Dendrogram

$$\max(\text{dist}(c_i, c_j))$$


Complete Linkage



Single Linkage Dendrogram


$$\min(\text{dist}(c_i, c_j))$$

Single Linkage




Average Linkage Dendrogram

$$\text{mean}(\text{dist}(c_i, c_j))$$



Ward Dendrogram

$\text{variance}(\text{merge}(c_i, c_j))$



Agglomerative Clustering Algorithm

Algorithm 1: Agglomerative Clustering Solution Algorithm

Input: Features from data

Output: k cluster labeling for each point

Initialize n clusters where every point is a cluster

while *cluster count reached greater than k* **do**

 Determine the two clusters closest to each other based on
 distance metric and linkage criteria

 Merge the two clusters into one

end

Non-negative Matrix Factorization


$$\mathbf{X} = \mathbf{FG}.$$

If \mathbf{X} is a $d \times n$ matrix, we can produce
a $d \times k$, \mathbf{F} matrix,
and $k \times n$, \mathbf{G} matrix.

The objective for NMF is,

$$\begin{aligned} \min_{\mathbf{F}, \mathbf{G}} \quad & \|\mathbf{X} - \mathbf{FG}\|_F^2 \\ \text{s.t.} \quad & \mathbf{F} \geq 0, \mathbf{G} \geq 0, \mathbf{GG}^T = \mathbf{I}. \end{aligned}$$

Euclidean vs Manifold




$$\mathbf{A} = \begin{bmatrix} a_{11} & a_{12} & a_{13} & \dots & a_{1n} \\ a_{21} & a_{22} & a_{23} & \dots & a_{2n} \\ a_{31} & a_{32} & a_{33} & \dots & a_{3n} \\ \dots & \dots & \dots & \dots & \dots \\ a_{n1} & a_{n2} & a_{n3} & \dots & a_{nn} \end{bmatrix}$$

$$\mathbf{D} = \begin{bmatrix} \sum_{i=1}^n a_{1i} & 0 & 0 & \dots & 0 \\ 0 & \sum_{i=1}^n a_{2i} & 0 & \dots & 0 \\ 0 & 0 & \sum_{i=1}^n a_{3i} & \dots & 0 \\ \dots & \dots & \dots & \dots & \dots \\ 0 & 0 & 0 & \dots & \sum_{i=1}^n a_{ni} \end{bmatrix}$$


$$\mathbf{L} = \mathbf{D} - \mathbf{A}$$

$$= \begin{bmatrix} (\sum_{i=2}^n a_{1i}) & -a_{12} & -a_{13} & \dots & -a_{1n} \\ -a_{21} & (\sum_{i=1, i \neq 2}^n a_{2i}) & -a_{23} & \dots & -a_{2n} \\ -a_{31} & -a_{32} & (\sum_{i=1, i \neq 3}^n a_{3i}) & \dots & -a_{3n} \\ \dots & \dots & \dots & \dots & \dots \\ -a_{n1} & -a_{n2} & -a_{n3} & \dots & (\sum_{i=1, i \neq n}^n a_{ni}) \end{bmatrix}$$

Spectral Clustering



Spectral Clustering



Questions

These slides are designed for educational purposes, specifically the CSCI-470 Introduction to Machine Learning course at the Colorado School of Mines as part of the Department of Computer Science.

Some content in these slides are obtained from external sources and may be copyright sensitive. Copyright and all rights therein are retained by the respective authors or by other copyright holders. Distributing or reposting the whole or part of these slides not for academic use is HIGHLY prohibited, unless explicit permission from all copyright holders is granted.