

Review

Just double checking...

Features vs Targets

- Features / Attributes
- Targets / Labels

Train - Test Split

- Train on training data **NOT** testing data
- Report scoring on testing data **NOT** training data
 - We determine the score on training data as a sanity check

Sklearn Estimators

Used to estimate a target value

- fit
- predict
- fit predict


Used to transform data from one form to another

- fit
- transform
- fit transform

Activation Function Ranges

- Sigmoid - $[0,1]$
- Step - $0,1$
- Softsign - $[-1,1]$
- Hyperbolic tan - $[-1,1]$
- ReLU - $[0, \infty]$
- Leaky ReLU - $[-\infty, \infty]$

Activation Functions



Softmax normalizes the values so that they add up to one.

Output Layer Activation Functions

- Regression - must contain range of possible values
- Binary Classification - sigmoid or $[0,1]$ range simulating probability of true class
- Multi-class Classification - softmax simulating probability of each class

Output Layer Units

Same number as what we need to predict

- Regression - number of Targets
- Binary Classification - 1
- Multi-class Classification - k

Questions

These slides are designed for educational purposes, specifically the CSCI-470 Introduction to Machine Learning course at the Colorado School of Mines as part of the Department of Computer Science.

Some content in these slides are obtained from external sources and may be copyright sensitive. Copyright and all rights therein are retained by the respective authors or by other copyright holders. Distributing or reposting the whole or part of these slides not for academic use is HIGHLY prohibited, unless explicit permission from all copyright holders is granted.