

Introduction to Molecular Interaction Fields (MIFs) in RDKit

David F. Hahn

david.hahn@phys.chem.ethz.ch

Novartis Institutes of Biomedical Research (NIBR), Basel
Laboratory of Physical Chemistry, ETH Zürich

September 2, 2015

Overview

MIFs
in RDKit

D.F.Hahn

Introduction

Methods

Implementation

Results

Conclusions

1 Introduction

2 Methods

3 Implementation

4 Results

5 Conclusions

Aim: Find active ingredient in silico.

MIFs
in RDKit

D.F.Hahn


Introduction

Methods

Implementation

Results

Conclusions



Procedure

Place grid around molecule

MIFs
in RDKit

D.F.Hahn



Introduction

Methods

Implementation

Results

Conclusions



Procedure

Defining probe and type of interaction

MIFs
in RDKit

D.F.Hahn

Introduction


Methods

Implementation

Results

Conclusions

- Type of interaction:
 - electrostatic interaction
 - van der Waals interaction
 - hydrogen bonding interaction
- Probe:
 - charge
 - atom (Lennard-Jones parameter)
 - hydrogen bond acceptor/donor



Implementation

MIFs
in RDKit

D.F.Hahn

Introduction

Methods

Implementation

Results

Conclusions

- `UniformRealValueGrid3D` for storing and manipulating fields
- Several descriptor functors, which are constructed for specific molecules
- Function `calculateDescriptors(UniformRealValueGrid3D, Functor)` to efficiently calculate MIF on the given `UniformRealValueGrid3D`
- PYTHON wrappers to C++ MIF library

Example code

MIFs
in RDKit
D.F.Hahn

Introduction

Methods

Implementation

Results

Conclusions

```
In [1]: import rdkit.Chem.AllChem as AllChem
        from rdkit.Chem.Draw import IPythonConsole
        import rdkit.Chem.rdMIF as Mif
```

Load structure from SDF file to mol.

```
In [2]: mol = AllChem.SDMolSupplier('mif_rdkit_tutorial/enalapril.sdf', removeHs=False)
        mol = mol.next()
```

Construct grid around molecule (using default values for spacing and margin).

```
grd = Mif.ConstructGrid(mol)
```

```
In [3]:
```

Construct a van der Waals descriptor class, calculate descriptor values on the grid and save it to a CUBE file.

```
In [4]: vdw = Mif.ConstructVdWaalsUFF(mol)
        Mif.CalculateDescriptors(grd, vdw)
        Mif.WriteToCubeFile(grd, mol, "mif_rdkit_tutorial/vdw.cube")
```

Visualize grid as an isosurface in PyMol. PyMol has to be running with the XML-RPC server active (-R argument to PyMol on launch).

```
In [5]: from rdkit.Chem import PyMol
        v = PyMol.MolViewer()
        v.ShowMol(mol)
        v.LoadFile("~/notebooks/mif_rdkit_tutorial/vdw.cube", "vdw")
        v.server.do("isosurface surf, vdw, 0")
        v.server.do('set transparency, 0.4, surf')
        v.GetPNG(h=500)
```

Van der Waals Field

Probe: sp^2 oxygen (e.g. in alcohol or ether) - Isosurface at 0.0 kJ mol^{-1}

MIFs
in RDKit

D.F.Hahn


Introduction

Methods

Implementation


Results

Conclusions



Coulomb field

Probe: positive charge (+1e) - colormap ranging from $-25.0 \text{ kJ mol}^{-1}$ (blue) via 0.0 kJ mol^{-1} (white) to $+25.0 \text{ kJ mol}^{-1}$ (red)



MIFs
in RDKit


D.F.Hahn

Introduction
Methods
Implementation
Results
Conclusions

Hydrogen bonding field

Probe: acceptor (C=O, red) - level $-25.0 \text{ kJ mol}^{-1}$

Probe: donor (OH, blue) - level $-20.0 \text{ kJ mol}^{-1}$



MIFs
in RDKit

D.F.Hahn

Introduction
Methods
Implementation
Results
Conclusions

Conclusions & Outlook

MIFs
in RDKit

D.F.Hahn

Introduction

Methods

Implementation

Results

Conclusions

The newly developed RDKit functionalities

- can compute different MIFs of different molecules.
- can be used in PYTHON.
- open new possibilities for 3D-QSAR studies in RDKit.

Further work

- Review and get code merged onto the master.
- Use them for 3D-QSAR studies.
- Implement descriptors based on MIFs, but independent of alignment.

Acknowledgment

MIFs
in RDKit

D.F.Hahn

Introduction

Methods

Implementation

Results

Conclusions

- Greg Landrum
- Niko Fechner
- NIBR IT Sigma