Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs( 1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

**For example:**

| Input | Result |
|---|---|
| 3<br>1<br>2<br>3<br>4<br>5<br>6 | 28 |

**Answer:** (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

int ascending(const void *a, const void *b) {
    return (*(int *)a - *(int *)b);
}

int descending(const void *a, const void *b) {
    return (*(int *)b - *(int *)a);
}

int main() {
    int n;
    scanf("%d", &n);

    int a[n], b[n];
    int i = 0;

```

```
    while (i < n) {
        scanf("%d", &a[i]);
        i = i + 1;
    }

    i = 0;
    while (i < n) {
        scanf("%d", &b[i]);
        i = i + 1;
    }

    qsort(a, n, sizeof(int), ascending);
    qsort(b, n, sizeof(int), descending);

    long long sum = 0;
    i = 0;

    while (i < n) {
        sum = sum + (long long)a[i] * b[i];
        i = i + 1;
    }

    printf("%lld", sum);

    return 0;
}

```

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✔ | 3<br>1<br>2<br>3<br>4<br>5<br>6 | 28 | 28 | ✔ |
| ✔ | 4<br>7<br>5<br>1<br>2<br>1<br>3<br>4<br>1 | 22 | 22 | ✔ |
| ✔ | 5<br>20<br>10<br>30<br>10<br>40<br>8<br>9<br>4<br>3<br>10 | 590 | 590 | ✔ |

Passed all tests! ✔

**Correct**

Marks for this submission: 1.00/1.00.