

# Team Notebook

NSU\_TernaryScreetch

June 24, 2022

## Contents

<b>1 Algebra</b>	<b>2</b>	<b>4 Data Structures</b>	<b>4</b>	4.3.6 nCrp-O(1) [SK] . . . . .	11
1.1 Fundamentals . . . . .	2	4.1 Graph . . . . .	4	4.3.7 Segment-Tree [SK] . . . . .	11
1.1.1 Extended GCD [NK] . . . . .	2	4.1.1 DSU [MB] . . . . .	4	4.3.8 Segment-TreeLazy-Updates [SK] . . . . .	12
1.1.2 Modular Binary Exponentiation (Power) [NK] . . . . .	2	4.1.2 DSU [NK] . . . . .	4	4.3.9 SegTree[MB] . . . . .	12
1.2 Modular Arithmetic . . . . .	2	4.1.3 LCA [MB] . . . . .	5	4.3.10 SparseTable[MB] . . . . .	12
1.2.1 Modular inverse [NK] . . . . .	2	4.2 NumberTheory . . . . .	5	4.4 String . . . . .	12
<b>2 Brute-force</b>	<b>2</b>	4.2.1 Combinatrics[MB] . . . . .	5	4.4.1 Hashing[MB] . . . . .	12
2.1 Power Set [NK] . . . . .	2	4.2.2 ModInt[MB] . . . . .	6	4.5 Trees . . . . .	13
<b>3 Concepts</b>	<b>2</b>	4.2.3 PrimePhiSieve[MB] . . . . .	7	<b>5 Starters</b>	<b>13</b>
3.1 General . . . . .	2	4.2.4 PrimeSieve[MB] . . . . .	7	5.1 C++ Include GNU PBDS [NK] . . . . .	13
3.1.1 Fraction[MB] . . . . .	2	4.3 QueryUpdate . . . . .	8	5.2 C++ Starter debug[MB] . . . . .	13
3.1.2 UnorderedMap[MB] . . . . .	2	4.3.1 BIT [MB] . . . . .	8	5.3 C++ Starter [MB] . . . . .	14
3.2 Graph . . . . .	3	4.3.2 Fraction-Functions [SK] . . . . .	8	5.4 C++ Starter [NK] . . . . .	14
3.2.1 edgeRemoveCC[MB] . . . . .	3	4.3.3 LazySegTree [MB] . . . . .	9	5.5 C++ Starter [SK] . . . . .	14
		4.3.4 Miller-Rabin-for-prime-checking [SK] . . . . .	10	<b>6 String Processing</b>	<b>14</b>
		4.3.5 MosAlgo [MB] . . . . .	10	6.1 Hashing [NK] . . . . .	14
				6.2 Z-Function [MB] . . . . .	18

# 1 Algebra

## 1.1 Fundamentals

### 1.1.1 Extended GCD [NK]

---

```
template <class Z>
constexpr Z extended_gcd(Z a, Z b, Z& x_ref, Z& y_ref) {
    x_ref = 1, y_ref = 0;
    Z x1 = 0, y1 = 1, tmp = 0, q = 0;
    while (b > 0) {
        q = a / b;
        tmp = a, a = b, b = tmp - (q * b);
        tmp = x_ref, x_ref = x1, x1 = tmp - (q * x1);
        tmp = y_ref, y_ref = y1, y1 = tmp - (q * y1);
    }
    return a;
}
```

---

### 1.1.2 Modular Binary Exponentiation (Power) [NK]

---

```
template <class B, class E, class M>
constexpr B power(B base, E expo, M mod = 0) {
    assert(expo >= 0);
    if (mod == 1) return 0;
    if (base == 0 || base == 1) return base;
    B res = 1;
    if (!mod) {
        while (expo) {
            if (expo & 1) res *= base;
            base *= base;
            expo >>= 1;
        }
    } else {
        assert(mod > 0);
        base %= mod;
        if (base <= 1) return base;
        while (expo) {
            if (expo & 1) res = (res * base) % mod;
            base = (base * base) % mod;
            expo >>= 1;
        }
    }
    return res;
}
```

---

## 1.2 Modular Arithmetic

### 1.2.1 Modular inverse [NK]

---

```
template <class Z>
constexpr Z inverse(Z num, Z mod) {
    assert(mod > 1);
    if (!(0 <= num && num < mod)) {
        num %= mod;
        if (num < 0) num += mod;
    }
    Z res = 1, tmp = 0;
    assert(extended_gcd(num, mod, res, tmp) == 1);
    if (res < 0) res += mod;
    return res;
}
```

---

# 2 Brute-force

## 2.1 Power Set [NK]

---

```
template <class T>
vector<vector<T>> power_set(const vector<T>& vec) {
    vector<vector<T>> res;
    list<T> buf;
    function<void(int)> recurse = [&](int i) -> void {
        if (i == vec.size()) {
            res.emplace_back(buf.begin(), buf.end());
            return;
        }
        recurse(i + 1);
        buf.push_back(vec[i]), recurse(i + 1), buf.pop_back();
    };
    recurse(0);
    return res;
}
```

---

# 3 Concepts

## 3.1 General

### 3.1.1 Fraction[MB]

---

```
struct Fraction {
    int p, q;

    Fraction (int _p, int _q) : p(_p), q(_q) {}

    std::strong_ordering operator<=> (const Fraction &oth) const {
        return p * oth.q <=> q * oth.p;
    }
};
```

---

### 3.1.2 UnorderedMap[MB]

---

```
#include <bits/stdc++.h>

// For gp_hash_table
#include <ext/pb_ds/assoc_container.hpp>

using namespace __gnu_pbds;
using namespace std;

struct custom_hash
{
    static uint64_t splitmix64(uint64_t x)
    {
        // http://xorshift.di.unimi.it/splitmix64.c
        x += 0x9e3779b97f4a7c15;
        x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
        x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
        return x ^ (x >> 31);
    }

    size_t operator()(uint64_t x) const
    {
        static const uint64_t FIXED_RANDOM = chrono::steady_clock::now().time_since_epoch().count();
        return splitmix64(x + FIXED_RANDOM);
    }
};

// Example Use
unordered_map<int, int, custom_hash> mp;

// Faster
gp_hash_table<int, int, custom_hash> mp;
```

---

## 3.2 Graph

### 3.2.1 edgeRemoveCC[MB]

---

```
#include <bits/stdc++.h>

using namespace std;

typedef long long ll;

#define var(...) " [" << #__VA_ARGS__ ": " << (__VA_ARGS__) << "]"
#define mem(x, n) memset(x, n, sizeof(x))
#define all(x) x.begin(), x.end()
#define sz(x) ((int)x.size())
#define vec vector
#define endl "\n"

class DSU
{
    std::vector<int> p, csz;

public:
    DSU() {}

    DSU(int dsz) // Max size
    {
        //Default empty
        p.resize(dsz + 5, 0), csz.resize(dsz + 5, 0);

        init(dsz);
    }

    void init(int n)
    {
        // n = size
        for (int i = 0; i <= n; i++)
        {
            p[i] = i, csz[i] = 1;
        }
    }

    //Return parent Recursively
    int get(int x)
    {
        if (p[x] != x)
            p[x] = get(p[x]);

        return p[x];
    }
}
```

```
// Return Size
int getSize(int x) { return csz[get(x)]; }
// Return if Union created Successfully or false if they
// are already in Union
bool merge(int x, int y)
{
    x = get(x), y = get(y);
    if (x == y)
        return false;

    if (csz[x] > csz[y])
        std::swap(x, y);

    p[x] = y;
    csz[y] += csz[x];

    return true;
}
};

void runCase([[maybe_unused]] const int &TC)
{
    int n, m;
    cin >> n >> m;

    auto g = vec(n + 1, set<int>());

    auto dsu = DSU(n + 1);

    for (int i = 0; i < m; i++)
    {
        int u, v;
        cin >> u >> v;

        g[u].insert(v);
        g[v].insert(u);
    }

    set<int> eligible;

    for (int i = 1; i <= n; i++)
    {
        eligible.insert(i);
    }

    int i = 1;
    int cnt = 0;

    while (sz(eligible))
```

```
{
    cnt++;
    queue<int> q;
    q.push(*eligible.begin());
    eligible.erase(eligible.begin());

    while (sz(q))
    {
        int fr = q.front();
        q.pop();

        auto v = eligible.begin();

        while (v != eligible.end())
        {
            if (g[fr].find(*v) == g[fr].end())
            {
                q.push(*v);
                v = eligible.erase(v);
            }
            else
            {
                v++;
            }
        }
    }

    cout << cnt - 1 << endl;
}

int main()
{
    ios_base::sync_with_stdio(false), cin.tie(0);

    int t = 1;
    //cin >> t;

    for (int tc = 1; tc <= t; tc++)
        runCase(tc);

    return 0;
}
```

### 3.2.2 treerooting[MB]

---

```
#include <bits/stdc++.h>

using namespace std;
```

```

typedef long long ll;

const int N = 2e5 + 5;

vector<int> g[N];
ll sz[N], dist[N], sum[N];

void dfs(int s, int p)
{
    sz[s] = 1;
    dist[s] = 0;
    for (int nxt : g[s])
    {
        if (nxt == p)
            continue;
        dfs(nxt, s);
        sz[s] += sz[nxt];
        dist[s] += (dist[nxt] + sz[nxt]);
    }
}

void dfs1(int s, int p)
{
    if (p != 0)
    {
        ll my_size = sz[s];
        ll my_contrib = (dist[s] + sz[s]);

        sum[s] = sum[p] - my_contrib + sz[s] - sz[s] + dist[s];
    }
    for (int nxt : g[s])
    {
        if (nxt == p)
            continue;
        dfs1(nxt, s);
    }
}

// problem link: https://cses.fi/problemset/task/1133

int main()
{
    int n;
    cin >> n;

    for (int i = 1, u, v; i < n; i++)
        cin >> u >> v, g[u].push_back(v), g[v].push_back(u);

```

```

dfs(1, 0);

sum[1] = dist[1];

dfs1(1, 0);

for (int i = 1; i <= n; i++)
    cout << sum[i] << " ";
cout << endl;

return 0;
}

```

## 4 Data Structures

### 4.1 Graph

#### 4.1.1 DSU [MB]

```

#include <bits/stdc++.h>

// 0 based
class DSU
{
    std::vector<int> p, csz;

public:
    DSU() {}

    //0 based
    DSU(int mx_size)
    {
        //Default empty
        p.resize(mx_size, 0), csz.resize(mx_size, 0);

        init(mx_size);
    }

    void init(int n)
    {
        // n = size
        for (int i = 0; i < n; i++)
        {
            p[i] = i, csz[i] = 1;
        }
    }

    //Return parent Recursively

```

```

int get(int x)
{
    if (p[x] != x)
        p[x] = get(p[x]);

    return p[x];
}

// Return Size
int get_comp_size(int component) { return csz[get(component)]; }

// Return if Union created Succesfully or false if they
// are already in Union
bool merge(int x, int y)
{
    x = get(x), y = get(y);
    if (x == y)
        return false;

    if (csz[x] > csz[y])
        std::swap(x, y);

    p[x] = y;
    csz[y] += csz[x];

    return true;
}
};

```

#### 4.1.2 DSU [NK]

```

struct DSU {
    int n_nodes = 0;
    int n_components = 0;
    vector<int> component_size;
    vector<int> component_root;

    DSU(int n_nodes, bool make_all_nodes = false)
        : n_nodes(n_nodes),
          component_root(n_nodes, -1),
          component_size(n_nodes, 0) {
        if (make_all_nodes) {
            for (int i = 0; i < n_nodes; ++i) {
                make_node(i);
            }
        }
    }

    void make_node(int v) {

```

```

    if (component_root[v] == -1) {
        component_root[v] = v;
        component_size[v] = 1;
        ++n_components;
    }
}

int root(int v) {
    auto res = v;
    while (component_root[res] != res) {
        res = component_root[res];
    }
    while (v != res) {
        auto u = component_root[v];
        component_root[v] = res;
        v = u;
    }
    return res;
}

int connect(int u, int v) {
    u = root(u), v = root(v);
    if (u == v) return u;
    if (component_size[u] < component_size[v]) {
        swap(u, v);
    }
    component_root[v] = u;
    component_size[u] += component_size[v];
    --n_components;
}
};

```

### 4.1.3 LCA [MB]

```

struct LCA
{
private:
    int n, lg;
    std::vector<int> depth;
    std::vector<std::vector<int>> up;
    std::vector<std::vector<int>> g;

public:
    LCA() : n(0), lg(0) {}

    LCA(int _n)
    {
        this->n = _n;
        lg = log2(n) + 2;
    }
};

```

```

    depth.resize(n + 5, 0);
    up.resize(n + 5, std::vector<int>(lg, 0));
    g.resize(n + 1);
}

LCA(std::vector<std::vector<int>> &graph) : LCA(graph.size()
())
{
    for (int i = 0; i < (int)graph.size(); i++)
        g[i] = graph[i];

    dfs(1, 0);
}

void dfs(int curr, int p)
{
    up[curr][0] = p;
    for (int next : g[curr])
    {
        if (next == p)
            continue;
        depth[next] = depth[curr] + 1;
        up[next][0] = curr;
        for (int j = 1; j < lg; j++)
            up[next][j] = up[up[next][j - 1]][j - 1];
        dfs(next, curr);
    }
}

void clear_v(int a)
{
    g[a].clear();
}

void clear(int n_ = -1)
{
    if (n_ == -1)
        n_ = ((int)(g.size())) - 1;

    for (int i = 0; i <= n_; i++)
    {
        g[i].clear();
    }
}

void add(int a, int b)
{
    g[a].push_back(b);
}

```

```

int par(int a)
{
    return up[a][0];
}

int get_lca(int a, int b)
{
    if (depth[a] < depth[b])
        std::swap(a, b);

    int k = depth[a] - depth[b];
    for (int j = lg - 1; j >= 0; j--)
    {
        if (k & (1 << j))
            a = up[a][j];
    }

    if (a == b)
        return a;

    for (int j = lg - 1; j >= 0; j--)
        if (up[a][j] != up[b][j])
        {
            a = up[a][j];
            b = up[b][j];
        }

    return up[a][0];
}

int get_dist(int a, int b)
{
    return depth[a] + depth[b] - 2 * depth[get_lca(a, b)];
}
};

```

## 4.2 NumberTheory

### 4.2.1 Combinatrics[MB]

```

#include <bits/stdc++.h>

using namespace std;

typedef long long ll;

const int N = 1e6, MOD = 998244353;

struct Combinatrics

```

```

{
vector<ll> fact, fact_inv, inv;
ll mod, nl;

Combinatrics() {}

Combinatrics(ll n, ll mod)
{
this->nl = n;
this->mod = mod;
fact.resize(n + 1, 1), fact_inv.resize(n + 1, 1), inv.
    resize(n + 1, 1);
init();
}

void init()
{
fact[0] = 1;

for (int i = 1; i <= nl; i++)
{
fact[i] = (fact[i - 1] * i) % mod;
}

inv[0] = inv[1] = 1;
for (int i = 2; i <= nl; i++)
    inv[i] = inv[mod % i] * (mod - mod / i) % mod;

fact_inv[0] = fact_inv[1] = 1;

for (int i = 2; i <= nl; i++)
    fact_inv[i] = (inv[i] * fact_inv[i - 1]) % mod;
}

ll ncr(ll n, ll r)
{
if (n < r)
{
return 0;
}

if (n > nl)
return ncr(n, r, mod);
return (((fact[n] * 1LL * fact_inv[r]) % mod) * 1LL *
    fact_inv[n - r]) % mod;
}

ll npr(ll n, ll r)
{
if (n < r)

```

```

{
return 0;
}

if (n > nl)
return npr(n, r, mod);
return (fact[n] * 1LL * fact_inv[n - r]) % mod;
}

ll big_mod(ll a, ll p, ll m = -1)
{
m = (m == -1 ? mod : m);
ll res = 1 % m, x = a % m;
while (p > 0)
    res = ((p & 1) ? ((res * x) % m) : res), x = ((x * x) % m), p >>= 1;
return res;
}

ll mod_inv(ll a, ll p)
{
return big_mod(a, p - 2, p);
}

ll ncr(ll n, ll r, ll p)
{
if (n < r)
return 0;
if (r == 0)
return 1;
return (((fact[n] * mod_inv(fact[r], p)) % p) * mod_inv(
    fact[n - r], p)) % p;
}

ll npr(ll n, ll r, ll p)
{
if (n < r)
return 0;
if (r == 0)
return 1;
return (fact[n] * mod_inv(fact[n - r], p)) % p;
}
};

```

#### 4.2.2 ModInt[MB]

```

#include <bits/stdc++.h>
// Tested By Ac

```

```

// submission : https://atcoder.jp/contests/abc238/
// submissions/29247261
// problem : https://atcoder.jp/contests/abc238/tasks/
// abc238_c

template <const int MOD>
struct ModInt
{
int val;
ModInt() { val = 0; }
ModInt(long long v) { v += (v < 0 ? MOD : 0), val = (int)(v
    % MOD); }
ModInt &operator+=(const ModInt &rhs)
{
val += rhs.val, val -= (val >= MOD ? MOD : 0);
return *this;
}
ModInt &operator-=(const ModInt &rhs)
{
val -= rhs.val, val += (val < 0 ? MOD : 0);
return *this;
}
ModInt &operator*=(const ModInt &rhs)
{
val = (int)((val * 1ULL * rhs.val) % MOD);
return *this;
}
ModInt pow(long long n) const
{
ModInt x = *this, r = 1;
while (n)
    r = ((n & 1) ? r * x : r), x = (x * x), n >>= 1;
return r;
}
ModInt inv() const { return this->pow(MOD - 2); }
ModInt &operator/=(const ModInt &rhs) { return *this = *
    this * rhs.inv(); }
friend ModInt operator+(const ModInt &lhs, const ModInt &
    rhs) { return ModInt(lhs) += rhs; }
friend ModInt operator-(const ModInt &lhs, const ModInt &
    rhs) { return ModInt(lhs) -= rhs; }
friend ModInt operator*(const ModInt &lhs, const ModInt &
    rhs) { return ModInt(lhs) *= rhs; }
friend ModInt operator/(const ModInt &lhs, const ModInt &
    rhs) { return ModInt(lhs) /= rhs; }
friend bool operator==(const ModInt &lhs, const ModInt &rhs
    ) { return lhs.val == rhs.val; }
friend bool operator!=(const ModInt &lhs, const ModInt &rhs
    ) { return lhs.val != rhs.val; }
}

```

```

friend std::ostream &operator<<(std::ostream &out, const
    ModInt &m) { return out << m.val; }
friend std::istream &operator>>(std::istream &in, ModInt &m
    ) { return in >> m.val; }
operator int() const { return val; }
};

const int MOD = 1e9 + 7;
using mint = ModInt<MOD>;

```

#### 4.2.3 PrimePhiSieve[MB]

```

#include <bits/stdc++.h>

using namespace std;

typedef long long ll;
typedef pair<int, int> pii;
typedef pair<ll, ll> pll;

struct PrimePhiSieve
{
private:
    ll n;
    vector<ll> primes, phi;
    vector<bool> is_prime;

public:
    PrimePhiSieve() {}

    PrimePhiSieve(ll n)
    {
        this->n = n, is_prime.resize(n + 5, true), phi.resize(n +
            5, 1);
        phi_sieve();
    }
    void phi_sieve()
    {
        is_prime[0] = is_prime[1] = false;

        for (ll i = 1; i <= n; i++)
            phi[i] = i;

        for (ll i = 1; i <= n; i++)
            if (is_prime[i])
            {
                primes.push_back(i);
                phi[i] *= (i - 1), phi[i] /= i;
            }
    }

```

```

        for (ll j = i + i; j <= n; j += i)
            is_prime[j] = false, phi[j] /= i, phi[j] *= (i - 1);
    }

    ll get_divisors_count(int number, int divisor)
    {
        return phi[number / divisor];
    }

    vector<pll> factorize(ll num)
    {
        vector<pll> a;
        for (int i = 0; i < (int)primes.size() && primes[i] * 1LL
            * primes[i] <= num; i++)
            if (num % primes[i] == 0)
            {
                int cnt = 0;
                while (num % primes[i] == 0)
                    cnt++, num /= primes[i];
                a.push_back({primes[i], cnt});
            }

        if (num != 1)
            a.push_back({num, 1});
        return a;
    }

    ll get_phi(int n)
    {
        return phi[n];
    }
    // (n/p) * (p-1) => n - (n/p);
    void segmented_phi_sieve(ll l, ll r)
    {
        vector<ll> current_phi(r - l + 1);
        vector<ll> left_over_prime(r - l + 1);

        for (ll i = 1; i <= r; i++)
            current_phi[i - l] = i, left_over_prime[i - l] = i;

        for (ll p : primes)
        {
            ll to = ((l + p - 1) / p) * p;

            if (to == p)
                to += p;

            for (ll i = to; i <= r; i += p)
            {

```

```

                while (left_over_prime[i - l] % p == 0)
                    left_over_prime[i - l] /= p;
                current_phi[i - l] -= current_phi[i - l] / p;
            }
        }

        for (ll i = 1; i <= r; i++)
        {
            if (left_over_prime[i - l] > 1)
                current_phi[i - l] -= current_phi[i - l] /
                    left_over_prime[i - l];
            cout << current_phi[i - l] << endl;
        }
    }

    ll phi_sqrt(ll n)
    {
        ll res = n;

        for (ll i = 1; i * i <= n; i++)
        {
            if (n % i == 0)
            {
                res /= i;
                res *= (i - 1);

                while (n % i == 0)
                    n /= i;
            }
        }

        if (n > 1)
            res /= n, res *= (n - 1);
        return res;
    }
};

```

#### 4.2.4 PrimeSieve[MB]

```

#include <bits/stdc++.h>

using namespace std;

typedef long long ll;
typedef pair<int, int> pii;
typedef pair<ll, ll> pll;

struct PrimeSieve
{

```

```

public:
vector<int> primes;
vector<bool> isprime;
int n;

PrimeSieve() {}

PrimeSieve(int n)
{
    this->n = n, isprime.resize(n + 5, true), primes.clear();
    sieve();
}

void sieve()
{
    isprime[0] = isprime[1] = false;

    primes.push_back(2);
    for (int i = 4; i <= n; i += 2)
        isprime[i] = false;

    for (int i = 3; 1LL * i * i <= n; i += 2)
        if (isprime[i])
            for (int j = i * i; j <= n; j += 2 * i)
                isprime[j] = false;

    for (int i = 3; i <= n; i += 2)
        if (isprime[i])
            primes.push_back(i);
}

vector<pll> factorize(ll num)
{
    vector<pll> a;
    for (int i = 0; i < (int)primes.size() && primes[i] * 1LL
        * primes[i] <= num; i++)
        if (num % primes[i] == 0)
        {
            int cnt = 0;
            while (num % primes[i] == 0)
                cnt++, num /= primes[i];
            a.push_back({primes[i], cnt});
        }

    if (num != 1)
        a.push_back({num, 1});
    return a;
}

vector<ll> segmented_sieve(ll l, ll r)

```

```

{
    vector<ll> seg_primes;
    vector<bool> current_primes(r - l + 1, true);
    for (ll p : primes)
    {
        ll to = (l / p) * p;
        if (to < l)
            to += p;
        if (to == p)
            to += p;
        for (ll i = to; i <= r; i += p)
        {
            current_primes[i - l] = false;
        }
    }

    for (int i = l; i <= r; i++)
    {
        if (i < 2)
            continue;
        if (current_primes[i - l])
        {
            seg_primes.push_back(i);
        }
    }
    return seg_primes;
}
};

```

## 4.3 QueryUpdate

### 4.3.1 BIT [MB]

```

struct BIT
{
private:
    std::vector<long long> mArray;

public:
    BIT(int sz) // Max size of the array
    {
        mArray.resize(sz + 1, 0);
    }

    void build(const std::vector<long long> &list)
    {
        for (int i = 1; i <= list.size(); i++)
        {

```

```

            mArray[i] = list[i];
        }

        for (int ind = 1; ind <= mArray.size(); ind++)
        {
            int ind2 = ind + (ind & -ind);
            if (ind2 <= mArray.size())
            {
                mArray[ind2] += mArray[ind];
            }
        }

        long long prefix_query(int ind)
        {
            int res = 0;
            for (; ind > 0; ind -= (ind & -ind))
            {
                res += mArray[ind];
            }
            return res;
        }

        long long range_query(int from, int to)
        {
            return prefix_query(to) - prefix_query(from - 1);
        }

        void add(int ind, long long add)
        {
            for (; ind < mArray.size(); ind += (ind & -ind))
            {
                mArray[ind] += add;
            }
        }
};

```

### 4.3.2 Fraction-Functions [SK]

```

pair<ll,ll> frac_add(pair<ll,ll> a,pair<ll,ll> b)
{
    ll g = a.second*b.second;
    pair<ll,ll> x;
    x.second = g;
    x.first = a.first * (b.second) + b.first * (a.second);
    ll y = __gcd(x.first,x.second);
    x.first/=y;
    x.second/=y;
}

```



```

    return x;
}
pair<ll,ll> frac_mult(pair<ll,ll> a,pair<ll,ll> b)
{
    pair<ll,ll> x;

    x.first = a.first * b.first;
    x.second = a.second * b.second;
    ll y = __gcd(x.first,x.second);
    x.first/=y;
    x.second/=y;
    return x;
}

```

### 4.3.3 LazySegTree [MB]

```

template <typename T, typename F, T (*op)(T, T), F (*
    lazy_to_lazy)(F, F), T (*lazy_to_seg)(T, F, int, int)>
struct LazySegTree
{
private:
    std::vector<T> segt;
    std::vector<F> lazy;
    int n;
    T neutral;
    F lazyE;

    int left(int si) { return si * 2; }
    int right(int si) { return si * 2 + 1; }
    int midpoint(int ss, int se) { return (ss + (se - ss) / 2);
    }

    T query(int ss, int se, int si, int qs, int qe)
    {
        // **** //
        if (lazy[si] != lazyE)
        {
            T curr = lazy[si];
            lazy[si] = lazyE;
            segt[si] = lazy_to_seg(segt[si], curr, ss, se);

            if (ss != se)
            {
                lazy[left(si)] = lazy_to_lazy(lazy[left(si)], curr);
                lazy[right(si)] = lazy_to_lazy(lazy[right(si)], curr);
            }
        }

        if (ss < qs || qe < ss)
            return neutral;

        if (qs <= ss && qe >= se)
            return segt[si];

        int mid = midpoint(ss, se);

        return op(query(ss, mid, left(si), qs, qe), query(mid + 1,
            se, right(si), qs, qe));
    }

    void update(int ss, int se, int si, int qs, int qe, F val)
    {
        // **** //

        if (lazy[si] != lazyE)
        {
            F curr = lazy[si];
            lazy[si] = lazyE;
            segt[si] = lazy_to_seg(segt[si], curr, ss, se);

            if (ss != se)
            {
                lazy[left(si)] = lazy_to_lazy(lazy[left(si)], curr);
                lazy[right(si)] = lazy_to_lazy(lazy[right(si)], curr);
            }
        }

        if (ss < qs || qe < ss)
            return;

        if (qs <= ss && qe >= se)
            segt[si] = lazy_to_seg(segt[si], val, ss, se);

        if (ss != se)
        {
            lazy[left(si)] = lazy_to_lazy(lazy[left(si)], val);
            lazy[right(si)] = lazy_to_lazy(lazy[right(si)], val);
        }
        return;
    }

    int mid = midpoint(ss, se);

    update(mid + 1, se, si * 2 + 1, qs, qe, val);
    update(ss, mid, left(si), qs, qe, val);
}

```

```

    if (se < qs || qe < ss)
        return neutral;

    if (qs <= ss && qe >= se)
        return segt[si];

    int mid = midpoint(ss, se);

    return op(query(ss, mid, left(si), qs, qe), query(mid + 1,
        se, right(si), qs, qe));
}

void update(int ss, int se, int si, int qs, int qe, F val)
{
    // **** //

    if (lazy[si] != lazyE)
    {
        F curr = lazy[si];
        lazy[si] = lazyE;
        segt[si] = lazy_to_seg(segt[si], curr, ss, se);
        if (ss != se)
        {
            lazy[left(si)] = lazy_to_lazy(lazy[left(si)], curr);
            lazy[right(si)] = lazy_to_lazy(lazy[right(si)], curr);
        }
    }

    if (se < qs || qe < ss)
        return;

    if (qs <= ss && qe >= se)
    {
        // **** //

        segt[si] = lazy_to_seg(segt[si], val, ss, se);

        if (ss != se)
        {
            lazy[left(si)] = lazy_to_lazy(lazy[left(si)], val);
            lazy[right(si)] = lazy_to_lazy(lazy[right(si)], val);
        }
        return;
    }

    int mid = midpoint(ss, se);

    update(mid + 1, se, si * 2 + 1, qs, qe, val);
    update(ss, mid, left(si), qs, qe, val);
}

```

```

    segt[si] = op(segt[left(si)], segt[right(si)]);
}

public:
    LazySegTree() : n(0) {}

    LazySegTree(int sz, T ini, T _neutral, F _lazyE)
    {
        this->n = sz + 1;
        this->neutral = _neutral;
        this->lazyE = _lazyE;
        segt.resize(n * 4 + 5, ini);
        lazy.resize(n * 4 + 5, _lazyE);
    }

    LazySegTree(const std::vector<T> &arr, T ini, T _neutral, F
        _lazyE) : LazySegTree((int)arr.size(), ini, _neutral,
        _lazyE)
    {
        init(arr);
    }

    void init(const std::vector<T> &arr)
    {
        this->n = (int)arr.size();
        for (int i = 0; i < n; i++)
            set(i, i, arr[i]);
    }

    T get(int qs, int qe)
    {
        return query(0, n - 1, 1, qs, qe);
    }

    void set(int from, int to, F val)
    {
        update(0, n - 1, 1, from, to, val);
    }
};

int op(int a, int b)
{
    return a + b;
}

int lazy_to_seg(int seg, int lazy_v, int l, int r)
{
    return seg + (lazy_v * (r - l + 1));
}

```

```
int lazy_to_lazy(int curr_lazy, int input_lazy)
{
    return curr_lazy + input_lazy;
}
```

#### 4.3.4 Miller-Rabin-for-prime-checking [SK]

```
typedef long long ll;

ll mulmod(ll a, ll b, ll c) {
    ll x = 0, y = a % c;
    while (b) {
        if (b & 1) x = (x + y) % c;
        y = (y << 1) % c;
        b >>= 1;
    }
    return x % c;
}

ll fastPow(ll x, ll n, ll MOD) {
    ll ret = 1;
    while (n) {
        if (n & 1) ret = mulmod(ret, x, MOD);
        x = mulmod(x, x, MOD);
        n >>= 1;
    }
    return ret;
}

bool isPrime(ll n) {
    ll d = n - 1;
    int s = 0;
    while (d % 2 == 0) {
        s++;
        d >>= 1;
    }

    // It's guranteed that these values will work for any
    // number smaller than 3*10**18 (3 and 18 zeros)
    int a[9] = { 2, 3, 5, 7, 11, 13, 17, 19, 23 };
    for(int i = 0; i < 9; i++) {
        bool comp = fastPow(a[i], d, n) != 1;
        if(comp) for(int j = 0; j < s; j++) {
            ll fp = fastPow(a[i], (1LL << (11)j)*d, n);
            if (fp == n - 1) {
                comp = false;
                break;
            }
        }
    }
}
```

```
    if(comp) return false;
}
return true;
}
```

#### 4.3.5 MosAlgo [MB]

```
#include <bits/stdc++.h>

using namespace std;

const int N = 3e4 + 5;
const int blk = sqrt(N) + 1;

struct Query
{
    int l, r, i;
    bool operator<(const Query q) const
    {
        if (this->l / blk == q.l / blk)
            return this->r < q.r;
        return this->l / blk < q.l / blk;
    }
};

vector<int> mos_algorithm(vector<Query> &queries, vector<
    int> &a)
{
    vector<int> answers(queries.size());
    sort(queries.begin(), queries.end());

    int sza = 1e6 + 5;
    vector<int> freq(sza);

    int cnt = 0;

    auto add = [&](int x) -> void
    {
        freq[x]++;
        if (freq[x] == 1)
            cnt++;
    };

    auto remove = [&](int x) -> void
    {
        freq[x]--;
        if (freq[x] == 0)
            cnt--;
    };

    int l = 0;
    int r = -1;
    for (Query q : queries)
    {
        while (l > q.l)
        {
            l--;
            add(a[l]);
        }
        while (r < q.r)
        {
            r++;
            add(a[r]);
        }
        while (l < q.l)
        {
            remove(a[l]);
            l++;
        }
        while (r > q.r)
        {
            remove(a[r]);
            r--;
        }
        answers[q.i] = cnt;
    }
    return answers;
}

int main()
{
    int n;
    cin >> n;

    vector<int> a(n);
    for (int i = 0; i < n; i++)
        cin >> a[i];

    int q;
    cin >> q;

    vector<Query> qr(q);

    for (int i = 0; i < q; i++)
    {
        int l, r;
        cin >> l >> r;

        l--, r--;
    }
}
```

```

    qr[i].l = l, qr[i].r = r, qr[i].i = i;
}

vector<int> res = mos_algorithm(qr, a);

for (int i = 0; i < q; i++)
    cout << res[i] << endl;

return 0;
}

```

#### 4.3.6 nCrp-O(1) [SK]

```

// array to store inverse of 1 to N
ll factorialNumInverse[N + 1];

// array to precompute inverse of 1! to N!
ll naturalNumInverse[N + 1];

// array to store factorial of first N numbers
ll fact[N + 1];

// Function to precompute inverse of numbers
void InverseofNumber(ll p)
{
    naturalNumInverse[0] = naturalNumInverse[1] = 1;
    for (int i = 2; i <= N; i++)
        naturalNumInverse[i] = naturalNumInverse[p % i] * (p
            - p / i) % p;
}

// Function to precompute inverse of factorials
void InverseofFactorial(ll p)
{
    factorialNumInverse[0] = factorialNumInverse[1] = 1;

    // precompute inverse of natural numbers
    for (int i = 2; i <= N; i++)
        factorialNumInverse[i] = (naturalNumInverse[i] *
            factorialNumInverse[i - 1]) % p;
}

// Function to calculate factorial of 1 to N
void factorial(ll p)
{
    fact[0] = 1;

    // precompute factorials
    for (int i = 1; i <= N; i++) {
        fact[i] = (fact[i - 1] * i) % p;
    }
}

```

```

    }
}

// Function to return nCr % p in O(1) time
ll Binomial(ll N, ll R, ll p)
{
    // n C r = n!*inverse(r!)*inverse((n-r)!)
    ll ans = ((fact[N] * factorialNumInverse[R])
        % p * factorialNumInverse[N - R])
        % p;
    return ans;
}

```

#### 4.3.7 Segment-Tree [SK]

```

pair<int,int>v[4*N];
int arr[N];

void build(int cur,int l,int r)
{
    if(l==r)
    {
        pair<int,int> tmp = {0,0};
        if(arr[l]==0)
        {
            tmp.second++;
        }
        else if(arr[l]<0)
        {
            tmp.first++;
        }
        v[cur] = tmp;
        return;
    }

    int mid = l + (r-l)/2;

    build(cur*2,l,mid);
    build(cur*2 + 1,mid+1,r);

    v[cur].first = v[cur*2].first + v[cur*2 + 1].first;
    v[cur].second = v[cur*2].second + v[cur*2 + 1].second;
    return;
}

pair<int,int>query(int cur,int l,int r,int x,int y)
{
    if(l==x && r==y)
    {

```

```

        return v[cur];
    }

    if(x>r || y<l)
    {
        return {-1,-1};
    }

    int mid = l + (r-l)/2;
    pair<int,int> left = query(cur*2,l,mid,x,min(mid,y));
    pair<int,int> right = query(cur*2 + 1,mid+1,r,max(mid+1,y),y);

    pair<int,int> res = {0,0};
    res.first = ((left.first!=-1)?left.first:0) + ((right.
        first!=-1)?right.first:0);
    res.second = ((left.second!=-1)?left.second:0) + ((right.
        second!=-1)?right.second:0);

    return res;
}

void update(int cur,int l,int r,int pos,int val)
{
    if(l==r)
    {
        arr[l] = val;
        pair<int,int> tmp = {0,0};
        if(arr[l]==0)
        {
            tmp.second++;
        }
        else if(arr[l]<0)
        {
            tmp.first++;
        }
        v[cur] = tmp;
        return;
    }

    int mid = l + (r-l)/2;

    if(pos<=mid)
    {
        update(cur*2,l,mid,pos,val);
    }
    else
    {
        update(cur*2 + 1,mid+1,r,pos,val);
    }
}

```

```

    v[cur].first = v[cur*2].first + v[cur*2 + 1].first;
    v[cur].second = v[cur*2].second + v[cur*2 + 1].second;
    return;
}

```

### 4.3.8 Segment-TreeLazy-Updates [SK]

```

ll v[4*N];
ll add[4*N];
int arr[N];

void push(int cur)
{
    add[cur*2] += add[cur];
    add[cur*2 + 1] += add[cur];
    add[cur] = 0;
}

/*
void build(int cur,int l,int r)
{
    if(l==r)
    {
        v[cur] = arr[l];
        return;
    }

    int mid = l + (r-1)/2;

    build(cur*2,l,mid);
    build(cur*2 + 1,mid+1,r);

    v[cur]= v[cur*2] + v[cur*2 + 1];

    return;
}
*/

ll query(int cur,int l,int r,int x,int y)
{
    if(x>r || y<l)
    {
        return 0;
    }

    if(l==r)

```

```

{
    return v[cur] + add[cur];
}

if(l==x && r==y)
{
    return v[cur] + add[cur]*(r-l+1);
}

int mid = l + (r-1)/2;

v[cur] += add[cur]*(r-l+1);
push(cur);

ll left = query(cur*2,l,mid,x,min(mid,y));
ll right = query(cur*2 + 1,mid+1,r,max(mid+1,x),y);

ll res = 0;

res = left + right ;

return res;
}

void update(int cur,int l,int r,int s,int e,int val)
{
    if(l==s && r==e)
    {
        add[cur] += val;
        return;
    }

    if(s>r || e<l)
    {
        return;
    }

    int mid = l + (r-1)/2;

    push(cur);

    update(cur*2,l,mid,s,min(e,mid),val);
    update(cur*2 + 1,mid+1,r,max(s,mid+1),e,val);

    v[cur] = (v[cur*2] + add[cur*2]*(mid-l+1)) + (v[cur*2 + 1] + add[cur*2 + 1]*(r-mid));

    return;
}

```

```

}

```

### 4.3.9 SegTree[MB]

### 4.3.10 SparseTable[MB]

## 4.4 String

### 4.4.1 Hashing[MB]

```

#include <bits/stdc++.h>

using namespace std;

typedef long long ll;

const int PRIMES[] = {2147462393, 2147462419, 2147462587,
    2147462633, 2147462747, 2147463167, 2147463203,
    2147463569, 2147463727, 2147463863, 2147464211,
    2147464549, 2147464751, 2147465153, 2147465563,
    2147465599, 2147465743, 2147465953, 2147466457,
    2147466463, 2147466521, 2147466721, 2147467009,
    2147467057, 2147467067, 2147467261, 2147467379,
    2147467463, 2147467669, 2147467747, 2147468003,
    2147468317, 2147468591, 2147468651, 2147468779,
    2147468801, 2147469017, 2147469041, 2147469173,
    2147469229, 2147469593, 2147469881, 2147469983,
    2147470027, 2147470081, 2147470177, 2147470673,
    2147470823, 2147471057, 2147471327, 2147471581,
    2147472137, 2147472161, 2147472689, 2147472697,
    2147472863, 2147473151, 2147473369, 2147473733,
    2147473891, 2147473963, 2147474279, 2147474921,
    2147474929, 2147475107, 2147475221, 2147475347,
    2147475397, 2147475971, 2147476739, 2147476769,
    2147476789, 2147476927, 2147477063, 2147477107,
    2147477249, 2147477807, 2147477933, 2147478017,
    2147478521};

// ll base_pow,base_pow_1;
ll base1 = 43, base2 = 47, mod1 = 1e9 + 7, mod2 = 1e9 + 9;

// **** Enable this function for codeforces
void generateRandomBM()
{

```

```

unsigned int seed = chrono::system_clock::now().
    time_since_epoch().count();
srand(seed); /// to avoid getting hacked in CF, comment
              this line for easier debugging

int q_len = (sizeof(PRIMES) / sizeof(PRIMES[0])) / 4;
base1 = PRIMES[rand() % q_len];
mod1 = PRIMES[rand() % q_len + q_len];
base2 = PRIMES[rand() % q_len + 2 * q_len];
mod2 = PRIMES[rand() % q_len + 3 * q_len];
}

struct Hash
{
public:
    vector<int> base_pow, f_hash, r_hash;
    ll base, mod;

    Hash() {}
    // Update it make it more dynamic like segTree class and
    // DSU
    Hash(int mxSize, ll base, ll mod) // Max size
    {
        this->base = base;
        this->mod = mod;
        base_pow.resize(mxSize + 2, 1), f_hash.resize(mxSize + 2,
            0), r_hash.resize(mxSize + 2, 0);

        for (int i = 1; i <= mxSize; i++)
        {
            base_pow[i] = base_pow[i - 1] * base % mod;
        }

        void init(string s)
        {
            int n = s.size();

            for (int i = 1; i <= n; i++)
            {
                f_hash[i] = (f_hash[i - 1] * base + int(s[i - 1])) % mod;
            }

            for (int i = n; i >= 1; i--)
            {
                r_hash[i] = (r_hash[i + 1] * base + int(s[i - 1])) % mod;
            }

            int forward_hash(int l, int r)

```

```

{
    int h = f_hash[r + 1] - (1LL * base_pow[r - 1 + 1] *
        f_hash[l]) % mod;
    return h < 0 ? mod + h : h;
}

int reverse_hash(int l, int r)
{
    int h = r_hash[l + 1] - (1LL * base_pow[r - 1 + 1] *
        r_hash[r + 2]) % mod;
    return h < 0 ? mod + h : h;
}
};

class DHash
{
public:
    Hash sh1, sh2;
    DHash() {}

    DHash(int mx_size)
    {
        sh1 = Hash(mx_size, base1, mod1);
        sh2 = Hash(mx_size, base2, mod2);
    }

    void init(string s)
    {
        sh1.init(s);
        sh2.init(s);
    }

    ll forward_hash(int l, int r)
    {
        return (ll(sh1.forward_hash(l, r)) << 32) | (sh2.
            forward_hash(l, r));
    }

    ll reverse_hash(int l, int r)
    {
        return ((ll(sh1.reverse_hash(l, r)) << 32) | (sh2.
            reverse_hash(l, r)));
    }
};

```

## 4.5 Trees

## 5 Starters

### 5.1 C++ Include GNU PBDS [NK]

```

#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
namespace pbds = __gnu_pbds;

template <class T>
using ordered_set = pbds::tree<T, pbds::null_type, std::less
    <T>,
                                pbds::rb_tree_tag,
                                pbds::
                                    tree_order_statistics_node_update
                                >;

template <class K, class V>
using hash_map = pbds::gp_hash_table<K, V>;

```

### 5.2 C++ Starter debug[MB]

```

#include <bits/stdc++.h>

using namespace std;

template <typename T, typename C = typename T::value_type>
typename enable_if<!is_same<T, string>::value, ostream &>::
    type operator<<(ostream &out, const T &c)
{
    for (auto it = c.begin(); it != c.end(); it++)
        out << (it == c.begin() ? "{ " : ", ") << *it;
    return out << (c.empty() ? "}" : ", ") << " ";
}

template <typename T, typename S>
ostream &operator<<(ostream &out, const pair<T, S> &p)
{
    return out << "{" << p.first << ", " << p.second << " ";
}

#define dbg(...) _dbg_print(__VA_ARGS__, __VA_ARGS__);

template <typename Arg1>
void _dbg_print(const char *name, Arg1 &&arg1)
{
    if (name[0] == ' ')
        name++;
}

```

```

cout << "[" << name << ": " << arg1 << "]"
<< "\n";
}

template <typename Arg1, typename... Args>
void _dbg_print(const char *names, Arg1 &&arg1, Args &&...
    args)
{
    const char *comma = strchr(names + 1, ',');
    cout << "[";
    cout.write(names, comma - names) << ": " << arg1 << "]" << " ";
    _dbg_print(comma + 1, args...);
}

```

### 5.3 C++ Starter [MB]

```

#if defined LOCAL && !defined ONLINE_JUDGE
#include "debug.cpp"
#else
#include <bits/stdc++.h>
using namespace std;
#define dbg(...) ;
#endif

typedef long long ll;
typedef pair<int, int> pii;
typedef pair<ll, ll> pll;

#define mem(x, n) memset(x, n, sizeof(x))
#define all(x) x.begin(), x.end()
#define sz(x) ((int)(x).size())
#define vec vector

inline bool read(auto &...a) { return (((cin >> a) ? true :
    false) && ...); }

inline void print(const auto &...a) { ((cout << a), ...); }
inline void println(const auto &...a) { print(a..., '\n'); }

void run_case([[maybe_unused]] const int &TC)
{

}

int main()
{
    ios_base::sync_with_stdio(false), cin.tie(0);

    int tt = 1;

```

```

read(tt);

for (int tc = 1; tc <= tt; tc++)
    run_case(tc);

return 0;
}

```

### 5.4 C++ Starter [NK]

```

#include <bits/stdc++.h>
using namespace std;

constexpr double eps = 1e-9;
constexpr int inf = 1 << 30;
constexpr int mod = 1e9 + 7;
constexpr int nmax = 1e6;

void runcase(int casen) {

    // cout << "Case " << casen << ": " << '\n';
}

int main() {
    ios_base::sync_with_stdio(false);
    cin.tie(nullptr);

    int ncases = 1;
    cin >> ncases; // Comment out for single-case tests
    for (int casen = 1; casen <= ncases; ++casen) {
        runcase(casen);
    }

    return 0;
}

```

### 5.5 C++ Starter [SK]

```

#include<bits/stdc++.h>
using namespace std;

typedef long long ll;
typedef unsigned long long ull;
#define endl "\n"
#define pi 3.142
const double eps = 1e-10;
int dx[] = {1,0,-1,0};

```

```

int dy[] = {0,1,0,-1};

const ll M = (1ll)(1e9) + 7;
const ll inf = (1ll)1e17;
const int N = (1ll)(1e6 + 10);

int main()
{

    cin.tie(0);
    cout.tie(0);
    ios_base::sync_with_stdio(false);

    //freopen("two.in", "r", stdin);
    //freopen("out.txt", "w", stdout);

}

/*
*/

```

## 6 String Processing

### 6.1 Hashing [NK]

```

#include <bits/stdc++.h>
using namespace std;

namespace hash_utils {
    constexpr std::array<int, 10U>
        bases = {257, 263, 269, 271, 277, 281, 283, 293, 307,
            311};
    constexpr std::array<int, 10U>
        moduli = {1000000007, 1000000009, 1000000021,
            1000000033, 1000000087,
            1000000093, 1000000097, 1000000103,
            1000000123, 1000000181};
} // namespace hash_utils

template <std::size_t Dim, class Tp>
using require_valid_hash_params_t =

```

```

std::enable_if_t<(1U <= Dim && Dim <= 3U) &&
    (std::is_same<Tp, int>::value ||
     std::is_same<Tp, std::int64_t>::value)>;

template <std::size_t Dim, class Tp = int,
         class = require_valid_hash_params_t<Dim, Tp>>
class Rolling_hash {
private:
    using Vec = std::vector<Tp>;

    static std::conditional_t<Dim == 1U, Tp, std::array<Tp,
        Dim>> base_;
    static std::conditional_t<Dim == 1U, Tp, std::array<Tp,
        Dim>> mod_;
    static std::conditional_t<Dim == 1U, Vec, std::array<Vec,
        Dim>> pow_;
    static std::conditional_t<Dim == 1U, Vec, std::array<Vec,
        Dim>> inv_;
    static int nchanges_;
    static bool ischanged_;

    std::conditional_t<Dim == 1U, Vec, std::array<Vec, Dim>>
        pref_;
    std::conditional_t<Dim == 1U, Vec, std::array<Vec, Dim>>
        suff_;
    int changeid_;
    bool ishashed_;
    bool isbidirect_;

    template <class T = Tp,
             std::enable_if_t<std::is_same<T, int>::value>* =
                 nullptr>
    static constexpr Tp mul(const Tp& a, const Tp& b, const
        Tp& mod) {
        return ((static_cast<std::int64_t>(a) * b) % mod);
    }

    template <class T = Tp,
             std::enable_if_t<std::is_same<T, std::int64_t>::
                 value>* = nullptr>
    static constexpr Tp mul(const Tp& a, const Tp& b, const
        Tp& mod) {
        long double prod = static_cast<long double>(a) * b;
        std::int64_t quot = prod / mod;
        return (prod - (quot * mod) + 1e-6);
    }

    template <class T = Tp,
             std::enable_if_t<std::is_same<T, int>::value>* =
                 nullptr>

```

```

static constexpr Tp add(const Tp& a, const Tp& b, const
    Tp& mod) {
    return ((static_cast<std::int64_t>(a) + b) % mod);
}

template <class T = Tp,
         std::enable_if_t<std::is_same<T, std::int64_t>::
             value>* = nullptr>
static constexpr Tp add(const Tp& a, const Tp& b, const
    Tp& mod) {
    long double sum = static_cast<long double>(a) + b;
    std::int64_t quot = sum / mod;
    return (sum - (quot * mod) + 1e-6);
}

static constexpr Tp inverse(Tp a, const Tp& mod) {
    Tp b = mod, x = 1, y = 0;
    Tp x1 = 0, y1 = 1, tmp = 0, q = 0;
    while (b > 0) {
        q = a / b;
        tmp = a, a = b, b = tmp - (q * b);
        tmp = x, x = x1, x1 = tmp - (q * x1);
        tmp = y, y = y1, y1 = tmp - (q * y1);
    }
    assert(a == 1);
    if (x < 0) x += mod;
    return x;
}

template <std::size_t KK = Dim, std::enable_if_t<KK == 1U
>* = nullptr>
static constexpr void normalize_kernel(std::size_t len) {
    if (!(ischanged_ || pow_.size() < len)) {
        return;
    }
    auto cur_len = ischanged_ ? 0U : pow_.size();
    pow_.resize(len);
    pow_[0U] = 1;
    for (auto i = ((cur_len == 0U) ? 1U : cur_len); i <
        len; ++i) {
        pow_[i] = mul(pow_[i - 1U], base_, mod_);
    }
    inv_.resize(len);
    for (auto i = cur_len; i < len; ++i) {
        inv_[i] = inverse(pow_[i], mod_);
    }
    ischanged_ = false;
}

```

```

template <std::size_t KK = Dim, std::enable_if_t<KK != 1U
>* = nullptr>
static constexpr void normalize_kernel(std::size_t len) {
    if (!(ischanged_ || pow_[0U].size() < len)) {
        return;
    }
    auto cur_len = ischanged_ ? 0U : pow_[0U].size();
    auto start_idx = (cur_len == 0U) ? 1U : cur_len;
    for (auto k = 0U; k < Dim; ++k) {
        const auto& m = mod_[k];
        pow_[k].resize(len);
        pow_[k][0U] = 1;
        for (auto i = start_idx; i < len; ++i) {
            pow_[k][i] = mul(pow_[k][i - 1U], base_[k], m);
        }
        inv_[k].resize(len);
        for (auto i = cur_len; i < len; ++i) {
            inv_[k][i] = inverse(pow_[k][i], m);
        }
    }
    ischanged_ = false;
}

public:
    Rolling_hash() : ishashed_(false), isbidirect_(false),
        changeid_(-1) {}

    template <class InputIter,
             std::RequireInputIter<InputIter>* = nullptr>
    Rolling_hash(InputIter first, InputIter last, bool
        bidirectional = false)
        : Rolling_hash() { hash(first, last, bidirectional);
    }

    template <class InputIter,
             std::RequireInputIter<InputIter>* = nullptr,
             std::size_t KK = Dim, std::enable_if_t<KK == 1U
                 >* = nullptr>
    void hash(InputIter first, InputIter last,
        bool bidirectional = false) {
        const std::size_t len = std::distance(first, last);
        assert(len > 0U);
        normalize_kernel(len);

        isbidirect_ = bidirectional;
        changeid_ = nchanges_;

        auto i = 0U, j = 0U;

```

```

    pref_.resize(len);
    pref_[0U] = static_cast<Tp>(*first) % mod_;
    i = 1U;
    for (auto it = next(first); it != last; ++it) {
        pref_[i] = add(pref_[i - 1U], mul(static_cast<Tp>
            >(*it), pow_[i], mod_), mod_);
        ++i;
    }

    if (!bidirectional) {
        ishashed_ = true;
        return;
    }

    suff_.resize(len);
    const auto &prev_first = prev(first), prev_last =
        prev(last);
    suff_[len - 1U] = static_cast<Tp>(*prev_last) % mod_;
    i = len - 2U, j = 1U;
    for (auto it = prev(prev_last); it != prev_first; --
        it) {
        suff_[i] = add(suff_[i + 1U], mul(static_cast<Tp>
            >(*it), pow_[j], mod_), mod_);
        --i, ++j;
    }

    ishashed_ = true;
}

template <class InputIter,
    std::RequireInputIter<InputIter>* = nullptr,
    std::size_t KK = Dim, std::enable_if_t<KK != 1U
        >* = nullptr>
void hash(InputIter first, InputIter last,
    bool bidirectional = false) {
    const std::size_t len = std::distance(first, last);
    assert(len > 0U);
    normalize_kernel(len);

    isbidirect_ = bidirectional;
    changeid_ = nchanges_;

    auto i = 0U, j = 0U;
    const auto &prev_first = prev(first), prev_last =
        prev(last);

    for (auto k = 0U; k < Dim; ++k) {
        const auto& m = mod_[k];
        pref_[k].resize(len);
        pref_[k][0U] = static_cast<Tp>(*first) % m;

```

```

        i = 1U;
        for (auto it = next(first); it != last; ++it) {
            pref_[k][i] = add(pref_[k][i - 1U],
                mul(static_cast<Tp>(*it), pow_
                    [k][i], m), m);
            ++i;
        }
        if (!bidirectional) {
            continue;
        }
        suff_[k].resize(len);
        suff_[k][len - 1U] = static_cast<Tp>(*prev_last)
            % m;
        i = len - 2U, j = 1U;
        for (auto it = prev(prev_last); it != prev_first;
            --it) {
            suff_[k][i] = add(suff_[k][i + 1U],
                mul(static_cast<Tp>(*it), pow_
                    [k][j], m), m);
            --i, ++j;
        }
    }

    ishashed_ = true;
}

template <std::size_t KK = Dim, std::enable_if_t<KK == 1U
    >* = nullptr>
Tp get(std::size_t pos = 0U, std::size_t len = SIZE_MAX)
    const {
    if (!ishashed_) {
        throw std::runtime_error("Not hashed yet");
    }
    if (changeid_ != nchanges_) {
        throw std::runtime_error("At least one of 'base'
            and 'modulus' has \
            changed and hence this instance can no longer be
            sliced");
    }
    if (pos >= pref_.size()) {
        throw std::out_of_range("Starting index is out of
            range");
    }
    if (len == 0U) {
        return 0;
    }

    std::size_t r = std::min(pos + len, pref_.size()) - 1
        U;
    if (pos == 0U) {

```

```

        return pref_[r];
    }
    return mul((pref_[r] - pref_[pos - 1U] + mod_) % mod_
        , inv_[pos], mod_);
}

template <std::size_t KK = Dim, std::enable_if_t<KK != 1U
    >* = nullptr>
std::array<Tp, Dim> get(std::size_t pos = 0U, std::size_t
    len = SIZE_MAX) const {
    if (!ishashed_) {
        throw std::runtime_error("Not hashed yet");
    }
    if (changeid_ != nchanges_) {
        throw std::runtime_error("At least one of 'base'
            and 'modulus' has \
            changed and hence this instance can no longer be
            sliced");
    }
    if (pos >= pref_[0U].size()) {
        throw std::out_of_range("Starting index is out of
            range");
    }
    if (len == 0U) {
        return std::array<Tp, Dim>({});
    }

    std::size_t r = std::min(pos + len, pref_[0U].size())
        - 1U;
    std::array<Tp, Dim> res;
    if (pos == 0U) {
        for (auto k = 0U; k < Dim; ++k) {
            res[k] = pref_[k][r];
        }
        return res;
    }
    for (auto k = 0U; k < Dim; ++k) {
        const auto& m = mod_[k];
        res[k] = mul((pref_[k][r] - pref_[k][pos - 1U] +
            m) % m,
            inv_[k][pos], m);
    }
    return res;
}

template <std::size_t KK = Dim, std::enable_if_t<KK == 1U
    >* = nullptr>
Tp getrev(std::size_t pos = 0U, std::size_t len =
    SIZE_MAX) const {
    if (!ishashed_) {

```



```

        throw std::runtime_error("Not hashed yet");
    }
    if (!isbidirect_) {
        throw std::runtime_error("Not hashed
            bidirectionally");
    }
    if (changeid_ != nchanges_) {
        throw std::runtime_error("At least one of 'base'
            and 'modulus' has \
            changed and hence this instance can no longer be
            sliced");
    }
    if (pos >= suff_.size()) {
        throw std::out_of_range("Starting index is out of
            range");
    }
    if (len == 0U) {
        return 0;
    }

    std::size_t r = std::min(pos + len, suff_.size()) - 1
        U;
    auto rem = suff_.size() - 1U - r;
    if (rem == 0U) {
        return suff_[pos];
    }
    return mul((suff_[pos] - suff_[r + 1U] + mod_) % mod_
        , inv_[rem], mod_);
}

template <std::size_t KK = Dim, std::enable_if_t<KK != 1U
    >* = nullptr>
std::array<Tp, Dim> getrev(std::size_t pos = 0U, std::
    size_t len = SIZE_MAX) const {
    if (!ishashed_) {
        throw std::runtime_error("Not hashed yet");
    }
    if (!isbidirect_) {
        throw std::runtime_error("Not hashed
            bidirectionally");
    }
    if (changeid_ != nchanges_) {
        throw std::runtime_error("At least one of 'base'
            and 'modulus' has \
            changed and hence this instance can no longer be
            sliced");
    }
    if (pos >= suff_[0U].size()) {
        throw std::out_of_range("Starting index is out of
            range");
    }

```

```

    }
    if (len == 0U) {
        return std::array<Tp, Dim>({});
    }

    std::size_t r = std::min(pos + len, suff_[0U].size())
        - 1U;
    auto rem = suff_[0U].size() - 1U - r;
    std::array<Tp, Dim> res;
    if (rem == 0U) {
        for (auto k = 0U; k < Dim; ++k) {
            res[k] = suff_[k][pos];
        }
        return res;
    }
    for (auto k = 0U; k < Dim; ++k) {
        const auto& m = mod_[k];
        res[k] = mul((suff_[k][pos] - suff_[k][r + 1U] +
            m) % m,
            inv_[k][rem], m);
    }
    return res;
}

bool is_hashed() const { return ishashed_; }
bool is_bidirectional() const { return isbidirect_; }

template <std::size_t KK = Dim, std::enable_if_t<KK == 1U
    >* = nullptr>
std::size_t size() const { return pref_.size(); }

template <std::size_t KK = Dim, std::enable_if_t<KK != 1U
    >* = nullptr>
std::size_t size() const { return pref_[0U].size(); }

template <std::size_t KK = Dim, std::enable_if_t<KK == 1U
    >* = nullptr>
static constexpr Tp base() { return base_; }

template <std::size_t KK = Dim, std::enable_if_t<KK != 1U
    >* = nullptr>
static constexpr Tp base(std::size_t i) { return base_[i]
    ]; }

template <std::size_t KK = Dim, std::enable_if_t<KK == 1U
    >* = nullptr>
static constexpr void base(Tp new_base) {
    if (new_base <= 1) {
        throw std::invalid_argument("'new_base' must be
            greater than 1");
    }
}

```

```

    }
    base_ = new_base;
    ischanged_ = true;
    ++nchanges_;
}

template <std::size_t KK = Dim, std::enable_if_t<KK != 1U
    >* = nullptr>
static constexpr void base(std::size_t i, Tp new_base) {
    if (new_base <= 1) {
        throw std::invalid_argument("'new_base' must be
            greater than 1");
    }
    base_[i] = new_base;
    ischanged_ = true;
    ++nchanges_;
}

template <std::size_t KK = Dim, std::enable_if_t<KK == 1U
    >* = nullptr>
static constexpr Tp modulus() { return mod_; }

template <std::size_t KK = Dim, std::enable_if_t<KK != 1U
    >* = nullptr>
static constexpr Tp modulus(std::size_t i) {
    return mod_[i];
}

template <std::size_t KK = Dim, std::enable_if_t<KK == 1U
    >* = nullptr>
static constexpr void modulus(Tp new_modulus) {
    if (new_modulus <= 1) {
        throw std::invalid_argument("'new_modulus' must
            be greater than 1");
    }
    mod_ = new_modulus;
    ischanged_ = true;
    ++nchanges_;
}

template <std::size_t KK = Dim, std::enable_if_t<KK != 1U
    >* = nullptr>
static constexpr void modulus(std::size_t i, Tp
    new_modulus) {
    if (new_modulus <= 1) {
        throw std::invalid_argument("'new_modulus' must
            be greater than 1");
    }
    mod_[i] = new_modulus;
    ischanged_ = true;
}

```

```

        ++nchanges_;
    }
};

template <std::size_t Dim, class Tp, class Enabler>
int Rolling_hash<Dim, Tp, Enabler>::nchanges_ = 0;
template <std::size_t Dim, class Tp, class Enabler>
bool Rolling_hash<Dim, Tp, Enabler>::ischanged_ = false;

#ifdef ROLLING_HASH_PARTIAL_SPEC_INIT
#define ROLLING_HASH_PARTIAL_SPEC_INIT(Tp)
    \
    template <>

    \
    std::array<Tp, 3U> Rolling_hash<3U, Tp>::base_ = {257,
        263, 269}; \
    template <>

    \
    std::array<Tp, 3U> Rolling_hash<3U, Tp>::mod_ =
        {1000000007, 1000000009, \
            1000000021};

    \
    template <>

    \
    std::array<std::vector<Tp>, 3U> Rolling_hash<3U, Tp>::
        pow_ = {}; \
    template <>

    \
    std::array<std::vector<Tp>, 3U> Rolling_hash<3U, Tp>::
        inv_ = {}; \

    template <>

```

```

    \
    std::array<Tp, 2U> Rolling_hash<2U, Tp>::base_ = {257,
        263}; \
    template <>

    \
    std::array<Tp, 2U> Rolling_hash<2U, Tp>::mod_ =
        {1000000007, 1000000009}; \
    template <>

    \
    std::array<std::vector<Tp>, 2U> Rolling_hash<2U, Tp>::
        pow_ = {}; \
    template <>

    \
    std::array<std::vector<Tp>, 2U> Rolling_hash<2U, Tp>::
        inv_ = {}; \

    template <>

    \
    Tp Rolling_hash<1U, Tp>::base_ = 257;
    \
    template <>

    \
    Tp Rolling_hash<1U, Tp>::mod_ = 1000000007;
    \
    template <>

    \
    std::vector<Tp> Rolling_hash<1U, Tp>::pow_ = {};
    \
    template <>

    \
    std::vector<Tp> Rolling_hash<1U, Tp>::inv_ = {};

```

```

ROLLING_HASH_PARTIAL_SPEC_INIT(int)
ROLLING_HASH_PARTIAL_SPEC_INIT(std::int64_t)
#endif

template <class Tp>
using single_hash = Rolling_hash<1U, Tp>;
template <class Tp>
using double_hash = Rolling_hash<2U, Tp>;
template <class Tp>
using triple_hash = Rolling_hash<3U, Tp>;

```

## 6.2 Z-Function [MB]

```

#include<bits/stdc++.h>

/*
    \
    tested by ac
    submission: https://codeforces.com/contest/432/submission/145953901
    problem: https://codeforces.com/contest/432/problem/D
*/
std::vector<int> z_function(const std::string &s)
{
    int n = (int)s.size();
    std::vector<int> z(n, 0);
    for (int i = 1, l = 0, r = 0; i < n; i++)
    {
        if (i <= r)
            z[i] = std::min(r - i + 1, z[i - l]);
        while (i + z[i] < n && s[z[i]] == s[i + z[i]])
            z[i]++;
        if (i + z[i] - 1 > r)
            l = i, r = i + z[i] - 1;
    }
    return z;
}

```