


Big O notation is a mathematical notation that describes the limiting behaviour of a function when the argument tends towards a particular value or infinity. Big O is a member of a family of notations invented by Paul Bachmann, Edmund Landau and others, collectively called **Bachmann–Landau notation** or **asymptotic notation**. The letter O was chosen by Bachmann to stand for Ordnung, meaning the order of approximation.

In computer science, big O notation is used to classify algorithms according to how their run time or space requirements grow as the input size grows. In analytic number theory, big O notation is often used to express a bound on the difference between an arithmetical function and a better understood approximation; a famous example of such a difference is the remainder term in prime number theorem. Big O notation is also used in many

other fields to provide similar estimates.


Big O notation characterizes functions according to their growth rates: different functions with the same growth rate may be represented using the same O notation. The letter O is used because the growth rate of a function is also referred to as the **order of the function**. A description of a function in terms of big O notation usually only provides an upper bound on the growth rate of the function.

Associated with big O notation are several related notations, using the symbols o , Ω , ω , and Θ , to describe other kinds of bounds on asymptotic growth rates.



Big O notation has two main areas of application:

- In mathematics, it is commonly used to describe how closely a finite series approximated a given function, especially in the case of a truncated Taylor series or asymptotic expansion.
- In computer science, it is useful in the analysis of algorithms.



In both applications, the function $g(x)$ appearing within

the $O(\cdot)$ is typically chosen to be as simple as possible, omitting constant factors and lower order terms.

There are two formally close, but noticeably different, usages of this notation:

- infinite asymptotics
- infinitesimal asymptotics.

This distinction is only in application and not in principle, however—the formal definition

for the "big O" is the same for both cases, only with different limits for the function argument.

In plain words, Big O notation describes the **complexity** of your code using algebraic terms.

To understand what Big O notation is, we can take a look at a typical example, **$O(n^2)$** , which is usually pronounced “***Big O squared***”. The letter “***n***” here represents

the **input size**, and the function “ $g(n) = n^2$ ” inside the “ $O()$ ” gives us an idea of how complex the algorithm is with respect to the input size.

A typical algorithm that has the complexity of $O(n^2)$ would be the **selection sort** algorithm.

Selection sort is a sorting algorithm that iterates through the list to ensure every element at index i is the ***ith*** smallest/largest element of the list.

The **CODEPEN** below gives a visual example of it.

The algorithm can be described by the following code.

```
SelectionSort(List) {  
    for(i from 0 to List.Length) {  
        SmallestElement = List[i]  
        for(j from i to List.Length) {  
            if(SmallestElement > List[j]) {  
                SmallestElement = List[j]  
            }  
        }  
        Swap(List[i], SmallestElement)  
    }  
}
```

In order to make sure the *ith* element is the *ith* smallest element in the list, this algorithm first iterates through the list with a for loop. Then for every element it uses another for loop to find the smallest element in the remaining part of the list.

1. $O(1)$ has the least complexity
Often called “***constant time***”, if you can create an algorithm to solve the problem in $O(1)$, you are probably at your best.

In some scenarios, the complexity may go beyond $O(1)$, then we can analyze them by finding its $O(1/g(n))$ counterpart. For example, $O(1/n)$ is more complex than $O(1/n^2)$.

2. $O(\log(n))$ is more complex than $O(1)$, but less complex than polynomials

As complexity is often related to divide and conquer algorithms, $O(\log(n))$ is generally a good complexity you can reach for sorting

algorithms. $O(\log(n))$ is less complex than $O(\sqrt{n})$, because the square root function can be considered a polynomial, where the exponent is 0.5.

3. Complexity of polynomials increases as the exponent increases

For example, $O(n^5)$ is more complex than $O(n^4)$. Due to the simplicity of it, we actually went over quite many examples of polynomials in the previous sections.

4. Exponentials have greater complexity than polynomials as long as the coefficients are positive multiples of n

$O(2^n)$ is more complex than $O(n^{99})$, but $O(2^n)$ is actually less complex than $O(1)$. We generally take 2 as base for exponentials and logarithms because things tends to be binary in Computer Science, but exponents can be changed by changing the coefficients. If not specified,

the base for logarithms is assumed to be 2.

5. Factorials have greater complexity than exponentials

If you are interested in the reasoning, look up the **Gamma function**, it is an **analytic continuation** of a factorial. A short proof is that both factorials and exponentials have the same number of multiplications, but the numbers that get multiplied grow for factorials, while

remaining constant for exponentials.

6. Multiplying terms

When multiplying, the complexity will be greater than the original, but no more than the equivalence of multiplying something that is more complex. For example, $O(n * \log(n))$ is more complex than $O(n)$ but less complex than $O(n^2)$, because $O(n^2) = O(n * n)$ and n is more complex than $\log(n)$.

To test your understanding, try ranking the following functions from the most complex to the least complex. The solutions with detailed explanations can be found in a later section as you read. Some of them are meant to be tricky and may require some deeper understanding of math. As you get to the solution, you will understand them more.

Sometimes an algorithm just has bad luck. Quick sort, for example, will have to go

through the list in $O(n)$ time if the elements are sorted in the opposite order, but on average it sorts the array in $O(n * \log(n))$ time. Generally, when we evaluate time complexity of an algorithm, we look at their **worst-case** performance. More on that and quick sort will be discussed in the next section as you read.

The average case complexity describes the expected performance of the algorithm. Sometimes involves calculating

the probability of each scenarios. It can get complicated to go into the details and therefore not discussed in this article. Below is a cheat-sheet on the time and space complexity of typical algorithms.

