NOW_WHAT? v1.1

Full Architecture and Capability Report

Generated from local source files for LLM context, future analysis, and functionality testing.

Field	Value
Generated at	`2026-07-10T01:12:02`
Repository	`D:\Projects\Now_What\now-what-v0.9.0\now-what-export`
Branch	`fix/dashboard-review-guide-cleanup`
Commit	`9322feb`
Git status	`?? output/` `?? tmp/`
Package	`now-what 1.1.0`
Primary runtime	`React + Vite + TypeScript + Dexie + Wouter`
Architecture posture	`Local-first, no login, no required cloud, rule-based engine, PWA-ready web app`

1. Executive Summary

NOW_WHAT? is a local-first daily command system implemented as a React, Vite, TypeScript, and Dexie PWA. It stores all core data in IndexedDB, scopes data to a generated local profile database, and uses a deterministic rule engine to produce one explainable next action. The app is intentionally not a login product, social product, gamified habit tracker, therapy app, motivational coach, or AI/ML recommender.

The current app can manage tasks, habits, goals, calendar blocks, daily plans, quick logs, reminders, daily and weekly reviews, local backups, restores, data integrity checks, a tutorial guide, and PWA shell caching. It also includes a NOW_WHAT? engine with deadline rules, calendar awareness, mood/energy/focus readiness adjustments, persistent dismiss cooldowns, clear empty states, and debug instrumentation.

Capability	Current implementation	Primary code ownership
Local profile identity	Creates a stable local profile ID in nowwhat_meta, opens a profile-scoped Dexie DB, migrates legacy nowwhat_db once, and stores app/profile metadata in settings.	`src/data/profile.ts, src/data/db.ts`
Tasks	Create tasks with title, category, priority, due date, estimated minutes, energy requirement, repeat metadata, notes, and optional goal link. Complete tasks and log completion activity.	`src/components/tasks/*, src/types/index.ts`
Habits	Create/edit/delete habits with daily/weekly/custom frequency, boolean/quantity/time/count completion, target value/unit, optional time window, notes, and optional goal link. Complete logs activity.	`src/components/habits/*`
Goals	Create active/paused/complete goals, link tasks and habits, reconcile goal ownership, display progress from linked completions.	`src/components/goals/*`
Calendar import/core	Manual blocks, .ics import, de-duplication, active/upcoming/past grouping, conversion of a calendar block to a task. Google/Apple connections are placeholders.	`src/data/calendar.ts, src/data/ics.ts, src/components/calendar/*`
Daily plan	Auto-creates today plan, supports primary focus, planned tasks/habits/calendar blocks, and carry-over candidates.	`src/engine/dailyPlan.ts, src/components/planning/DailyPlanPanel.tsx`
Quick log/lifestyle context	Logs water, meal, focus, exercise, mood, energy, rest, distraction, and notes. These feed timeline, review, reminders, and engine context.	`src/components/quicklog/QuickLogModal.tsx, src/types/index.ts`
NOW_WHAT? engine	Builds context from Dexie, ranks rule candidates, applies focus-readiness adjustments, respects calendar/deadline hard rules, persists suggestions and cooldowns.	`src/engine/nowWhat.ts, src/components/dashboard/NowWhatCard.tsx`
Reminders	System scheduler creates task due, habit window, calendar block, daily review, previous review, hydration, movement reminders; users can create manual reminders; browser notifications opt-in.	`src/data/reminders.ts, src/components/reminders/*`
Reviews	Daily review generated only when activity is reviewable; weekly review summarizes patterns; carry-over/missed/skip/keep resolution flows.	`src/data/review.ts, src/components/review/*`
Export/import	Exports active profile data as JSON backup with metadata; validates import shape and restores stores transactionally.	`src/data/exportImport.ts, src/components/data/*`
Integrity checks	Finds broken references, duplicate plan refs, invalid calendar/review/log/reminder records, and offers limited explicit fixes.	`src/data/integrity.ts, src/components/data/IntegrityPanel.tsx`
PWA/offline shell	Manifest, icons, service worker shell cache, asset discovery from index.html, dev-host unregister behavior, offline navigation fallback.	`public/manifest.webmanifest, public/service-worker.js, src/App.tsx`

2. Technology Stack and Build Surface

- Package name and version: now-what 1.1.0.

- Runtime: React 19.1.0, React DOM 19.1.0, Vite 7.3.x, TypeScript 6.0.x.

- Routing: wouter 3.3.5 with base derived from import.meta.env.BASE_URL.

- Persistence: Dexie 4.4.x and dexie-react-hooks 4.4.x over IndexedDB.

- UI dependencies: many Radix/shadcn-style primitives are present, but current product surfaces mostly use inline HUD-minimal styles plus src/index.css tokens.

- Scripts: npm run dev, npm run build, npm run preview, npm run typecheck.

- PWA files: public/manifest.webmanifest, public/service-worker.js, SVG icons and favicon.

3. Runtime Bootstrap and Route Map

src/main.tsx mounts the React app. src/App.tsx owns service worker registration, local profile boot, reminder scheduler boot, keyboard shortcuts, global modal state, engine debug state, route setup, and global event listeners.

App boot order: service worker registration/unregistration effect runs; initializeProfileSession opens profile DB and settings; only after profile readiness does App render the router/shell; generateSystemRemindersForToday runs after profile readiness and repeats every five minutes plus regenerate events.

Route	Component	Purpose
`/`	`Dashboard`	Command surface containing NOW_WHAT?, review prompt, reminder tray, daily plan, calendar strip, lifestyle strip, goal strip, and activity feed.
`/guide`	`TutorialPage`	Factual quick start guide and tutorial completion flow.
`/tasks`	`TasksPage`	Task list, filters, complete actions, and add task modal trigger.
`/habits`	`HabitsPage`	Habit list, frequency filters, completion, edit, delete, add modal.
`/goals`	`GoalsPage`	Goal list, status filters, link progress, add/edit modal.
`/calendar`	`CalendarPage`	Manual calendar blocks, today/upcoming/past display, .ics import, edit/convert flow.
`/review`	`DailyReviewPage`	Daily and weekly review tabs, today/yesterday review state, carry-over.
`/timeline`	`Timeline`	Recent activity logs, grouped by today and earlier.
`/data`	`DataPage`	Status/schema, export, import, integrity, and danger zone tabs.
`/reminders`	`RemindersPage`	Scheduled/sent/dismissed reminders, manual reminder form, settings.

Event or shortcut	Producer(s)	Consumer(s)	Behavior
`T`	window keydown in App	App modal state	Opens TaskModal unless typing in input/textarea/select/contenteditable.
`H`	window keydown in App	App modal state	Opens HabitModal.
`G`	window keydown in App	open_goal_modal listener	Opens GoalModal.
`L`	window keydown in App	App modal state	Opens QuickLogModal.
`N`	window keydown in App	NowWhatCard, reminder scheduler	Dispatches regenerate_now_what.
`Shift+N`	window keydown in App	App debug state	Toggles EngineDebugPanel.
`open_task_modal`	NOW_WHAT?, TaskList, TasksPage, DailyPlan	App	Opens TaskModal.
`open_habit_modal`	NOW_WHAT?, DailyPlan	App	Opens HabitModal.
`open_goal_modal`	App shortcut	App	Opens GoalModal.
`open_quick_log`	NOW_WHAT?, reminder tray	App	Opens QuickLogModal.
`focus_task`	NOW_WHAT?	NavigationHandler	Navigates to /tasks.
`navigate_review`	NOW_WHAT?	NavigationHandler	Navigates to /review.
`navigate_review_yesterday`	NOW_WHAT?, reminder tray, review prompt	DailyReviewPage	Switches review page to daily/yesterday.
`show_toast`	Most mutations	ToastProvider	Displays transient HUD toast.
`engine_debug_update`	NowWhatCard	App/EngineDebugPanel	Shares latest context, candidates, selected suggestion.

4. Local-First Data Core

The database architecture uses two IndexedDB areas: a meta database named nowwhat_meta and an active profile database named nowwhat_profile_<localProfileId>. A legacy database named nowwhat_db still exists as DEFAULT_LEGACY_DB_NAME for migration. The module exports a mutable db singleton, but initializeProfileSession replaces it with the profile DB before the app renders. All components import that singleton after boot.

The profile ID is generated with crypto.randomUUID() and prefixed with nwloc_. It is stable per browser/device through metaDb.appMeta key activeProfileId. Settings store the localProfileId, appVersion, schemaVersion, and feature settings. There is no signup, login, remote profile, cloud sync, or required account flow.

Store	Indexes	Primary purpose
`settings`	`id`	App version, schema version, profile id, tutorial state, reminder settings, import/export timestamps.

Store	Indexes	Primary purpose
tasks	id, status, priority, dueDate, energyRequired, goalId, createdAt	Task commitments and task metadata used by engine, plan, review, reminders, goals.
habits	id, frequency, createdAt	Recurring habit definitions and embedded completion history.
goals	id, status, horizon, createdAt	Goal entities and link arrays for tasks/habits.
calendarBlocks	id, startAt, endAt, createdAt	Manual/imported calendar time blocks.
activityLogs	id, type, createdAt, relatedTaskId, relatedHabitId	Fact log for task/habit completions, quick logs, notes, lifestyle context.
dailyPlans	id, date, createdAt	Daily planning state: focus, planned ids, calendar ids, carry-over, review status.
suggestions	id, status, actionType, createdAt	NOW_WHAT? suggestion lifecycle and cooldown metadata in contextSnapshot.
dailyReviews	id, date, createdAt	Per-day generated review data and user notes.
weeklyReviews	id, weekStart, createdAt	Generated weekly summaries and derived pattern fields.
reminders	id, type, status, scheduledAt, targetId, targetType, createdAt	System/user reminders and reminder lifecycle.

Type	Important fields and compatibility notes
Task	id, title, category, priority low/medium/high/critical, status pending/complete/skipped/missed, estimatedMinutes, dueDate, dueTime, repeatRule, energyRequired, goalId, notes, carryOverHistory, missedCount, timestamps.
Habit	id, name, category, frequency daily/weekly/custom, completionType boolean/quantity/time/count, targetValue, targetUnit, optional time window, goalId, notes, embedded completionHistory, timestamps.
Goal	id, title, category, horizon week/month/semester/year/ongoing, linkedTaskIds, linkedHabitIds, status active/paused/complete, reviewNotes, timestamps.
CalendarBlock	id, source manual/ics/google_ics/google_api/apple_ics/google_stub/apple_stub, externalId, title, startAt, endAt, location, calendarName, importedAt, convertedTaskIds, timestamps.
ActivityLog	id, type task_completed/habit_completed/water/meal/exercise/focus/mood/energy/rest/distraction/calendar/note, label, start/end, duration, quantity/unit, related ids, notes, createdAt.
DailyPlan	id, date, primaryFocus, plannedTaskIds, plannedHabitIds, calendarBlockIds, lifestyleMinimums, carryOverTaskIds, reviewStatus, timestamps.
Suggestion	id, createdAt, actionType, targetId, command, targetLabel, reason, status shown/accepted/dismissed/completed/ignored, contextSnapshot. Cooldowns are stored inside contextSnapshot.
DailyReview	Back-compatible optional fields for completed/missed task ids, completed habits, focus/distraction/rest/water/meals/movement, sleep, calendar ids, carry-over ids, generatedSummary, reflectionNote, status.
WeeklyReview	weekStart/weekEnd, task/habit/activity counts, mostConsistentHabits, mostMissedHabits, repeatedMissedTaskTitles, bestFocusWindow, struggleWindow, goalProgressNotes, generatedSummary.
Settings	theme dark, appVersion, schemaVersion, localProfileId, import/export timestamps, seedEnabled, tutorial timestamps, reminder settings.
Reminder	type task_due/habit_window/calendar_block/planned_focus/daily_review/previous_review/hydration/movement/manual/custom, target, scheduledAt, status, source, repeat, enabled, sentAt.

5. Import, Export, Integrity, and Danger Zone

Export creates a JSON file named now_what_backup_YYYY-MM-DD_HH-mm.json. The backup includes app name NOW_WHAT?, exportVersion 2, schemaVersion from PROFILE_SCHEMA_VERSION, exportedAt, profile metadata, and arrays for all active profile stores. Import validates app name, supported schemaVersion 1..current, required stores, array shape, valid id strings, and duplicate ids before enabling restore. Schema version 1 backups may omit reminders; they import with empty reminders.

- restoreDatabase clears all stores inside one Dexie transaction and bulkAdds backup store arrays. Settings are patched to the active local profile id.

- clearAllStores clears all profile stores transactionally. clearSuggestionsOnly clears only suggestions and regenerates NOW_WHAT?.

- Danger Zone can reset demo data, but normal first launch stays clean because seedIfEmpty is intentionally a no-op.

- Integrity checks inspect goal links, daily plan references, calendar block time ranges and converted task ids, daily review references, activity log required fields/references, and reminder types/status/targets.

- Some integrity findings are fixable only through explicit user actions, such as removing missing ids from goals/daily plans or cancelling orphaned reminders.

6. Calendar Import Core

Calendar functionality is intentionally not a full calendar app. Calendar blocks provide read-only time context unless the user converts a block to a task. Manual blocks and .ics import are supported. Future Google/Apple connection surfaces currently display connect-later text only.

- Manual blocks use date, optional start/end time, optional location, and optional calendar name. Missing times default to 00:00:00 and 23:59:00.

- .ics import reads VEVENT records through parseIcsVevents, normalizes to CalendarBlock records, de-duplicates by source/externalId or source/title/start/end fallback, bulk-adds new blocks, and reports imported/skipped/unsupported recurrence counts.

- Calendar page partitions blocks into today, upcoming next 14 days, and past; past blocks are hidden until user toggles show past.

- convertCalendarBlockToTask creates one pending medium Admin task due on the block date, notes Created from calendar block <id>, and records the task id in block.convertedTaskIds. Existing converted task id prevents duplicate task creation.

- NOW_WHAT? gives active calendar blocks highest priority and uses the next block to compute availableWindowMinutes for task fit.

7. NOW_WHAT? Engine Architecture

The engine is deterministic and explainable. generateWithDebugInfo marks prior shown suggestions as ignored, builds Context from Dexie, creates rule candidates, attaches stable identities, filters candidates by active dismiss cooldowns, selects the top candidate, optionally persists it, and returns debug context plus candidates.

Context inputs

- Task context: total tasks, pending tasks, critical overdue tasks, tasks due today, high/critical tasks, goal-linked pending tasks, completed task count today.

- Habit context: all habits, pending daily habits within current time window, pending daily habits anywhere.

- Activity context: today logs, meaningful activity count excluding calendar logs, water/focus/rest/movement/distraction totals, latest mood and energy values, last water/focus times.

- State context: latestMoodState, latestEnergyLevel, currentFocusCapacity derived from mood, energy, focus, rest, distraction, and recency of focus.

- Plan/goal context: active goals, today daily plan, planned task ids, planned habit ids, primary focus.

- Calendar context: today calendar blocks, active block, next block, minutes until next block, available window minutes.

- Review context: today review status, whether today has reviewable activity, whether yesterday review is incomplete.

- Reliability context: hasUserContext, activeCooldownCount, selectedCandidateIdentity, excludedCandidateIdentities.

Mood, energy, and focus readiness

- normalizeEnergyLevel maps numeric energy to LOW for <=2, HIGH for >=4, otherwise MEDIUM.

- normalizeMoodState maps mood/energy/rest/distraction into CLEAR, NEUTRAL, LOW, STRESSED, RESTLESS, or OVERLOADED.

- deriveFocusCapacity maps current conditions into DEEP, NORMAL, LIGHT, or RECOVERY.

- Task fit adjusts score but does not override hard responsibilities. Critical overdue, closest deadline, and active calendar block are hard rules that bypass state adjustment.

- CLEAR boosts planned, goal-linked, high-priority, longer fitting work; LOW boosts short, low-energy, admin/maintenance tasks; STRESSED boosts concrete short due/planned work; RESTLESS boosts physical/short actions; OVERLOADED boosts smallest planned, low-energy, short actions and avoids long high-energy tasks unless urgent.

Priority	Rule name	Command	Action type	Trigger summary
0	`active_calendar_block`	`IN BLOCK`	`acknowledge_block`	A calendar block is currently active.
1	`critical_overdue_task`	`START TASK`	`start_task`	Pending critical task due before today.
2	`closest_deadline_task`	`START TASK`	`start_task`	Pending task with soonest dueDate, priority tie-breaker, readiness tie-breaker.
3	`high_priority_task`	`START TASK`	`start_task`	High/critical fitting task, with plan/goal/window notes.

Priority	Rule name	Command	Action type	Trigger summary
3.5	end_of_day_all_done	REVIEW DAY	review_day	After 20:00, planned tasks done, today reviewable, review incomplete.
4	easy_task_low_energy	START TASK	start_task	Low energy/LOW/OVERLOADED state and task is low-energy, short, admin, or maintenance.
5	habit_in_window	COMPLETE HABIT	complete_habit	Daily habit pending and current time is inside its window.
6	hydration	LOG WATER	log_water	No prior water log or last water more than 180 minutes ago. Requires user context because no-context returns first.
7	rest_after_focus	TAKE REST	rest	Focus logged, more than 90 minutes since focus, rest today under 10 minutes.
8	movement_midday	LOG MOVEMENT	move	No movement today and current hour >= 12.
9	general_pending_task	START TASK	start_task	Fallback pending task selected by readiness.
10	remaining_daily_habit	COMPLETE HABIT	complete_habit	Fallback daily habit still pending.
11	end_of_day_review	REVIEW DAY	review_day	After 20:00, today has reviewable activity, review incomplete.
11.5	yesterday_review_incomplete	COMPLETE REVIEW	review_day	Yesterday has reviewable activity and incomplete review.
12	clear_state	CLEAR STATE	clear_state	No active recommendation remains and context exists.
12	no_context_available	NO CONTEXT AVAILABLE	clear_state	Fresh/blank profile without user-created context. Not persisted.
12	no_action_ready	NO ACTION READY	clear_state	All actionable candidates are cooling down. Not persisted.

Candidate identities and cooldowns

Candidate family	Stable identity format	Cooldown
Task start	task:start:<taskId>	45 min, except critical overdue 20 min and closest deadline 30 min.
Habit complete	habit:complete:<habitId>	45 min.
Water	lifestyle:water	3 hours.
Meal	lifestyle:meal	3 hours.
Movement	lifestyle:movement	3 hours.
Rest	lifestyle:rest	3 hours.
Begin focus	focus:begin	Default 45 min if used.
Review day	review:daily:<todayStr or yesterdayStr>	2 hours.
Plan tomorrow	plan:tomorrow:<todayStr>	Default 45 min if used.
Calendar block	calendar:block:<blockId>	30 min.
State cards	state:no_context_available, state:no_action_ready, state:clear_state	No persisted suggestion/cooldown.

Dismissed suggestions are updated in the existing suggestions store. No Dexie schema migration is required because contextSnapshot is a flexible Record. The snapshot receives dismissedAt, cooldownUntil, and cooldownIdentity. Regenerate respects the same cooldown set by reading dismissed suggestions whose cooldownUntil is still in the future.

Empty-state behavior: if hasUserContext is false, the engine returns NO CONTEXT AVAILABLE with body Add a task, habit, or calendar block to activate recommendations and reason NOW_WHAT? needs user-created context before it can choose the next action. The card offers ADD TASK and ADD HABIT. It does not show LOG WATER or other lifestyle fallback for blank profiles.

Cooldown-state behavior: if context exists but all valid action candidates are cooling down, the engine returns NO ACTION READY with body Current recommendations are in cooldown and reason Dismissed actions will return when their cooldown expires or when new context is added. If pending tasks exist, it appends a factual pending task count. The card offers VIEW TASKS and ADD TASK.

8. Dashboard and UI Composition

The app uses a strict black-and-white HUD-minimal visual language. src/index.css defines color tokens, Space Mono/Inter font roles, hairline borders, focus-visible outlines, pointer/hover/active affordances, hidden file input styling, responsive sidebar/mobile behavior, reduced motion handling, and modal/dashboard responsive rules.

- Topbar: mobile hamburger, clickable NOW_WHAT? logo linking to dashboard, online/offline indicator, real-time 24-hour clock. Install prompt is captured in AppShell but not visibly rendered by current Topbar.

- Sidebar: primary workflow routes are Dashboard, Tasks, Habits, Goals, Calendar, Review, Reminders, Timeline, Data. Guide is placed in the bottom support area above displayed v1.1.

- Dashboard: max width 960px, NOW_WHAT? dominant card, ReviewPrompt, InAppReminderTray, DailyPlanPanel, CalendarStrip, LifestyleStrip, GoalStrip, ActivityFeed.

- Modal surfaces: shared Modal and key custom modals constrain width and maxHeight to viewport and scroll internally to avoid laptop viewport overflow.

- Global interactions: all clickable elements should receive pointer and visible hover/focus/active behavior through global CSS plus component styles.

9. Daily Plan, Reviews, and Activity Timeline

DailyPlanPanel calls getOrCreateTodaysPlan on mount. The plan can store primary focus, planned tasks, planned habits, planned calendar blocks, and carry-over task ids. Planned items influence NOW_WHAT? ranking and review data. Carry-over increments missedCount only once per task/date and adds the task to both carryOverTaskIds and plannedTaskIds.

Daily reviews are gated by hasReviewableActivity. Reviewable activity includes meaningful log types and tasks created from calendar blocks. If no reviewable activity exists, no review is generated and review prompts are hidden. The daily review panel displays generated summaries, completed/missed task ids, habit status, activity totals, calendar blocks, goals touched, carry-over ids, reflection notes, and completion actions.

Weekly review is generated on demand for the week starting Monday. It summarizes completed/missed tasks, habit completions, focus/distraction/rest/movement/water/meals, most consistent/missed habits, repeated missed tasks, best focus windows, struggle windows, and goal progress notes.

Timeline reads the latest 100 activity logs in descending createdAt order and displays today versus earlier logs. It resolves related task/habit names when possible and shows duration, quantity, unit, related item, and notes.

10. Reminder System

The reminder system is local and action-based. App.tsx runs generateSystemRemindersForToday after profile boot, every five minutes, and on regenerate_now_what. A single-flight flag prevents overlapping scheduler runs. Reminders can also be manually created from RemindersPage.

Reminder type	Creation condition	Action behavior
`task_due`	Pending task is overdue or due today. Critical overdue bypasses quiet hours.	Tray OPEN navigates to tasks. Completion/cancellation happens through normal task state or reminder actions.
`habit_window`	Daily habit pending, time window open, closes within 30 minutes, outside quiet hours.	Tray COMPLETE completes habit and writes habit_completed log; OPEN navigates to habits.
`calendar_block`	Today block starts within roughly 0-20 minutes, outside quiet hours.	OPEN navigates to calendar.
`daily_review`	After 20:00, outside quiet hours, today has reviewable activity, review not complete.	OPEN navigates to review.
`previous_review`	Yesterday has reviewable activity and incomplete review, outside quiet hours.	OPEN navigates to review and emits navigate_review_yesterday.
`hydration`	Opt-in, outside quiet hours, after 08:00, no water in 180 minutes and no recent hydration reminder.	Tray LOG WATER writes 250ml water log and completes reminder.
`movement`	Opt-in, outside quiet hours, after 14:00, no exercise log today.	OPEN opens quick log.
`manual`	User-created title/date/time/note from RemindersPage.	Displayed in reminders list/tray with dismiss/complete/cancel; no target navigation unless target type is known.

Default reminder settings: remindersEnabled true, browserNotificationsEnabled false, quiet hours 22:00 to 08:00, hydration/movement disabled, review/calendar/task due/habit window enabled. Browser notifications require Notification.requestPermission and are only sent when permission is granted and setting is enabled.

11. PWA and Offline Behavior

The manifest describes NOW_WHAT? as a standalone, portrait-primary app with dark theme and SVG icons. The service worker cache name is nowwhat-shell-v1.1.0. In development hosts localhost/127.0.0.1/::1, the service worker skips app caching, deletes caches, unregisters itself, and claims clients. In production it caches shell URLs, discovers same-origin and Google font assets from index.html,

caches Google font stylesheets and gstatic font files, deletes old caches on activation, and serves navigation network-first with cached index fallback. Static assets are served cache-first with background update.

12. Security, Privacy, and Local-Only Boundaries

- No account, login, signup, remote user id, or required cloud endpoint exists in the codebase.

- Data is stored in IndexedDB under local profile-specific databases. Export/import is explicit user action.

- Browser notifications are opt-in and disabled by default.

- The app currently has placeholders for future Google/Apple calendar connection but no OAuth or API connection logic.

- The service worker only handles same-origin requests and Google font origins; it ignores non-GET and unrelated origins.

- Potential privacy consideration for future work: exported JSON includes all local profile data and should be treated as sensitive by users.

13. Known Functional Boundaries and Testing Notes

- Task repeatRule is stored but no recurring task generation engine is visible in the current code.

- Google Calendar and Apple Calendar integration are visible placeholders only.

- The PWA install prompt is captured by AppShell but Topbar currently does not expose an install button in the rendered JSX.

- Habit completion history is embedded in Habit records; long-term scaling may eventually benefit from a separate completion store, but current schema keeps it embedded.

- Suggestion cooldown state is stored in contextSnapshot to avoid migration. This is flexible but less indexable than a dedicated cooldown store.

- There are many UI primitive files under src/components/ui that are included in the package but most app screens use inline HUD styling instead of those primitives.

- A future automated test harness should cover fresh profile empty state, suggestion cooldown regeneration, critical overdue precedence, active calendar precedence, review gating, import validation, calendar dedupe, reminder dedupe/cancellation, and modal viewport scaling.

14. Source File Architecture Map

File	Lines	Role
`.env.example`	9	Project configuration or documentation.
`.gitignore`	5	Project configuration or documentation.
`README.md`	152	Project configuration or documentation.
`components.json`	20	Project configuration or documentation.
`index.html`	34	Project configuration or documentation.
`package-lock.json`	4952	Project configuration or documentation.
`package.json`	78	Project configuration or documentation.
`public/favicon.svg`	6	PWA/static public asset.
`public/icon-192.svg`	7	PWA/static public asset.
`public/icon-512.svg`	7	PWA/static public asset.
`public/manifest.webmanifest`	25	PWA/static public asset.
`public/robots.txt`	2	PWA/static public asset.
`public/service-worker.js`	214	PWA/static public asset.
`src/App.tsx`	238	Root app: service worker registration, profile boot, reminder scheduler, router, global modals, shortcuts, debug panel.
`src/components/calendar/CalendarBlockModal.tsx`	247	Calendar UI module.
`src/components/calendar/CalendarBlockRow.tsx`	65	Calendar UI module.
`src/components/calendar/CalendarPage.tsx`	213	Calendar UI module.

File	Lines	Role
src/components/dashboard/ActivityFeed.tsx	56	Dashboard UI module or strip feeding command surface context.
src/components/dashboard/CalendarStrip.tsx	48	Dashboard UI module or strip feeding command surface context.
src/components/dashboard/Dashboard.tsx	24	Dashboard UI module or strip feeding command surface context.
src/components/dashboard/GoalStrip.tsx	83	Dashboard UI module or strip feeding command surface context.
src/components/dashboard/LifestyleStrip.tsx	59	Dashboard UI module or strip feeding command surface context.
src/components/dashboard/NowWhatCard.tsx	342	Dashboard UI module or strip feeding command surface context.
src/components/dashboard/ReviewPrompt.tsx	97	Dashboard UI module or strip feeding command surface context.
src/components/dashboard/TaskList.tsx	63	Dashboard UI module or strip feeding command surface context.
src/components/data/DangerZone.tsx	161	Data/status/export/import/integrity/danger UI module.
src/components/data/DataPage.tsx	75	Data/status/export/import/integrity/danger UI module.
src/components/data/ExportPanel.tsx	71	Data/status/export/import/integrity/danger UI module.
src/components/data/ImportPanel.tsx	183	Data/status/export/import/integrity/danger UI module.
src/components/data/IntegrityPanel.tsx	144	Data/status/export/import/integrity/danger UI module.
src/components/data/SchemaPanel.tsx	109	Data/status/export/import/integrity/danger UI module.
src/components/debug/EngineDebugPanel.tsx	110	Project file included in core package.
src/components/goals/GoalModal.tsx	370	Goal UI module.
src/components/goals/GoalRow.tsx	117	Goal UI module.
src/components/goals/GoalsPage.tsx	91	Goal UI module.
src/components/habits/HabitModal.tsx	247	Habit UI module.
src/components/habits/HabitRow.tsx	86	Habit UI module.
src/components/habits/HabitsPage.tsx	102	Habit UI module.
src/components/layout/AppShell.tsx	75	Application shell, topbar, or sidebar layout.
src/components/layout/Sidebar.tsx	106	Application shell, topbar, or sidebar layout.
src/components/layout/Topbar.tsx	95	Application shell, topbar, or sidebar layout.
src/components/planning/DailyPlanPanel.tsx	375	Daily planning UI module.
src/components/quicklog/QuickLogModal.tsx	189	Quick log UI module.
src/components/reminders/InAppReminderTray.tsx	232	Reminder UI module.
src/components/reminders/ReminderRow.tsx	125	Reminder UI module.
src/components/reminders/ReminderSettingsPanel.tsx	193	Reminder UI module.
src/components/reminders/RemindersPage.tsx	285	Reminder UI module.
src/components/review/CarryOverReview.tsx	117	Review UI module.
src/components/review/DailyReviewPage.tsx	181	Review UI module.
src/components/review/DailyReviewPanel.tsx	425	Review UI module.
src/components/tasks/TaskModal.tsx	201	Task UI module.
src/components/tasks/TaskRow.tsx	58	Task UI module.
src/components/tasks/TasksPage.tsx	87	Task UI module.
src/components/timeline/Timeline.tsx	98	Activity timeline UI module.
src/components/tutorial/TutorialPage.tsx	307	Guide/onboarding UI module.
src/components/tutorial/TutorialPrompt.tsx	144	Guide/onboarding UI module.
src/components/tutorial/TutorialSection.tsx	54	Guide/onboarding UI module.
src/components/ui/Modal.tsx	42	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/Toast.tsx	48	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/accordion.tsx	54	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/alert-dialog.tsx	138	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/alert.tsx	58	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/aspect-ratio.tsx	5	Reusable UI primitive/shadcn-style component included in project.

File	Lines	Role
src/components/ui/avatar.tsx	49	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/badge.tsx	42	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/breadcrumb.tsx	114	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/button-group.tsx	82	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/button.tsx	64	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/calendar.tsx	212	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/card.tsx	82	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/carousel.tsx	259	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/chart.tsx	366	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/checkbox.tsx	27	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/collapsible.tsx	11	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/command.tsx	152	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/context-menu.tsx	197	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/dialog.tsx	119	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/drawer.tsx	115	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/dropdown-menu.tsx	200	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/empty.tsx	103	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/field.tsx	243	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/form.tsx	178	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/hover-card.tsx	26	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/input-group.tsx	167	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/input-otp.tsx	68	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/input.tsx	21	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/item.tsx	192	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/kbd.tsx	28	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/label.tsx	25	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/menubar.tsx	253	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/navigation-menu.tsx	127	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/pagination.tsx	116	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/popover.tsx	30	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/progress.tsx	27	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/radio-group.tsx	41	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/resizable.tsx	44	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/scroll-area.tsx	45	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/select.tsx	158	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/separator.tsx	28	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/sheet.tsx	139	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/sidebar.tsx	726	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/skeleton.tsx	15	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/slider.tsx	25	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/sonner.tsx	31	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/spinner.tsx	15	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/switch.tsx	26	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/table.tsx	119	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/tabs.tsx	52	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/textarea.tsx	21	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/toaster.tsx	4	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/toggle-group.tsx	60	Reusable UI primitive/shadcn-style component included in project.

File	Lines	Role
src/components/ui/toggle.tsx	42	Reusable UI primitive/shadcn-style component included in project.
src/components/ui/tooltip.tsx	31	Reusable UI primitive/shadcn-style component included in project.
src/data/calendar.ts	211	Manual calendar block CRUD, .ics import normalization/dedupe, convert block to task.
src/data/db.ts	60	Dexie database class, schema versions, active db singleton.
src/data/exportImport.ts	341	Backup export/import validation/restore and data clearing helpers.
src/data/ics.ts	147	.ics VEVENT parser and date conversion helpers.
src/data/integrity.ts	314	Cross-store data integrity report and selected fix functions.
src/data/profile.ts	257	Local profile metadata DB, active profile resolution, profile DB creation, legacy migration, settings bootstrap.
src/data/reminders.ts	447	Reminder settings, scheduler, CRUD, manual reminder creation, notifications.
src/data/review.ts	440	Daily/weekly review generation, review gating, carry-over and missed task actions.
src/data/seed.ts	136	Demo data reset only; normal seed is disabled.
src/data/tutorial.ts	74	Tutorial prompt/seen/dismissed/completed status in settings.
src/engine/dailyPlan.ts	78	Daily plan creation and mutation helpers.
src/engine/nowWhat.ts	1172	NOW_WHAT? context builder, rule engine, ranking, focus readiness, suggestion persistence, dismiss cooldowns.
src/hooks/use-mobile.tsx	21	Shared React hook utility.
src/hooks/use-toast.ts	4	Shared React hook utility.
src/index.css	328	Global HUD tokens, layout, focus/interaction states, responsive rules.
src/lib/utils.ts	7	Project file included in core package.
src/main.tsx	7	React DOM entrypoint.
src/pages/not-found.tsx	23	Project file included in core package.
src/types/index.ts	267	Central TypeScript domain model definitions.
src/utils/dateUtils.ts	86	Date/time utility.
tsconfig.json	26	Project configuration or documentation.
vite.config.ts	26	Project configuration or documentation.

15. Exported Symbol Inventory

File	Line	Symbol
src/App.tsx	78	`export default function App() {`
src/components/calendar/CalendarBlockModal.tsx	25	`export default function CalendarBlockModal({ block, onClose, onSaved }: Props) {`
src/components/calendar/CalendarBlockRow.tsx	10	`export default function CalendarBlockRow({ block, isActive, onEdit }: Props) {`
src/components/calendar/CalendarPage.tsx	10	`export default function CalendarPage() {`
src/components/dashboard/ActivityFeed.tsx	6	`export default function ActivityFeed() {`
src/components/dashboard/CalendarStrip.tsx	7	`export default function CalendarStrip() {`
src/components/dashboard/Dashboard.tsx	11	`export default function Dashboard() {`
src/components/dashboard/GoalStrip.tsx	6	`export default function GoalStrip() {`
src/components/dashboard/LifestyleStrip.tsx	6	`export default function LifestyleStrip() {`
src/components/dashboard/NowWhatCard.tsx	24	`export default function NowWhatCard() {`
src/components/dashboard/ReviewPrompt.tsx	8	`export default function ReviewPrompt() {`
src/components/dashboard/TaskList.tsx	7	`export default function TaskList() {`
src/components/data/DangerZone.tsx	7	`export default function DangerZone() {`
src/components/data/DataPage.tsx	10	`export default function DataPage() {`
src/components/data/ExportPanel.tsx	4	`export default function ExportPanel() {`
src/components/data/ImportPanel.tsx	7	`export default function ImportPanel() {`
src/components/data/IntegrityPanel.tsx	5	`export default function IntegrityPanel() {`

File	Line	Symbol
src/components/data/SchemaPanel.tsx	29	export default function SchemaPanel() {
src/components/debug/EngineDebugPanel.tsx	12	export default function EngineDebugPanel({ context, candidates, suggestion, onClose }: EngineDebugPanelProps) {
src/components/goals/GoalModal.tsx	31	export default function GoalModal({ goal, onClose }: Props) {
src/components/goals/GoalRow.tsx	14	export default function GoalRow({ goal, allTasks, habits, todayStr, onEdit }: Props) {
src/components/goals/GoalsPage.tsx	9	export default function GoalsPage() {
src/components/habits/HabitModal.tsx	12	export default function HabitModal({ habit, onClose, onSaved }: Props) {
src/components/habits/HabitRow.tsx	13	export default function HabitRow({ habit, onComplete, onEdit, onDelete, goalTitle }: Props) {
src/components/habits/HabitsPage.tsx	9	export default function HabitsPage() {
src/components/layout/AppShell.tsx	11	export default function AppShell({ children }: { children: React.ReactNode }) {
src/components/layout/Sidebar.tsx	9	export default function Sidebar({ isOpen, onClose }: Props) {
src/components/layout/Topbar.tsx	16	export default function Topbar({ onMenuToggle, isOnline }: Props) {
src/components/planning/DailyPlanPanel.tsx	21	export default function DailyPlanPanel() {
src/components/quicklog/QuickLogModal.tsx	11	export default function QuickLogModal({ onClose }: Props) {
src/components/reminders/InAppReminderTray.tsx	14	export default function InAppReminderTray() {
src/components/reminders/ReminderRow.tsx	33	export default function ReminderRow({ reminder, showActions, onDismiss, onComplete, onCancel }: Props) {
src/components/reminders/ReminderSettingsPanel.tsx	5	export default function ReminderSettingsPanel() {
src/components/reminders/RemindersPage.tsx	12	export default function RemindersPage() {
src/components/review/CarryOverReview.tsx	14	export default function CarryOverReview({ pendingTasks, date, onAction }: Props) {
src/components/review/DailyReviewPage.tsx	110	export default function DailyReviewPage() {
src/components/review/DailyReviewPanel.tsx	60	export default function DailyReviewPanel({ date }: Props) {
src/components/tasks/TaskModal.tsx	12	export default function TaskModal({ onClose, onSaved }: Props) {
src/components/tasks/TaskRow.tsx	4	export default function TaskRow({ task, onComplete, goalTitle }: { task: Task, onComplete?: () => void, goalTitle?: string }) {
src/components/tasks/TasksPage.tsx	7	export default function TasksPage() {
src/components/timeline/Timeline.tsx	7	export default function Timeline() {
src/components/tutorial/TutorialPage.tsx	39	export default function TutorialPage() {
src/components/tutorial/TutorialPrompt.tsx	5	export default function TutorialPrompt() {
src/components/tutorial/TutorialSection.tsx	9	export default function TutorialSection({ index, title, children }: TutorialSectionProps) {
src/components/ui/Modal.tsx	3	export default function Modal({ children, onClose }: { children: React.ReactNode, onClose: () => void }) {
src/components/ui/Toast.tsx	5	export function ToastProvider({ children }: { children: React.ReactNode }) {
src/components/ui/Toast.tsx	44	export function useToast() {
src/components/ui/badge.tsx	32	export interface BadgeProps
src/components/ui/button.tsx	44	export interface ButtonProps
src/components/ui/chart.tsx	8	export type ChartConfig = {
src/components/ui/toaster.tsx	2	export function Toaster() {
src/data/calendar.ts	6	export type CalendarImportSource = 'ics' | 'google_ics' | 'apple_ics';
src/data/calendar.ts	8	export interface ManualCalendarBlockInput {
src/data/calendar.ts	17	export interface CalendarImportResult {
src/data/calendar.ts	23	export interface ConvertCalendarBlockResult {
src/data/calendar.ts	28	export class CalendarImportError extends Error {
src/data/calendar.ts	51	export async function getCalendarBlocksForDate(database: NowWhatDB, date: string): Promise<CalendarBlock[]> {
src/data/calendar.ts	56	export function getTodaysCalendarBlocks(database: NowWhatDB): Promise<CalendarBlock[]> {

File	Line	Symbol
src/data/calendar.ts	60	export async function getUpcomingCalendarBlocks(database: NowWhatDB, days: number): Promise<CalendarBlock[]> {
src/data/calendar.ts	73	export async function createManualCalendarBlock(database: NowWhatDB, input: ManualCalendarBlockInput): Promise<CalendarBlock> {
src/data/calendar.ts	93	export async function updateCalendarBlock(
src/data/calendar.ts	104	export async function deleteCalendarBlock(database: NowWhatDB, id: string): Promise<void> {
src/data/calendar.ts	108	export function normalizeExternalEventToBlock(
src/data/calendar.ts	128	export async function dedupeCalendarBlocks(
src/data/calendar.ts	150	export async function importIcsFile(database: NowWhatDB, file: File): Promise<CalendarImportResult> {
src/data/calendar.ts	173	export async function convertCalendarBlockToTask(
src/data/db.ts	4	export const DEFAULT_LEGACY_DB_NAME = 'nowwhat_db';
src/data/db.ts	5	export const PROFILE_SCHEMA_VERSION = 2;
src/data/db.ts	7	export class NowWhatDB extends Dexie {
src/data/db.ts	43	export function createProfileDb(dbName: string): NowWhatDB {
src/data/db.ts	47	export function setActiveDb(nextDb: NowWhatDB): void {
src/data/db.ts	54	export function getActiveDb(): NowWhatDB {
src/data/db.ts	58	export function getActiveDbName(): string {
src/data/exportImport.ts	6	export const EXPORT_VERSION = 2;
src/data/exportImport.ts	7	export const SCHEMA_VERSION = PROFILE_SCHEMA_VERSION;
src/data/exportImport.ts	8	export const APP_NAME = 'NOW_WHAT?';
src/data/exportImport.ts	14	export interface BackupProfile {
src/data/exportImport.ts	21	export interface NowWhatBackup {
src/data/exportImport.ts	42	export interface ValidationResult {
src/data/exportImport.ts	49	export interface ImportSummary {
src/data/exportImport.ts	117	export async function getSettingsInfo(): Promise<Settings> {
src/data/exportImport.ts	123	export async function exportDatabase(): Promise<void> {
src/data/exportImport.ts	196	export function validateBackup(data: unknown): ValidationResult {
src/data/exportImport.ts	282	export async function restoreDatabase(backup: NowWhatBackup): Promise<void> {
src/data/exportImport.ts	324	export async function clearAllStores(): Promise<void> {
src/data/exportImport.ts	339	export async function clearSuggestionsOnly(): Promise<void> {
src/data/ics.ts	1	export interface IcsEvent {
src/data/ics.ts	10	export interface IcsParseResult {
src/data/ics.ts	101	export function parseIcsVevents(text: string): IcsParseResult {
src/data/integrity.ts	4	export interface IntegrityIssue {
src/data/integrity.ts	14	export interface IntegrityReport {
src/data/integrity.ts	19	export async function runIntegrityChecks(): Promise<IntegrityReport> {
src/data/profile.ts	12	export interface LocalProfile {
src/data/profile.ts	23	export interface AppMeta {
src/data/profile.ts	41	export const metaDb = new NowWhatMetaDB();
src/data/profile.ts	47	export function getProfileDbName(profileId: string): string {
src/data/profile.ts	207	export async function getActiveProfileRecord(): Promise<LocalProfile | null> {
src/data/profile.ts	213	export async function ensureProfileSettings(profile: LocalProfile): Promise<Settings> {
src/data/profile.ts	246	export async function initializeProfileSession(): Promise<LocalProfile> {
src/data/reminders.ts	13	export const REMINDER_DEFAULTS = {
src/data/reminders.ts	26	export type ReminderSettings = typeof REMINDER_DEFAULTS;
src/data/reminders.ts	28	export async function getReminderSettings(): Promise<ReminderSettings> {
src/data/reminders.ts	46	export async function updateReminderSettings(updates: Partial<Settings>): Promise<void> {

File	Line	Symbol
src/data/reminders.ts	66	export function isWithinQuietHours(quietStart = '22:00', quietEnd = '08:00'): boolean {
src/data/reminders.ts	80	export async function getScheduledReminders(): Promise<Reminder[]> {
src/data/reminders.ts	84	export async function getDueReminders(): Promise<Reminder[]> {
src/data/reminders.ts	92	export async function markReminderSent(id: string): Promise<void> {
src/data/reminders.ts	107	export async function dismissReminder(id: string): Promise<void> {
src/data/reminders.ts	111	export async function completeReminder(id: string): Promise<void> {
src/data/reminders.ts	115	export async function cancelReminder(id: string): Promise<void> {
src/data/reminders.ts	119	export interface ManualReminderInput {
src/data/reminders.ts	126	export async function createManualReminder(input: ManualReminderInput): Promise<Reminder> {
src/data/reminders.ts	158	export async function clearOldReminders(): Promise<void> {
src/data/reminders.ts	198	export async function generateSystemRemindersForToday(): Promise<void> {
src/data/review.ts	5	export function getYesterdayStr(): string {
src/data/review.ts	11	export function getWeekStart(date: Date = new Date()): string {
src/data/review.ts	19	export function getWeekEnd(weekStart: string): string {
src/data/review.ts	24	export function generateDailySummaryText(data: {
src/data/review.ts	89	export async function hasReviewableActivity(date: string): Promise<boolean> {
src/data/review.ts	104	export async function isDailyReviewIncomplete(date: string): Promise<boolean> {
src/data/review.ts	112	export async function generateDailyReviewData(date: string): Promise<
src/data/review.ts	176	export async function getOrCreateDailyReview(date: string): Promise<DailyReview> {
src/data/review.ts	193	export async function refreshDailyReview(reviewId: string, date: string): Promise<DailyReview> {
src/data/review.ts	201	export async function saveDailyReviewNote(reviewId: string, note: string): Promise<void> {
src/data/review.ts	208	export async function completeDailyReview(reviewId: string, date: string): Promise<void> {
src/data/review.ts	225	export async function carryTaskToTomorrow(taskId: string, fromDate?: string): Promise<void> {
src/data/review.ts	275	export async function markTaskMissedForDate(taskId: string, date: string): Promise<void> {
src/data/review.ts	289	export function generateWeeklySummaryText(data: {
src/data/review.ts	311	export async function generateWeeklySummary(weekStart: string): Promise<WeeklyReview> {
src/data/seed.ts	5	export async function seedIfEmpty() {
src/data/seed.ts	9	export async function reseedWithDemoData() {
src/data/tutorial.ts	5	export interface TutorialStatus {
src/data/tutorial.ts	38	export async function getTutorialStatus(): Promise<TutorialStatus> {
src/data/tutorial.ts	54	export async function markTutorialPromptSeen(): Promise<void> {
src/data/tutorial.ts	60	export async function markTutorialDismissed(): Promise<void> {
src/data/tutorial.ts	68	export async function markTutorialCompleted(): Promise<void> {
src/engine/dailyPlan.ts	5	export async function getOrCreateTodaysPlan(): Promise<DailyPlan> {
src/engine/dailyPlan.ts	27	export async function setTodaysPrimaryFocus(planId: string, focus: string): Promise<void> {
src/engine/dailyPlan.ts	31	export async function addTaskToPlan(planId: string, taskId: string, currentIds: string[]): Promise<void> {
src/engine/dailyPlan.ts	36	export async function removeTaskFromPlan(planId: string, taskId: string, currentIds: string[]): Promise<void> {
src/engine/dailyPlan.ts	40	export async function addHabitToPlan(planId: string, habitId: string, currentIds: string[]): Promise<void> {
src/engine/dailyPlan.ts	45	export async function removeHabitFromPlan(planId: string, habitId: string, currentIds: string[]): Promise<void> {
src/engine/dailyPlan.ts	49	export async function addCalendarBlockToPlan(planId: string, blockId: string, currentIds: string[]): Promise<void> {

File	Line	Symbol
src/engine/dailyPlan.ts	55	export async function removeCalendarBlockFromPlan(planId: string, blockId: string, currentIds: string[]): Promise<void> {
src/engine/dailyPlan.ts	60	export async function carryOverTask(planId: string, taskId: string, currentCarryOverIds: string[], currentPlannedIds: string[])...
src/engine/nowWhat.ts	7	export type MoodState = 'CLEAR' | 'NEUTRAL' | 'LOW' | 'STRESSED' | 'RESTLESS' | 'OVERLOADED';
src/engine/nowWhat.ts	8	export type EnergySignal = 'LOW' | 'MEDIUM' | 'HIGH';
src/engine/nowWhat.ts	9	export type FocusCapacity = 'DEEP' | 'NORMAL' | 'LIGHT' | 'RECOVERY';
src/engine/nowWhat.ts	11	export interface Context {
src/engine/nowWhat.ts	62	export interface CandidateAction {
src/engine/nowWhat.ts	111	export function normalizeEnergyLevel(value: number | null): EnergySignal | null {
src/engine/nowWhat.ts	118	export function normalizeMoodState(input: StateSignalInput): MoodState {
src/engine/nowWhat.ts	138	export function deriveFocusCapacity(input: StateSignalInput & { moodState: MoodState; energyLevel: EnergySignal | null }): Focu...
src/engine/nowWhat.ts	390	export async function getCurrentContext(): Promise<Context> {
src/engine/nowWhat.ts	572	export interface ExcludeTarget {
src/engine/nowWhat.ts	780	export function getCandidateActions(ctx: Context, excludeTargets: ExcludeTarget[] = []): CandidateAction[] {
src/engine/nowWhat.ts	1038	export function rankCandidateActions(candidates: CandidateAction[]): CandidateAction | null {
src/engine/nowWhat.ts	1042	export async function persistSuggestion(s: Suggestion): Promise<void> {
src/engine/nowWhat.ts	1046	export async function generateWithDebugInfo(excludeTargets: ExcludeTarget[] = []): Promise<{
src/engine/nowWhat.ts	1138	export async function generateNowWhatSuggestion(): Promise<Suggestion> {
src/engine/nowWhat.ts	1143	export async function acceptSuggestion(id: string) {
src/engine/nowWhat.ts	1147	export async function dismissSuggestion(id: string) {
src/engine/nowWhat.ts	1170	export async function completeSuggestion(id: string) {
src/hooks/use-mobile.tsx	5	export function useIsMobile() {
src/hooks/use-toast.ts	2	export function useToast() {
src/lib/utils.ts	5	export function cn(...inputs: ClassValue[]) {
src/pages/not-found.tsx	4	export default function NotFound() {
src/types/index.ts	1	export type Priority = 'low' | 'medium' | 'high' | 'critical';
src/types/index.ts	2	export type TaskStatus = 'pending' | 'complete' | 'skipped' | 'missed';
src/types/index.ts	3	export type EnergyLevel = 'low' | 'medium' | 'high';
src/types/index.ts	4	export type TaskCategory = 'School' | 'Work' | 'Health' | 'Admin' | 'Personal' | 'Creative' | 'Social' | 'Maintenance' | string;
src/types/index.ts	6	export interface RepeatRule {
src/types/index.ts	12	export interface Task {
src/types/index.ts	32	export interface HabitCompletion {
src/types/index.ts	38	export interface Habit {
src/types/index.ts	56	export interface Goal {
src/types/index.ts	69	export interface CalendarBlock {
src/types/index.ts	84	export type LogType =
src/types/index.ts	98	export interface ActivityLog {
src/types/index.ts	114	export interface DailyPlan {
src/types/index.ts	134	export type SuggestionActionType =
src/types/index.ts	147	export interface Suggestion {
src/types/index.ts	163	export interface DailyReview {
src/types/index.ts	186	export interface WeeklyReview {
src/types/index.ts	213	export interface Settings {
src/types/index.ts	242	export interface Reminder {
src/utils/dateUtils.ts	4	export function localDateStr(d: Date): string {

File	Line	Symbol
src/utils/dateUtils.ts	12	export function localDateFromTimestamp(value: string): string {
src/utils/dateUtils.ts	20	export function isLocalDate(value: string, dateStr: string): boolean {
src/utils/dateUtils.ts	25	export function getTodayStr(): string {
src/utils/dateUtils.ts	30	export function getYesterdayStr(): string {
src/utils/dateUtils.ts	40	export function dayAfter(dateStr: string): string {
src/utils/dateUtils.ts	51	export function useTodayStr(): string {

16. Suggested Functional Test Matrix

Area	High-value tests
Fresh profile	Clear local data, reload, verify clean profile, no demo tasks, NOW_WHAT? shows NO CONTEXT AVAILABLE, ADD TASK/ADD HABIT open modals.
Engine priority	Create critical overdue task, lower priority due task, active calendar block; verify active calendar wins while active, critical overdue wins otherwise.
Cooldown	Dismiss a task suggestion, regenerate/refresh; verify same task is excluded until cooldown and NO ACTION READY appears if no alternatives.
Focus readiness	Log low energy and create short low-energy and long high-energy tasks; verify short/low task boost. Log clear/high state and verify planned/goal-linked high-value tasks boost.
Review gating	Fresh day no activity: no review prompt. Complete task/log activity: review becomes available after conditions. Complete review: prompt and review recommendation disappear.
Calendar import	Import .ics with duplicates; verify import/skipped counts, no duplicates, calendar rows appear, convert creates one task only.
Reminders	Create due task/habit window/calendar block and run scheduler; verify reminder dedupe, tray actions, quiet hours behavior, completed targets cancel reminders.
Export/import	Export backup, validate JSON stores/profile metadata, import into clean profile, verify record counts and settings localProfileId.
Integrity	Construct broken references through imported JSON; verify report catches goal/task/habit/daily plan/calendar/review/log/reminder issues and fix buttons behave.
PWA/offline	Production build + preview; verify service worker cache, offline navigation fallback, old cache cleanup, dev unregister behavior on localhost.