

Event Booking & Ticket Validation API

Objective

You need to build a backend that simulates an event booking platform. The system allows users to:

- Register / log in
- View and book events
- Validate tickets

Use in-memory arrays for all data (no DB). Authentication is handled via JWT tokens.

Instructions

You must:

- Store all data in memory (let users = [], let events = [], etc.).
- Passwords can be stored in plain text (no hashing needed for this test).

Routes to Implement

1. POST /auth/register

Registers a new user.

Request:

```
{  
  "name": "rahul", "email": "rahul@gmail.com", "password": "123", "role": "organizer"  
}
```

Response:

```
{  
  "message": "User registered successfully",  
  "userId": 1  
}
```

2. POST /auth/login

Request:

```
{  
  "email": "rahul@example.com",  
  "password": "1234"
```

```
}
```

Response:

```
{  
  "token": "eyJhbGciOiJIUzI1NilsInR5..."  
}
```

3. POST /events

Create a new event

Request Body:

```
{  
  "name": "Tech Tournament",  
  "date": "2025-12-01",  
  "totalTickets": 50  
}
```

Response:

```
{  
  "message": "Event created successfully",  
  "eventId": 1  
}
```

4. GET /events

List all available events with remaining tickets.

Response:

```
[  
  {  
    "id": 1,  
    "name": "Event 1",  
    "date": "2025-12-01",  
    "ticketsAvailable": 50  
  }  
]
```

5. POST /events/:id/book

Book a ticket for an event.

Example Request:

POST /events/1/book

Response:

```
{  
  "message": "Ticket booked successfully",  
  "eventId": 1  
}
```

```
        "ticketCode": "TCK-98217"  
    }  
}
```

6. GET /my-bookings

Returns all tickets booked by the logged-in user.

Response:

```
[  
  {  
    "event": "Tech Tournament",  
    "ticketCode": "TCK-98217",  
    "validated": false  
  }  
]
```

7. POST /tickets/validate

Validate a ticket at the event entrance.

Request:

```
{  
  "ticketCode": "TCK-98217"  
}
```

Response (if valid):

```
{  
  "message": "Ticket validated successfully",  
  "event": "Tech Tournament",  
  "userId": 1  
}
```

Response (if invalid or already validated):

```
{  
  "error": "Invalid or already validated ticket"  
}
```

Note: Organizer can only validate tickets for their own events.

8. GET /events/:id/attendees

List all validated tickets for your event.

Response:

```
{  
  "event": "Event 2",  
  "attendees": [  
    { "userId": 1, "ticketCode": "TCK-98217" }  
  ]  
}
```