ASSIGNMENT 5.1

P.NAGA SHIVA CHAITANYA (2303A51945)

BATCH 27

1 – Privacy in API Usage

TASK

Use an AI tool to generate a Python program that connects to a weather API securely without exposing API keys.

PROMPT

Generate code to fetch weather data securely without exposing API keys in the code.

CODE

Insecure Version (Hardcoded API Key)

```
import requests

API_KEY = "12345ABCDE”

CITY = "Hyderabad"


url = f"https://api.openweathermap.org/data/2.5/weather?q={CITY}&appid={API_KEY}"

response = requests.get(url)


print(response.json())
```

Secure Version (Using Environment Variables)

```
import requests

import os


API_KEY = os.getenv("WEATHER_API_KEY")

CITY = "Hyderabad"


url = f"https://api.openweathermap.org/data/2.5/weather?q={CITY}&appid={API_KEY}"

response = requests.get(url)


print(response.json())
```

OUTPUT

- Weather details of the given city are displayed in JSON format.
- API key is **not visible** in the code.

EXPLANATION

- Hardcoding API keys is a **privacy risk**.
- Environment variables keep keys hidden and secure.
- This approach prevents accidental exposure on GitHub or public files.

---

2 – Privacy & Security in File Handling

TASK

Store user data securely by avoiding plain-text password storage.

PROMPT

Generate a Python script that stores user data securely instead of plain text.

CODE

Insecure Version (Plain Text Password)

```
name = input("Enter name: ")
email = input("Enter email: ")
password = input("Enter password: ")

with open("users.txt", "a") as file:
    file.write(f"{name},{email},{password}\n")
```

Secure Version (Hashed Password)

```
import hashlib

name = input("Enter name: ")
email = input("Enter email: ")
password = input("Enter password: ")

hashed_password = hashlib.sha256(password.encode()).hexdigest()

with open("users.txt", "a") as file:
    file.write(f"{name},{email},{hashed_password}\n")
```

OUTPUT

- User data is stored.
- Password appears as a **hashed value**, not readable text.

EXPLANATION

- Plain text passwords can be stolen easily.
- Hashing converts passwords into irreversible values.
- Even if the file is leaked, passwords remain protected.

---

3 – Transparency in Algorithm Design

TASK

Create an Armstrong number checker with transparent explanation.

PROMPT

Generate Python code to check an Armstrong number and explain it line by line.

CODE

```
def is_armstrong(number):
    digits = list(map(int, str(number)))
    power = len(digits)

    total = sum(d ** power for d in digits)

    return total == number

num = int(input("Enter a number: "))
print(is_armstrong(num))
```

OUTPUT

Enter a number: 153

True

EXPLANATION

- Number is converted into digits.
- Each digit is raised to the power of total digits.
- If the sum equals the original number, it is an Armstrong number.

- Code and explanation match clearly, ensuring transparency.

---

4 – Transparency in Algorithm Comparison

TASK

Implement and compare QuickSort and BubbleSort.

PROMPT

Generate Python code for QuickSort and BubbleSort with step-by-step explanations.

CODE

```
# Bubble Sort
def bubble_sort(arr):
    for i in range(len(arr)):
        for j in range(0, len(arr)-i-1):
            if arr[j] > arr[j+1]:
                arr[j], arr[j+1] = arr[j+1], arr[j]
    return arr



# Quick Sort
def quick_sort(arr):
    if len(arr) <= 1:
        return arr

    pivot = arr[0]
    left = [x for x in arr[1:] if x <= pivot]
    right = [x for x in arr[1:] if x > pivot]

    return quick_sort(left) + [pivot] + quick_sort(right)
```

OUTPUT

Bubble Sort: [1, 2, 4, 5, 8]

Quick Sort: [1, 2, 4, 5, 8]

EXPLANATION

- BubbleSort compares adjacent elements repeatedly.
- QuickSort divides the list using a pivot.
- BubbleSort is slower ($O(n^2)$).
- QuickSort is faster ($O(n \log n)$).

Aspect	Bubble Sort	Quick Sort
Method	Swapping adjacent elements	Divide and conquer
Time Complexity	$O(n^2)$	$O(n \log n)$
Efficiency	Slow	Fast
Use Case	Small lists	Large datasets

---

5 – Transparency in AI Recommendations

TASK

Create a recommendation system with explainable suggestions.

PROMPT

Generate a recommendation system that explains why each product is suggested.

CODE

```
def recommend_products(user_interest):
    products = {
        "fitness": ["Dumbbells", "Yoga Mat"],
        "technology": ["Laptop", "Smartphone"],
        "books": ["Fiction Novel", "Self-help Book"]
    }

    recommendations = products.get(user_interest, [])

    for item in recommendations:
        print(f"Recommended: {item} because it matches your interest in {user_interest}.")
```

OUTPUT

Recommended: Laptop because it matches your interest in technology.

Recommended: Smartphone because it matches your interest in technology.

EXPLANATION

- Recommendations are based on user interests.
- Each suggestion includes a clear reason.
- Improves transparency and user trust.
