

- 1.
select (row_number() over (order by salary desc)) as s_no, emp_name, department, salary
from employees;
- 2.
select (rank() over (order by salary desc)) as s_no, emp_name, department, salary from
employees;
- 3.
select (dense_rank() over (order by salary desc)) as s_no, emp_name, department, salary
from employees;
- 4.
select (row_number() over (partition by department order by salary desc)) as s_no,
emp_name, department, salary from employees;
- 5.
select (rank() over (partition by department order by salary desc)) as s_no, emp_name,
department, salary from employees;
- 6.
select emp_name, department, salary from (select (dense_rank() over (partition by
department order by salary desc)) as s_no, emp_name, department, salary from employees)
t where s_no <= 2;
- 7.
select (first_value(emp_name) over (partition by department order by salary desc)) as s_no,
emp_name, department, salary from employees;
- 8.
select (last_value(emp_name) over (partition by department order by salary desc rows
between unbounded preceding and unbounded following)) as s_no, emp_name, department,
salary from employees;
- 9.
select emp_name, department, salary, (first_value(salary) over (partition by department
order by salary desc)) as highest_salary, (last_value(salary) over (partition by department
order by salary desc rows between unbounded preceding and unbounded following)) as
lowest_salary from employees;
- 10.

```
select emp_id, emp_name, department, salary from (select (dense_rank() over (order by
salary desc)) as s_no, emp_id, emp_name, department, salary from employees) t where
s_no = 2;
```