Railway Reservation System

Code and Branch Coverage Report

Updated using the complete automated test run against the dedicated MongoDB test database (railway_test).

1. Test Execution Summary

Metric	Result
Test cases	81
Passed	81
Failed	0
Skipped	0
Test suites	13
Execution time	7.52 seconds

2. Overall Coverage

Coverage metric	Percentage
Statements	83.05%
Branches	80.00%
Functions	100.00%
Lines	83.05%

3. Coverage by Module

Module	Statements	Branches	Functions	Lines
src	74.32%	73.46%	100%	74.32%
src/config	100%	100%	100%	100%
src/middleware	70.58%	75%	100%	70.58%
src/models	98.16%	83.33%	100%	98.16%
src/routes	70.54%	74.73%	100%	70.54%
src/services	98.06%	85.98%	100%	98.06%

4. File-Level Coverage Highlights

• 100% coverage: fares.js, languages.js, waitlist.js (config), Booking.js, User.js, holds.js, pnr.js, publicBooking.js, refund.js.

• High coverage: bookings.js route (86.96% statements), waitlist.js route (92.92%), payment.js service (96.72%), waitlist.js service (97.33%).

• Lower coverage areas: users.js route (34.24%), auth.js middleware (70.58%), server.js (74.32%).

5. Notes

All 81 tests passed with no failures, cancellations, skipped tests, or TODO tests. Mongoose emitted deprecation warnings for the `new` option in findOneAndUpdate/findOneAndReplace; these warnings did not affect test execution.

Coverage describes the code exercised by the automated tests. Remaining uncovered lines and branches can be inspected in the generated HTML coverage report.