

GeeksforGeeks

A computer science portal for geeks

GeeksQuiz

- [Home](#)
- [Algorithms](#)
- [DS](#)
- [GATE](#)
- [Interview Corner](#)
- [Q&A](#)
- [C](#)
- [C++](#)
- [Java](#)
- [Books](#)
- [Contribute](#)
- [Contests](#)
- [Jobs](#)

[Array](#)

[Bit Magic](#)

[C/C++](#)

[Articles](#)

[GFacts](#)

[Linked List](#)

[MCQ](#)

[Misc](#)

[Output](#)

[String](#)


[Tree](#)

[Graph](#)

Memory Layout of C Programs

A typical memory representation of C program consists of following sections.

1. Text segment
2. Initialized data segment
3. Uninitialized data segment
4. Stack
5. Heap



A typical memory layout of a running process

1. Text Segment:

A text segment, also known as a code segment or simply as text, is one of the sections of a program in an object file or in memory, which contains executable instructions.

As a memory region, a text segment may be placed below the heap or stack in order to prevent heaps and stack overflows from overwriting it.

Usually, the text segment is sharable so that only a single copy needs to be in memory for frequently executed programs, such as text editors, the C compiler, the shells, and so on. Also, the text segment is often read-only, to prevent a program from accidentally modifying its instructions.

2. Initialized Data Segment:

Initialized data segment, usually called simply the Data Segment. A data segment is a portion of virtual address space of a program, which contains the global variables and static variables that are initialized by the programmer.

Note that, data segment is not read-only, since the values of the variables can be altered at run time.

This segment can be further classified into initialized read-only area and initialized read-write area.

For instance the global string defined by `char s[] = "hello world"` in C and a C statement like `int debug=1` outside the main (i.e. global) would be stored in initialized read-write area. And a global C statement like `const char* string = "hello world"` makes the string literal "hello world" to be stored in initialized read-only area and the character pointer variable `string` in initialized read-write area.

Ex: `static int i = 10` will be stored in data segment and `global int i = 10` will also be stored in data segment

3. Uninitialized Data Segment:

Uninitialized data segment, often called the "bss" segment, named after an ancient assembler

operator that stood for “block started by symbol.” Data in this segment is initialized by the kernel to arithmetic 0 before the program starts executing

uninitialized data starts at the end of the data segment and contains all global variables and static variables that are initialized to zero or do not have explicit initialization in source code.

For instance a variable declared `static int i;` would be contained in the BSS segment.

For instance a global variable declared `int j;` would be contained in the BSS segment.

4. Stack:

The stack area traditionally adjoined the heap area and grew the opposite direction; when the stack pointer met the heap pointer, free memory was exhausted. (With modern large address spaces and virtual memory techniques they may be placed almost anywhere, but they still typically grow opposite directions.)

The stack area contains the program stack, a LIFO structure, typically located in the higher parts of memory. On the standard PC x86 computer architecture it grows toward address zero; on some other architectures it grows the opposite direction. A “stack pointer” register tracks the top of the stack; it is adjusted each time a value is “pushed” onto the stack. The set of values pushed for one function call is termed a “stack frame”; A stack frame consists at minimum of a return address.

Stack, where automatic variables are stored, along with information that is saved each time a function is called. Each time a function is called, the address of where to return to and certain information about the caller’s environment, such as some of the machine registers, are saved on the stack. The newly called function then allocates room on the stack for its automatic and temporary variables. This is how recursive functions in C can work. Each time a recursive function calls itself, a new stack frame is used, so one set of variables doesn’t interfere with the variables from another instance of the function.

5. Heap:

Heap is the segment where dynamic memory allocation usually takes place.

The heap area begins at the end of the BSS segment and grows to larger addresses from there. The Heap area is managed by `malloc`, `realloc`, and `free`, which may use the `brk` and `sbrk` system calls to adjust its size (note that the use of `brk/sbrk` and a single “heap area” is not required to fulfill the contract of `malloc/realloc/free`; they may also be implemented using `mmap` to reserve potentially non-contiguous regions of virtual memory into the process’ virtual address space). The Heap area is shared by all shared libraries and dynamically loaded modules in a process.

Examples.

The `size(1)` command reports the sizes (in bytes) of the text, data, and bss segments. (for more details please refer man page of `size(1)`)

1. Check the following simple C program

```
#include <stdio.h>
```

```
int main(void)
{
    return 0;
}
```

```
[narendra@CentOS]$ gcc memory-layout.c -o memory-layout
[narendra@CentOS]$ size memory-layout
```

text	data	bss	dec	hex	filename
960	248	8	1216	4c0	memory-layout

2. Let us add one global variable in program, now check the size of bss (highlighted in red color).

```
#include <stdio.h>
```

```
int global; /* Uninitialized variable stored in bss*/
```

```
int main(void)
{
    return 0;
}
```

```
[narendra@CentOS]$ gcc memory-layout.c -o memory-layout
[narendra@CentOS]$ size memory-layout
text      data      bss      dec      hex      filename
960       248       12      1220     4c4      memory-layout
```

3. Let us add one static variable which is also stored in bss.

```
#include <stdio.h>
```

```
int global; /* Uninitialized variable stored in bss*/
```

```
int main(void)
{
    static int i; /* Uninitialized static variable stored in bss */
    return 0;
}
```

```
[narendra@CentOS]$ gcc memory-layout.c -o memory-layout
[narendra@CentOS]$ size memory-layout
text      data      bss      dec      hex      filename
960       248       16      1224     4c8      memory-layout
```

4. Let us initialize the static variable which will then be stored in Data Segment (DS)

```
#include <stdio.h>
```

```
int global; /* Uninitialized variable stored in bss*/
```

```
int main(void)
{
    static int i = 100; /* Initialized static variable stored in DS*/
    return 0;
}
```

```
[narendra@CentOS]$ gcc memory-layout.c -o memory-layout
[narendra@CentOS]$ size memory-layout
text      data      bss      dec      hex      filename
960       252       12      1224     4c8      memory-layout
```

5. Let us initialize the global variable which will then be stored in Data Segment (DS)

```
#include <stdio.h>
```

```
int global = 10; /* initialized global variable stored in DS*/
```

```
int main(void)
{
    static int i = 100; /* Initialized static variable stored in DS*/
    return 0;
}
```

```
[narendra@CentOS]$ gcc memory-layout.c -o memory-layout
[narendra@CentOS]$ size memory-layout
text      data      bss      dec      hex      filename
960        256         8      1224      4c8      memory-layout
```

This article is compiled by **Narendra Kangralkar**. Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

Source:

http://en.wikipedia.org/wiki/Data_segment

http://en.wikipedia.org/wiki/Code_segment

<http://en.wikipedia.org/wiki/.bss>

<http://www.amazon.com/Advanced-Programming-UNIX-Environment-2nd/dp/0201433079>



Related Topics:

- [An interesting time complexity question](#)
- [A Problem in Many Binary Search Implementations](#)
- [Analysis of Algorithms | Set 4 \(Analysis of Loops\)](#)
- [Analysis of Algorithms | Set 3 \(Asymptotic Notations\)](#)
- [NP-Completeness | Set 1 \(Introduction\)](#)
- [Static and Dynamic Libraries | Set 1](#)
- [The Ubiquitous Binary Search | Set 1](#)
- [Reservoir Sampling](#)

Tags: [Memory Layout Of C Program](#)

Like 165 Tweet 10 G+1 42

Writing code in comment? Please use ideone.com and share the link here.

140 Comments GeeksforGeeks



Login ▾

-

-

**GeeksforGeeks**

Like

101,391 people like GeeksforGeeks.

-

-

- [Interview Experiences](#)
- [Advanced Data Structures](#)
- [Dynamic Programming](#)
- [Greedy Algorithms](#)
- [Backtracking](#)
- [Pattern Searching](#)
- [Divide & Conquer](#)
- [Mathematical Algorithms](#)
- [Recursion](#)
- [Geometric Algorithms](#)



The advertisement features the Payoneer logo at the top. Below it, the title 'Freelancer Income Survey Report' is displayed in a large, white, sans-serif font. A green diagonal banner on the left side reads 'India Edition'. The central image shows a woman with long dark hair, wearing a yellow top, sitting at a desk and looking at a laptop. The laptop screen displays a large yellow arrow pointing to the right. At the bottom, a dark grey box contains the text 'Are You Earning Enough? Get the Freelancer Income Report Now and Find Out!' in white, followed by an orange button with the text 'Free Download' in white.

• Popular Posts

- [All permutations of a given string](#)
- [Memory Layout of C Programs](#)
- [Understanding “extern” keyword in C](#)
- [Median of two sorted arrays](#)
- [Tree traversal without recursion and without stack!](#)
- [Structure Member Alignment, Padding and Data Packing](#)
- [Intersection point of two Linked Lists](#)
- [Lowest Common Ancestor in a BST.](#)
- [Check if a binary tree is BST or not](#)
- [Sorted Linked List to Balanced BST](#)

Follow @GeeksforGeeks

• Recent Comments

- [Cracker](#)

Round 2: Question 3:...

[Paytm Interview Experience | Set 4 \(Walk-in Drive\)](#) · [0 minutes ago](#)

◦ [Mr. Lazy](#)

See your forked code <http://ideone.com/nxDksE...>

[Connect nodes at same level](#) · [1 minute ago](#)

◦ [shivendra pratap singh](#)

Given strings SUNDAY and SATURDAY. We want to...

[Dynamic Programming | Set 5 \(Edit Distance\)](#) · [7 minutes ago](#)

◦ [Harshit Agrawal](#)

Lecture Handouts for DBMS are not available

[GATE](#) · [10 minutes ago](#)

◦ [DS+Algo](#)

<http://ideone.com/CEvXG9> See, my logic is...

[Connect nodes at same level](#) · [18 minutes ago](#)

◦ [Tequila](#)

use recursion

[Printing Longest Common Subsequence](#) · [20 minutes ago](#)

Ads by Google

▶ [Memory Map](#)

▶ [In Memory](#)

• ▶ [Shared Memory](#)

Ads by Google

▶ [In Memory](#)

▶ [Physical Memory](#)

▶ [Memory Program](#)

Ads by Google

▶ [Memory Class](#)

▶ [Layout Tutorial](#)

▶ [Virtual Memory](#)

@geeksforgeeks, [Some rights reserved](#) [Contact Us!](#) [About Us!](#)

Powered by [WordPress](#) & [MooTools](#), customized by geeksforgeeks