

[Questions](#) [Tags](#) [Users](#) [Badges](#) [Unanswered](#) [Ask](#)

## How to set a timer in android

81

android

What is the proper way to set a timer in android in order to kick off a task (a function that I create which does not change the UI)? Use this the Java way:

<http://java.sun.com/j2se/1.4.2/docs/api/java/util/Timer.html>

Or there is a better way in android (android's handler)?

[share](#) [improve this question](#)**n179911**

3,019 ●11 ●45 ●75

**Asked**  
Dec 9 '09 at 22:35**RedBlueThing**

21.8k ●9 ●62 ●96

**Edited**  
Sep 22 '10 at 23:29

10 Answers

order by [votes](#)

90

Standard Java way to use timers via [java.util.Timer](#) and [java.util.TimerTask](#) works fine in Android, but you should be aware that this method creates a new thread.

You may consider using the very convenient [Handler](#) class (`android.os.Handler`) and send messages to the handler via `sendMessageAtTime(android.os.Message, long)` or `sendMessageDelayed(android.os.Message, long)`. Once you receive a message, you can run desired tasks. Second option would be to create a [Runnable](#) object and schedule it via `Handler's` functions `postAtTime(java.lang.Runnable, long)` or `postDelayed(java.lang.Runnable, long)`.

[share](#) [improve this answer](#)**MannyNS**

3,600 ●1 ●12 ●14

**Answered**  
Dec 10 '09 at 0:30

6

This is the wrong way to do things in android. In android, you want to use the Alarm Manager ( [developer.android.com/reference/android/app/AlarmManager.html](http://developer.android.com/reference/android/app/AlarmManager.html) ) for running tasks far in the future. – [Kurtis Nusbaum](#) Oct 15 '11 at 4:16

6

@Kurtis Nusbaum The question doesn't say how far in the future the task is. – [Christopher Perry](#) Nov 5 '11 at 7:25

48

@KurtisNusbaum That's not necessarily true, it depends on the context. The docs on `AlarmManager` say, "Note: The Alarm Manager is intended for cases where you want to have your application code

run at a specific time, even if your application is not currently running. For normal timing operations (ticks, timeouts, etc) it is easier and much more efficient to use Handler." – [Christopher Perry Nov 5 '11 at 18:42](#)

3 @Scienceprodigy Ah, I see. Fair enough. – [Kurtis Nusbaum Nov 5 '11 at 19:07](#)

6 using the Handler method of scheduling a task is reliable only if the application has acquired a wakeLock and hence you are sure that the phone shall not go into the sleep state. If phone does go to the sleep state then sendMessageDelayed as well as sendMessageAtTime will not work. Hence in that scenario AlarmManager would be reliable choice. – [crazyaboutliv Jan 27 '12 at 21:59](#)

[show 3 more comments](#)

79 As I have seen it, [java.util.Timer](#) is the most used for implementing a timer.

**For a repeating task:**

```
new Timer().scheduleAtFixedRate(task, after, interval);
```

**For a single run of a task:**

```
new Timer().schedule(task, after);
```

**task** being the method to be executed  
**after** the time to initial execution  
**(interval** the time for repeating the execution)

[share](#) [improve this answer](#)



**MrThys**

1,990 ●14 ●60 ●100

**Answered**

Dec 10 '09 at 22:03



**naxa**

1,343 ●1 ●9 ●23

**Edited**

Sep 30 '13 at 7:55

5 I'll just add that time is in milliseconds – [Uri Dec 27 '12 at 3:40](#)

awesome thanks.. – [Houston Apr 3 '13 at 6:12](#)

1 android dev docs for [scheduleAtFixedRate](#) – [naxa Sep 30 '13 at 7:51](#)

1 task may be an instance of your class that inherits from [java.util.TimerTask](#) and overrides void run(). – [naxa Sep 30 '13 at 7:54](#)

So many upvotes. You could do this. But @Samuel describes the better way. See his "Which is explained Here" link for why. Also, can't update UI from a Timer thread! And see these other Handler-based answers in other threads: (simple) [stackoverflow.com/a/6702767/199364](#), or (shows various alternatives) [stackoverflow.com/a/4598737/199364](#) – [ToolmakerSteve Sep 12 at 16:38](#)

66 yes java's timer *can be used*, but as the question asks for **better way** (for mobile). Which is explained [Here](#).

---

### For the sake of StackOverflow:

Since [Timer](#) creates a new thread it may be considered heavy,

if all you need is to get is a call back while the activity is running a [Handler](#) can be used in conjunction with a

#### [Runnable](#):

```
private final int interval = 1000; // 1 Second
private Handler handler = new Handler();
private Runnable runnable = new Runnable(){
    public void run() {
        Toast.makeText(MyActivity.this, "C'Mom no hands!", Toast.LENGTH_SHORT).show();
    }
};
...
handler.postAtTime(runnable, System.currentTimeMillis()+interval);
handler.postDelayed(runnable, interval);
```

or a [Message](#)

```
private final int EVENT1 = 1;
private Handler handler = new Handler() {
    @Override
    public void handleMessage(Message msg) {
        switch (msg.what) {
            case Event1:
                Toast.makeText(MyActivity.this, "Event 1", Toast.LENGTH_SHORT).show();
                break;

            default:
                Toast.makeText(MyActivity.this, "Unhandled", Toast.LENGTH_SHORT).show();
                break;
        }
    }
};
...

Message msg = handler.obtainMessage(EVENT1);
handler.sendMessageAtTime(msg, System.currentTimeMillis()+interval);
handler.sendMessageDelayed(msg, interval);
```

on a side note this approach can be used, if you want to run a piece of code in the UI thread from an another thread.

if you need to get a call back even if your activity is not running then, you can use an [AlarmManager](#)



Samuel

4,670 ● 1 ● 16 ● 30

Answered

Oct 20 '10 at 6:42



Adrian Toman

5,025 ● 3 ● 23 ● 38

Edited

Jul 15 at 8:24

- 1 Oh yea, I googled exactly this answer. Take my upvote for the useful link. – [ulidtko Jul 24 '11 at 10:15](#)
- 1 Link doesn't work :( – [SSH This Jul 7 '12 at 5:34](#)
- 1 updated the link, talk about google having trouble maintaining links. – [Samuel Jul 10 '12 at 1:17](#)
- 1 This article from 2007 - not saying it's wrong, but I'm always suspicious of a mobile article if it's older than 3 years. Things change pretty quickly. – [StackOverflowed Sep 22 '12 at 13:13](#)
- 1 it would be more like StackOverflow if you could quote the main points of your link here in your answer. – [naxa Sep 30 '13 at 7:56](#)

[show 4 more comments](#)

- 9 It is situational.
- The Android documentation suggests that you should use [AlarmManager](#) to register an Intent that will fire at the specified time if your application may not be running.
- Otherwise, you should use Handler.

Note: The Alarm Manager is intended for cases where you want to have your application code run at a specific time, even if your application is not currently running. For normal timing operations (ticks, timeouts, etc) it is easier and much more efficient to use Handler.

[share](#) [improve this answer](#)



Timothy Lee Russell

2,558 ● 1 ● 12 ● 25

Answered

Sep 22 '10 at 23:37

- 7 Here we go.. We will need two classes. I am posting a code which changes mobile audio profile after each 5 seconds (5000 mili seconds) ...

***Our 1st Class***

```

public class ChangeProfileActivityMain extends Activity {

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        // TODO Auto-generated method stub
        super.onCreate(savedInstanceState);

        Timer timer = new Timer();
        TimerTask updateProfile = new CustomTimerTask(ChangeProfileActivityMain.this);
        timer.scheduleAtFixedRate(updateProfile, 0, 5000);
    }

}

```

### Our 2nd Class

```

public class CustomTimerTask extends TimerTask {

    private AudioManager audioManager;
    private Context context;
    private Handler mHandler = new Handler();

    // Write Custom Constructor to pass Context
    public CustomTimerTask(Context con) {
        this.context = con;
    }

    @Override
    public void run() {
        // TODO Auto-generated method stub

        // your code starts here.
        // I have used Thread and Handler as we can not show Toast without starting new thread
        when we are inside a thread.
        // As TimePicker has run() thread running., So We must show Toast through Handler.post in
        a new Thread. Thats how it works in Android..
        new Thread(new Runnable() {

```

[share](#) [improve this answer](#)



**Rizwan Sohaib**  
729 ● 8 ● 17

**Answered**  
Apr 11 '12 at 6:47

**Edited**  
Apr 11 '12 at 11:27

4

I'm an Android newbie but here is the timer class I created based on the answers above. It works for my app but I welcome any suggestions.

Usage example:

```

...{
public Handler uiHandler = new Handler();

private Runnable runMethod = new Runnable()
{
    public void run()
    {
        // do something
    }
};

timer = new UITimer(handler, runMethod, timeoutSeconds*1000);
timer.start();
}...

public class UITimer
{
    private Handler handler;
    private Runnable runMethod;
    private int intervalMs;
    private boolean enabled = false;
}

```

[share](#) [improve this answer](#)



**user868020**

41 ● 1

**Answered**

Jul 28 '11 at 17:49

2

I believe the way to do this on the android is that you need a background service to be running. In that background application, create the timer. When the timer "ticks" (set the interval for how long you want to wait), launch your activity which you want to start.

<http://developer.android.com/guide/topics/fundamentals.html> (<-- this article explains the relationship between activities, services, intents and other core fundamentals of Android development)

[share](#) [improve this answer](#)



**Crowe T. Robot**

1,808 ● 9 ● 16

**Answered**

Dec 9 '09 at 22:39

1

For timing operation you should use Handler. See

<http://developer.android.com/resources/articles/timed-ui-updates.html>

If you need to run a background service the AlarmManager is the way to go. Have a look to the BuzzBox SDK

<http://hub.buzzbox.com/android-sdk/>

you can create a Task and schedule it using a cron string and it will work similarly to crontab on linux

[share](#) [improve this answer](#)



1

## Probably Timerconcept

```
new CountDownTimer(40000, 1000) { //40000 milli seconds is total time, 1000 milli seconds is time interval
```

```
    public void onTick(long millisUntilFinished) {  
    }  
    public void onFinish() {  
    }  
}.start();
```

or

Method 2 ::

Program the timer

Add a new variable of int named time. Set it to 0. Add the following code to onCreate function in MainActivity.java.

```
//Declare the timer  
Timer t = new Timer();  
//Set the schedule function and rate  
t.scheduleAtFixedRate(new TimerTask() {  
  
    @Override  
    public void run() {  
        //Called each time when 1000 milliseconds (1 second) (the period parameter)  
    }  
  
},  
//Set how long before to start calling the TimerTask (in milliseconds)  
0,  
//Set the amount of time between each execution (in milliseconds)  
1000);
```

Go into the run method and add the following code.

```
//We must use this function in order to change the text view text  
runOnUiThread(new Runnable() {  
  
    @Override  
    public void run() {  
        TextView tv = (TextView) findViewById(R.id.main_timer_text);  
        tv.setText(String.valueOf(time));  
        time += 1;  
    }  
  
});
```



vkulkarni  
107 ● 6

Answered  
Oct 11 '13 at 8:18

1

I hope this one is helpful and may take less efforts to implement, [Android CountdownTimer class](#)

e.g.

```
new CountdownTimer(30000, 1000) {  
  
    public void onTick(long millisUntilFinished) {  
        mTextField.setText("seconds remaining: " + millisUntilFinished / 1000);  
    }  
  
    public void onFinish() {  
        mTextField.setText("done!");  
    }  
}.start();
```

[share](#) [improve this answer](#)



Gaurav Adurkar  
17 ● 4

Answered  
Mar 10 at 7:25

## Your Answer

[log in](#)

or

Name

Email



Home Page

By posting your answer, you agree to the [privacy policy](#) and [terms of service](#).

Post Your Answer