

NXTWAVE SEMICONDUCTOR

Careers Handover Guide

Managing open roles, applications, Resend email delivery, and Vercel deployment.

Current setup: Career roles are managed in code through `data/jobs.ts`. Applications are submitted through the existing form and sent by the Next.js API route at `/api/careers`.

1. Managing Career Roles

All open roles are stored in `data/jobs.ts`. There is currently no CMS or admin dashboard. Role updates require editing the file and deploying the project.

Add a role

Add a new object inside the `jobs` array:

```
{
  slug: 'verification-engineer',
  title: 'Verification Engineer',
  department: 'VLSI / Verification',
  domain: 'Design Verification',
  serviceId: 'design-verification',
  experience: 'Mid-level',
  experienceYears: '3+ years',
  location: 'Bangalore, IN',
  workModel: 'Hybrid',
  employmentType: 'Full-time',
  overview: 'Role introduction goes here.',
  responsibilities: ['Responsibility one.', 'Responsibility two.'],
  requiredQualifications: ['Required qualification.'],
  preferredQualifications: ['Preferred qualification.'],
  skills: ['SystemVerilog', 'UVM'],
  benefits: ['Benefit or working condition.'],
}
```

Required role fields

Field	Purpose
<code>slug</code>	Unique lowercase URL identifier, for example <code>verification-engineer</code> .
<code>title</code>	Role title shown to candidates.

<code>department</code> , <code>domain</code>	Role classification and display information.
<code>serviceId</code>	Connects the role to the Services filter. Use an existing ID from <code>lib/site.ts</code> .
<code>experience</code>	Used by the experience filter. Keep values consistent, such as Senior, Lead, or Mid-level.
<code>experienceYears</code> , <code>location</code> , <code>workModel</code> , <code>employmentType</code>	Candidate-facing role metadata.
<code>overview</code>	Main role introduction.
Responsibilities, qualifications, skills, benefits	Arrays of candidate-facing content.

Edit a role

Find the role in `data/jobs.ts` and update the required fields. Avoid changing the `slug` unless the URL should change. A changed slug creates a new URL and invalidates the old one.

Delete a role

Remove the complete role object from the `jobs` array. The role will disappear from the listing and its old URL will return a 404 after deployment. Check whether the old URL is externally shared or indexed before deleting it.

2. Role URLs and Filters

Role pages are generated automatically by `app/careers/[slug]/page.tsx` :

```
/careers/<slug>
```

The Careers listing filters by:

- **Service:** based on `serviceId` .
- **Experience:** based on `experience` .

Use only service IDs already defined in `lib/site.ts` , such as `design-verification` , `physical-design` , or `analog-mixed-signal` .

3. Application and Email Flow

The application form is included automatically on each role page. It submits multipart form data to:

```
/api/careers
```

The API reads the server-only environment variables below and sends the application through Resend.

Environment variable	Purpose
RESEND_API_KEY	Private Resend API key. Never expose or commit it.
RESEND_FROM_EMAIL	Verified sender, currently <code>careers@nxtwavesemi.com</code> .
CAREERS_RECIPIENT_EMAIL	Application recipient, currently <code>info@nxtwavesemiconductor.com</code> .

Security: Never put the real API key in `.env.example`, frontend code, Git, screenshots, or chat. Use local `.env.local` or Vercel Environment Variables only.

4. Local Development

Create a local `.env.local` file with private values, then restart the development server:

```
RESEND_API_KEY=your_private_resend_api_key
RESEND_FROM_EMAIL=careers@nxtwavesemi.com
CAREERS_RECIPIENT_EMAIL=info@nxtwavesemiconductor.com
```

```
pnpm dev
```

Test a role page, complete the form, and upload a real PDF, DOC, or DOCX resume under 10 MB. The local API returns an error when required environment variables are missing.

5. Vercel Deployment

1. Open the correct Vercel project.
2. Open **Settings** → **Environment Variables**.
3. Add `RESEND_API_KEY`, `RESEND_FROM_EMAIL`, and `CAREERS_RECIPIENT_EMAIL`.
4. Configure Production variables for the live site.
5. Configure Preview variables separately if preview testing is required.
6. Redeploy after adding or changing environment variables.

Environment changes do not automatically update an already deployed build.

6. Resend Delivery Verification

The API reports success only when Resend returns a valid email ID. The server logs:

- Whether each required environment variable is present.
- Safe request context such as role and resume size.
- Resend error name, message, and status code when sending fails.

- The Resend email ID when accepted.

After a real submission, copy the email ID from Vercel logs and check it in Resend. Confirm whether the status is queued, sent, delivered, bounced, failed, or suppressed.

If Resend reports delivered but the recipient cannot find the message, check spam, quarantine, mailbox rules, and recipient mail-server filtering.

7. Safe Update Procedure

1. Create a branch for the role update.
2. Edit only `data/jobs.ts`.
3. Check the slug is unique.
4. Check the service ID exists in `lib/site.ts`.
5. Run `pnpm exec tsc --noEmit`.
6. Run `pnpm build`.
7. Run `pnpm dev` and test the Careers listing, filters, role URL, and application form.
8. Commit, push, review, and deploy.

8. Files to Know

File	Purpose
<code>data/jobs.ts</code>	Career role data.
<code>app/careers/page.tsx</code>	Careers listing page.
<code>app/careers/[slug]/page.tsx</code>	Individual role page and application form placement.
<code>components/application-form.tsx</code>	Candidate application form and submission behavior.
<code>app/api/careers/route.ts</code>	Multipart validation and Resend email delivery.
<code>.env.example</code>	Safe configuration template with placeholders only.

NXTwave Semiconductor | Careers Handover Guide | Keep private environment values out of source control.