Building ToDo app Bootstrap

Bootstrap is a CSS framework which lets us to format stuffs in a very very easier way.
Formatting our list-todos page
Bootstrap
Add dependency in pom.xml to support bootstrap in your application

```
<dependency>
            <groupId>org.webjars</groupId>
            <artifactId>bootstrap</artifactId>
        <version>4.5.3</version>
</dependency>
<dependency>
        <groupId>org.webjars</groupId>
        <artifactId>jquery</artifactId>
            <version>3.5.1</version>
</dependency>
```

Copy the script and link in list-todos.jsp

```
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c"%>
<html>
    <head>
        <title>Todo's for ${name}</title>
        <link href="webjars/bootstrap/4.5.3/css/
bootstrap.min.css" rel="stylesheet">
    </head>

    <body>
        <div class = "container">
            <caption>Your Todos are</caption>
            <table class = "table table-striped">
                <thead>
                    <tr>
                        <th>Description</th>
                        <th>Target Date</th>
                        <th>Is it Done ?</th>
                    </tr>
                </thead>
                <tbody>
                    <c:forEach items="${todos}" var =
"todo">
                        <tr>
                            <td>${todo.desc}</td>
                            <td>${todo.targetDate}</td>
                            <td>${todo.done}</td>
                        </tr>
                    </c:forEach>
                </tbody>
            </table>
            <div>
                <a class = "button" href = "add-todo">Add a
Todo</a>
```

```html
            </div>
            <script src="webjars/jquery/3.5.1/jquery.min.js"></script>
            <script src="webjars/bootstrap/4.5.3/js/bootstrap.min.js"></script>
        </div>
    </body>
</html>
```