

Practical no. 3: Create a calculator with HTML ,CSS and JS.

Code :

```
<!DOCTYPE html>

<html lang="en">

<head>

  <meta charset="UTF-8">

  <meta name="viewport" content="width=device-width, initial-scale=1.0">

  <title>Simple Calculator</title>

  <style>

    body {

      font-family: Arial, sans-serif;

      display: flex;

      justify-content: center;

      align-items: center;

      height: 100vh;

      margin: 0;

      background-color: #f0f0f0;

    }

    .calculator {

      background-color: #fff;

      padding: 20px;

      border-radius: 10px;

      box-shadow: 0 0 10px rgba(0, 0, 0, 0.2);

      width: 300px;

    }

    #display {

      width: 100%;

      height: 50px;

      font-size: 24px;
```

```
    text-align: right;

    margin-bottom: 10px;

    padding: 5px;

    border: 1px solid #ccc;

    border-radius: 5px;

    box-sizing: border-box;
}

.buttons {

    display: grid;

    grid-template-columns: repeat(4, 1fr);

    gap: 5px;
}

button {

    padding: 15px;

    font-size: 18px;

    border: 1px solid #ccc;

    border-radius: 5px;

    background-color: #f9f9f9;

    cursor: pointer;
}

button:hover {

    background-color: #e0e0e0;
}

.operator {

    background-color: #ff9500;

    color: white;
}

.operator:hover {

    background-color: #e68a00;
}
```

```

.clear {
    background-color: #ff3b30;
    color: white;
}

.clear:hover {
    background-color: #e3342f;
}

.equals {
    background-color: #007aff;
    color: white;
}

.equals:hover {
    background-color: #0066cc;
}
</style>
</head>
<body>
<div class="calculator">
    <input type="text" id="display" readonly value="0">
    <div class="buttons">
        <button class="clear" onclick="clearDisplay()">C</button>
        <button onclick="appendToDisplay('(')">(</button>
        <button onclick="appendToDisplay('')">)</button>
        <button class="operator" onclick="appendToDisplay('/')">/</button>
        <button onclick="appendToDisplay('7')">7</button>
        <button onclick="appendToDisplay('8')">8</button>
        <button onclick="appendToDisplay('9')">9</button>
        <button class="operator" onclick="appendToDisplay('*')">*</button>
        <button onclick="appendToDisplay('4')">4</button>
        <button onclick="appendToDisplay('5')">5</button>
    </div>
    </div>
</body>
</html>

```

```

<button onclick="appendToDisplay('6')">6</button>
<button class="operator" onclick="appendToDisplay('-')">-</button>
<button onclick="appendToDisplay('1')">1</button>
<button onclick="appendToDisplay('2')">2</button>
<button onclick="appendToDisplay('3')">3</button>
<button class="operator" onclick="appendToDisplay('+')">+</button>
<button onclick="appendToDisplay('0')">0</button>
<button onclick="appendToDisplay('.')">.</button>
<button onclick="backspace()">⌫</button>
<button class="equals" onclick="calculate()">=</button>
</div>
</div>

```

```

<script>
  let display = document.getElementById('display');

  function appendToDisplay(value) {
    if (display.value === '0' && value !== '.') {
      display.value = value;
    } else {
      display.value += value;
    }
  }

  function clearDisplay() {
    display.value = '0';
  }

  function backspace() {

```

```
display.value = display.value.slice(0, -1);  
if (display.value === "") {  
    display.value = '0';  
}  
}
```

```
function calculate() {  
    try {  
        display.value = eval(display.value);  
    } catch (error) {  
        display.value = 'Error';  
        setTimeout(clearDisplay, 1000);  
    }  
}  
  
</script>  
</body>  
</html>
```

