

School of Computer Science and Artificial Intelligence**Lab Assignment # 4.2**

Program	: B. Tech (CSE)
Specialization	:
Course Title	: AI Assisted coding
Course Code	:
Semester	: II
Academic Session	: 2025-2026
Name of Student	: A.Nagasai
Enrollment No.	: 2403A51L18
Batch No.	: 51
Date	:20-01-2026

Task Description-1

- ❖ Zero-shot: Prompt AI with only the instruction. Write a Python function to determine
- ❖ whether a given number is prime

```
def is_prime(n):
    if n <= 1:
        return False
    for i in range(2, int(n ** 0.5) + 1):
        if n % i == 0:
            return False
    return True
n=int(input())
print(is_prime(n))

*** 7
True
```

Step-by-step explanation:**1. Function Definition**

- `def is_prime(n):`
 - This function takes an integer `n` as input and checks whether it is a prime number.

2. Check for invalid prime numbers

- `if n <= 1:`

- Numbers less than or equal to 1 are not prime, so the function returns **False**.

3. Optimized loop for checking factors

- **for i in range(2, int(n ** 0.5) + 1):**
- A number only needs to be checked for divisibility up to its square root.
- If **n** has a factor greater than its square root, it must also have a smaller factor.

4. Divisibility test

- **if n % i == 0:**
- If **n** is divisible by any number **i** in the loop, it is not prime, so return **False**.

5. Prime confirmation

- **return True**
- If no divisors are found, the number is prime.

Example:

- **is_prime(7) → True** (7 has no divisors other than 1 and itself)
- **is_prime(10) → False** (10 is divisible by 2)

❖ Task2:One-shot:

- ❖ Provide one example: Input: [1, 2, 3, 4], Output: 10 to help AI generate a function that calculates the sum of elements in a list.

```
def sum_of_list(nums):
    total = 0
    for num in nums:
        total += num
    return total
nums=list(map(int,input().split()))
print(sum_of_list(nums))

... 1 2 3 4
     10
```

Step-by-step explanation:

1. Function Definition

- `def sum_of_list(nums):`
- This function accepts a list of numbers called `nums`.

2. Initialize the sum

- `total = 0`
- A variable `total` is created to store the running sum of the elements.

3. Loop through the list

- `for num in nums:`
- The loop goes through each element (`num`) in the list.

4. Add each element ○ `total += num`

- Each number in the list is added to `total`.

5. Return the result

- `return total`
- After all elements are processed, the function returns the final sum.

Example using the one-shot input:

- Input: `[1, 2, 3, 4]`
- Calculation: $1 + 2 + 3 + 4 = 10$
- Output: `10`

❖ Task3:Few-shot:

- ❖ Give 2–3 examples to create a function that extracts digits from a alphanumeric string.

```
def extract_digits(s):  
    result = ""  
    for ch in s:  
        if ch.isdigit():  
            result += ch  
    return result  
s=input()  
print(extract_digits(s))  
  
*** 12s34g5h6  
123456
```

Explanation:

1. The function takes a string `s` as input.

2. An empty string **result** is initialized to store digits.
 3. The function loops through each character in the string.
 4. **isdigit()** checks whether the character is a digit (0–9).
 5. If it is a digit, it is added to **result**.
 6. Finally, the function returns all extracted digits as a string.
- ❖ Task4: Compare zero-shot vs few-shot prompting for generating a function that counts the number of vowels in a string.

```
def count_vowels(s):  
    vowels = "aeiouAEIOU"  
    count = 0  
    for ch in s:  
        if ch in vowels:  
            count += 1  
    return count  
s=input()  
print(count_vowels(s))  
  
*** vowels  
2
```

Step-by-step explanation:

1. Function definition
 - **def count_vowels(s):**
 - Defines a function named **count_vowels** that takes a string **s** as input.
2. Vowel list
 - **vowels = "aeiouAEIOU"**
 - Stores all lowercase and uppercase vowels.
 - This ensures the function counts vowels regardless of case.

3. Initialize counter

- `count = 0`

- A variable to keep track of how many vowels are found.

4. Loop through the string

- `for ch in s:`

- Iterates over each character (`ch`) in the input string.

5. Check for vowels

- `if ch in vowels:`

- Checks whether the current character is a vowel.

6. Increase count

- `count += 1`

- Increments the counter whenever a vowel is found.

7. Return result

- `return count`

- Sends back the total number of vowels in the string.

8. User input

- `s = input()`

- Takes a string input from the user.

9. Print output

- `print(count_vowels(s))`
- Calls the function and prints the number of vowels

❖ Task5: Use few-shot prompting with 3 sample inputs to generate a function that determines the minimum of three numbers without using the built-in `min()` function.

```
def minimum_of_three(a, b, c):  
    min_val = a  
    if b < min_val:  
        min_val = b  
    if c < min_val:  
        min_val = c  
    return min_val  
print(minimum_of_three(3,2,1))  
print(minimum_of_three(3,2,4))  
print(minimum_of_three(3,5,4))  
  
... 1  
     2  
     3
```

Explanation:

- The function starts by assuming `a` is the smallest.
- It compares `b` with the current minimum and updates if needed.
- It then compares `c` with the updated minimum.
- Finally, it returns the smallest of the three numbers.