

STANDARD OPERATING PROCEDURE & SAFETY DIRECTIVES

DOC ID: SOP-ENG-204-REV-E | CLASSIFICATION: CONFIDENTIAL | STD: ASME SEC VIII DIV 1 / API 510

SECTION 1: OPERATING ENVELOPE & INTERLOCK TRIP SETPOINTS

Normal Operating Pressure: 31.2 bar gauge (Monitored via Dual PT-204A/B and Local PI-204)
Maximum Allowable Working Pressure (MAWP): 42.5 bar gauge
High Pressure Alarm Setpoint: 33.5 bar gauge (Operator Attention Required)
Emergency Shutdown High Trip (ESD-01): 35.0 bar gauge (Automated Loop Isolation)
Mechanical Relief Valve Lift Setpoint (PRV-204): 42.5 bar gauge
Secondary Quench Flow Baseline: 294 L/min (Minimum allowable: 260 L/min)
Maximum Bed Temperature: 440.0 °C | Max Allowable Heating Ramp: 25.0 °C / hour

SECTION 2: MULTILINGUAL EMERGENCY DIRECTIVES / [REDACTED] / [REDACTED]

[ENGLISH DIRECTIVE · CRITICAL SAFETY LIMIT]

Do not exceed 42.5 BAR operating pressure. Immediately isolate valve HV-204 and notify supervisor if pressure exceeds 42.8 BAR.

[HINDI DIRECTIVE · [REDACTED]]

रिएक्टर परिचालन दबाव 42.5 BAR से अधिक न होने दें। यदि दबाव 42.8 BAR से अधिक हो जाए, तो तुरंत वाल्व HV-204 बंद करें।

[KANNADA DIRECTIVE · [REDACTED]]

ರಿಯಾಕ್ಟರ್ ಕಾರ್ಯಾಚರಣೆಯ ದಾಖಲೆ 42.5 BAR ಮೀರುವುದನ್ನು ತಡೆಯಿರಿ. ಒತ್ತಡವು 42.8 BAR ಮೀರಿದರೆ, ತಕ್ಷಣ ವಾಲ್ವ್ HV-204 ಅನ್ನು ಪ್ರತ್ಯೇಕಿಸಿ.