

Dt : 25/9/2023

=>we can perform the following operations on StringBuffer Object:

(i)insert()

(ii)delete()

(iii)reverse()

Program : DemoBuffer5.java

```
package maccess;
public class DemoBuffer5
{
    public static void main(String[] args)
    {
        StringBuffer sb = new StringBuffer();
        sb.append("java language program");
        System.out.println("data in sb :
"+sb.toString());
        System.out.println("*****insert()*****");
        sb.insert(5, "HYD-NIT ");
        System.out.println("data in sb :
"+sb.toString());
        System.out.println("*****delete()*****");
        sb.delete(5, 13);
        System.out.println("data in sb :
"+sb.toString());
        sb.deleteCharAt(7);
        System.out.println("data in sb :
"+sb.toString());
        System.out.println("*****reverse()*****");
        sb.reverse();
        System.out.println("data in sb :
"+sb.toString());
    }
}
o/p:
```

data in sb : java language program

********insert()********

data in sb : java HYD-NIT language program

*******delete()*******

data in sb : java language program

data in sb : java laguage program

*******reverse()*******

data in sb : margorp egaugal avaj

=====

Assignment:

wap to read a String and check the String is Palindrome String or not?

(Using reverse() method)

=====

Note:

=>StringBuffer class is known as "Synchronized Class".

faq:

define Synchronized Class?

***=>The class which is declared with "synchronized methods" is known as
synchronized class.***

faq:

define synchronized methods?


=>The methods which are declared with "synchronized" keyword are known as synchronized methods.

faq:

wt is the behaviour of synchronized method?

=>These synchronized methods will be under the synchronized-lock and the methods are used by one user at-a-time.

Diagram:



=====

=

(c)StringBuilder:

=>StringBuilder class is from java.lang package and which also generate Mutable Objects.

=>The following are some important constructors from the StringBuilder:

public java.lang.StringBuilder();

public java.lang.StringBuilder(int);

public java.lang.StringBuilder(java.lang.String);

public java.lang.StringBuilder(java.lang.CharSequence);

=>StringBuilder is having same behaviour like StringBuffer, but

StringBuilder is NonSynchronized class.

=>NonSynchronized class means the class is holding NonSynchronized methods.

Note:

**=>In realtime,StringBuffer is used in Multi-User Applications and
StringBuilder is used in Single-User Applications.**

=====

faq:

define Utility Classes?

**=>The Classes which perform operations on other Objects are known as
Utility Classes.**

=>The following are two Utility classes related to String-Objects:

(a)StringTokenizer class

(b)StringJoiner class(Java8 - new Component)

(a)StringTokenizer class:

=>StringTokenizer class is from java.util package and which is used to break the given string into pieces(tokens) based on "delimiter" (delimiter - means break specification)

=>The following are some important methods of StringTokenizer:

```
public java.util.StringTokenizer  
    (java.lang.String, java.lang.String);  
public boolean hasMoreTokens();  
public java.lang.String nextToken();  
public java.lang.String nextToken(java.lang.String);  
public boolean hasMoreElements();  
public java.lang.Object nextElement();  
public int countTokens();
```

Program : DemoStringTokenizer1.java

```
package maccess;  
import java.util.*;  
public class DemoStringTokenizer1 {  
    public static void main(String[] args) {  
        Scanner s = new Scanner(System.in);
```

```

try(s;){
    System.out.println("Enter the String:");
    String str = s.nextLine();
    System.out.println("Enter the delimiter:");
    String dl = s.nextLine();
    StringTokenizer ob1 = new
StringTokenizer(str,dl);
    StringTokenizer ob2 = new
StringTokenizer(str,dl);
    System.out.println("Str : "+str.toString());
    System.out.println("Count of
Tokens:"+ob1.countTokens());
    System.out.println("****Tokens-
hasMoreElements()****");
    while(ob1.hasMoreElements())
    {
        String ele = (String)ob1.nextElement();
        System.out.println("Token :
"+ele.toString());
    }
    System.out.println("Count of
Tokens:"+ob1.countTokens());
    System.out.println("****Tokens-
hasMoreTokens()****");
    while(ob2.hasMoreTokens())
    {
        String ele = ob2.nextTokn();
        System.out.println("Token : "+ele.toString());
    }
    System.out.println("Count of
Tokens:"+ob2.countTokens());
} //end of try with resource
}
}

```

o/p:

Enter the String:

java language program

Enter the delimiter:

n

Str : java language program

Count of Tokens:2

*******Tokens-hasMoreElements()*******

Token : java la

Token : guage program

Count of Tokens:0

*******Tokens-hasMoreTokens()*******

Token : java la


Token : guage program

Count of Tokens:0

=====

`str = "java language program"`

`dl="n"`



Cursor

```
StringTokenizer ob = new StringTokenizer(str,dl);
```

Venkatesh