

Salesforce System Integration Interview Prep

Remote Process Invocation – Request and Reply

Best solutions

1. **External Services** – invokes a REST API call – allows to invoke externally hosted service in declarative manner. External REST service are available in a an OpenAPI or Integrant schema definition. Contains primitive data types, nested objects not supported. Transaction invoked from Lightning Flow. Integration transaction doesn't risk exceeding the synchronous Apex governor limits.
2. **Salesforce Lighting** – consume WSDL and generate Apex proxy. Enable HTTP (REST) services, GET, PUT, POST, DELETE methods.
3. **Custom Visualforce page or button initiates Apex HTTP callout** – user initiated action calls and Apex action that executed this proxy Apex class

Suboptimal

1. **Trigger** – calls must be asynchronous (@future)
2. **Batch job callout** – bundle responses together and make 1 callout for every 200 records processed.

Endpoint capability

Endpoint should be able to receive a web services call via HTTP. Salesforce must be able to access endpoint via the internet, curl or postman. Apex SOAP callout- WSDL 1.1, SOAP 1.1

Apex HTTP callout -REST service using standard GET, POST, PUT, DELETE methods

Data Volumes

Small volume, real time activities, due to small timeout values and maximum size of the request or response from Apex call solution.

Timeliness

1. Request is typically invoked from user interface, must not keep user waiting
2. Governor limit of 120 second timeout for callouts
3. Remote process needs to be completed in SF limit and user expectations else seen as slow system
4. Apex synchronous apex limits are 10 transaction than run for 5 seconds
 - Make sure external server callout is less than 5 seconds

State management

1. Salesforce stores the external system External Id for specific record
2. The remote system stores the Salesforce unique record ID or other unique key

Security

Any call to external service should maintain:

1. Confidentiality
2. Integrity
3. Availability

Apex SOAP and HTTP callouts security considerations

1. One way SSL is enabled by default
2. 2 way SSL is enabled by self-signed certificate or CA-signed certificate
3. WS-Security is not supported
4. If necessary use one way hash or digital signature using Apex Crypto to ensure message integrity
5. Remote system must be protected by appropriate firewall mechanism

Error Handling – error occurs in form of error http error codes

400 – Bad request, 401 – Unauthorized, 404 – Not Found, 500 – Internal server error

Recovery – changes not committed to Salesforce until successful response, retry

x amount of times until success received else log error.

Idempotent Design consideration – duplicate calls when something goes wrong needs

need to have a message ID to make sure duplicates are not created

```
1  Http h = new Http();
2  HttpRequest req = new HttpRequest();
3  req.setEndpoint(url); //
4  req.setMethod('GET'); //
5
6  //Basic Authentication - specify in Named Credentials so no code change needed
7  String username = 'myname';
8  String password = 'mypwd';
9
10 Blob headerValue = Blob.valueOf(username + ':' + password);
11 String authorizationHeader = 'Basic ' +
12 EncodingUtil.base64Encode(headerValue);
13 req.setHeader('Authorization', authorizationHeader);
14
15 HttpResponse response = h.send(req);
16
17 if (response.getStatusCode() == 200) {
18     Map<><String, Object>>> results = (Map<><String, Object>>>)
19     JSON.deserializeUntyped(response.getBody());
20     List<><Object>>> animals = (List<><Object>>>) results.get('animals');
21     System.debug('Received the following animals:');
22     for (Object animal: animals) {
23         System.debug(animal);
24     }
25 }
26
27 //Implement httpCalloutMock
28 global class YourHttpCalloutMockImpl implements HttpCalloutMock {
29     global HTTPResponse respond(HTTPRequest req) {
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
```

Remote Process Invocation – Fire and forget

Best solutions

1. **Process-driven platform events** – using process builder/workflow rules to create process to publish insert or update event
2. **Event messages** – the process of communicating changes and responding to them without writing complex logic. One or more subscribers can listen to the same event and carry out actions through CometD.
3. **Customized-driven platform events** – events are created by Apex triggers or batch classes
4. **Workflow driven outbound messaging** – remote process is invoked from an insert or update event. Salesforce provides workflow-driven outbound messaging capability that allow sending SOAP messages to remote systems.
5. **Outbound messaging and callbacks** – callback helps mitigate out-of-sequence messaging also 2 things Idempotency and Retrieve of more data. When creating a new record and update externalId with the recordId from external system.

Suboptimal

1. **Lightning components** – user interface based scenarios, must guarantee delivery of message in code
2. **Triggers** – Apex triggers to perform automation based on records changes
3. **Batch jobs** – calls to remote system can be performed from a batch job. Solution allows batch remote process execution and for processing of repos from remote system.

```
1  MyEventObject__e newEvent = new MyEventObject__e();
2  newEvent.Name__c = 'Test Platform Event';
3  newEvent.Description__c = 'This is a test message';
4  List<Database.SaveResult> results = EventBus.publish(newEvent);
5
6
7  Test.startTest();
8  // Create test events
9  // ...
10 // Publish test events with EventBus.publish()
11 // ...
12 // Deliver test events
13 Test.getEventBus().deliver();
14 // Perform validation
15 // ...
16 Test.stopTest();
17
18
19 //Listener - EMPConnector use login to and create EmpConnector(bayeuxParameters)
20 import static com.salesforce.emp.connector.LoginHelper.login;
21 //create consumer
22 SalesforceEventPayload eventPayload = new SalesforceEventPayload();
23     Consumer<Map<String, Object>>> consumer = event -> {
24         eventPayload.setPayload(event);
25         itsReqHandler.handleRequest(eventPayload.getPayload());
26     };
27
28 //add subscription to event
29 subscription = empConnector.subscribe("/event/" + EVENT_NAME, replayFrom, consumer).get(WAIT_TIME, TimeUnit.SECONDS);
```

Error handling and recovery

Error handling – because this pattern is asynchronous the callout of event publish handles need to be handles as well as the remote system needs to handle queuing, processing and error handling.

Recovery

More complex, need some retry strategy if no retry is receive in the QoS (Quality of Service) time period

Idempotent Design considerations

Platform events are published once, there is no retry on the Salesforce side. It is up to the ESB to request that the events be replayed. In a replay, the platform events reply ID remains the same and ESB can try to duplicate messages based on reply ID.

Unique Id for outbound messages is sent and needs to be tracked by the remote system to make sure duplicate messages or events are not repossessed.

Security

1. **Platform events** – conforms to the security of the existing Salesforce org
2. **Outbound messages** – One way SSL enabled, two way SSL can be used with outbound message certificate. Whitelist the IP ranges of the remote integration servers, remote server needs appropriate firewalls
3. **Apex callout** – one way SSL enabled, 2 way SSL through self signed or CA signed certificates. Use one way hash or digital signature (Apex Crypto class) to ensure integrity of message. Remote system protected by appropriate firewall mechanisms.

Timeliness

Less important, control handed back to client immediate or after successful deliver message. Outbound message acknowledgment must occur in 24 hours (can be extended to seven days) otherwise message expires.

Platform events – send events to event bus and doesn’t wait for confirmation or acknowledgement from subscriber. If subscribe doesn’t pick up the message they can reply the event using replayID. High volume message are stored for 72 hours (3 days). Subscriber use CometD to subscribe to channel.

State management

Unique record identifiers are important for ongoing state tracking:

1. Salesforce store remote system primary or unique surrogate key for remote record
2. Remote system store Salesforce unique record ID or some unique surrogate key

Governor Limits

Limits depends on the type of outbound call and timing of the call

Reliable Messaging

1. **Platform Events** – form of reliable messaging. Salesforce pushed the event to subscribers. If the message doesn’t gets picked up it can be replayed using reply ID.
2. **Apex callout** – recommend that the remote system implement JMS, MQ however it doesn’t guarantee delivery to remote system, specific techniques such as processing positive acknowledgement from remote endpoint in addition to custom retry logic must be implemented.
3. **Outbound messaging** – if no positive acknowledgment receive, retry up to 24 hours. Retry interval increase exponentially 15 sec to 60 min intervals.

Publisher and subscriber not in same transaction

Publish event before committed to the database, subscriber receives the event and does lookup to not find the record.

Publish behavior – publish immediately/publish after commit

Publish events – @future or @queueable to callout to events only when commit has complete

Message sequencing

Remote system discard message with duplicate message ID

Salesforce send RecordId, remote system makes callback to Salesforce

Handing Deletes

Salesforce workflow can't track deletion of records, can't call outbound message for deletion. Workaround:

- 1. Create custom object called Deleted_Records__c
- 2. Create trigger to store info (unique identifier) in custom object
- 3. Implement workflow rule to initiate message based on the creation of custom object

Batch Data Synchronization

Best solutions

- 1. **Salesforce change data capture (Salesforce master)**
- 2. **Replication via third party ETL Tool (Remote system master)** – Bulk API
- 3. **Replication via third party ETL Tool (Salesforce master)** – SOAP API getUpdated()

Suboptimal

- 1. **Remote call-in** – call into SF, causes lots of traffic, error handling, locking
- 2. **Remote process invocation** – call to remote system, causes traffic, error handling, locking

Extract and transform accounts, contacts, opportunities from current CRM to Salesforce (initial data load import)

Extract, transform, load billing data into Salesforce from remote system on weekly basis (ongoing)

Data master

Salesforce or Remote system

Salesforce Change Data Capture

Publish insert, update, delete, undelete events which represents changes to Salesforce. Receive near real time changes of records and sync to external data store.

Takes care of continuous synchronization part, needs integration app to receive events and perform update to external system

Channel – /data/{objectName}_Change

Error handling – Pattern is async remote system should handle message queuing, processing and error handling.

Recovery – initiate retry based on service quality of service requirement. Use replyID to reply stream of events. Use CometD to retrieve past messages up to 72 hours.

Bulk API – Replication via 3rd party ETL tool (more than 100 000 records)

Allow to run change data capture against source data. Tool reacts to change in the source data set, transforms the data and them call Salesforce Bulk API to issue DML statement, can also use SOAP API.

- 1. Read control table to determine last time job ran, other control values needed
- 2. Use above control values to filter query
- 3. Apply predefine processing rules, validation rules, enrichments
- 4. Use available connectors/transformation capability to create destination data set
- 5. Write the data to Salesforce objects
- 6. If processing is success update the control variable
- 7. If process fail update control variable for process to restart

Consider

- 1. Chain and sequence ETL jobs to provide cohesive process
- 2. Use primary key for both systems to match incoming data
- 3. Use specific API methods to extract only updated data
- 4. Importing master-detail or lookup, consider using the parent key at the source to avoid locking. Group contacts for an account to be imported at the same time.
- 5. Post-import processing should only process data selectively
- 6. Disable Apex triggers, workflow and validation rules
- 7. Use the defer calculations permission to defer sharing calculations until all data loaded

Error handling

If error occur during read operation, retry for errors. If errors repeat implement control tables/error tables in context of:

- 1. Log the error
- 2. Retry the read operation
- 3. Terminate if successful
- 4. Send a notification

Security

- 1. Lightning Platform license with at least “API Only” user permission
- 2. Standard encryption to keep password access secure
- 3. Use HTTPS protocol

Timeliness

Take care to design the interface so all batch processes complete in a designated batch window

Loading batches during business hours not recommended

Global operations should run all batch processes at the same time

State management

Use surrogate key between two systems.

Standard optimistic locking occurs on platform and any updates made using the API require the user who is editing the record to initiate a refresh and initiate their transaction. Optimistic locking means:

- 1. Salesforce doesn't maintain state of record being edited
- 2. Upon read, records time when data was extracted
- 3. If user updated the record and before save checks if another user has updated
- 4. System notified user update was made and use retrieve the latest version before updating

Middleware capabilities

Middleware tool that supports Bulk API

Supports the getUpdated() function – provide closest implementation to standard change data capture capability in Salesforce

Extracting data

Use the getUpdated() and getDeleted() SOAP API to sync an external system with Salesforce at intervals greater than 5 minutes. Use outbound messaging for more frequent syncing.

When querying can return more than an million results, consider the query capability of the Bulk API.

Remote Call-In

Best solutions

- 1. **SOAP API** – Publish events, query data, CRUD. Synchronous API, waits until it receives a response. Generated WSDL – enterprise (strongly-typed), partner (loosely typed). Must have a valid login and obtain session to perform calls. Allows partial success if the records are marked with errors, also allows “all or nothing” behavior.
- 2. **REST API** – Publish events, query data, CRUD. Synchronous API, waits until it receives a response. Lightweight and provides simple method for interacting with Salesforce. Must have a valid login and obtain session to perform calls. Allows partial success if the records are marked with errors, also allows “all or nothing” behavior. Output of one to use as input to next call.

Suboptimal

- 1. **Apex Web services** – use when: full transaction support is required, custom logic needs to be applied before commenting.
- 2. **Apex REST services** – lightweight implementation of REST services
- 3. **Bulk API** – submitting a number of batches to query, update, upsert or delete large number of records.

Authentication

Salesforce supports SSL (Security Socket Layer) and TLS (Transport Later Security), Ciphers must be at least length 128 bits

Remote system has to authenticate before accessing any REST service. Remote system can use OAuth 2.0 or username/password. Client has to set the authorization HTTP header with the appropriate value.

Recommend client caches the session ID rather than creating a new session ID for every call.

Accessibility

Salesforce provides a REST API that remote system can use to:

- 1. Query data in org
- 2. Publish events to org
- 3. CRUD of data
- 4. Metadata

Synchronous API

After call to server it waits for a response, asynchronous call to Salesforce is not supported

REST vs SOAP

REST exposes resources as URI and uses HTTP verbs to define CRUD operations. Unlike SOAP, REST required no predefined contract, utilize XML and JSON for responses, and has loosely typed. Advantage includes ease of integration and great use for mobile and web apps.

Security

Client executing the REST needs a valid Salesforce login and obtain a access token. API respects the object and field level security for the logged in user

Transaction/Commit Behavior

By default every record is treated as a separate transaction and committed separately. Failure of one records does not cause rollback of other changes. Using the composite API makes a series of updates in one call.

Rest composite resource

Perform multiple operation in a single API call. Also use output of one call to be input of next call. All response bodies and HTTP statuses are returned in a single response body. The entire requires counts as single call towards API limit.

Bulk API

For bulk operations use Rest-based BULK API

Event driven architecture

Platform events are defined the same way as you define a Salesforce object. Publishing to event bus is same as inserting Salesforce record. Only create and insert is supported.

Error handling

All remote call-in methods or custom API require remote system to handle any subsequent errors such as timeouts and retries. Middleware can be used to provide logic for recovery and error handling

Recovery

A custom retry mechanism needs to be created if QoS requirements dictate it. Important to consider impotent design characteristic.

Timeliness

Session timeout – session timeout when no activity based on SF org session timeout

Query timeout – each query has a timeout limit of 120 seconds

Data volumes

CRUD – 200 records per time

Blob size – 2GB ContentVersion (Chatter)

Query – query(), queryMore() return 500 records, max 2000

State management

Salesforce stores remote system primary key or unique key for the remote record

The remote system stores the Salesforce ID unique record ID or some unique

Governor limits

5000 API calls per 24 hour

10 query cursors open at time

Reliable messaging

Resolve the issue that delivery of a message to remote system where the individual components may be unreliable. SOAP API and REST API are synchronous and don't provide explicit support for any reliable messaging protocols.

Data visualization

Best solutions

- 1. Salesforce Connect

Suboptimal

- 1. 1. Request and reply – Salesforce web services APIs (SOAP or REST) to make ad-hoc data requests to access and update external system data

Access data from external sources along with Salesforce data. Pull data from legacy systems, SAP, Microsoft, Oracle in real time without making a copy of the data.

Salesforce connect maps data tables in external systems to external objects in your org. External objects are similar to custom objects, except they map to data located outside SF org. Uses live connection to external data to keep external objects up to date.

Salesforce connects lets you

- 1. Query data in a external system
- 2. CRUD data in external system
- 3. Define relationships between external objects and standard or custom objects
- 4. Enable Chatter feed on external object page for collaboration
- 5. Run reports on external data

Salesforce Connect Adapters

OData adapter 2.0 or OData adapter 4.0 – connects data to exposed by any OData 2.0 or OData 4.0 producer

Cross-org adapter – connects to data that's stored in another Salesforce org. Used the Lightning Platform REST API

Custom adapter created via Apex – develop own adapter with the Apex Connector framework

Calling mechanism

External Objects – maps SF external objects to data tables in external systems. Connect access the data on demand and in real time. Provides seamless integration with Lightning Platform can do global search, lookup relationships, record feeds.

Also available to Apex, SOSL, SOQL queries, Salesforce API, Metadata API, change sets and packages.

Error handling

Run Salesforce Connector Validator tool to run some common queries and notice error types and failure causes

Benefits

- 1. Doesn't consume data storage in SF
- 2. Don't have to worry about regular sync between systems
- 3. Declarative setup can be setup quickly
- 4. Users can access external data with same functionality
- 5. Ability to do federated search
- 6. Ability to run reports

Considerations

Impact reports performance

Security considerations

Adhere to Salesforce org-level security, use HTTPS connect to any remote system.

OData understand behaviors, limitations and recommendations for CSRF (Cross-Site Request Forgery)

Timeliness

Request invoked by user interface, should not keep the user waiting

May take long to relieve data from external system, SF configured 120 sec maximum timeout

Completion of remote process should execute in timely manner

Data volumes

Use mainly for small volume, real time activities, due to small timeout and maximum size of request or response for Apex call solution.

State management

Salesforce stores primary or unique surrogate key for the remote record

Remote system store SF unique record ID or other unique surrogate key