

Access grants tables

- Object Record Tables: Example: **Quote__c**
 - Store records of the object
 - Has record ownership field: **OwnerId** referencing to [**"Group"**, **"User"**]
 - OwnerId is base field on which Platform's sharing is built-on
- Object Sharing Tables: Example: **Quote__Share**
 - Store data that supports:
 - explicit** grants
 - implicit** grants
 - Each Object (thus Object Record Table) has its own Object Sharing table (*unless the object is a **detail** in a master-detail relationship*)
 - In master-detail relationships, the Object Sharing table for the **master** object **controls** access to the **detail** object - since the detail objects do not have **OwnerId** field.
- Group Maintenance Tables
 - store the data supporting:
 - group membership
 - inherited access grants

Table	Function
Object Sharing Tables	Store access grants to individuals and groups. Each of rows (called sharing rows) grants a user or group access to a particular record
Group Maintenance Tables	Store the list of users or groups that belong to each group, indicating group membership . Single group membership or inherited access grant can give several users and groups multiple ways to access a record. Also includes including system-defined group. System-defined groups are groups of users that Salesforce creates and manages internally to support various features and behaviors, such as queues and hierarchies. For every node in role hierarchy, 2 types of system-defined groups is used : Role groups and RoleAndSubordinates groups

Object Record Table: **Quote__c**:

describe Quote__c

⚡

✖

⬅

➡

3

Response

Table

History

Sharing ERD

Arch

Sharing Table

Industries

Roles

Dict

Dict CSV

Drawings

Machine Learning

SLDS

Label	Name	Nullable	Picklistvalues	Referenceto	Relationshipname	Type	Unique	Updateable
Record ID	Id	false	--	--	null	id	false	false
Owner ID	OwnerId	false	--	["Group", "User"]	Owner	reference	false	true
Deleted	IsDeleted	false	--	--	null	boolean	false	false
Quote Name	Name	true	--	--	null	string	false	true
Created Date	CreatedDate	false	--	--	null	datetime	false	false
Created By ID	CreatedById	false	--	["User"]	CreatedBy	reference	false	false
Last Modified Date	LastModifiedDate	false	--	--	null	datetime	false	false

Object Sharing Table: **Quote__sharing**:

SELECT ParentId, UserOrGroupId, AccessLevel, RowCause FROM Quote__share

⚡

✖

⬅

➡

3

Response

Table

History

Sharing ERD

Arch

Sharing Table

Industries

Roles

Dict

Dict CSV

Drawings

Machine Learning

SLDS

	ParentId	UserOrGroupId	AccessLevel	RowCause
1	a0661000002hup1AAA	0056100000195Y2AAI	All	Owner
2	a0661000002hup1AAA	00561000001VmT8AAK	Edit	Quote_Write_Sharing__c
3	a0661000002hup1AAA	00561000001VmT8AAK	Read	Manual

Group Maintenance Tables: **Group** and **GroupMember**:

Describe Group:

Label	Name	Nillable	Picklistvalues	Referenceto	Relationshipname	Type	Unique	Updateable
Group ID	Id	FALSE	--	--	null	id	FALSE	FALSE
Name	Name	FALSE	--	--	null	string	FALSE	TRUE
Developer Name	DeveloperName	TRUE	--	--	null	string	FALSE	TRUE
Related ID	RelatedId	TRUE	--	["User", "UserRole"]	null	reference	FALSE	FALSE
Type	Type	FALSE	["AllCustomerPortal" , "CollaborationGroup" , "Manager" , "ManagerAndSubordinatesInternal" , "Organization" , "PRMOrganization" , "Queue" , "Regular" , "Role" , "RoleAndSubordinates" , "RoleAndSubordinatesInternal" , "SharingRuleGroup" , "Territory" , "TerritoryAndSubordinates"]	--	null	picklist	FALSE	FALSE
Email	Email	TRUE	--	--	null	email	FALSE	TRUE
Owner ID	OwnerId	FALSE	--	["Organization", "User"]	Owner	reference	FALSE	FALSE
Send Email to Members	DoesSendEmailToMembers	FALSE	--	--	null	boolean	FALSE	TRUE
Include Bosses	DoesIncludeBosses	FALSE	--	--	null	boolean	FALSE	TRUE

describe GroupMember

⚡

✕

←

→

3

Response

Table

History

Sharing ERD

Arch

Sharing Table

Industries

Roles

Dict

Dict CSV

Drawings

Machine Learning

SLDS

Label	Name	Nillable	Picklistvalues	Referenceto	Relationshipname	Type	Unique	Updateable
Group Member ID	Id	false	--	--	null	id	false	false
Group ID	GroupId	false	--	["Group"]	Group	reference	false	false
User/Group ID	UserOrGroupId	false	--	["Group", "User"]	null	reference	false	false
System Modstamp	SystemModstamp	false	--	--	null	datetime	false	false

describe QueueSObject

⚡

✕

←

→

3

Response

Table

History

Sharing ERD

Arch

Sharing Table

Industries

Roles

Dict


Dict CSV

Drawings

Machine Learning

SLDS

Label	Name	Nillable	Picklistvalues	Referenceto	Relationshipname	Type	Unique	Updateable
Queue Subject ID	Id	false	--	--	null	id	false	false
Group ID	QueueId	false	--	["Group"]	Queue	reference	false	false
Subject Type	SubjectType	false	["Aircraft__c" , "Case" , "Goal" , "Job__c" , "Lead" , "Macro" , "Metric" , "Mohan_test_100__c" , "mohan_tester_1__c" , "Order" , "Product__c" , "Proposal__c" , "Quote__c" , "UserProvisioningRequest" , "WorkCoaching" , "WorkFeedback" , "WorkFeedbackQuestion" , "WorkFeedbackQuestionSet" , "WorkFeedbackRequest" , "WorkFeedbackTemplate" , "WorkPerformanceCycle"]	--	null	picklist	false	false
Created By ID	CreatedById	false	--	["User"]	CreatedBy	reference	false	false
System Modstamp	SystemModstamp	false	--	--	null	datetime	false	false



How Salesforce joins entities to providing access to record (RecordId) of ObjectRecordTable:

- Org wide Filter: orgId
- Logged in user: userId
- Get the **OwnerId** of the record (recordId) the user seeking access from ObjectRecordTable (**recordId**, **OwnerId**, ...)

```

1 // pseudo code
2
3
4 var access = provide_record_access_to(objectRecordTable, userId);
5
6
7 function provide_record_access_to(objectRecordTable, userId) {
8
9     var isOwner = filter(objectRecordTable, "count()", "ownerId = $userId").length != 0;
10
11     if( isOwner) return 'All';
12     else return consult_group_maintenance_tables(ownerId, userId);
13 }
14
15 //
16 function consult_group_maintenance_tables(ownerId, userId) {
17
18     get_record_access(
19         _intersection( filter(GroupMemberTable, "GroupId", " UserOrGroupId = $ownerId "),
20             filter(GroupMemberTable, "GroupId", " UserOrGroupId = $userId ")
21         );
22     );
23 }
24
25
26 function get_record_access( groupIds) {
27
28     var access = ''; // 'All' or 'Read' or 'Edit' ...
29     //TODO: do the sharing calc for the given groupIds
30
31     return access;
32 }
33

```

- record must exist
- either the Object Sharing Table or the Group Maintenance tables must grant access

