

AD 2 AERODROMES

RJEC AD 2.1 AERODROME LOCATION INDICATOR AND NAME

RJEC - ASAHIKAWA

RJEC AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	ARP coordinates and site at AD	434015N/1422651E 154° / 1.25km from RWY16 THR
2	Direction and distance from (city)	7nm SSE from Asahikawa city
3	Elevation/ Reference temperature	690ft / 27°C(2004-2008)
4	Geoid undulation at AD ELEV PSN	105ft
5	MAG VAR/ Annual change	9°(2008) / -
6	AD Administration, address, telephone, telefax, telex, AFS, e-mail and/or Web-site addresses	Hokkaido Airports Co.,Ltd. Asahikawa Airport Office 15-96 Higashi-2-sen, Higashi-Kagura-cho, Kamikawa-gun, Hokkaido TEL:0166-83-2200 FAX:0166-83-3643 e-MAIL:hap-rjec-unjyo@hokkaido-airports.co.jp
7	Types of traffic permitted(IFR/VFR)	IFR/VFR
8	Remarks	Nil

RJEC AD 2.3 OPERATIONAL HOURS

1	AD Administration	2300 - 1200
2	Customs and immigration	Customs: 2330-0815 Immigration: INTL SKED FLT hours only
3	Health and sanitation	Quarantine(human): 2330-0815 Quarantine(animal, plant): INTL SKED FLT hours only
4	AIS Briefing Office	Nil
5	ATS Reporting Office(ARO)	Nil
6	MET Briefing Office	H24 (NEW CHITOSE)
7	ATS	2300 - 1200
8	Fuelling	2300 - 1200
9	Handling	2300 - 1200
10	Security	2300 - 1200
11	De-icing	Nil
12	Remarks	Nil

RJEC AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	A full range of cargo handling equipment is available up to B747-400 aircraft.
2	Fuel/ oil types	Fuel grades : JET A-1
3	Fuelling facilities/ capacity	Fuel truck refueling / Ask AD administration
4	De-icing facilities	Nil
5	Hangar space for visiting aircraft	Nil
6	Repair facilities for visiting aircraft	Nil
7	Remarks	Nil

RJEC AD 2.5 PASSENGER FACILITIES

1	Hotels	Nil
2	Restaurants	At airport
3	Transportation	Buses, taxi
4	Medical facilities	Nil
5	Bank and Post Office	At airport(ATM only)
6	Tourist Office	Nil
7	Remarks	Nil

RJEC AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD category for fire fighting	CAT9
2	Rescue equipment	Chemical fire fighting truck x 3, Water-supply truck, Rescue and foam solution transport truck, Emergency medical equipments conveyance truck
3	Capability for removal of disabled aircraft	Ask AD administration
4	Remarks	Nil

RJEC AD 2.7 SEASONAL AVAILABILITY-CLEARING

1	Types of clearing equipment	Snow removal equipments: Sweeper x 7, Snowplow x 4, Rotary x 3, Grader x 2, Tractor-shovel x 3
2	Clearance priorities	(1) RWY 16/34, TWY T1, T5 (2) TWY T2 - T4, Apron
3	Remarks	Seasonal availability : All seasons

RJEC AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS DATA

1	Apron surface and strength	Spot NR1, 2, 3, 4, 5 : Surface : cement concrete, Strength : PCN 74/R/B/X/T Spot NR11, 12, 13, 14, 15 : Surface : cement concrete, Strength : PCN 11/R/B/Y/T
2	Taxiway width, surface and strength	T1 - T3, T5 ,A1 ,P1 ,P2 ,P5 : Width : 30m, Surface : asphalt-concrete, Strength : PCN 89/F/C/X/T T4, A2, P3, P4 : Width : 30m, Surface : asphalt-concrete, Strength : PCN 79/F/B/X/T
3	ACL and elevation	Not available
4	VOR checkpoints	Not available
5	INS checkpoints	Spot NR 1: 434018.01N/1422709.88E 2: 434016.16N/1422710.69E 3: 434014.59N/1422712.16E 4: 434012.59N/1422713.10E 5: 434010.62N/1422714.70E
6	Remarks	Nil

RJEC AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand ID signs, TWY guide lines and Visual docking/ parking guidance system of aircraft stands	ACFT stand identification signs installed as appropriate. ACFT stand taxi lane :Spot NR 1, 2, 3, 4, 5, 11, 12, 13, 14, 15
2	RWY and TWY markings and LGT	RWY: RWY16/34 (Marking) RWY designation, RWY CL, RWY THR, TDZ, RWY side stripe, Aiming point (LGT) RCLL, REDL, RTHL, RENL, RTZL(RWY34), WBAR, RWY DIST marker LGT TWY: (Marking) TWY CL, TWY side stripe (LGT) TWY edge LGT, TWY CL LGT (Other than A1,A2), RWY guard LGT(T1-T5), Taxiing guidance sign (as appropriate)
3	Stop bars	Nil
4	Remarks	(Marking) Overrun area (LGT) Apron flood LGT

RJEC AD 2.10 AERODROME OBSTACLES

■ In Area2 See Obstacle data

■ In Area3 To be developed

RJEC AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Associated MET Office	NEW CHITOSE
2	Hours of service MET Office outside hours	H24 (NEW CHITOSE)
3	Office responsible for TAF preparation Periods of validity	NEW CHITOSE 30 HoursNEW CHITOSE
4	Trend forecast Interval of issuance	Nil
5	Briefing/ consultation provided	Briefing is available upon inquiry at NEW CHITOSE
6	Flight documentation Language(s) used	C En
7	Charts and other information available for briefing or consultation	S ₆ , U ₈₅ , U ₇ , U ₅ , U ₃ , U ₂₅ , U ₂ /T _r , P _s , P ₅ , P ₃ , P ₂₅ , P _{SWE} , P _{SWF} , P _{SWG} , P _{SWI} , P _{SWM} , P _{SW} (domestic), E, C, W _E , W _F , W _G , W _I , W, N
8	Supplementary equipment available for providing information	Nil
9	ATS units provided with information	TWR
10	Additional information(limitation of service, etc.)	Nil

RJEC AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY(M)	Strength(PCN) and surface of RWY	THR coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
16	154.17°	2500×60	PCN 89/F/C/X/T Asphalt Concrete	434051.04N/1422626.96E 105.2ft	THR ELEV: 660ft
34	334.17°	2500×60	PCN 89/F/C/X/T Asphalt Concrete	433938.12N/1422715.59E 105.3ft	THR ELEV: 721ft TDZ ELEV: 717.7ft
Slope of RWY		Strip Dimensions(M)	RESA (Overrun) Dimensions(M)		Remarks
7		10	11		14
See AD2.24 AD CHART		2620×300	135 × (MNM:226 MAX:300)*		RWY Grooving:2500×60m
		2620×300	190 × (MNM:220 MAX:300)*		
*For detail, ask airport administrator					

RJEC AD 2.13 DECLARED DISTANCES

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)	Remarks
1	2	3	4	5	6
16	2500	2500	2500	2500	Nil
34	2500	2500	2500	2500	Nil

RJEC AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	APCH LGT type LEN INTST	RTHL Color WBAR	PAPI (VASIS) Angle DIST FM THR MEHT	RTZL LEN	RCLL LEN Spacing Color INTST	REDL LEN Spacing Color INTST	RENL Color WBAR	STWL LEN Color
1	2	3	4	5	6	7	8	9
16	SALS (*1) 420m LIH	Green Green	PAPI 3.0°/LEFT 400.2m 74ft	Nil	2,500m 30m Coded color (White/Red) LIH	2,500m 60m Coded color (White/Yellow) LIH	Red	Nil (*2)
34	PALS (CAT I) 900m LIH	Green Green	PAPI 3.0°/LEFT 499.2m 66ft	900m	2,500m 30m Coded color (White/Red) LIH	2,500m 60m Coded color (White/Yellow) LIH	Red	Nil (*2)
Remarks								
10								
SALS with APCH LGT beacon(906m and 596m FM RWY THR)(*1) Over run area edge LGT(LEN:60m,Color:Red)(*2)								

RJEC AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	ABN/IBN location, characteristics and hours of operation	ABN: 434013N/1422718E, White/Green EV4.3sec,HO
2	LDI location and LGT Anemometer location and LGT	LDI:Nil Anemometer: RWY16:300m from RWY16 THR, LGTD RWY34: 430m from RWY34 THR, LGTD
3	TWY edge and center line lighting	TWY edge and center line lights installed, see AD2.9
4	Secondary power supply/ switch-over time	Within 1sec : REDL, RTHL, RENL, WBAR, RCLL, Overrun area edge LGT Within 15sec: Other LGT
5	Remarks	WDI LGT

RJEC AD 2.16 HELICOPTER LANDING AREA

Nil

RJEC AD 2.17 ATS AIRSPACE

Designation and lateral limits		Vertical limits (ft)	Airspace classification	ATS unit call sign Language	Remarks
1		2	3	4	6
Daisetsu CTR	Area within a radius of 5nm(9km) of Asahikawa / RJEC ARP (43°40'N 142°27'E)	4,000 or below (Exclude the area of Asahikawa Control Zone)	D	Daisetsu Tower En	

RJEC AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	Call sign	Frequency	Hours of operation	Remarks
1	2	3	4	5
TWR	Daisetsu Tower	118.55MHz(1) 126.2MHz 121.5MHz(E) 243.0MHz(E)	2300 - 1200	(1)Primary

RJEC AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid (VOR declination)	ID	Frequency	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
VOR (9°W/2018)	AWE	113.5MHz	H24	434002.15N/ 1422724.65E		VOR/DME Unusable: 080°-090° beyond 35nm BLW 9000ft. VOR Unusable: 090°-110° beyond 35nm BLW 10000ft. 110°-130° beyond 30nm BLW 10000ft. 130°-170° beyond 35nm BLW 10000ft.
DME	AWE	1169MHz (CH-82X)	H24	434002.15N/ 1422724.65E	769ft	DME Unusable: 090°-110° beyond 25nm BLW 10000ft. 110°-170° beyond 30nm BLW 10000ft. 220°-230° beyond 30nm BLW 6000ft. 230°-240° beyond 35nm BLW 6000ft. 240°-260° beyond 20nm BLW 6000ft. 260°-290° beyond 35nm BLW 7000ft.
ILS-LOC 34	IAW	110.5MHz	2300 - 1200	434057.88N/ 1422622.40E		LOC: 235m(771ft) away FM RWY16 THR, BRG (MAG) 343°.
ILS-GP 34	-	329.6MHz	2300 - 1200	433947.05N/ 1422703.34E		GP: 368m(1207ft) inside FM RWY 34 THR, 126m(413ft) W of RCL. HGT of ILS Ref datum 16.5m. Angle 3.0°
ILS-DME 34	IAW	1003MHz (CH-42X)	2300 - 1200	433947.34N/ 1422702.97E	727ft	DME: 379m(1243ft) inside FM RWY 34 THR, 130m(427ft) W of RCL.
MSAS		1575.42MHz	H24			Transmitting antennas are satellite based



RJEC AD 2.20 LOCAL TRAFFIC REGULATIONS

1. Airport regulations

PPR

Prior permission is required for transient aircraft due to parking congestion except scheduled and/or emergency flight.

Tel : Asahikawa Airport Office 0166-83-2200

2. Taxiing to and from stands

Nil

3. Parking area for small aircraft(General aviation)

Nil

4. Parking area for helicopters

Nil

5. Apron - taxiing during winter conditions

Nil

6. Taxiing - limitations

1.Wing tip clearance at the TWY intersection (REF. AD1.1 item 6.8)

Wing tip clearance at the TWY intersection between the ACFT holding at the stop marking on the TWY and the other ACFT taxiing behind it are as follows.

When A306 holding at the stop marking on TWY T2,T3 or T4.

Wing span(WS) of ACFT taxiing on TWY P1-P5	WS<=59.8m	59.8m<WS<=76.8m	WS>76.8m
Wing tip clearance	A*	B*	C*

Legend :

A*:Wing tip clearance >=15m

B*:6.5m<=Wing tip clearance <15m

C*:Wing tip clearance<6.5m

7. School and training flights - technical test flights - use of runways

Nil

8. Helicopter traffic - limitation

Nil

9. Removal of disabled aircraft from runways

Nil

RJEC AD 2.21 NOISE ABATEMENT PROCEDURES

Nil

RJEC AD 2.22 FLIGHT PROCEDURES**1.TAKE OFF MINIMA**

	RWY	ACFT CAT	REDL & RCLL		REDL or RCLL or RCL marking		NIL (DAYTIME ONLY)	
			RVR	VIS	RVR	VIS	RVR	VIS
Multi-Engine ACFT with TKOF ALTN AP FILED	16	A,B,C,D	-	400m	-	400m	-	500m
	34	A,B,C,D	400m	400m	400m	400m	-	500m
Other	16	A,B,C,D	AVBL LDG MINIMA					
	34	A,B,C,D						

RJEC AD 2.23 ADDITIONAL INFORMATION

Nil

RJEC AD 2.24 CHARTS RELATED TO AN AERODROME

Aerodrome/Heliport Chart
 Standard Departure Chart - Instrument (KAGRA, ASAHIKAWA REVERSAL)
 Standard Arrival Chart - Instrument (OSOBA-RNAV)
 Instrument Approach Chart (ILS Z or LOC Z RWY34)
 Instrument Approach Chart (ILS Y or LOC Y RWY34)
 Instrument Approach Chart (VOR A)
 Instrument Approach Chart (VOR B)
 Instrument Approach Chart (VOR C)
 Instrument Approach Chart (RNAV(GNSS) Z RWY16)
 Instrument Approach Chart (RNAV(RNP) Y RWY16)
 Other Chart (Visual REP)
 Other Chart (MVA CHART)