AD 2 AERODROMES

RJSR AD 2.1 AERODROME LOCATION INDICATOR AND NAME

RJSR - ODATE-NOSHIRO

RJSR AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	ARP coordinates and site at AD	*401131N/1402218E* 109°/1.0km from RWY11 THR
2	Direction and distance from (city)	8.3NM W FM OODATE City
3	Elevation/ Reference temperature	276ft /31°C（1997-2008）
4	Geoid undulation at AD ELEV PSN	126ft
5	MAG VAR/ Annual change	8°W(2006) / 1'E
6	AD Administration, address, telephone, telefax, telex, AFS, e-mail and/or Web-site addresses	Odate-Noshiro Airport Administration Office (Akita prefectural government) 21-144,Wakigami-aza,karamushi-tai,kita-Akita City,AKITA,018-3454 JAPAN. TEL:0186-63-1001 FAX:0186-63-1009 E-mail:oodatenoshirokuukoujimusho@pref.akita.lg.jp
7	Types of traffic permitted (IFR/ VFR)	IFR/VFR
8	Remarks	Nil

RJSR AD 2.3 OPERATIONAL HOURS

1	AD Administration	2300 - 1030
2	Customs and immigration	On request Customs: 018-845-0735 Immigration: 018-895-5221
3	Health and sanitation	Quarantine(human): On request(018-846-8280) Quarantine(animal, plant): Nil
4	AIS Briefing Office	Nil
5	ATS Reporting Office(ARO)	Nil
6	MET Briefing Office	H24(SENDAI)
7	ATS	2300 - 1030 Remarks: Airport Remote Mobile Communication Service provided by Sendai FSC
8	Fuelling	2300 - 0930
9	Handling	2240 - 0900
10	Security	2300 - 1030
11	De-icing	Nil
12	Remarks	Nil

RJSR AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	AVBL up to B767 passenger plane
2	Fuel/ oil types	JET A1
3	Fuelling facilities/ capacity	Fuel truck /200kl
4	De-icing facilities	Nil
5	Hangar space for visiting aircraft	Nil
6	Repair facilities for visiting aircraft	Nil
7	Remarks	Nil

RJSR AD 2.5 PASSENGER FACILITIES

1	Hotels	Nil
2	Restaurants	At Airport
3	Transportation	Bus,Taxi
4	Medical facilities	Nil
5	Bank and Post Office	Nil
6	Tourist Office	Nil
7	Remarks	Nil

RJSR AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD category for fire fighting	CAT 7
2	Rescue equipment	Chemical fire fighting truck x 2 Emergency medical equipments conveyance truck x 1
3	Capability for removal of disabled aircraft	Ask AD administration
4	Remarks	Nil

RJSR AD 2.7 SEASONAL AVAILABILITY-CLEARING

1	Types of clearing equipment	Snow plow x 4, Snow sweeper x 4, rotary x 4, spreader equipment x 1
2	Clearance priorities	RWY, TWY, APRON
3	Remarks	Nil

RJSR AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS DATA

1	Apron surface and strength	Surface: Concrete Strength: PCN 55/R/B/X/T
2	Taxiway width, surface and strength	Width 30m Surface: asphalt-Concrete Strength: PCN 75/F/C/X/T
3	ACL and elevation	Not available
4	VOR checkpoints	Not available
5	INS checkpoints	(Spot NR) *1 401142.42N ,1402218.33E* *2 401142.04N ,1402220.50E* *3 401141.71N ,1402223.00E* *5 401141.37N ,1402225.50E*
6	Remarks	Nil

RJSR AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand ID signs, TWY guide lines and Visual docking/ parking guidance system of aircraft stands	Nil
2	RWY and TWY markings and LGT	RWY:RWY 11/29 (Marking): RWY designation, RWY CL, RWY THR, RWY middle point, Aiming point, TDZ, RWY side stripe, RWY turn pad edge, RWY turn pad CL (LGT): RCLL, REDL, RTHL, RENL, RTZL(RWY11), WBAR, Turning point indicator LGT, RWY DIST marker LGT TWY: (Marking):TWY CL, RWY HLDG PSN, TWY side stripe (LGT):TWY edge LGT, TWY CL LGT, Taxiing guidance sign
3	Stop bars	Nil
4	Remarks	(Marking):Overrun area (LGT):Apron flood LGT

RJSR / ODATE-NOSHIRO 180° Turn on RWY

B767 型機用の滑走路 180° 転回実施要領

1. 滑走路中心線からターニングパッド中心線標識に従って進行する。
2. 転回灯 1 が一直線に見えるように進行し、転回灯 2 が一直線に見えたとき転回を開始する。転回時は MAX STEERING ANGLE を使用する。

180°turn procedure on RWY for B767 aircraft

1. Proceed along the RWY Center Line to the starting point of the RWY Turn Pad Center Line Marking ; then
2. Proceed along the RWY Turn Pad Center Line Marking to see the Turning Point Indicator Light 1 on a straight line, then commence turn at the spot where you (pilot)can see the Turning Point Indicator Light 2 on a straight line at an angle of 9 o'clock. When turning, take MAX STEERING ANGLE.

ODATE-NOSHIRO AP





RJSR AD 2.10 AERODROME OBSTACLES

In Area2 See Obstacle data

In Area3 To be developed

RJSR AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Associated MET Office	SENDAI
2	Hours of service MET Office outside hours	H24(SENDAI)
3	Office responsible for TAF preparation Periods of validity	Nil
4	Trend forecast Interval of issuance	Nil
5	Briefing/ consultation provided	Briefing is available upon inquiry at SENDAI
6	Flight documentation Language(s) used	C En
7	Charts and other information available for briefing or consultation	S_6, U_{85}, U_7, U_5, U_3, U_{25}, U_2/T_r, P_s, P_5, P_3, P_{25}, P_{SWE}, P_{SWF}, P_{SWG}, P_{SWI}, P_{SWM}, P_{SW}(domestic), E, C, W_E, W_F, W_G, W_I, W, N
8	Supplementary equipment available for providing information	Nil
9	ATS units provided with information	REMOTE
10	Additional information(limitation of service, etc.)	Nil

RJSR AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY(M)	Strength(PCN) and surface of RWY	THR coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
11	100.30°	2000×45	PCN 75/F/C/X/T Asphalt-Concrete	*401136.37N* *1402135.51E* 125.7FT	THR ELEV:259.2FT TDZ ELEV:269FT
29	280.30°	2000×45	PCN 75/F/C/X/T Asphalt-Concrete	*401125.10N* *1402258.78E* 126FT	THR ELEV:292.0FT

Slope of RWY	Strip Dimensions(M)	RESA (Overrun) Dimensions (M)	Remarks
7	10	11	14
See below figure	2120×300 2120×300	190×(MNM:149 MAX:297)* 40×(MNM:250 MAX:300)* *For detail, ask airport administrator	RWY Grooving : 2000×45m

LONGITUDINAL PROFILE OF RUNWAY



RJSR AD 2.13 DECLARED DISTANCES

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)	Remarks
1	2	3	4	5	6
11	2000	2000	2000	2000	Nil
29	2000	2000	2000	2000	Nil

RJSR AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	APCH LGT type LEN INTST	RTHL Color WBAR	PAPI (VASIS) Angle DIST FM THR MEHT	RTZL LEN	RCLL LEN Spacing Color INTST	REDL LEN Spacing Color INTST	RENL Color WBAR	STWL LEN Color
1	2	3	4	5	6	7	8	9
11	PALS (CAT I) 900m LIH	Green Green	PAPI 3.0° /Left 347.2m 61ft	900m	2000m 30m Coded color (White/Red) LIH	2000m 60m Coded color (White/Yellow) LIH	Red	Nil (*2)
29	SALS (*1) 420m LIH	Green Nil	PAPI 3.0° /Left 414.9m 61ft	Nil	2000m 30m Coded color (White/Red) LIH	2000m 60m Coded color (White/Yellow) LIH	Red	Nil (*2)
Remarks								
10								
SALS with APCH LGT beacon(570m and 900m FM RWY 29 THR)(*1) Overrun area edge LGT(LEN:60m Color:Red) (*2) CGL for RWY 29 only								

RJSR AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	ABN/IBN location, characteristics and hours of operation	ABN: *401148N/1402216E*, White/Green EV4.3sec, HO
2	LDI location and LGT Anemometer location and LGT	LDI:Nil Anemometer : RWY11:300m from RWY11 THR. LGTD RWY29:300m from RWY29 THR. LGTD
3	TWY edge and centerline lighting	TWY edge and center line lights installed, see AD 2.9
4	Secondary power supply/ switch-over time	Within 15sec : ALL LGT
5	Remarks	WDI LGT

RJSR AD 2.16 HELICOPTER LANDING AREA

Nil

RJSR AD 2.17 ATS AIRSPACE

Designation and lateral limits		Vertical limits (ft)	Airspace classification	ATS unit call sign Language	Remarks
1		2	3	4	6
Odate Noshiro information zone	Area within a radius of 9km(5NM) of Odate-Noshiro ARP.	3,000 or below	E	Odate Remote En	

RJSR AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	Call sign	Frequency	Hours of operation	Remarks
1	2	3	4	5
A/G	Odate Remote	118.75MHz	2300 - 1030	RAG Controlled by Sendai FSC

RJSR AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid (VOR declination)	ID	Frequency	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
VOR (9°W/2015)	ODE	114.75MHz	2300 - 1030	*401154.03N/ 1402142.68E*		VOR unusable: 010°-020° beyond 35nm BLW 8000ft. 100°-110° beyond 35nm BLW 6000ft. 110°-130° beyond 35nm BLW 9000ft. 150°-160° beyond 30nm BLW 8000ft. 320°-340° beyond 35nm BLW 6000ft. 340°-350° beyond 25nm BLW 6000ft. 350°-360° beyond 35nm BLW 8000ft.
DME	ODE	1055MHz (CH-94Y)	2300 - 1030	*401154.03N/ 1402142.68E*	308ft	DME unusable: 100°-110° beyond 35nm BLW 6000ft. 110°-130° beyond 35nm BLW 9000ft. 150°-160° beyond 30nm BLW 8000ft. 320°-340° beyond 35nm BLW 6000ft. 340°-350° beyond 35nm BLW 6000ft. 350°-360° beyond 35nm BLW 8000ft.
ILS-LOC 11	IOD	110.15MHz	2300 - 1030	*401123.77N/ 1402308.57E*		LOC:235m(771ft) away FM RWY 29 THR, BRG(MAG)110°.
ILS-GP 11	-	334.25MHz	2300 - 1030	*401130.74N/ 1402146.51E*		GP:287m(942ft) inside FM RWY 11 THR. 125m(410ft) S of RCL. HGT of ILS REF datum 16.5m (54ft). GP angle 3.0°.
ILS-DME 11	IOD	1125MHz	2300 - 1030	*401130.42N/ 1402146.43E*	278ft	DME:287m(942ft) inside FM RWY 11 THR. 135m(443ft) S of RCL.

ILS



REMARKS : 1 . ILS-LOC beam (BRG) 110°
2 . ILS-GP Angle 3.0°
3 . HGT of ILS REF datum 16.5m(54ft)
4 . ELEV of ILS-DME 84.86(278ft)

RJSR AD 2.20 LOCAL TRAFFIC REGULATIONS

1. Airport regulations

Nil

2. Taxiing to and from stands

Nil

3. Parking area for small aircraft(General aviation)

Nil

4. Parking area for helicopters

Nil

5. Apron - taxiing during winter conditions

Nil

6. Taxiing - limitations

Nil

7. School and training flights - technical test flights - use of runways

Nil

8. Helicopter traffic - limitation

Nil

9. Removal of disabled aircraft from runways

Nil

RJSR AD 2.21 NOISE ABATEMENT PROCEDURES

Nil

RJSR AD 2.22 FLIGHT PROCEDURES

1.TAKE OFF MINIMA

	RWY	ACFT CAT	REDL & RCLL		REDL or RCLL or RCL Marking		NIL (DAYTIME ONLY)	
			CEIL-RVR	CEIL-VIS	CEIL-RVR	CEIL-VIS	CEIL-RVR	CEIL-VIS
Multi-Engine ACFT with TKOF ALTN AP FILED	11	A, B, C, D	200'-800m	200'-800m	200'-800m	200'-800m	-	200'-800m
	29	A, B, C, D	-	200'-800m	-	200'-800m	-	200'-800m
OTHER	11	A, B, C, D	AVBL LDG MINIMA					
	29	A, B, C, D						

RJSR AD 2.23 ADDITIONAL INFORMATION

Nil

RJSR AD 2.24 CHARTS RELATED TO AN AERODROME

Aerodrome/Heliport Chart
Standard Departure Chart - Instrument (ODATE REVERSAL)
Standard Departure Chart - Instrument (LAGOON)
Standard Arrival Chart - Instrument
Instrument Approach Chart (ILS Z or LOC Z RWY11)
Instrument Approach Chart (ILS Y or LOC Y RWY11)
Instrument Approach Chart (VOR A)
Instrument Approach Chart (RNAV(RNP) Z RWY29)
Instrument Approach Chart (RNAV(RNP) Y RWY29)
Other Chart (Visual REP)
Other Chart (LDG CHART)
Other Chart (MVA CHART)