
INSTRUMENT APPROACH CHART



INSTRUMENT APPROACH CHART

RJAF / MATSUMOTO

RNAV(RNP) Y RWY36

RNAV(RNP) Y RWY36

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	PAPNA	1	-	-8.0	1	1	+12000	1	-	-
002	TF	AF654	1	178 (170.2)	-8.0	21.5	1	ı	ı	1	1.0
003	TF	AF655	1	178 (170.3)	-8.0	5.0	-	7500	-	-	0.3
004	RF Center: AFRF4 r=4.89NM	AF656	1	ı	-8.0	3.0	R	6800	1	1	0.3
005	RF Center: AFRF4 r=4.89NM	AF657	1	-	-8.0	7.1	R	4179	1	-3.50	0.2 0.3
006	TF	AF652	1	296 (288.4)	-8.0	1.4	ı	3657	ı	-3.50	0.2 0.3
007	RF Center: AFRF2 r=2.02NM	AF653	1	-	-8.0	2.2	R	2837	1	-3.50	0.2 0.3
800	TF	RW36	Υ	359 (351.1)	-8.0	1.6	1	2232	-	-3.50/50	0.2 0.3
009	FA	-	-	359 (351.1)	-8.0	-	-	+7000	-	-	1.0
010	DF	MBE	-	-	-8.0	-	R	10000	-	-	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
PAPNA	363721.74N / 1380122.92E	AFRF4	361027.73N / 1380059.34E
AF654	361613.48N / 1380553.24E	AFRF2	360810.39N / 1375813.97E
AF655	361117.56N / 1380656.02E		
AF656	360820.76N / 1380625.54E		
AF657	360549.12N / 1375905.80E		
AF652	360615.53N / 1375727.24E		
AF653	360751.55N / 1375546.68E		
RW36	360928.29N / 1375527.85E		
MBE	360921.51N / 1375511.34E		
		_	