

AD 2 AERODROMES

RJFG AD 2.1 AERODROME LOCATION INDICATOR AND NAME

RJFG - TANEGASHIMA

RJFG AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

| | | |
|---|--|---|
| 1 | ARP coordinates and site at AD | 303618N/1305930E 123°/1.0km FM RWY13 THR |
| 2 | Direction and distance from (city) | 7.6nm S FM Nishinoomote City |
| 3 | Elevation/ Reference temperature | 768ft / - |
| 4 | Geoid undulation at AD ELEV PSN | 29.4m(96ft) |
| 5 | MAG VAR/ Annual change | 5° 47'W (2005) / Annual Change 2'W |
| 6 | AD Administration, address, telephone, telefax, telex, AFS, e-mail and/or Web-site addresses | KAGOSHIMA PREF Nakatane-Town, Kagoshima Pref. 891-3603 Japan Tel: 0997-27-5111, Fax: 0997-27-7373 E-mail:tane-kanri@ever.ocn.ne.jp |
| 7 | Types of traffic permitted (IFR/VFR) | IFR/VFR |
| 8 | Remarks | Nil |

RJFG AD 2.3 OPERATIONAL HOURS

| | | |
|----|---------------------------|--|
| 1 | AD Administration | 2330-0930 |
| 2 | Customs and immigration | On request Customs: 099-260-3125 Immigration: 099-222-5658 |
| 3 | Health and sanitation | Quarantine(human): On request(099-222-8670) Quarantine(animal, plant): Nil |
| 4 | AIS Briefing Office | Nil |
| 5 | ATS Reporting Office(ARO) | Nil |
| 6 | MET Briefing Office | H24 (FUKUOKA) |
| 7 | ATS | 2330-0930 Remarks: Airport Remote Mobile Communication Service provided by Kagoshima FSC. |
| 8 | Fuelling | 2330-0930 |
| 9 | Handling | 2330-0930 |
| 10 | Security | 2330-0930 |
| 11 | De-icing | Nil |
| 12 | Remarks | Nil |

RJFG AD 2.4 HANDLING SERVICES AND FACILITIES

| | | |
|---|---|------------------------------------|
| 1 | Cargo-handling facilities | Nil |
| 2 | Fuel/ oil types | Fuel grades: Jet A1, AVGAS |
| 3 | Fuelling facilities/ capacity | Fuel Truck / ASK AD Administration |
| 4 | De-icing facilities | Not available |
| 5 | Hangar space for visiting aircraft | Not available |
| 6 | Repair facilities for visiting aircraft | Not available |
| 7 | Remarks | Nil |

RJFG AD 2.5 PASSENGER FACILITIES

| | | |
|---|----------------------|---|
| 1 | Hotels | Hotels in Nishinoomote city |
| 2 | Restaurants | At Airport |
| 3 | Transportation | Buses and Taxi |
| 4 | Medical facilities | Hospital in Nishinoomote city 14km |
| 5 | Bank and Post Office | Bank and Post Office in Nishinoomote city |
| 6 | Tourist Office | Not available |
| 7 | Remarks | Nil |

RJFG AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

| | | |
|---|---|----------------------------------|
| 1 | AD category for fire fighting | CAT 7 |
| 2 | Rescue equipment | Chemical fire fighting truck × 2 |
| 3 | Capability for removal of disabled aircraft | to be developed |
| 4 | Remarks | Nil |

RJFG AD 2.7 SEASONAL AVAILABILITY-CLEARING

| | | |
|---|-----------------------------|---------------|
| 1 | Types of clearing equipment | Not available |
| 2 | Clearance priorities | Nil |
| 3 | Remarks | Nil |

RJFG AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS DATA

| | | |
|---|-------------------------------------|---|
| 1 | Apron surface and strength | Surface: cement-concrete Strength: PCN 53/R/C/X/T |
| 2 | Taxiway width, surface and strength | Width: 23m, Surface: asphalt-concrete Strength: PCN 42/F/A/X/T |
| 3 | ACL and elevation | Not available |
| 4 | VOR checkpoints | Not available |
| 5 | INS checkpoints | (Spot NR) 1 303632N 1305927E 2 303631N 1305929E 3 303630N 1305930E |
| 6 | Remarks | Nil |

RJFG AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

| | | |
|---|--|---|
| 1 | Use of aircraft stand ID signs, TWY guide lines and Visual docking/ parking guidance system of aircraft stands | Nil |
| 2 | RWY and TWY markings and LGT | RWY: (RWY 13/31) (Marking): RWY designation, RWY CL, RWY THR, RWY middle point, Aiming point, TDZ, RWY side stripe (LGT): RCLL, REDL, RTHL, RENL, RTZL(RWY31), WBAR(RWY31) TWY: All TWY (Marking): TWY CL, RWY HLDG PSN, TWY side stripe (LGT): TWY edge LGT, TWY CL LGT |
| 3 | Stop bars | Nil |
| 4 | Remarks | (Marking) Overrun area marking (LGT) Apron flood LGT |

RJFG AD 2.10 AERODROME OBSTACLES

- In Area2 Nil
- In Area3 To be developed

RJFG AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

| | | |
|----|--|---|
| 1 | Associated MET Office | FUKUOKA |
| 2 | Hours of service MET Office outside hours | H24 (FUKUOKA) |
| 3 | Office responsible for TAF preparation Periods of validity | Nil |
| 4 | Trend forecast Interval of issuance | Nil |
| 5 | Briefing/ consultation provided | Briefing is available upon inquiry at FUKUOKA |
| 6 | Flight documentation Language(s) used | C En |
| 7 | Charts and other information available for briefing or consultation | S ₆ , U ₈₅ , U ₇ , U ₅ , U ₃ , U ₂₅ , U _{2/T} , P _S , P ₅ , P ₃ , P ₂₅ , P _{SWE} , P _{SWF} , P _{SWG} , P _{SWI} , P _{SWM} , P _{SW(domestic)} , E, C, W _E , W _F , W _G , W _I , W, N |
| 8 | Supplementary equipment available for providing information | Nil |
| 9 | ATS units provided with information | REMOTE |
| 10 | Additional information(limitation of service, etc.) | Nil |

RJFG AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

| Designations RWY NR | TRUE BRG | Dimensions of RWY(M) | Strength(PCN) and surface of RWY | THR coordinates THR geoid undulation | THR elevation and highest elevation of TDZ of precision APP RWY |
|---|----------|-------------------------|-------------------------------------|---|---|
| 1 | 2 | 3 | 4 | 5 | 6 |
| 13 | 122.91° | 2000×45 | PCN42/F/A/X/T Asphalt Concrete | 303636N/1305858E 97ft | THR ELEV:778ft |
| 31 | 302.91° | 2000×45 | PCN42/F/A/X/T Asphalt Concrete | 303601N/1310001E 96ft | THR ELEV:758ft TDZ ELEV:766.7ft |
| Slope of RWY | | Strip Dimensions(M) | RESA(Overrun) Dimensions(M) | | Remarks |
| 7 | | 10 | 11 | | 14 |
| See below figure | | 2120×300 | 40×300 | | RWY grooving: 2000×30m |
| See below figure | | 2120×300 | 190x(MNM:160 MAX:300)* | | RWY grooving: 2000×30m |
| *For detail, ask airport administrator | | | | | |
| <div><div><div>RWY 13</div><div>778ft</div><div>0m</div></div><div><div>0.30%</div></div><div><div>RWY 31</div><div>758ft</div><div>2000m</div></div></div> | | | | | |

RJFG AD 2.13 DECLARED DISTANCES

| RWY Designator | TORA (m) | TODA (m) | ASDA (m) | LDA (m) | Remarks |
|----------------|-------------|-------------|-------------|------------|---------|
| 1 | 2 | 3 | 4 | 5 | 6 |
| 13 | 2000 | 2000 | 2000 | 2000 | Nil |
| 31 | 2000 | 2000 | 2000 | 2000 | Nil |

RJFG AD 2.14 APPROACH AND RUNWAY LIGHTING

| RWY Designator | APCH LGT type LEN INTST | RTHL Color WBAR | PAPI (VASIS) Angle DIST FM THR MEHT | RTZL LEN | RCLL LEN Spacing Color INTST | REDL LEN Spacing Color INTST | RENL Color WBAR | STWL LEN Color |
|---|-----------------------------|-----------------|-------------------------------------|----------|--|---|-----------------|----------------|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| 13 | SALS (*1) 420m LIH | Green - | PAPI 3.0°/LEFT 323m 49ft | - | 2,000m 30m Coded color (White/Red) LIH | 2,000m 60m Coded color (White/Yellow) LIH | Red | Nil(*2) |
| 31 | PALS (CAT I) 900m LIH | Green Green | PAPI 3.0°/LEFT 327m 55ft | 900m | 2,000m 30m Coded color (White/Red) LIH | 2,000m 60m Coded color (White/Yellow) LIH | Red | Nil(*2) |
| Remarks | | | | | | | | |
| 10 | | | | | | | | |
| SALS with APCH LGT beacon(600m and 870m FM RWY THR)(*1) Overrun area edge LGT(LEN:60m Color:Red)(*2) | | | | | | | | |

RJFG AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

| | | |
|---|--|--|
| 1 | ABN/IBN location, characteristics and hours of operation | ABN: 303631N/1305935E White/Green EV4.3sec, HO |
| 2 | LDI location and LGT Anemometer location and LGT | LDI: Nil Anemometer: RWY13: 300m from RWY13 THR, LGTD RWY31: 294m from RWY31 THR, LGTD |
| 3 | TWY edge and centerline lighting | TWY edge LGT: Blue TWY centerline LGT: ALTN Green/Yellow FM RWY leaving report point, other Green |
| 4 | Secondary power supply/ switch-over time | Within 1sec: REDL, RENL, RTHL, WBAR, RCLL and Overrun area edge LGT Within 15sec: Other Lights |
| 5 | Remarks | WDI LGT |

RJFG AD 2.16 HELICOPTER LANDING AREA

Nil

RJFG AD 2.17 ATS AIRSPACE

| Designation and lateral limits | | Vertical limits (ft) | Airspace classification | ATS unit call sign Language | Remarks |
|--------------------------------|---|----------------------|-------------------------|-----------------------------|---------|
| 1 | | 2 | 3 | 4 | 6 |
| Tanegashima Information zone | Area within a radius of 5nm of Tanegashima ARP (30° 36'N130° 59'E). | ----- 3000 | E | TANEGASHIMA REMOTE En | |

RJFG AD 2.18 ATS COMMUNICATION FACILITIES

| Service designation | Call sign | Frequency | Hours of operation | Remarks |
|---------------------|-----------------------|--------------------------|--------------------|--|
| 1 | 2 | 3 | 4 | 5 |
| A/G | Tanegashima Remote | 118.75MHz(1) 126.2MHz | 2330 - 0930 | Remote air-ground facilities controlled by Kagoshima FSC (1)Primary |

RJFG AD 2.19 RADIO NAVIGATION AND LANDING AIDS

| Type of aid (VOR declination) | ID | Frequency | Hours of operation | Position of transmitting antenna coordinates | Elevation of DME transmitting antenna | Remarks |
|----------------------------------|-----|----------------------|-----------------------|---|--|---|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 |
| VOR (7° W/2019) | TGE | 115.4MHz | H24 | 303607.76N/ 1305929.52E | | |
| DME | TGE | 1188MHz (CH-101X) | H24 | 303607.76N/ 1305929.52E | 810.4ft | DME Unusable: 130°-160° beyond 15nm BLW 3000ft. |
| ILS-LOC 31 (CAT-I) | ITN | 108.95MHz | 2330-0930 | 303640.08N/ 1305850.76E | | BRG(MAG) 310° 235m away FM RWY13 THR |
| ILS-GP 31 | | 329.15MHz | 2330-0930 | 303602.61N/ 1305949.42E | | GP angle 3.0° HGT of ILS Ref datum 54ft. 297.8m inside FM RWY31 THR 120m SW of RCL |
| ILS-DME 31 | ITN | 1113MHz (CH-26Y) | 2330-0930 | 303602.49N/ 1305949.29E | 777ft | 297.8m inside FM RWY31 THR 125m SW of RCL |
| MSAS | | 1575.42MHz | H24 | | | Transmitting antennas are satellite based |



RJFG AD 2.20 LOCAL TRAFFIC REGULATIONS

1. Airport regulations

| |
|-----|
| Nil |
|-----|

2. Taxiing to and from stands

| |
|-----|
| Nil |
|-----|

3. Parking area for small aircraft(General aviation)

| |
|-----|
| Nil |
|-----|

4. Parking area for helicopters

| |
|-----|
| Nil |
|-----|

5. Apron - taxiing during winter conditions

| |
|-----|
| Nil |
|-----|

6. Taxiing - limitations

| |
|-----|
| Nil |
|-----|

7. School and training flights - technical test flights - use of runways

| |
|-----|
| Nil |
|-----|

8. Helicopter traffic - limitation

| |
|-----|
| Nil |
|-----|

9. Removal of disabled aircraft from runways

| |
|-----|
| Nil |
|-----|

RJFG AD 2.21 NOISE ABATEMENT PROCEDURES

| |
|-----|
| Nil |
|-----|

RJFG AD 2.22 FLIGHT PROCEDURES

1. TAKE OFF MINIMA

| | RWY | REDL & RCLL AVBL | | REDL or RCLL AVBL | | REDL & RCLL OUT | |
|-----------------------|-----|---------------------|----------|----------------------|----------|--------------------|----------|
| | | CEIL-RVR | CEIL-VIS | CEIL-RVR | CEIL-VIS | CEIL-RVR | CEIL-VIS |
| TKOF ALTN AP FILED | 13 | - | 0 - 400m | - | 0 - 600m | - | 0 - 800m |
| | 31 | 0 - 500m | 0 - 400m | 0 - 600m | 0 - 600m | - | 0 - 800m |
| OTHER | 13 | AVBL LDG MINIMA | | | | | |
| | 31 | | | | | | |

NOTE: SIDs are designed in accordance with provisional standards for FLIGHT PROCEDURE DESIGN.

2. TAKE OFF MINIMA for RNAV DEPARTURE

| | RWY | ACFT CAT | REDL & RCLL | | REDL or RCLL or RCL Marking | | NIL (DAYTIME ONLY) | |
|--|-----|-------------|-----------------|------|--------------------------------|------|-----------------------|------|
| | | | RVR | VIS | RVR | VIS | RVR | VIS |
| Multi-Engine ACFT with TKOF ALTN AP FILED | 13 | A,B,C,D | - | 400m | - | 400m | - | 500m |
| | 31 | A,B,C,D | 400m | 400m | 400m | 400m | - | 500m |
| OTHER | 13 | A,B,C,D | AVBL LDG MINIMA | | | | | |
| | 31 | | | | | | | |

RJFG AD 2.23 ADDITIONAL INFORMATION

Nil

RJFG AD 2.24 CHARTS RELATED TO AN AERODROME

Aerodrome/Heliport Chart
 Standard Departure Chart - Instrument (QUEEN, KINKO, TANEGASHIMA-REVERSAL)*
 Standard Departure Chart - Instrument (FREDY-RNAV)
 Standard Departure Chart - Instrument (KAGYA-RNAV)
 Standard Arrival Chart - Instrument)*
 Instrument Approach Chart (VOR/DME/ILS RWY 31)*
 Instrument Approach Chart (VOR/DME RWY 31)*
 Instrument Approach Chart (VOR/DME RWY 13)*
 Instrument Approach Chart (RNAV(GNSS) RWY 13)
 Other Chart (Visual REP)
 Other Chart (MVA CHART)

*: Designed in accordance with provisional standards for FLIGHT PROCEDURE DESIGN.

INTENTIONALLY LEFT BLANK

AD CHART

TANEGASHIMA AP

TRUE NORTH

WIND SPEED METER

WDI

RVR 303601N 1310001E

CEILO METER

RTHL

327m

PAPI Angle 3.0°

MEHT 16.7m(55ft)

ARP 303618N 1305930E

APRON FLOOD LGT

ABN

TERMINAL BLD

1 2 3

WIND SPEED METER

WDI

323.1m

PAPI Angle 3.0°

MEHT 14.9m(49ft)

RTHL

303636N 1305858E

OVERRUN AREA EDGE LGT

TANEGASHIMA

REMARKS :

| | | |
|-------------------------------|-------------|----------------|
| RWY GROOVING | 2000m x 30m | PCN 42/F/A/X/T |
| WIDTH & STRENGTH OF RWY | 2000m x 45m | PCN 42/F/A/X/T |
| WIDTH & STRENGTH OF TWY | 23m | PCN 53/R/C/X/T |
| DIMENSION & STRENGTH OF APRON | 185m x 90m | PCN 53/R/C/X/T |

LONGITUDINAL PROFILE OF RWY

RWY 13

237.00m (778ft)

RWY 31

231.00m (758ft)

0.3%

0m

2000m

APCH LGT BEACONS

SALS

600.0m

420.0m

270.0m

ALS

300.0m

600.0m

900.0m

SEQUENCED FLASHING LGT (SFL-V)

INTENTIONALLY LEFT BLANK

STANDARD DEPARTURE CHART - INSTRUMENT

RJFG / TANEGASHIMA

SID

QUEEN TWO DEPARTURE

RWY13: Climb RWY HDG until 1NM from RWY end/TGE 1.5DME, turn left,...

RWY31: Climb RWY HDG until 1NM from RWY end/TGE 1.7DME, turn right,...

...Climb via TGE R-045 to QUEEN.
Cross TGE R-045/27DME at or above 7,000ft, cross QUEEN at assigned altitude.

KINKO TWO DEPARTURE

RWY13: Climb RWY HDG until 1NM from RWY end/TGE 1.5DME, turn left,...

RWY31: Climb RWY HDG until 1NM from RWY end/TGE 1.7DME, turn right,...

...Climb via TGE R-349 to KINKO.
Cross TGE R-349/19DME at or above 6,000ft.


TANEGASHIMA REVERSAL TWO DEPARTURE

RWY13: Climb RWY HDG until 1NM from RWY end/TGE 1.5DME, turn left,...

RWY31: Climb RWY HDG until 1NM from RWY end/TGE 1.7DME, turn right,...

...Climb via TGE R-349, then turn left proceed to TGE VOR/DME within TGE 10DME.

CHANGE: PROC renamed. Radial FM TGE.



STANDARD DEPARTURE CHART -INSTRUMENT

RJFG / TANEGASHIMA

RNAV SID

FREDY ONE RNAV DEPARTURE

Basic RNP1

Note GNSS required.

VAR 6°W (2011)



FREDY ONE RNAV DEPARTURE

RWY13 : Climb on HDG 129° at or above 1200FT, turn left direct to FREDY at or above 7000FT, to QUEEN.

RWY31 : Climb on HDG 309° at or above 1300FT, turn right direct to FREDY at or above 7000FT, to QUEEN.

STANDARD DEPARTURE CHART -INSTRUMENT

RJFG / TANEGASHIMA

RNAV SID

FREDY ONE RNAV DEPARTURE

RWY13

| Rcmd. Path Terminator | Fix ID (Waypoint Name) | Fly Over | Distance (NM) | MAG Track (TRUE Track) | Turn Direction | Altitude (FT) | Speed Limit (KIAS) | Vertical Angle | Navigation Performance |
|-----------------------|------------------------|----------|---------------|------------------------|----------------|---------------|--------------------|----------------|------------------------|
| VA | — | — | — | 129° (122.9°) | — | +1200 | — | — | Basic RNP1 |
| DF | FREDY | — | — | — | L | +7000 | — | — | Basic RNP1 |
| TF | QUEEN | — | 24.9 | 044° (038.0°) | — | — | — | — | Basic RNP1 |

RWY31

| Rcmd. Path Terminator | Fix ID (Waypoint Name) | Fly Over | Distance (NM) | MAG Track (TRUE Track) | Turn Direction | Altitude (FT) | Speed Limit (KIAS) | Vertical Angle | Navigation Performance |
|-----------------------|------------------------|----------|---------------|------------------------|----------------|---------------|--------------------|----------------|------------------------|
| VA | — | — | — | 309° (302.9°) | — | +1300 | — | — | Basic RNP1 |
| DF | FREDY | — | — | — | R | +7000 | — | — | Basic RNP1 |
| TF | QUEEN | — | 24.9 | 044° (038.0°) | — | — | — | — | Basic RNP1 |

STANDARD DEPARTURE CHART -INSTRUMENT

RJFG / TANEGASHIMA

RNAV TRANSITION



STANDARD DEPARTURE CHART -INSTRUMENT

RJFG / TANEGASHIMA

RNAV SID



STANDARD DEPARTURE CHART -INSTRUMENT

RJFG / TANEGASHIMA

RNAV SID

KAGYA ONE RNAV DEPARTURE

RWY13

| Rcmd. Path Terminator | Fix ID (Waypoint Name) | Fly Over | Distance (NM) | MAG Track (TRUE Track) | Turn Direction | Altitude (FT) | Speed Limit (KIAS) | Vertical Angle | Navigation Performance |
|-----------------------|------------------------|----------|---------------|------------------------|----------------|---------------|--------------------|----------------|------------------------|
| VA | — | — | — | 129° (122.9°) | — | +1200 | — | — | Basic RNP1 |
| DF | KAGYA | — | — | — | L | — | — | — | Basic RNP1 |
| TF | FG801 | — | 8.3 | 348° (342.4°) | — | +6000 | — | — | Basic RNP1 |
| TF | KINKO | — | 25.7 | 348° (342.3°) | — | — | — | — | Basic RNP1 |

RWY31

| Rcmd. Path Terminator | Fix ID (Waypoint Name) | Fly Over | Distance (NM) | MAG Track (TRUE Track) | Turn Direction | Altitude (FT) | Speed Limit (KIAS) | Vertical Angle | Navigation Performance |
|-----------------------|------------------------|----------|---------------|------------------------|----------------|---------------|--------------------|----------------|------------------------|
| VA | — | — | — | 309° (302.9°) | — | +1300 | — | — | Basic RNP1 |
| DF | KAGYA | — | — | — | R | — | — | — | Basic RNP1 |
| TF | FG801 | — | 8.3 | 348° (342.4°) | — | +6000 | — | — | Basic RNP1 |
| TF | KINKO | — | 25.7 | 348° (342.3°) | — | — | — | — | Basic RNP1 |

STANDARD ARRIVAL CHART - INSTRUMENT

RJFG / TANEGASHIMA

STAR

KAGYA ARRIVAL

From over TEPPPO, proceed via TGE 12DME counterclockwise ARC to KAGYA.
Cross KAGYA at or above 6,000ft.

CHANGE: Radial FM TGE. Bearing on HOLD Pattern.




INTENTIONALLY LEFT BLANK

INSTRUMENT APPROACH CHART

RJFG / TANEGASHIMA


VOR/DME/ILS RWY31



INSTRUMENT APPROACH CHART


RJFG / TANEGASHIMA

VOR/DME RWY31

**MISSED APPROACH**

At TGE VOR/DME, climb to 3,000ft, via TGE R-301, then turn right within TGE 10DME proceed to TGE VOR/DME and hold.
Contact TANEGASHIMA REMOTE.

Remain within TGE 10DME



| | | |
|--------|---------------|--------------|
| MINIMA | THR elev. 758 | AD elev. 768 |
|--------|---------------|--------------|


| CAT | | | CIRCLING | | |
|-----|------------|-------------|--------------|--------------|------|
| | MDA(H) | RVR/ CMV | MDA(H) | | VIS |
| | | | SOUTH of RWY | NORTH of RWY | |
| A | 1240 (482) | 1000 | 1240 (472) | 1500 (732) | 1600 |
| B | | 1200 | | 1800 (1032) | 2400 |
| C | | | | | |
| D | | | 1600 | 1320 (552) | |

CHANGE: ATC call sign.

INSTRUMENT APPROACH CHART

RJFG / TANEGASHIMA


VOR/DME RWY13



INSTRUMENT APPROACH CHART

RJFG / TANEGASHIMA

RNAV(GNSS) RWY13




| NM to Next Fix | FAF | 3 | 2 | 1 | MAPt |
|----------------------|------|------|------|------|------|
| ALT (3.0° APCH Path) | 2000 | 1782 | 1464 | 1145 | — |

MISSED APPROACH

Climb to 6000FT, direct to KAGYA and hold.
Contact TANEGASHIMA REMOTE.

(For using VOR/DME)
Climb to 6000FT, via TGE R349 to KAGYA and hold.
Contact TANEGASHIMA REMOTE.



| MINIMA | THR elev. 778 | AD elev. 768 |
|--------|---------------|--------------|
|--------|---------------|--------------|

| CAT | LNAV/VNAV | | LNAV | | CIRCLING | |
|-----|------------|------|------------|------|-------------|------|
| | DA(H) | CMV | MDA(H) | CMV | MDA(H) | VIS |
| A | 1140 (362) | 1200 | 1140 (372) | 1200 | 1500 (732) | 1600 |
| B | | 1300 | | 1300 | | |
| C | | 1400 | | 1400 | 1800 (1032) | 2400 |
| D | | 1600 | | 1600 | | |

Circling to NORTH side of RWY only.

CHANGE: ATC call sign.

RJFG / TANEGASHIMA

Visual REP



| Call sign | BRG / DIST from ARP | Remarks |
|---------------------|---------------------|--------------------|
| 喜志鹿崎 Kishigazaki | 014°/14.6NM | 灯台 Lighthouse |
| 西之表 Nishinoomote | 359°/ 7.5NM | 西之表港 Harbor |
| 10NM W | 270°/10.0NM | 海上 Over the sea |
| 島間 Shimama | 219°/10.5NM | 港 Harbor |
| 竹崎 Takezaki | 187°/12.9NM | 灯台 Lighthouse |

RJFG / TANEGASHIMA

Minimum Vectoring Altitude CHART



*1 : 302013N/1302957E RADIUS : 10NM

CENTER: 303618N/1305930E (ARP)