

---

**AD 2 AERODROMES****RJSH AD 2.1 AERODROME LOCATION INDICATOR AND NAME****RJSH - HACHINOHE****RJSH AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA**

1	ARP coordinates and site at AD	403307N 1412802E
2	Direction and distance from (city)	3.0nm NW
3	Elevation/ Reference temperature	152ft / -
4	Geoid undulation at AD ELEV PSN	Nil
5	MAG VAR/ Annual change	Nil
6	AD Administration, address, telephone, telefax, telex, AFS, e-mail and/or Web-site addresses	JSDF-M
7	Types of traffic permitted(IFR/ VFR)	IFR/VFR
8	Remarks	Nil

**RJSH AD 2.3 OPERATIONAL HOURS**

1	AD Administration	H24
2	Customs and immigration	Nil
3	Health and sanitation	Nil
4	AIS Briefing Office	H24
5	ATS Reporting Office(ARO)	Nil
6	MET Briefing Office	H24
7	ATS	H24
8	Fuelling	Nil
9	Handling	Nil
10	Security	Nil
11	De-icing	Nil
12	Remarks	Nil

**RJSH AD 2.4 HANDLING SERVICES AND FACILITIES**

1	Cargo-handling facilities	Nil
2	Fuel/ oil types	JET A-1 PLUS
3	Fuelling facilities/ capacity	To be issued later
4	De-icing facilities	Nil
5	Hangar space for visiting aircraft	Nil
6	Repair facilities for visiting aircraft	Nil
7	Remarks	Nil

**RJSH AD 2.5 PASSENGER FACILITIES**

1	Hotels	Nil
2	Restaurants	Nil
3	Transportation	Nil
4	Medical facilities	Nil
5	Bank and Post Office	Nil
6	Tourist Office	Nil
7	Remarks	Nil

**RJSH AD 2.6 RESCUE AND FIRE FIGHTING SERVICES**

1	AD category for fire fighting	Nil
2	Rescue equipment	Nil
3	Capability for removal of disabled aircraft	Nil
4	Remarks	Nil

**RJSH AD 2.7 SEASONAL AVAILABILITY-CLEARING**

1	Types of clearing equipment	Nil
2	Clearance priorities	Nil
3	Remarks	Nil

**RJSH AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS DATA**

1	Apron surface and strength	To be issued later
2	Taxiway width, surface and strength	To be issued later
3	ACL and elevation	Not available
4	VOR checkpoints	Nil
5	INS checkpoints	Nil
6	Remarks	Nil

**RJSH AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS**

1	Use of aircraft stand ID signs, TWY guide lines and Visual docking/ parking guidance system of aircraft stands	Nil
2	RWY and TWY markings and LGT	RWY: 07/25 (LGT) RTHL, TKOF aiming LGT  TWY: (LGT) TWY edge LGT
3	Stop bars	Nil
4	Remarks	Nil

**RJSH AD 2.10 AERODROME OBSTACLES**

RWY/Area affected	Obstacle type	Coordinates	Elevation	Markings/ LGT	Remarks
Nil					

## RJSH AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Associated MET Office	HACHINOHE
2	Hours of service MET Office outside hours	H24
3	Office responsible for TAF preparation Periods of validity	Nil
4	Trend forecast Interval of issuance	Nil
5	Briefing/ consultation provided	Nil
6	Flight documentation Language(s) used	Ja,En
7	Charts and other information available for briefing or consultation	S,U
8	Supplementary equipment available for providing information	Nil
9	ATS units provided with information	Nil
10	Additional information(limitation of service, etc.)	Nil

## RJSH AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY(M)	Strength(PCN) and surface of RWY	THR coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
07	063.57°	2250×45	SW36500kg(80500lbs) DW56000kg(123500lbs) DTW117000kg(258000lbs) Concrete	403251.01N 1412718.94E	THR ELEV : 152ft
25	243.57°	2250×45	SW36500kg(80500lbs) DW56000kg(123500lbs) DTW117000kg(258000lbs) Concrete	403323.51N 1412844.64E	THR ELEV : 96.9ft TDZ ELEV : 118.8ft
Slope of RWY		Strip Dimensions(M)	Remarks		
7		10	12		
See below figure		2370×300 2370×300	Nil		

**RJSH AD 2.13 DECLARED DISTANCES**

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)	Remarks
1	2	3	4	5	6

**RJSH AD 2.14 APPROACH AND RUNWAY LIGHTING**

RWY Designator	APCH LGT type LEN INTST	RTHL Color WBAR	PAPI (VASIS) Angle DIST FM THR MEHT	RTZL LEN	RCLL LEN Spacing Color INTST	REDL LEN Spacing Color INTST	RENL Color WBAR	STWL LEN Color
1	2	3	4	5	6	7	8	9
07			PAPI 3.0°/Left 334m 45ft					
25	AVBL		PAPI 2.5°/Left 395m 59ft					
Remarks								
10								
RWY THR ID LGT for RWY07 THR (Color:White)								

**RJSH AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY**

1	ABN/IBN location, characteristics and hours of operation	ABN: 403249N/1412816E, White/Green EV10sec, HO
2	LDI location and LGT Anemometer location and LGT	LDI:LGTD
3	TWY edge and centerline lighting	TWY edge LGT:AVBL
4	Secondary power supply/ switch-over time	Nil
5	Remarks	WDI LGT, OBST LGT

## RJSH AD 2.16 HELICOPTER LANDING AREA

To be issued later

## RJSH AD 2.17 ATS AIRSPACE

Designation and lateral limits		Vertical limits (ft)	Airspace classification	ATS unit call sign Language	Remarks
1		2	3	4	6
HACHINOHE CTR	Area within a radius of 5 nm of HACHINOHE ARP(40°33'N 141°28'E)	6000 or below	D	HACHINOHE TOWER En	

## RJSH AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	Call sign	Frequency	Hours of operation	Remarks
1	2	3	4	5
TWR	Hachinohe Tower	228.2MHz 126.2MHz(4) 325.4MHz 138.3MHz 236.8MHz(2)(3) 123.1MHz(1) 121.5MHz(E) 243.0MHz(E) 141.2MHz	H24	APP provided by Misawa APP.  (1)For rescue only. (2)Required specification on flight plan. (3)AVBL on request (4)Secondary
GND	Hachinohe Ground	325.4MHz	H24	
GCA-ASR -PAR	Hachinohe GCA	335.6MHz 270.8MHz 134.1MHz 125.3MHz 335.8MHz 289.4MHz 258.6MHz 139.55MHz 123.1MHz(1) 258.2MHz 243.0MHz(E) 121.5MHz(E)	2300 - 0800 EXC FRI0801 - SUN2259 and HOL Other time 1HR PN	ASR RWY 07/25 PAR RWY 25 Glide path 2.5° Maintenance period: 2300 - 0800 1st SAT in VMC
ATIS	Hachinohe Airport	245.8MHz	2200 - 1300 EXC FRI1301 - SUN2159 and HOL Other time 1HR PN	

## RJSH AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid	ID	Frequency	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
NDB	JC	381KHz	H24	403301N 1412842E		
TACAN	HVT	984MHz (CH-23X)	H24	403321N 1412812E	45.1m (147.9ft)	TACAN Unusable: R155-165 beyond 32NM BLW 6000ft.
ILS-LOC 25	IHE	111.3MHz	H24	403247N 1412709E		LOC : 274m(899ft) away FM RWY 07 THR,BRG(MAG)251°
ILS-GP 25		332.3MHz	H24	403322N 1412830E		GP:330m(1083ft) inside FM RWY 25 THR, 125m(410ft) N of RCL. HGT of ILS Ref datum 16.8m(55ft) Angle 2.5°
ILS-DME 25	IHE	1011MHz (CH-50X)	H24	403322N 1412829E	35.9m (117.9ft)	DME:333m(1093ft) inside FM RWY 25 THR, 131m(430ft) N of RCL.

ILS for RWY25



REMARKS : 1. LOC beam BRG(MAG) 251°  
 2. HGT of ILS REF datum 16.8m (55ft)  
 3. GP Angle 2.5°  
 4. ELEV of ILS-DME 35.9m(117.9ft)

## RJSH AD 2.20 LOCAL TRAFFIC REGULATIONS

## 1. Airport regulations

■

Nil

## 2. Taxiing to and from stands

Nil

## 3. Parking area for small aircraft(General aviation)

Nil

## 4. Parking area for helicopters

Nil

## 5. Apron - taxiing during winter conditions

Nil
-----

## 6. Taxiing - limitations

Nil
-----

## 7. School and training flights - technical test flights - use of runways

Nil
-----

## 8. Helicopter traffic - limitation

Nil
-----

## 9. Removal of disabled aircraft from runways

Nil
-----

## RJSH AD 2.21 NOISE ABATEMENT PROCEDURES

Nil
-----

## RJSH AD 2.22 FLIGHT PROCEDURES

## 1. TAKE OFF MINIMA

	RWY	CEIL-RVR	CEIL-VIS
TKOF ALTN AP FILED	25	200'-800m	200'-800m
	07	-	200'-800m
OTHER	25	AVBL LDG MINIMA	
	07		

## 2. WX MINIMA CONCERNING PAR/ASR APCH PROCEDURE

ASR RWY 25

MINIMA		THR elev. 97	AD elev. 152	
CAT			CIRCLING	
	MDA(H)	RVR/CMV	MDA(H)	VIS
A	580 (483)	1400	580 (428)	1600
B		1500	660 (508)	
C		1600	740 (588)	2400
D		1800		3200



## ASR RWY 07

MINIMA		THR elev. 152	AD elev. 152	
CAT			CIRCLING	
	MDA(H)	CMV	MDA(H)	VIS
A	660 (508)	1500	660 (508)	1600
B				
C		2000	740 (588)	2400
D				3200

## PAR RWY 25

MINIMA		THR elev. 97	AD elev. 152	
CAT			CIRCLING	
	DA(H)	RVR/CMV	MDA(H)	VIS
A	320 (223)	750	580 (428)	1600
B			660 (508)	
C			740 (588)	2400
D				3200

**3. Lost communication procedures for arrival aircraft under radar navigational guidance**

If radio communications with Hachinohe GCA are lost for 1 minute(PAR,ASR RWY 25)/30 seconds(ASR RWY 07)in the pattern or 5 seconds (PAR)/15 seconds (ASR) on final approach, squawk Mode A/3 Code 7600 and;

- (I)
1. Contact Misawa Radar.
  2. If unable, proceed in accordance with visual flight rules.
  3. If unable, proceed to ENBRY/JC NDB at last assigned altitude or 3,000 feet whichever is higher, and execute instrument approach.
- (II) Procedures other than above will be issued when situation required.

**RJSH AD 2.23 ADDITIONAL INFORMATION**

Nil

**RJSH AD 2.24 CHARTS RELATED TO AN AERODROME**

Standard Departure Chart - Instrument  
Instrument Approach Chart (ILS Z or LOC Z RWY25)  
Instrument Approach Chart (ILS Y or LOC Y RWY25)  
Instrument Approach Chart (ILS X or LOC X RWY25)  
Instrument Approach Chart (TACAN RWY25)  
Instrument Approach Chart (NDB A)  
Instrument Approach Chart (NDB B)  
Other Chart (LDG CHART)

**INTENTIONALLY LEFT BLANK**

STANDARD DEPARTURE CHART -INSTRUMENT

RJSH / HACHINOHE

SID

HACHINOHE TWO DEPARTURE

RWY07 : Climb via HVT R070(070 degrees from JC NDB) to 1000FT within HVT 8DME (8NM from RWY end),turn right, ...

RWY25 : Climb via HVT R250(250 degrees from JC NDB) to 1000FT within HVT 8DME (8NM from RWY end),turn left, ...

... direct to HVT(JC NDB), cross HVT(JC NDB) at or above 3000FT.

HACHINOHE REVERSAL ONE DEPARTURE

RWY07 : Turn right, ...

RWY25 : Turn left, ...

... climb via HVT R190(190 degrees from JC NDB) until reaching at or above 1/2 of assigned altitude, turn right, direct to HVT(JC NDB) within HVT 15DME (15NM from JC NDB), cross HVT(JC NDB) at assigned altitude.




CHANGE : Update

**INTENTIONALLY LEFT BLANK**

INSTRUMENT APPROACH CHART

RJSH / HACHINOHE

ILS Z or LOC Z RWY25



MISSED APPROACH

Climb to 3000FT via HVT R250 to  
HVT 10.0DME and hold.  
Contact MISAWA APP.




MINIMA		THR elev. 97		AD elev. 152		
CAT	CAT I		LOC		CIRCLING	
	DA(H)	RVR/ CMV	MDA(H)	RVR/ CMV	MDA(H)	VIS
A	320 (223)	750	460 (363)	1200	580 (428)	1600
B				1300	660 (508)	
C				1400	740 (588)	2400
D				1600		3200

CHANGE : Editorial

## INSTRUMENT APPROACH CHART

RJSH / HACHINOHE

ILS Y or LOC Y RWY25



CHANGE : Editorial

INSTRUMENT APPROACH CHART


RJSH / HACHINOHE

ILS X or LOC X RWY25



MISSED APPROACH

Climb to 3000FT via HVT R250 to HVT 10.0DME and hold.  
Contact MISAWA APP.



MINIMA

THR elev. 97

AD elev. 152

CAT	CAT I		LOC		CIRCLING	
	DA(H)	RVR/CMV	MDA(H)	RVR/CMV	MDA(H)	VIS
A	320 (223)	750	460 (363)	1200	580 (428)	1600
B				1300	660 (508)	
C				1400	740 (588)	2400
D				1600		3200

CHANGE : Editorial


## RJSH / HACHINOHE

MISAWA APP  
317.8 - 261.2  
125.3 - 120.7

HACHINOHE TACAN  
HVT CH-23X ☐-  
40°33'21"N/141°28'12"E

HACHINOHE TOWER  
126.2 - 228.2 - 325.4  
138.3 - 236.8

GCA AVBL  
CALL  
MISAWA APP



Climb to 3000FT via HVT R250 to  
HVT 10.0DME and hold.  
Contact MISAWA APP.



MINIMA		THR elev. 97	AD elev. 152	
CAT			CIRCLING	
	MDA(H)	RVR/ CMV	MDA(H)	VIS
A	520 (423)	1200	580 (428)	1600
B		1300	660 (508)	
C		1400	740 (588)	2400
D		1600		3200


Civil Aviation Bureau, Japan (EFF:10 OCT 2019)



INSTRUMENT APPROACH CHART

RJSH / HACHINOHE

NDB A



CHANGE : Editorial


## INSTRUMENT APPROACH CHART

RJSH / HACHINOHE

NDB B

**MISSED APPROACH**

At JC NDB, turn left, climb to 5000FT via 250DEG from JC NDB.  
Contact MISAWA APP.

**MINIMA**

AD elev. 152

CAT	CIRCLING	
	MDA(H)	VIS
A	720 (568)	1600
B		
C	740 (588)	2400
D		3200

CHANGE : Editorial

