


RJNO / OKI

AD CHART



## STANDARD DEPARTURE CHART -INSTRUMENT

RJNO / OKI


SID

DOZEN FOUR DEPARTURE

RWY08 : Climb RWY HDG to 800FT, turn right HDG258°...

RWY26 : Climb RWY HDG to 900FT, turn left HDG168°...


...to intercept and proceed via OIE R213 to DOZEN.



STANDARD DEPARTURE CHART -INSTRUMENT

RJNO / OKI

➡ RNAV SID



## STANDARD DEPARTURE CHART -INSTRUMENT

RJNO / OKI

➡ RNAV SID

NAKAU ONE DEPARTURE

## RWY08

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	076 (067.8)	-7.9	—	—	+700	—	—	Basic RNP1
002	DF	DONDO	—	—	-7.9	—	R	—	—	—	Basic RNP1
003	TF	NAKAU	—	199 (191.6)	-7.9	23.7	—	+4000	—	—	Basic RNP1


## RWY26

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	256 (247.8)	-7.9	—	—	+800	—	—	Basic RNP1
002	DF	DONDO	—	—	-7.9	—	L	—	—	—	Basic RNP1
003	TF	NAKAU	—	199 (191.6)	-7.9	23.7	—	+4000	—	—	Basic RNP1

STANDARD DEPARTURE CHART -INSTRUMENT

RJNO / OKI

➡ RNAV SID



## STANDARD DEPARTURE CHART -INSTRUMENT

RJNO / OKI

➡ RNAV SID

OKUNI ONE DEPARTURE

## RWY08

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	076 (067.8)	-7.9	—	—	+700	—	—	Basic RNP1
002	DF	TIBRI	—	—	-7.9	—	R	—	—	—	Basic RNP1
003	TF	OKUNI	—	224 (216.2)	-7.9	42.4	—	+3000	—	—	Basic RNP1


## RWY26

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	256 (247.8)	-7.9	—	—	+800	—	—	Basic RNP1
002	DF	TIBRI	—	—	-7.9	—	L	—	—	—	Basic RNP1
003	TF	OKUNI	—	224 (216.2)	-7.9	42.4	—	+3000	—	—	Basic RNP1

STANDARD DEPARTURE CHART -INSTRUMENT

RJNO / OKI

➡ RNAV SID



## STANDARD DEPARTURE CHART -INSTRUMENT

RJNO / OKI

➡ RNAV SID

TSUNO ONE DEPARTURE

## RWY08

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	076 (067.8)	-7.9	—	—	+700	—	—	Basic RNP1
002	DF	DISEN	—	—	-7.9	—	R	+11000	—	—	Basic RNP1
003	TF	TSUNO	—	139 (130.7)	-7.9	40.7	—	—	—	—	Basic RNP1

## RWY26

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	256 (247.8)	-7.9	—	—	+800	—	—	Basic RNP1
002	DF	DISEN	—	—	-7.9	—	L	+11000	—	—	Basic RNP1
003	TF	TSUNO	—	139 (130.7)	-7.9	40.7	—	—	—	—	Basic RNP1




STANDARD ARRIVAL CHART-INSTRUMENT

RJNO / OKI

➡ RNAV STAR

SAIGO ARRIVAL	Basic RNP1
---------------	------------

Note GNSS required.



SAIGO ARRIVAL



From TSUNO, to DISEN at or above 11000FT, to SAIGO at or above 6000FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	TSUNO	—	—	-7.9	—	—	—	—	—	Basic RNP1
002	TF	DISEN	—	319 (311.1)	-7.9	40.7	—	+11000	—	—	Basic RNP1
003	TF	SAIGO	—	346 (337.8)	-7.9	14.1	—	+6000	—	—	Basic RNP1

## INSTRUMENT APPROACH CHART

RJNO / OKI

LOC Z RWY08



Missed APCH climb gradient MNM 4.0%

MINIMA		THR elev. 253	AD elev. 262
CAT			CIRCLING
	MDA(H)	CMV	MDA(H) VIS
A	550 (297)	1500	730 (468) 1600
B			
C		1600	830 (568) 2400
D		1800	960 (698) 3200


Circling to SOUTH side of RWY only.

MINIMA with Missed APCH climb gradient of 2.5% are not established.

## INSTRUMENT APPROACH CHART

RJNO / OKI


LOC Y RWY08



## INSTRUMENT APPROACH CHART


RJNO / OKI

VOR RWY26



**MISSED APPROACH**  
 Climb to 1800FT via OIE  
 R252, turn left, direct to OIE  
 VOR/DME and hold at 4000FT.  
 Contact OKI REMOTE.

Timing not authorized for defining MAPt.




MINIMA		THR elev. 272	AD elev. 262
CAT	CIRCLING		
	MDA(H)	CMV	VIS
A	920 (658)	1500	1600
B			2400
C		2000	3200
D			

Circling to SOUTH side of RWY only.

## INSTRUMENT APPROACH CHART

RJNO / OKI


RNAV(GNSS) RWY08



## INSTRUMENT APPROACH CHART

RJNO / OKI

RNAV(GNSS) RWY26



Visual REP




Call sign	BRG / DIST from ARP	Remarks
ポイント アルファ Point Alfa	212°/10.0NM	海上 Over the sea
ポイント ブラボー Point Bravo	193°/10.0NM	海上 Over the sea
ポイント チャーリー Point Charlie	157°/10.0NM	空港標点と倉吉市（ＪＲ倉吉駅）とを結ぶ直線上 On the straight line connecting ARP and Kurayoshi City. (JR Kurayoshi Station)



RJNO / OKI

LDG CHART



注： 隠岐空港の北側に廃止された滑走路が（なお、禁止標識が6カ所設置されている）視認できる状態であるので、隠岐空港に着陸する航空機は当該滑走路と誤認しないように注意すること。

NOTE: There is remained the abolished runway with 6 closed markings at north side of Oki Airport. As the abolished runway in sharp is visible, the aircraft which will land on Oki airport shall pay a special attention not to confuse the runway.



RJNO / OKI

➡ Minimum Vectoring Altitude CHART

