

## AD 2 AERODROMES

## RJTE AD 2.1 AERODROME LOCATION INDICATOR AND NAME

## RJTE - TATEYAMA

## RJTE AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

|   |  |                                       |
|---|--|---------------------------------------|
| 1 | ARP coordinates and site at AD   | 345915N 1394955E                      |
| 2 | Direction and distance from (city)   | 1.6nm WSW of Tateyama Railway Station |
| 3 | Elevation/ Reference temperature   | 10ft / -                              |
| 4 | Geoid undulation at AD ELEV PSN  | Nil                                   |
| 5 | MAG VAR/ Annual change   | Nil                                   |
| 6 | AD Administration, address, telephone, telefax, telex, AFS, e-mail and/or Web-site addresses | JSDF-M                                |
| 7 | Types of traffic permitted(IFR/ VFR)   | IFR/VFR                               |
| 8 | Remarks  | Nil                                   |

## RJTE AD 2.3 OPERATIONAL HOURS

|    |                           |     |
|----|---------------------------|-----|
| 1  | AD Administration         | H24 |
| 2  | Customs and immigration   | Nil |
| 3  | Health and sanitation     | Nil |
| 4  | AIS Briefing Office       | H24 |
| 5  | ATS Reporting Office(ARO) | Nil |
| 6  | MET Briefing Office       | H24 |
| 7  | ATS                       | H24 |
| 8  | Fuelling                  | Nil |
| 9  | Handling                  | Nil |
| 10 | Security                  | Nil |
| 11 | De-icing                  | Nil |
| 12 | Remarks                   | Nil |

**RJTE AD 2.4 HANDLING SERVICES AND FACILITIES**

|   |   |                    |
|---|---|--------------------|
| 1 | Cargo-handling facilities               | Nil                |
| 2 | Fuel/ oil types                         | 100/130 JP-5 80/87 |
| 3 | Fuelling facilities/ capacity           | To be issued later |
| 4 | De-icing facilities                     | Nil                |
| 5 | Hangar space for visiting aircraft      | Nil                |
| 6 | Repair facilities for visiting aircraft | Nil                |
| 7 | Remarks                                 | Nil                |

**RJTE AD 2.5 PASSENGER FACILITIES**

|   |                      |     |
|---|----------------------|-----|
| 1 | Hotels               | Nil |
| 2 | Restaurants          | Nil |
| 3 | Transportation       | Nil |
| 4 | Medical facilities   | Nil |
| 5 | Bank and Post Office | Nil |
| 6 | Tourist Office       | Nil |
| 7 | Remarks              | Nil |

**RJTE AD 2.6 RESCUE AND FIRE FIGHTING SERVICES**

|   |   |     |
|---|---|-----|
| 1 | AD category for fire fighting               | Nil |
| 2 | Rescue equipment                            | Nil |
| 3 | Capability for removal of disabled aircraft | Nil |
| 4 | Remarks                                     | Nil |

**RJTE AD 2.7 SEASONAL AVAILABILITY-CLEARING**

|   |                             |     |
|---|-----------------------------|-----|
| 1 | Types of clearing equipment | Nil |
| 2 | Clearance priorities        | Nil |
| 3 | Remarks                     | Nil |

**RJTE AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS DATA**

|   |                                     |                    |
|---|-------------------------------------|--------------------|
| 1 | Apron surface and strength          | To be issued later |
| 2 | Taxiway width, surface and strength | To be issued later |
| 3 | ACL and elevation                   | Not Available      |
| 4 | VOR checkpoints                     | Nil                |
| 5 | INS checkpoints                     | Nil                |
| 6 | Remarks                             | Nil                |

**RJTE AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS**

|   |  |   |
|---|--|---|
| 1 | Use of aircraft stand ID signs, TWY guide lines and Visual docking/ parking guidance system of aircraft stands | Nil   |
| 2 | RWY and TWY markings and LGT   | RWY:09/27<br>(LGT) RTHL,TKOF aiming LGT<br><br>TWY:<br>(LGT) TWY edge LGT |
| 3 | Stop bars  | Nil   |
| 4 | Remarks  | Nil   |

**RJTE AD 2.10 AERODROME OBSTACLES**

| RWY/Area affected | Obstacle type | Coordinates | Elevation | Markings/ LGT | Remarks |
|-------------------|---------------|-------------|-----------|---------------|---------|
| Nil               |               |             |           |               |         |

## RJTE AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

|    |  |            |
|----|--|------------|
| 1  | Associated MET Office  | TATEYAMA   |
| 2  | Hours of service<br>MET Office outside hours                           | H24        |
| 3  | Office responsible for TAF preparation<br>Periods of validity          | Nil        |
| 4  | Trend forecast<br>interval of issuance                                 | Nil        |
| 5  | Briefing/ consultation provided  | P, Ja      |
| 6  | Flight documentation<br>Language(s) used                               | Ja, En     |
| 7  | Charts and other information available<br>for briefing or consultation | S, U, P, N |
| 8  | Supplementary equipment<br>available for providing information         | Nil        |
| 9  | ATS units provided with information                                    | Nil        |
| 10 | Additional information(limitation of<br>service, etc.)                 | Nil        |

## RJTE AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

| Designations<br>RWY<br>NR | TRUE BRG              | Dimensions of<br>RWY(M) | Strength(PCN)and<br>surface of RWY        | THR coordinates<br>THR geoid undulation | THR elevation and<br>highest elevation of TDZ<br>of precision APP RWY |
|---------------------------|-----------------------|-------------------------|---|---|---|
| 1                         | 2                     | 3                       | 4   | 5                                       | 6   |
| 09                        | To be issued<br>Later | 300×45                  | SW 12500kg (27500lbs)<br>Concrete Asphalt | Nil                                     | Nil   |
| 27                        | To be issued<br>Later | 300×45                  | SW 12500kg (27500lbs)<br>Concrete Asphalt | Nil                                     | Nil   |
| Slope of RWY              |                       | Strip<br>Dimensions(M)  | Remarks                                   |   |   |
| 7                         |                       | 10                      | 12  |   |   |
| Nil                       |                       | 420×150<br>420×150      | Nil                                       |   |   |

## RJTE AD 2.13 DECLARED DISTANCES

|                | TORA | TODA | ASDA | LDA |         |
|----------------|------|------|------|-----|---------|
| RWY Designator | (m)  | (m)  | (m)  | (m) | Remarks |
| 1              | 2    | 3    | 4    | 5   | 6       |
|                |      |      |      |     |         |

## RJTE AD 2.14 APPROACH AND RUNWAY LIGHTING

| RWY<br>Designator | APCH<br>LGT<br>type<br>LEN<br>INTST | RTHL<br>Color<br>WBAR | PAPI<br>(VASIS)<br>Angle<br>DIST FM<br>THR<br>MEHT | RTZL<br>LEN | RCLL<br>LEN<br>Spacing<br>Color<br>INTST | REDL<br>LEN<br>Spacing<br>Color<br>INTST | RENL<br>Color<br>WBAR | STWL<br>LEN<br>Color |
|-------------------|-------------------------------------|-----------------------|--|-------------|--|--|-----------------------|----------------------|
| 1                 | 2                                   | 3                     | 4  | 5           | 6  | 7  | 8                     | 9                    |
| 09                |                                     |                       |  |             |  |  |                       |                      |
| 27                |                                     |                       |  |             |  |  |                       |                      |
| Remarks           |                                     |                       |  |             |  |  |                       |                      |
| 10                |                                     |                       |  |             |  |  |                       |                      |
| Nil               |                                     |                       |  |             |  |  |                       |                      |

## RJTE AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

|   |  |   |
|---|--|---|
| 1 | ABN/IBN location, characteristics and hours of operation | ABN: 345902N/1395025E, White/Green, EV10sec, HO |
| 2 | LDI location and LGT<br>Anemometer location and LGT      | LDI:LGTD  |
| 3 | TWY edge and center line lighting                        | TWY edge LGT:AVBL                               |
| 4 | Secondary power supply/ switch-over time                 | Nil   |
| 5 | Remarks  | WDI LGT,BDRY(HELIPORT)                          |

## RJTE AD 2.16 HELICOPTER LANDING AREA

|                    |
|--------------------|
| To be issued later |
|--------------------|

## RJTE AD 2.17 ATS AIRSPACE

| Designation and lateral limits |   | Vertical<br>limits<br>(ft) | Airspace<br>classification | ATS unit call<br>sign Language | Remarks |
|--------------------------------|---|----------------------------|----------------------------|--------------------------------|---------|
| 1                              |   | 2                          | 3                          | 4                              | 6       |
| TATEYAMA<br>CTR                | Area within a radius of 5nm of TATEYAMA<br>ARP(34°59'N139°50'E) | 2000 or below              | D                          | Tateyama<br>Tower<br>En        |         |

## RJTE AD 2.18 ATS COMMUNICATION FACILITIES

| Service designation | Call sign      | Frequency  | Hours of operation   | Remarks  |
|---------------------|----------------|--|--|--|
| 1                   | 2              | 3  | 4  | 5  |
| TWR                 | Tateyama Tower | 126.2MHz<br>233.8MHz(1)<br>228.2MHz<br>123.1MHz(2)<br>122.0MHz<br>243.0MHz(E)<br>121.5MHz(E)         | H24  | APP provided by Tokyo APP.<br>(1) Primary<br>(2) For Rescue only.  |
| GCA-ASR<br>-PAR     | Tateyama GCA   | 319.0MHz<br>317.2MHz<br>306.8MHz<br>141.25MHz<br>133.0MHz<br>139.55MHz<br>243.0MHz(E)<br>121.5MHz(E) | 2300 - 0800<br>EXC<br>FRI0801-SUN2259<br>and HOL.<br><br>Other time 1HR PN | PAR RWY 09<br>ASR RWY 09/27<br>Glide path 3.0°<br>Maintenance period : 2300-0800 FRI in VMC.<br>ASR for RWY 09 restricted to VFR training only.<br>IFF/SIF restricted to spot beyond 36NM S through SW for site. |

## RJTE AD 2.19 RADIO NAVIGATION AND LANDING AIDS

| Type of aid<br>(VOR declination) | ID  | Frequency           | Hours of operation | Position of transmitting antenna coordinates | Elevation of DME transmitting antenna | Remarks   |
|----------------------------------|-----|---------------------|--------------------|--|---------------------------------------|---|
| 1                                | 2   | 3                   | 4                  | 5  | 6                                     | 7   |
| DME                              | PQD | 1159MHz<br>(CH-72X) | H24                | 345646.42N<br>1395343.16E                    | 600ft                                 |   |
| TACAN                            | TET | 986MHz<br>(CH-25X)  | H24                | 345815N<br>1395017E                          | 517ft                                 | TACAN Unusable:<br>R010-030 beyond 38nm BLW 8000ft.<br>R110-120 beyond 28nm BLW 2000ft.<br>R120-130 beyond 24nm BLW 2000ft.<br>R130-140 beyond 35nm BLW 2000ft. |

---

### RJTE AD 2.20 LOCAL TRAFFIC REGULATIONS

1. Airport regulations

|     |
|-----|
| Nil |
|-----|

2. Taxiing to and from stands

|     |
|-----|
| Nil |
|-----|

3. Parking area for small aircraft(General aviation)

|     |
|-----|
| Nil |
|-----|

4. Parking area for helicopters

|     |
|-----|
| Nil |
|-----|

5. Apron - taxiing during winter conditions

|     |
|-----|
| Nil |
|-----|

6. Taxiing - limitations

|     |
|-----|
| Nil |
|-----|

7. School and training flights - technical test flights - use of runways

|     |
|-----|
| Nil |
|-----|

8. Helicopter traffic - limitation

|     |
|-----|
| Nil |
|-----|

9. Removal of disabled aircraft from runways

|     |
|-----|
| Nil |
|-----|

### RJTE AD 2.21 NOISE ABATEMENT PROCEDURES

|     |
|-----|
| Nil |
|-----|

## RJTE AD 2.22 FLIGHT PROCEDURES

## 1.TAKE OFF MINIMA

|                       | RWY | REDL AVBL       | REDL OUT   |
|-----------------------|-----|-----------------|------------|
|                       |     | CEIL-VIS        | CEIL-VIS   |
| TKOF ALTN<br>AP FILED | 09  | 600'-1600m      | 600'-1600m |
|                       | 27  | 600'-1600m      | 600'-1600m |
| OTHER                 | 09  | AVBL LDG MINIMA |            |
|                       | 27  |                 |            |

## 2.WX MINIMA CONCERNING PAR/ASR APCH PROCEDURE

PAR RWY 09

| MINIMA |          | THR elev. 8 |          | AD elev. 10 |  |
|--------|----------|-------------|----------|-------------|--|
| CAT    |          |             | CIRCLING |             |  |
|        | DA(H)    | CMV         | MDA(H)   | VIS         |  |
| A      | 210(202) | 1000        | 600(590) | 1600        |  |
| B      |          |             |          |             |  |
| C      | -        | -           | -        | -           |  |
| D      |          |             |          |             |  |

ASR RWY 09

| MINIMA |          | THR elev. 8 |          | AD elev. 10 |  |
|--------|----------|-------------|----------|-------------|--|
| CAT    |          |             | CIRCLING |             |  |
|        | MDA(H)   | CMV         | MDA(H)   | VIS         |  |
| A      | 600(590) | 1500        | 600(590) | 1600        |  |
| B      |          |             |          |             |  |
| C      | -        | -           | -        | -           |  |
| D      |          |             |          |             |  |

ASR RWY 27

| MINIMA |          | THR elev. 7 |          | AD elev. 10 |  |
|--------|----------|-------------|----------|-------------|--|
| CAT    |          |             | CIRCLING |             |  |
|        | MDA(H)   | CMV         | MDA(H)   | VIS         |  |
| A      | 600(590) | 1500        | 600(590) | 1600        |  |
| B      |          |             |          |             |  |
| C      | -        | -           | -        | -           |  |
| D      |          |             |          |             |  |



**3. Lost communication procedures for arrival aircraft under radar navigational guidance**

If radio communications with Tateyama GCA are lost for 1 minute in the pattern, or 5 seconds (PAR)/15 seconds (ASR) on final approach, squawk Mode A/3 Code 7600 and ;

- (I)
  - 1. Contact Tateyama Tower.
  - 2. If unable, proceed in accordance with Visual Flight Rules.
  - 3. If unable, proceed to TACAN A IAF at last assigned altitude or 2,500 feet whichever is higher and execute TACAN A approach.
- (II) Procedures other than above will be issued when situation required.

**RJTE AD 2.23 ADDITIONAL INFORMATION**

OBST : 689ft lighted & marked antenna (DECCA lo station) located 121° / AI 3.5nm FM ARP

**RJTE AD 2.24 CHARTS RELATED TO AN AERODROME**

Figure-07 Standard Departure Chart-Instrument (TATEYAMA REVERSAL, TATEYAMA WEST)  
Figure-10 Instrument Approach Chart (TACAN A)

**INTENTIONALLY LEFT BLANK**

STANDARD DEPARTURE CHART-INSTRUMENT

RJTE/TATEYAMA

SID and WX MNM

TATEYAMA REVERSAL TWO DEPARTURE

RWY 09 : Turn left,...

RWY 27 : Turn right,...

...Climb via TET R310 to 1500FT or above, turn left within TET 5DME to TET TACAN, then proceed as specified by ATC.

Cross TET TACAN at assigned altitude.

TATEYAMA WEST TWO DEPARTURE

RWY 09 : Turn left,...

RWY 27 : Turn right,...

...Climb via TET R290 to 1500FT or above, turn left within TET 5DME, then proceed as specified by ATC.

## INSTRUMENT APPROACH CHART

RJTE / TATEYAMA

TACAN A

