RORK / KITADAITO AD CHART



STANDARD DEPARTURE CHART -INSTRUMENT

RORK / KITADAITO SID

SOUTH SIX DEPARTURE

RWY03 : Climb RWY HDG to 500FT, turn right, direct to MDE VOR/DME.
RWY21 : Climb to MDE VOR/DME.
Cross MDE VOR/DME at or above 2400FT.



STANDARD DEPARTURE CHART -INSTRUMENT

RORK / KITADAITO RNAV SID

CORCO NORTH ONE DEPARTURE	Basic RNP1

Note GNSS required.



CORCO NORTH ONE DEPARTURE

RWY03 : Climb on HDG030˚ at or above 500FT, turn left direct to CORCO at or above 5000FT.
RWY21 : Climb on HDG210˚ at or above 500FT, turn right direct to CORCO at or above 5000FT.

NOTE RWY03 : 4.0% climb gradient required up to 500FT due to airspace restrictions only.

RWY03

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	030 (025.4)	-4.9	–	–	+500	–	–	Basic RNP1
002	DF	CORCO	–	–	-4.9	–	L	+5000	–	–	Basic RNP1

RWY21

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	210 (205.4)	-4.9	–	–	+500	–	–	Basic RNP1
002	DF	CORCO	–	–	-4.9	–	R	+5000	–	–	Basic RNP1

INSTRUMENT APPROACH CHART

RORK / KITADAITO — VOR Z RWY03

KOBE CONTROL	MINAMIDAITO VOR/DME	DAITO REMOTE	NO RADAR
124.5 - 279.5	117.8 MDE CH-125X *25°51′16″N/131°15′50″E*	118.55	



NM from MDE	FAF	1	2	3	4	MAPt
ALT (3.0° APCH Path)	2030	1711	1393	1075	756	–



*Not applicable for circling

MISSED APPROACH

Climb to 500FT via MDE R038,
turn right, direct to MDE VOR/DME
and hold at 2000FT.
Contact DAITO REMOTE.

Timing not authorized for defining the MAPt.

0	2.0	4.8	5.2	6.0	DME from MDE
6.0	4.0	1.2	0.8	0	NM to THR

MINIMA	THR elev. 74		AD elev. 71	
CAT			CIRCLING	
	MDA(H)	CMV	MDA(H)	VIS
A B	480 (409)	1500	560 (489)	1600
C	490 (419)	1800	630 (559)	2400
D	–	–	–	–

CHANGE : COM

INSTRUMENT APPROACH CHART

RORK / KITADAITO — VOR Y RWY03

KOBE CONTROL	MINAMIDAITO VOR/DME	DAITO REMOTE	NO RADAR
124.5 - 279.5	117.8 MDE CH-125X *25°51′16″N/131°15′50″E*	118.55	



NM from MDE	FAF	1	2	3	4	MAPt
ALT (3.0° APCH Path)	2030	1711	1393	1075	756	–



MISSED APPROACH

Climb to 500FT via MDE R038,
turn right, direct to MDE VOR/DME
and hold at 2000FT.
Contact DAITO REMOTE

Timing not authorized for defining the MAPt.

7.0	0	2.0	4.8	5.2	6.0	DME to/from MDE
13.0	6.0	4.0	1.2	0.8	0	NM to THR

MINIMA — THR elev. 74 — AD elev. 71

CAT			CIRCLING	
	MDA(H)	CMV	MDA(H)	VIS
A B	480 (409)	1500	560 (489)	1600
C	490 (419)	1800	630 (559)	2400
D	–	–	–	–

CHANGE : COM

INSTRUMENT APPROACH CHART

RORK / KITADAITO — RNAV(GNSS) RWY03

KOBE CONTROL	1. DME/DME RNP0.3 not authorized. 2. RNP0.3 required. 3. GNSS required.	DAITO REMOTE	NO RADAR
124.5 - 279.5		118.55	



NM to Next Fix	FAF	3	2	1	MAPt
ALT (3.0˚ APCH Path)	1100	1079	760	442	–

MISSED APPROACH

Turn left direct to MDE and hold at 2000FT.
Contact DAITO REMOTE.

(For using VOR/DME)
Turn left, direct to MDE VOR/DME and hold at 2000FT.
Contact DAITO REMOTE.



MINIMA — THR elev. 74 — AD elev. 71

CAT	LNAV/VNAV		LNAV		CIRCLING	
	DA(H)	CMV	MDA(H)	CMV	MDA (H)	VIS
A	440 (366)	1500	440 (369)	1500	560 (489)	1600
B						
C		1800		1800	630 (559)	2400
D	–	–	–	–	–	–

CHANGE : COM

RORK / KITA-DAITO

Visual REP



Call sign	BRG / DIST from ARP	Remarks
10NM N	000°/10NM	海上 Over the sea
10NM W	270°/10NM	海上 Over the sea
南 大 東 島 Minamidaitojima	215°/6.7NM	南大東空港 Minamidaito Airport

RORK / KITADAITO Minimum Vectoring Altitude CHART