

STANDARD DEPARTURE CHART-INSTRUMENT

RJOZ / OZUKI

SID

OZUKI REVERSAL THREE DEPARTURE

RWY 17: ...

RWY 35: Turn left ...

... Climb via OCT R170, turn left to OCT TACAN within 10DME.

Cross OCT TACAN at or above 4000FT.

Then proceed via OCT R330, turn right to OCT TACAN within 5DME.

Cross OCT TACAN at or above 5000FT or specified altitude.

Note RWY 35: Maintain visual contact until passing 1700FT.

KUGA TRANSITION

From over OCT TACAN, via OCT R170 to intercept and proceed via IWT R266 to IWT TACAN.

FUKUOKA TRANSITION

From over OCT TACAN, via OCT R170 to intercept and proceed via DGC R080 (MRA 11000FT) to DGC VORTAC.

Note: This TRANSITION is for TACAN equipped aircraft only.

CHANGE : Update.

STANDARD DEPARTURE CHART-INSTRUMENT


RJOZ / OZUKI

SID




RJOZ / OZUKI

TACAN A



At 0.5DME prior to OCT TACAN,
turn right climb via OCT R-120 to
2,000ft, turn right and proceed via
OCT 10DME ARC to MAZYA
then proceed via OCT R-157
to 7DME and hold.
Contact TSUIKI APP.




MINIMA		AD elev. 13
CAT	CIRCLING	
	MDA(H)	VIS
A	900 (887)	1600
B		
C	—	—
D		

INSTRUMENT APPROACH CHART

RJOZ / OZUKI


TACAN B



MISSED APPROACH

At 0.5 DME prior to OCT TACAN, turn right climb via OCT R-120 to 2,000ft, turn right and proceed via OCT 10DME ARC to MAZYA then proceed via OCT R-157 to 7DME and hold.

Contact TSUIKI APP.



MINIMA

AD elev. 13

CAT	CIRCLING	
	MDA(H)	VIS
A	900 (887)	1600
B		
C	—	—
D		

RJOZ / OZUKI

LDG CHART



AERODROME LIGHTING

Aerodrome beacon : Alternating flashing
white / green

Runway edge lights : white

Threshold lighting : green

Other lighting : Blue taxiway edge lights,
lighted wind direction in-
dicator, obstruction light,
take-off target light,
angle of approach lights.

RADIO DATA

TWR 122.0, 228.2, 126.2, 236.8, 302.2, EU-EV

FACILITIES AVAILABLE

Weather, fuel (JETA-1 PLUS), Hangar

CHANGE : NDB OZUKI abolished, Fuel Type