

STANDARD DEPARTURE CHART-INSTRUMENT

RJOW / IWAMI

SID and TRANSITION

SAMBA TWO DEPARTURE

RWY11 : Climb RWY HDG to 800FT, turn left HDG351°, ...  
RWY29 : Climb RWY HDG to 700FT, turn right HDG081°, ...  
...to intercept and proceed via IME R036 to SAMBA.  
Cross SAMBA at or above 7000FT.

Note RWY11 : 5.7% climb gradient required up to 1700FT.  
OBST ALT 1177FT located at 4.83NM 093° FM end of RWY11.

IZUMO TRANSITION

From over SAMBA, via XZE R252 to XZE VOR/DME.  
Cross CARNY at or below 13000FT, cross BAARU at or below FL230.



## STANDARD DEPARTURE CHART-INSTRUMENT

RJOW / IWAMI

➔ RNAV TRANSITION

## VIBEL TRANSITION

## RNAV1

Note 1) DME/DME/IRU or GNSS required.

2) RADAR service required.

VAR 8°W (2017)

VIBEL TRANSITION

From SAMBA at or above 7000FT, to OSPEL at or below 13000FT, to VIBEL at or below FL230.

Critical DME	STD : SAMBA – VIBEL
DME GAP	–
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1.


Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	SAMBA	–	–	-7.8	–	–	+7000	–	–	RNAV1
002	TF	OSPEL	–	077 (069.7)	-7.8	10.5	–	-13000	–	–	RNAV1
003	TF	VIBEL	–	078 (069.8)	-7.8	10.2	–	-FL230	–	–	RNAV1

CHANGE : New PROC

## INSTRUMENT APPROACH CHART

RJOW / IWAMI


ILS or LOC RWY11



## INSTRUMENT APPROACH CHART

RJOW / IWAMI

VOR RWY11




CHANGE: ATC call sign.

INSTRUMENT APPROACH CHART

RJOW / IWAMI


VOR A



MISSED APPROACH

Turn right, climb to 4000FT via IME  
R036 to BLUES and hold.  
Contact IWAMI REMOTE.

Timing not authorized for defining the MAPt.



MINIMA		AD elev. 177	
CAT	CIRCLING		
	MDA(H)	VIS	
A	1000 (823)	1600	
B	1100 (923)		
C	1400 (1223)	2400	
D	1600 (1423)	3200	

Circling to NORTH side of RWY only

CHANGE: ATC call sign.

## INSTRUMENT APPROACH CHART

RJOW / IWAMI

RNAV(RNP) RWY11

KOBE CONTROL  
132.5 - 246.1  
134.25 - 315.5

GNSS and RF required.




IWAMI REMOTE  
122.2

NO RADAR

For uncompensated Baro-VNAV systems, procedure not authorized below -5 °C / above 45°C

VAR 8°W (2017)

MSA RW11 25NM



**MISSED APPROACH**  
From RW11 on track 113°, at or above 600FT turn left, direct to BLUE and hold at 4000FT.

Contact IWAMI REMOTE.

CHANGE: ATC call sign.

Missed APCH climb gradient MNM 5.0%		
MINIMA THR elev. 184 AD elev. 177		
CAT	RNP 0.30	
	DA(H)	RVR/CMV
A	-	-
B	-	-
C	484(300)	1000
D	-	-

MINIMA with Missed APCH climb gradient of 2.5% are not established.

# RNP AR

Special Authorization Required

## INSTRUMENT APPROACH CHART

RJOW / IWAMI

➔ RNAV(RNP) RWY11

RNAV(RNP) RWY11Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/RDH (°/FT)	RNP Value
001	IF	BLUES	—	—	-7.8	—	—	+4000	—	—	1.0
002	TF	OW150	—	237 (229.3)	-7.8	9.8	—	2600	—	—	1.0
003	TF	OW151	—	237 (229.2)	-7.8	1.4	—	2139	-165	-3.00	0.3
004	RF Center: OWRF1 r=2.03NM	OW152	—	—	-7.8	4.4	L	736	—	-3.00	0.3
005	TF	RW11	Y	113 (104.8)	-7.8	1.6	—	238	—	-3.00/54	0.3
006	FA	—	—	113 (104.8)	-7.8	—	—	+600	—	—	1.0
007	DF	BLUES	—	—	-7.8	—	L	4000	—	—	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
BLUES	345159.02N/1315423.09E	OWRF1	344304.90N/1314534.53E
OW150	344533.91N/1314518.52E		
OW151	344437.18N/1314358.51E		
OW152	344107.26N/1314456.99E		
RW11	344043.28N/1314647.11E		

CHANGE : New PROC



## RJOW / IWAMI

KOBE CONTROL  
132.5 - 246.1  
134.25 - 315.5

IWAMI REMOTE


122.2

NO RADAR

For uncompensated Baro-VNAV systems, procedure not authorized below -5 °C / above 39°C

VAR 8°W (2017)

MSA RW29 25NM



NOT TO SCALE

MHA 4000  
MAX 230KIAS

D18.0  
IME

BLUES  
(MAHF)  
D13.0 IME

— VOR/DME —  
IWAMI  
115.05 IME  
CH-97Y —  
0°34'N/131°46'48"E



10NM

BLUES  
(IF/MAHF)  
D13.0 IME

OW950  
(FAF)

OW951  
MAX 150KIAS

OW952


OW950(FAF) : 344606.97/1315256.13E

### MISSED APPROACH

From RW29 on track 293°, at or above 600FT turn right, direct to BLUES and hold at 4000FT.

Contact IWAMI REMOTE.

PAPI not coincident with VPA.



Missed APCH climb gradient MNM 4.0%

MINIMA	THR elev. 171	AD elev. 177
--------	---------------	--------------

CAT	RNP 0.16		RNP 0.30	
	DA(H)	CMV	DA(H)	CMV
A	—	—	—	—
B	—	—	—	—
C	471(300)	1400	489(318)	1400
D	—	—	—	—

MINIMA with Missed APCH climb gradient of 2.5% are not established.

**RNP AR**  
Special Authorization Required

CHANGE: ATC call sign.

## INSTRUMENT APPROACH CHART

RJOW / IWAMI

➡ RNAV(RNP) RWY29

RNAV(RNP) RWY29Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/RDH (°/FT)	RNP Value
001	IF	BLUES	—	—	-7.8	—	—	+4000	—	—	1.0
002	TF	OW950	—	199 (191.5)	-7.8	6.0	—	3100	—	—	1.0
003	TF	OW951	—	199 (191.5)	-7.8	5.3	—	1374	-150	-3.10	0.16 0.3
004	RF Center: OWRF2 r=1.20NM	OW952	—	—	-7.8	2.0	R	731	—	-3.10	0.16 0.3
005	TF	RW29	Y	293 (284.9)	-7.8	1.5	—	221	—	-3.10/50	0.16 0.3
006	FA	—	—	293 (284.9)	-7.8	—	—	+600	—	—	1.0
007	DF	BLUES	—	—	-7.8	—	R	4000	—	—	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
BLUES	345159.02N/1315423.09E	OWRF2	344112.62N/1315014.52E
OW950	344606.97N/1315256.13E		
OW951	344058.27N/1315140.08E		
OW952	344002.90N/1314952.21E		
RW29	344026.72N/1314803.07E		

CHANGE : New PROC

RJOW / IWAMI

Visual REP



CHANGE : Map updated. BRG/DIST from ARP. Remarks.

※図中に標高を示す数字がある場合、単位はメートル(m)である。The unit of measurement used to express elevation is meter(m).

Call sign	BRG / DIST from ARP	Remarks
魚待 Uomachi	038°T / 6.0NM	岬 Cape
高山 Takayama	266°T / 8.8NM	岬 Cape
日原 Nichihara	166°T / 8.9NM	駅 Station



RJOW / IWAMI

Minimum Vectoring Altitude CHART



CENTER : 344035N/1314725E (ARP)