RJFS / SAGA

AD CHART



CHANGE : Spot NR renamed(11→10, 12→11, 13→12).

INTENTIONALLY LEFT BLANK

STANDARD DEPARTURE CHART - INSTRUMENT

RJFS / SAGA SID

SAGA REVERSAL TWO DEPARTURE

RWY11 : Climb RWY HDG to 500FT, turn right,...
RWY29 : Climb RWY HDG to 500FT,turn left HDG 090˚ to intercept and proceed...
...via SGE R135 to 9.0DME, turn left, direct to SGE VOR/DME.
Cross SGE VOR/DME at 6000FT.

Note RWY29 : 3.5% climb gradient required up to 500FT.

ARIAKE REVERSAL TWO DEPARTURE

RWY11 : Climb RWY HDG to 500FT, turn right HDG 288˚...
RWY29 : Climb RWY HDG to 500FT, turn left HDG 198˚...
...to intercept and proceed via SGE R243 to 7.0DME, turn right, direct to SGE VOR/DME.
Cross SGE VOR/DME at or above 6000FT.

Note RWY29 : 3.5% climb gradient required up to 500FT.



STANDARD DEPARTURE CHART - INSTRUMENT

RJFS / SAGA TRANSITION

KUMAMOTO TRANSITION

From over SGE VOR/DME, via SGE R195 to 18.0DME, turn left, via KUE R271 to KUE VOR/DME.

Cross SGE R195/6.0DME at 6000FT, cross SGE R195/18.0DME at or above 10000FT.

NAGASAKI TRANSITION

From over SGE VOR/DME, via SGE R195 to 18.0DME, turn right, direct to OLE VOR/DME.

Cross SGE R195/6.0DME at 6000FT, cross SGE R195/18.0DME at or above 10000FT.



STANDARD DEPARTURE CHART - INSTRUMENT

RJFS / SAGA SID

KIKYU FIVE DEPARTURE

RWY11 : Climb RWY HDG to 500FT, turn right,...
RWY29 : Climb RWY HDG to 500FT, turn left HDG075˚ to intercept and proceed...
... via SGE R120 to 9.0DME, turn left HDG048˚ to intercept
and proceed via SGE R093 to KIKYU.
Cross KIKYU at or above 13000FT.

Note RWY29 : 3.5% climb gradient required up to 500FT.



KIKYU FIVE DEPARTURE

STANDARD DEPARTURE CHART - INSTRUMENT

RJFS / SAGA TRANSITION

MUSASHI TRANSITION

From over KIKYU, via TFE R253 to TFE VOR/DME.

Cross TFE R253/38.0DME at or above FL140, cross TFE R253/31.0DME at or above FL170.



STANDARD DEPARTURE CHART - INSTRUMENT

RJFS / SAGA RNAV TRANSITION

OOITA TRANSITION		RNAV1
NOTE 1) DME/DME/IRU or GNSS required. 2) RADAR service required.	Critical DME	–
	DME GAP	–
	Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

VAR 7° W(2016)



OOITA TRANSITION

From KIKYU at or above 13000FT, to WAITA at or above FL170, to OOITA.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	KIKYU	–	–	-7.2	–	–	+13000	–	–	RNAV1
002	TF	WAITA	–	094 (086.3)	-7.2	8.1	–	+FL170	–	–	RNAV1
003	TF	OOITA	–	094 (086.4)	-7.2	30.9	–	–	–	–	RNAV1

INTENTIONALLY LEFT BLANK

STANDARD DEPARTURE CHART - INSTRUMENT

RJFS / SAGA RNAV SID

BALLOON ONE DEPARTURE	Basic RNP1
Note GNSS required.	

VAR 7˚ W(2016)



BALLOON ONE DEPARTURE

BALLOON ONE DEPARTURE

RWY11 : Climb on HDG106˚ at or above 500FT, turn right to FS100 on track 120˚, to KIKYU at or above 13000FT.

RWY29 : Climb on HDG286˚ at or above 500FT, turn left direct to FS900, to FS100, to KIKYU at or above 13000FT.

NOTE RWY29 : 3.5% climb gradient required up to 500FT.

STANDARD DEPARTURE CHART - INSTRUMENT

RJFS / SAGA RNAV SID

BALLOON ONE DEPARTURE

RWY11

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	106 (099.3)	-7.2	–	–	+500	–	–	Basic RNP1
002	CF	FS100	–	120 (113.2)	-7.2	–	–	–	–	–	Basic RNP1
003	TF	KIKYU	–	084 (076.8)	-7.2	24.3	–	+13000	–	–	Basic RNP1

RWY29

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	286 (279.3)	-7.2	–	–	+500	–	–	Basic RNP1
002	DF	FS900	–	–	-7.2	–	L	–	–	–	Basic RNP1
003	TF	FS100	–	089 (081.8)	-7.2	8.4	–	–	–	–	Basic RNP1
004	TF	KIKYU	–	084 (076.8)	-7.2	24.3	–	+13000	–	–	Basic RNP1

STANDARD DEPARTURE CHART - INSTRUMENT

RJFS / SAGA RNAV SID

SOIGI ONE DEPARTURE	Basic RNP1
Note GNSS required.	



SOIGI ONE DEPARTURE

RWY11 : Climb on HDG106° at or above 500FT, turn right direct to FS110, to FS111 at or above 6000FT, to FS112, to KUE.

RWY29 : Climb on HDG286° at or above 500FT, turn left direct to FS110, to FS111 at or above 6000FT, to FS112, to KUE.

NOTE RWY29 : 3.5% climb gradient required up to 500FT.

STANDARD DEPARTURE CHART - INSTRUMENT

RJFS / SAGA RNAV SID

SOIGI ONE DEPARTURE

RWY11

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	106 (099.3)	-7.2	–	–	+500	–	–	Basic RNP1
002	DF	FS110	–	–	-7.2	–	R	–	–	–	Basic RNP1
003	TF	FS111	–	153 (145.5)	-7.2	6.6	–	+6000	–	–	Basic RNP1
004	TF	FS112	–	153 (145.6)	-7.2	6.8	–	–	–	–	Basic RNP1
005	TF	KUE	–	091 (083.4)	-7.2	19.2	–	–	–	–	Basic RNP1

RWY29

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	286 (279.3)	-7.2	–	–	+500	–	–	Basic RNP1
002	DF	FS110	–	–	-7.2	–	L	–	–	–	Basic RNP1
003	TF	FS111	–	153 (145.5)	-7.2	6.6	–	+6000	–	–	Basic RNP1
004	TF	FS112	–	153 (145.6)	-7.2	6.8	–	–	–	–	Basic RNP1
005	TF	KUE	–	091 (083.4)	-7.2	19.2	–	–	–	–	Basic RNP1

STANDARD ARRIVAL CHART-INSTRUMENT

RJFS / SAGA STAR

CHANGE: New PROC

IRPIN NORTH ARRIVAL

From over IRPIN, via OLE R102 to MILEP, via SGE R194 to SGE VOR/DME via UGAMU.
Cross MILEP at 6000FT, cross SGE VOR/DME at or above 5000FT.

IRPIN SOUTH ARRIVAL

From over IRPIN, via OLE R102 to MILEP.
Cross MILEP at 6000FT.



INTENTIONALLY LEFT BLANK

INSTRUMENT APPROACH CHART

RJFS / SAGA — ILS or LOC RWY29

FUKUOKA RADAR	ILS - LOC	SAGA RADIO	NO RADAR
119.7 – 279.2	110.15 ISG ILS-GP 334.25 ILS-DME CH-38Y	118.025 – 126.2 (2130–2300(UTC) 1030–1500 SAGA REMOTE 118.025)	



NM to ISG	MAPt	1	2	3	4	5	FAF
ALT (3.0˚ APCH Path)	–	319	638	956	1275	1593	1769

SASSY(FAF) : *330801.58N/1302505.75E*

MISSED APPROACH

Climb to 500FT on HDG286˚,
turn left HDG090˚ to intercept and
proceed via SGE R135 to 9.0DME,
turn left, direct to SGE VOR/DME
and hold at 5000FT.
Contact FUKUOKA RADAR.

Timing not authorized for defining the MAPt.



DME to ISG		0.2	0.6	1.0	4.0	5.5	8.0
NM to THR		0	0.5	0.8	3.8	5.4	7.8

Missed APCH climb gradient MNM 3.0%

MINIMA THR elev. 6 AD elev. 6

CAT	CAT I		LOC		CIRCLING	
	DA(H)	RVR/CMV	MDA(H)	RVR/CMV	MDA(H)	VIS
A	206 (200)	550	300 (294)	800	360 (354)	1600
B					460 (454)	
C						2400
D				1200	560 (554)	3200

MINIMA with Missed APCH climb gradient of 2.5% are not established.
Circling to SOUTH side of RWY only.

CHANGE : ATC callsign changed (FUKUOKA DEP→FUKUOKA RADAR). ATC FREQ changed.

INSTRUMENT APPROACH CHART

RJFS / SAGA — VOR RWY29

FUKUOKA RADAR	SAGA VOR/DME	SAGA RADIO	NO RADAR
119.7 – 279.2	114.75 SGE CH-94Y 33°08′55″N/130°17′34″E	118.025 – 126.2	2130–2300(UTC) 1030–1500 SAGA REMOTE 118.025



NM to SGE	MAPt	2	3	4	5	FAF
ALT (3.0° APCH Path)	–	374	693	1011	1330	1648

MOSSA(FAF) : *330825.59N/1302441.67E*

MISSED APPROACH

Climb to 500FT via SGE R282,
turn left HDG090° to intercept and
proceed via SGE R135 to 9.0DME,
turn left, direct to SGE VOR/DME
and hold at 5000FT.
Contact FUKUOKA RADAR.

Timing not authorized for defining the MAPt.



DME to SGE		1.0	1.9	4.0	6.0	9.0
NM to THR		0	0.9	3.0	5.0	8.0

MINIMA THR elev. 6 AD elev. 6

CAT			CIRCLING	
	MDA(H)	RVR/ CMV	MDA(H)	VIS
A	320 (314)	900	360 (354)	1600
B		1000	460 (454)	
C				2400
D		1400	560 (554)	3200

Circling to SOUTH side of RWY only.

CHANGE : ATC callsign changed (FUKUOKA DEP→FUKUOKA RADAR). ATC FREQ changed.

INSTRUMENT APPROACH CHART

RJFS / SAGA — VOR RWY11

FUKUOKA RADAR	SAGA VOR/DME	SAGA RADIO	NO RADAR
119.7 – 279.2	114.75 SGE CH-94Y 33°08′55″N/130°17′34″E	118.025 – 126.2 (2130–2300(UTC) 1030–1500) SAGA REMOTE 118.025	



NM to SGE	FAF	4	3	2	1	MAPt
ALT (3.0° APCH Path)	1617	1299	980	662	343	–

MITCH(FAF) : *331003.89N/1301146.58E*



MISSED APPROACH

Climb to 500FT via SGE R110, turn right HDG288° to intercept and proceed via SGE R243 to 7.0DME, turn right, direct to SGE VOR/DME and hold at 5000FT.
Contact FUKUOKA RADAR.

Timing not authorized for defining the MAPt.

8.0	5.0		0.1	DME to SGE
7.9	4.9		0	NM to THR

MINIMA THR elev. 6 AD elev. 6

CAT			CIRCLING	
	MDA(H)	CMV	MDA(H)	VIS
A	300 (294)	1000	360 (354)	1600
B		1100	460 (454)	
C		1200		2400
D		1400	560 (554)	3200

Circling to SOUTH side of RWY only.

CHANGE : ATC callsign changed (FUKUOKA DEP→FUKUOKA RADAR). ATC FREQ changed.

INSTRUMENT APPROACH CHART

RJFS / SAGA

RNAV(RNP) RWY29

FUKUOKA RADAR	GNSS and RF required.	SAGA RADIO	(2130–2300(UTC) 1030–1500 SAGA REMOTE 118.025)	NO RADAR
119.7 – 279.2		118.025 – 126.2		

For uncompensated Baro-VNAV systems, procedure not authorized below -10℃ / above 45℃



MISSED APPROACH

From RW29 on track287° at or above 500FT, turn left direct to FS955, direct to SGE and hold at 5000FT.

Contact FUKUOKA RADAR.



MINIMA	THR elev.6	AD elev.6
CAT	RNP 0.30	
	DA(H)	RVR/CMV
A	–	–
B		
C	306 (300)	1000
D		1400

RNP AR

Special Authorization Required

CHANGE : ATC callsign changed (FUKUOKA DEP→FUKUOKA RADAR). ATC FREQ changed.

INSTRUMENT APPROACH CHART

RJFS / SAGA RNAV(RNP) RWY29

RNAV(RNP) RWY29

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	MILEP	-	-	-7.5	-	-	6000	-	-	-
002	TF	NIVAL	-	017 (009.2)	-7.5	4.7	-	5000	-	-	0.3
003	TF	LEENO	-	017 (009.2)	-7.5	5.0	-	-	-	-	0.3
004	TF	EAZAR	-	062 (054.2)	-7.5	4.7	-	1998	-165	-	0.3
005	RF Center: FSRF8 r=2.02NM	FS956	-	-	-7.5	1.6	L	1493	-	-3.00	0.3
006	RF Center: FSRF9 r=1.98NM	FS957	-	-	-7.5	1.6	L	990	-	-3.00	0.3
007	RF Center: FSRF0 r=1.75NM	FS958	-	-	-7.5	1.4	L	551	-	-3.00	0.3
008	TF	RW29	Y	287 (279.3)	-7.5	1.5	-	60	-	-3.00/54	0.3
009	FA	-	-	287 (279.3)	-7.5	-	-	+500	-	-	1.0
010	DF	FS955	Y	-	-7.5	-	L	-	-	-	1.0
011	DF	SGE	-	-	-7.5	-	L	5000	-	-	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
MILEP	*325250.49N/1301501.22E*	FSRF8	*330645.72N/1301958.78E*
NIVAL	*325726.55N/1301554.33E*	FSRF9	*330646.63N/1302001.15E*
LEENO	*330223.31N/1301651.53E*	FSRF0	*330654.73N/1302014.52E*
EAZAR	*330507.25N/1302122.72E*		
FS956	*330626.19N/1302220.91E*		
FS957	*330756.35N/1302156.32E*		
FS958	*330838.87N/1302034.72E*		
RW29	*330853.77N/1301846.08E*		
FS955	*330424.77N/1301815.75E*		
SGE	*330855.03N/1301734.43E*		

CHANGE: Update

INSTRUMENT APPROACH CHART

RJFS / SAGA — RNAV(RNP) RWY11

FUKUOKA RADAR	GNSS and RF required.	SAGA RADIO	(2130–2300(UTC) 1030–1500 SAGA REMOTE)	NO RADAR
119.7 – 279.2		118.025 – 126.2	118.025	

For uncompensated Baro-VNAV systems, procedure not authorized below -10°C / above 45°C





Missed APCH climb gradient MNM 3.0%

MINIMA	THR elev.6	AD elev.6
CAT	RNP 0.30	
	DA(H)	CMV
A	–	–
B		
C	306 (300)	1400
D		1600

MINIMA with Missed APCH climb gradient of 2.5% are not established.

RNP AR

Special Authorization Required

CHANGE : ATC callsign changed (FUKUOKA DEP→FUKUOKA RADAR). ATC FREQ changed.

INSTRUMENT APPROACH CHART

RJFS / SAGA RNAV(RNP) RWY11

RNAV(RNP) RWY11

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	MILEP	-	-	-7.5	-	-	6000	-	-	-
002	TF	NIVAL	-	017 (009.2)	-7.5	4.7	-	5000	-	-	0.3
003	TF	LEENO	-	017 (009.2)	-7.5	5.0	-	-	-	-	0.3
004	TF	WEKKA	-	332 (324.3)	-7.5	4.7	-	1990	-165	-	0.3
005	RF Center: FSRF5 r=2.02NM	FS154	-	-	-7.5	1.6	R	1486	-	-3.00	0.3
006	RF Center: FSRF6 r=1.98NM	FS155	-	-	-7.5	1.6	R	989	-	-3.00	0.3
007	RF Center: FSRF7 r=1.77NM	FS156	-	-	-7.5	1.4	R	550	-	-3.00	0.3
008	TF	RW11	Y	107 (099.3)	-7.5	1.6	-	56	-	-3.00/50	0.3
009	FA	-	-	107 (099.3)	-7.5	-	-	+500	-	-	1.0
010	DF	FS153	Y	-	-7.5	-	R	-	-	-	1.0
011	DF	SGE	-	-	-7.5	-	R	5000	-	-	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates
MILEP	*325250.49N/1301501.22E*
NIVAL	*325726.55N/1301554.33E*
LEENO	*330223.31N/1301651.53E*
WEKKA	*330612.58N/1301335.04E*
FS154	*330742.91N/1301309.63E*
FS155	*330900.65N/1301406.71E*
FS156	*330919.21N/1301540.15E*
RW11	*330904.20N/1301729.91E*
FS153	*330340.13N/1301934.46E*
SGE	*330855.03N/1301734.43E*

RF Arc Center Identifier	Coordinates
FSRF5	*330723.51N/1301531.82E*
FSRF6	*330723.80N/1301529.68E*
FSRF7	*330735.05N/1301520.05E*

CHANGE: Update

INSTRUMENT APPROACH CHART

RJFS/SAGA VOR A

FUKUOKA RADAR	SAGA VOR/DME 114.75 SGE CH-94Y	SAGA RADIO	2130–2300(UTC) 1030–1500	NO RADAR
119.7 – 279.2	33°08′55″N/130°17′34″E	118.025 – 126.2	SAGA REMOTE 118.025	





MISSED APPROACH

At 1.2DME prior to SGE VOR/DME,
turn left and climb via SGE R194,
turn left direct to SGE VOR/DME within
SGE 9.0DME and hold at 5000FT.
Contact FUKUOKA RADAR.

MINIMA AD elev. 6

CAT	CIRCLING	
	MDA(H)	VIS
A	360(354)	1600
B	460(454)	
C		2400
D	560(554)	3200

Circling to SOUTH side of RWY only.

CHANGE : ATC callsign changed (FUKUOKA DEP→FUKUOKA RADAR). ATC FREQ changed.

INSTRUMENT APPROACH CHART

RJFS/SAGA VOR B

FUKUOKA RADAR	SAGA VOR/DME 114.75 SGE CH-94Y	SAGA RADIO	(2130–2300(UTC) 1030–1500 SAGA REMOTE 118.025)	NO RADAR
119.7 – 279.2	33°08′55″N/130°17′34″E	118.025 – 126.2		





Missed APCH climb gradient MNM 5.0%

MINIMA		AD elev. 6
CAT	CIRCLING	
	MDA(H)	VIS
A	360(354)	1600
B	460(454)	
C		2400
D	560(554)	3200

Circling to SOUTH side of RWY only.

CHANGE : ATC callsign changed (FUKUOKA DEP→FUKUOKA RADAR). ATC FREQ changed.

INSTRUMENT APPROACH CHART

RJFS/SAGA VOR C

FUKUOKA RADAR	SAGA VOR/DME 114.75 SGE CH-94Y 33°08′55″N/130°17′34″E	SAGA RADIO 118.025 – 126.2	(2130–2300(UTC) 1030–1500 SAGA REMOTE 118.025)	NO RADAR
119.7 – 279.2				





MISSED APPROACH

At 1.2DME prior to SGE VOR/DME, turn left and climb via SGE R194, turn left direct to SGE VOR/DME within SGE 9.0DME and hold at 5000FT.
Contact FUKUOKA RADAR.

MINIMA AD elev. 6

CAT	CIRCLING	
	MDA(H)	VIS
A	360(354)	1600
B	460(454)	
C		2400
D	560(554)	3200

Circling to SOUTH side of RWY only.

CHANGE : ATC callsign changed (FUKUOKA DEP→FUKUOKA RADAR). ATC FREQ changed.

RJFS / SAGA

Visual REP



Call sign	BRG / DIST from ARP	Remarks
鹿　島 Kashima	250°/ 9.9NM	新浜大橋 Bridge
竹　崎 Takezaki	199°/12.3NM	竹崎港 Harbor
大 牟 田 Ohmuta	135°/10.1NM	JR大牟田駅 Station
筑　後 Chikugo	071°/11.8NM	八女インターチェンジ Interchange
大 中 島 Ohnakashima	038°/ 5.0NM	筑後川昇開橋 Bridge
久 保 田 Kubota	329°/ 5.0NM	久保田橋 Bridge
佐 賀 大 和 Sagayamato	354°/10.5NM	佐賀大和インターチェンジ Interchange
南　関 Nankan	111°/13.2NM	南関インターチェンジ Interchange
10NM S	180°/10.0NM	海上 Over the sea

RJFS / SAGA BALLOON

熱気球の飛行が下図区域内で行われる。（期間：5月中旬から6月中旬まで及び10月中旬から2月下旬まで：RJFSノータム参照）

Hot air balloon flight will be conducted within below area.

(Period: from mid MAY to mid JUN and from mid OCT to late FEB: see NOTAM RJFS)



飛行高度 3000ft 以下
FLT ALT At or below 3000ft

飛行高度 4000ft 以下
FLT ALT At or below 4000ft

I Balloon FLT area Nr1 II Balloon FLT area Nr2* III Balloon FLT area Nr3*

* 佐賀空港を発着する航空機に対し、熱気球に係る情報（飛行空域2及び3内で飛行する気球の概数等）の提供が佐賀レディオまたは佐賀ﾘﾓｰﾄにより行われる。

* The information of hot air balloon(aprx number of balloon etc.in flight area number 2 and 3) will be provided for departing/arriving acft from/to SAGA airport by SAGA RADIO or SAGA REMOTE.

Example of phraseology:"Two flying balloons reported in balloon flight area number two."

CHANGE : NOTAM location (RJFF→RJFS).

RJFS / SAGA Minimum Vectoring Altitude CHART



① 1900
② 2000
③ 2200
④ 2300
⑤ 2400
⑥ 3300

(1) *334821N/1311428E*

CENTER：*333525N/1302627E* (RJFF No.1 RADAR SITE)
CENTER：*333453N/1302650E* (RJFF No.2 RADAR SITE)
✳：*324949N/1305040E* (RJFT RADAR SITE)