


## AD CHART



## STANDARD DEPARTURE CHART - INSTRUMENT

RJOK / KOCHI

SID

**SHIMIZU SIX DEPARTURE**


RWY 14 : Climb RWY HDG to 500FT, turn right HDG 268°...

RWY 32 : Climb RWY HDG to 800FT, turn right...

...to intercept and proceed via KRE R223/SUC R043 to SUC VORTAC.

Note RWY32 : 6.0% climb gradient required up to 2500FT.

OBST ALT 2165FT located at 6.6NM 358° FM end of RWY32.

**SHIMIZU SIX DEPARTURE**

STANDARD DEPARTURE CHART - INSTRUMENT

RJOK / KOCHI

SID

KOCHI REVERSAL FIVE DEPARTURE

RWY 14 : Climb RWY HDG to 500FT, turn right...

RWY 32 : Climb RWY HDG to 800FT, turn right HDG 205°...



...to intercept and proceed via KRE R160 to KRE 10.0DME, then turn left  
proceed to KRE VOR/DME.

Cross KRE VOR/DME at or above 6000FT.

Note RWY32 : 6.0% climb gradient required up to 2500FT.

OBST ALT 2165FT located at 6.6NM 358° FM end of RWY32.

KOCHI REVERSAL FIVE DEPARTURE



## STANDARD DEPARTURE CHART - INSTRUMENT

RJOK / KOCHI

SID

URADO REVERSAL THREE DEPARTURE

RWY 14 : Climb RWY HDG to 500FT, turn right HDG 255°...


RWY 32 : Climb RWY HDG to 800FT, turn right...

...to intercept and proceed via KRE R210 to KRE 15.0DME, then turn right  
proceed to KRE VOR/DME.

Cross KRE VOR/DME at or above 6000FT.

Note RWY32 : 6.0% climb gradient required up to 2500FT.

OBST ALT 2165FT located at 6.6NM 358° FM end of RWY32.

URADO REVERSAL THREE DEPARTURE

## STANDARD DEPARTURE CHART -INSTRUMENT

RJOK / KOCHI

RNAV SID

## KARIN ONE RNAV DEPARTURE

## RNAV 1

Note 1) DME/DME/IRU or GNSS required.

※The aircraft equipped with only DME/DME/IRU must be able to update its position without delay at the starting point of take-off roll.

2) RADAR service required.

Critical DME

RWY14 : KRE 3.0NM fm DER - 7NM to KARIN  
SUC 3.0NM fm DER - 10NM to KARIN  
RWY32 : KRE 9NM to OK32C - 10NM to KARIN  
SUC 9NM to OK32C - 4NM to OK32C


DME GAP

RWY14 : DER - 3.0NM fm DER  
RWY32 : DER - 9NM fm OK32C

Inappropriate NavAids

See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

VAR 7° W(2009)



DESIGNATION	COORDINATES
OK14A	33 24 50.3N 133 43 34.2E
OK14B	33 24 02.9N 133 50 40.3E
OK32A	33 36 15.7N 133 44 17.5E
OK32C	33 28 04.1N 133 55 42.6E
KARIN	33 40 24.4N 134 11 14.9E

Note RWY32: 6.0% climb gradient required up to 2300FT.

RWY14 : Climb on HDG137° at or above 500FT, turn right direct to OK14A, to OK14B, to KARIN at or above 8000FT.

RWY32 : Climb on HDG317° at or above 600FT, turn right direct to OK32A, to OK32C, to KARIN at or above 8000FT.

Note RWY32: 6.0% climb gradient required up to 2300FT.

OBST ALT 1970FT located at 6.13NM 004° FM end of RWY32.

## STANDARD DEPARTURE CHART -INSTRUMENT

RJOK / KOCHI

RNAV SID

KARIN ONE RNAV DEPARTURE

## RWY14

Rcmd. Path Terminator	Fix ID (Waypoint Name)	Fly Over	Distance (NM)	MAG Track (TRUE Track)	Turn Direction	Altitude (FT)	Speed Limit (KIAS)	Vertical Angle	Navigation Performance
VA	—	—	—	137° (130.6°)	—	+500	—	—	RNAV1
DF	OK14A	—	—	—	R	—	—	—	RNAV1
TF	OK14B	—	6.0	104° (097.5°)	—	—	—	—	RNAV1
TF	KARIN	—	23.7	053° (046.3°)	—	+8000	—	—	RNAV1

## RWY32

Rcmd. Path Terminator	Fix ID (Waypoint Name)	Fly Over	Distance (NM)	MAG Track (TRUE Track)	Turn Direction	Altitude (FT)	Speed Limit (KIAS)	Vertical Angle	Navigation Performance
VA	—	—	—	317° (310.6°)	—	+600	—	—	RNAV1
DF	OK32A	—	—	—	R	—	—	—	RNAV1
TF	OK32C	—	12.6	138° (130.7°)	—	—	—	—	RNAV1
TF	KARIN	—	17.9	053° (046.3°)	—	+8000	—	—	RNAV1

## STANDARD DEPARTURE CHART -INSTRUMENT

RJOK / KOCHI

RNAV SID

## KAIFU ONE RNAV DEPARTURE

## RNAV 1

Note 1 ) DME/DME/IRU or GNSS required.

※The aircraft equipped with only DME/DME/IRU must be able to update its position without delay at the starting point of take-off roll.

2 ) RADAR service required.

Critical DME

RWY14 : KRE 3.0NM fm DER - 23NM to KAIFU  
SUC 3.0NM fm DER - 32NM to KAIFU  
RWY32 : KRE 9NM to OK32C - 28NM to KAIFU  
SUC 9NM to OK32C - 4NM to OK32C

DME GAP

RWY14 : DER - 3.0NM fm DER  
RWY32 : DER - 9NM to OK32C

Inappropriate NavAids

See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

VAR 7° W(2009)



DESIGNATION	COORDINATES
OK14A	33 24 50.3N 133 43 34.2E
OK14B	33 24 02.9N 133 50 40.3E
OK32A	33 36 15.7N 133 44 17.5E
OK32C	33 28 04.1N 133 55 42.6E
KAIFU	33 36 10.0N 134 32 31.2E

Note RWY32: 6.0% climb gradient required up to 2300FT.

RWY14 : Climb on HDG137° at or above 500FT, turn right direct to OK14A, to OK14B, to KAIFU.

RWY32 : Climb on HDG317° at or above 600FT, turn right direct to OK32A, to OK32C, to KAIFU.

Note RWY32: 6.0% climb gradient required up to 2300FT.

OBST ALT 1970FT located at 6.13NM 004° FM end of RWY32.

## STANDARD DEPARTURE CHART -INSTRUMENT

RJOK / KOCHI

RNAV SID

KAIFU ONE RNAV DEPARTURE

## RWY14

Rcmd. Path Terminator	Fix ID (Waypoint Name)	Fly Over	Distance (NM)	MAG Track (TRUE Track)	Turn Direction	Altitude (FT)	Speed Limit (KIAS)	Vertical Angle	Navigation Performance
VA	—	—	—	137° (130.6°)	—	+500	—	—	RNAV1
DF	OK14A	—	—	—	R	—	—	—	RNAV1
TF	OK14B	—	6.0	104° (097.5°)	—	—	—	—	RNAV1
TF	KAIFU	—	37.0	077° (070.7°)	—	—	—	—	RNAV1

## RWY32


Rcmd. Path Terminator	Fix ID (Waypoint Name)	Fly Over	Distance (NM)	MAG Track (TRUE Track)	Turn Direction	Altitude (FT)	Speed Limit (KIAS)	Vertical Angle	Navigation Performance
VA	—	—	—	317° (310.6°)	—	+600	—	—	RNAV1
DF	OK32A	—	—	—	R	—	—	—	RNAV1
TF	OK32C	—	12.6	138° (130.7°)	—	—	—	—	RNAV1
TF	KAIFU	—	31.8	082° (075.0°)	—	—	—	—	RNAV1



## STANDARD DEPARTURE CHART -INSTRUMENT

RJOK / KOCHI

RNAV SID and TRANSITION



## STANDARD DEPARTURE CHART -INSTRUMENT

RJOK / KOCHI

RNAV SID and TRANSITION

MUROT ONE RNAV DEPARTURE

## RWY14

Rcmd. Path Terminator	Fix ID (Waypoint Name)	Fly Over	Distance (NM)	MAG Track (TRUE Track)	Turn Direction	Altitude (FT)	Speed Limit (KIAS)	Vertical Angle	Navigation Performance
VA	—	—	—	137° (130.6°)	—	+500	—	—	RNAV1
DF	OK14A	—	—	—	R	—	—	—	RNAV1
TF	MUROT	—	30.9	104° (097.6°)	—	—	—	—	RNAV1

## RWY32

Rcmd. Path Terminator	Fix ID (Waypoint Name)	Fly Over	Distance (NM)	MAG Track (TRUE Track)	Turn Direction	Altitude (FT)	Speed Limit (KIAS)	Vertical Angle	Navigation Performance
VA	—	—	—	317° (310.6°)	—	+600	—	—	RNAV1
DF	OK32A	—	—	—	R	—	—	—	RNAV1
TF	OK32D	—	20.9	138° (130.7°)	—	—	—	—	RNAV1
TF	MUROT	—	14.3	105° (097.7°)	—	—	—	—	RNAV1

KUSHIMOTO TRANSITION

Rcmd. Path Terminator	Fix ID (Waypoint Name)	Fly Over	Distance (NM)	MAG Track (TRUE Track)	Turn Direction	Altitude (FT)	Speed Limit (KIAS)	Vertical Angle	Navigation Performance
IF	MUROT	—	—	—	—	—	—	—	RNAV1
TF	MIYAT	—	19.0	100° (093.3°)	—	—	—	—	RNAV1
TF	MERID	—	12.3	089° (082.0°)	—	—	—	—	RNAV1
TF	KUSHIMOTO (KEC)	—	42.3	089° (082.2°)	—	—	—	—	RNAV1

## STANDARD DEPARTURE CHART -INSTRUMENT

RJOK / KOCHI

RNAV SID

## OMOGO TWO RNAV DEPARTURE

## RNAV 1

Note 1) DME/DME/IRU or GNSS required.

※The aircraft equipped with only DME/DME/IRU must be able to update its position without delay at the starting point of take-off roll.

2) RADAR service required.

Critical DME

RWY14 : KRE 16NM to YUZNO - 7NM to YUZNO  
SUC 16NM to YUZNO - 7NM to YUZNO  
RWY32 : KRE 4NM to OK32B - 25NM to YUZNO  
SUC 4NM to OK32B - 25NM to YUZNO

DME GAP

RWY14 : DER - 16NM to YUZNO  
RWY32 : DER - 4NM to OK32B  
25NM to YUZNO - 18NM to YUZNO

Inappropriate NavAids

See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

VAR 7° W(2017)



RWY14 : Climb on HDG138° at or above 500FT, turn right direct to OK14C, to YUZNO, to OMOGO.

RWY32 : Climb on HDG318° at or above 600FT, turn right direct to OK32A, to OK32B, to OK32E, to YUZNO, to OMOGO.

Note RWY32: 6.0% climb gradient required up to 2300FT.

OBST ALT 1970FT located at 6.1NM 004° FM end of RWY32.

## STANDARD DEPARTURE CHART -INSTRUMENT

RJOK / KOCHI

RNAV SID

**OMOGO TWO RNAV DEPARTURE****RWY14**

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	138 (130.6)	-7.4	—	—	+500	—	—	RNAV1
002	DF	OK14C	—	—	-7.4	—	R	—	—	—	RNAV1
003	TF	YUZNO	—	320 (312.9)	-7.4	18.8	—	—	—	—	RNAV1
004	TF	OMOGO	—	296 (288.5)	-7.4	4.0	—	—	—	—	RNAV1

**RWY32**

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	318 (310.6)	-7.4	—	—	+600	—	—	RNAV1
002	DF	OK32A	—	—	-7.4	—	R	—	—	—	RNAV1
003	TF	OK32B	—	138 (130.7)	-7.4	7.0	—	—	—	—	RNAV1
004	TF	OK32E	—	230 (222.8)	-7.4	13.3	—	—	—	—	RNAV1
005	TF	YUZNO	—	320 (312.9)	-7.4	25.9	—	—	—	—	RNAV1
006	TF	OMOGO	—	296 (288.5)	-7.4	4.0	—	—	—	—	RNAV1

## STANDARD ARRIVAL CHART -INSTRUMENT

RJOK / KOCHI


RNAV STAR

## YOSAKOI NORTH ARRIVAL

RNAV 1

Note 1 ) DME/DME/IRU or GNSS required.  
2 ) RADAR service required.

VAR 7° W(2012)



From POPPY, to JYAMU at or above 8000FT, to BATAK at or above 6000FT, to CHEEZ at or above 4500FT, to ANPAN.

Critical DME	GBD	POPPY - 2NM to BATAK
	SUC	7NM to BATAK - ANPAN
	KRE	1NM to BATAK - ANPAN
DME GAP	-	
Inappropriate Nav aids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1	

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course [°M(°T)]	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	POPPY	—	—	-6.9	—	—	—	—	—	RNAV1
002	TF	JYAMU	—	171 (164.2)	-6.9	3.9	—	+8000	—	—	RNAV1
003	TF	BATAK	—	171 (164.2)	-6.9	11.7	—	+6000	—	—	RNAV1
004	TF	CHEEZ	—	182 (175.5)	-6.9	8.2	—	+4500	-200	—	RNAV1
005	TF	ANPAN	—	264 (257.6)	-6.9	3.7	—	—	—	—	RNAV1

## STANDARD ARRIVAL CHART -INSTRUMENT

RJOK / KOCHI

RNAV STAR

## YOSAKOI EAST ARRIVAL

RNAV 1

Note 1 ) DME/DME/IRU or GNSS required.  
2 ) RADAR service required.

VAR 7° W(2012)



From PANCH, to ANPAN.

Critical DME	KRE	PANCH - ANPAN
	SUC	8NM to ANPAN - ANPAN
DME GAP	-	
Inappropriate Nav aids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1	

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course [°M(°T)]	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	PANCH	—	—	-6.9	—	—	—	—	—	RNAV1
002	TF	ANPAN	—	326 (318.7)	-6.9	18.3	—	—	—	—	RNAV1

STANDARD ARRIVAL CHART -INSTRUMENT

RJOK / KOCHI

RNAV STAR

YOSAKOI SOUTH ARRIVAL

RNAV 1

Note 1 ) DME/DME/IRU or GNSS required.  
2 ) RADAR service required.

VAR 7° W(2012)



From OKITU, to BIRKN, to ANPAN.

Critical DME	IWT	OKITU - 26NM to BIRKN
	SUC	12NM to BIRKN - ANPAN
	KRE	12NM to BIRKN - ANPAN
DME GAP	26NM to BIRKN - 12NM to BIRKN	
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1	

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course [°M(°T)]	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	OKITU	—	—	-6.9	—	—	—	—	—	RNAV1
002	TF	BIRKN	—	064 (057.3)	-6.9	29.6	—	—	-230	—	RNAV1
003	TF	ANPAN	—	047 (040.6)	-6.9	4.5	—	—	—	—	RNAV1

## STANDARD ARRIVAL CHART -INSTRUMENT

RJOK / KOCHI

RNAV STAR

## YOSAKOI WEST ARRIVAL

RNAV 1

Note 1 ) DME/DME/IRU or GNSS required.  
2 ) RADAR service required.

VAR 7° W(2012)

VOR/DME  
KOCHI  
113.7 KRE  
CH-84X  
33°32'30"N/133°40'49"E  
100FT



From KABIL, to DOKIN at or above 5000FT, to BIRKN, to ANPAN.

Critical DME	KRE	1NM to DOKIN - 16NM to BIRKN 7NM to BIRKN - ANPAN
	SUC	1NM to DOKIN - 16NM to BIRKN 7NM to BIRKN - ANPAN
DME GAP	16NM to BIRKN - 7NM to BIRKN	
Inappropriate Nav aids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1	

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course [°M(°T)]	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	KABIL	—	—	-6.9	—	—	—	—	—	RNAV1
002	TF	DOKIN	—	113 (105.9)	-6.9	5.8	—	+5000	—	—	RNAV1
003	TF	BIRKN	—	113 (105.9)	-6.9	20.3	—	—	-230	—	RNAV1
004	TF	ANPAN	—	047 (040.6)	-6.9	4.5	—	—	—	—	RNAV1



## INSTRUMENT APPROACH CHART

RJOK / KOCHI

ILS Z or LOC Z RWY32



## MISSED APPROACH

Climb to 800FT on HDG318°, turn left HDG178° to intercept and proceed via KRE R223 to SUSAK and hold at 3000FT. Contact KANSAI APP.

Timing not authorized for defining the MAPt.



Missed APCH climb gradient MNM 5.0%

MINIMA

THR elev. 18

AD elev. 29

CAT	CAT I		LOC		CIRCLING	
	DA(H)	RVR/CMV	MDA(H)	RVR/CMV	MDA(H)	VIS
A	218 (200)	700	320 (302)	1200	690 (661)	1600
B				1300		
C				1400	760 (731)	2400
D				1600	830 (801)	3200

Circling to EAST side of RWY only.


MINIMA with Missed APCH climb gradient of 2.5% are not established.

CHANGE : VAR

## INSTRUMENT APPROACH CHART

RJOK / KOCHI


ILS Y or LOC Y RWY32



## MISSED APPROACH

Climb to 800FT on HDG318°, turn left HDG178° to intercept and proceed via KRE R223 to SUSAK and hold at 3000FT. Contact KANSAI APP.

Timing not authorized for defining the MAPt.



DME to IKR	0.6	1.0	4.6	
NM to THR	0	0.4	0.8	4.4

Missed APCH climb gradient MNM 5.0%

MINIMA THR elev. 18 AD elev. 29

CAT	CAT I		LOC		CIRCLING	
	DA(H)	RVR/CMV	MDA(H)	RVR/CMV	MDA(H)	VIS
A	218 (200)	700	320 (302)	1200	690 (661)	1600
B				1300		
C				1400	760 (731)	2400
D				1600	830 (801)	3200

Circling to EAST side of RWY only.

MINIMA with Missed APCH climb gradient of 2.5% are not established.

CHANGE : VAR

## INSTRUMENT APPROACH CHART

RJOK / KOCHI

VOR RWY32



## MISSED APPROACH

Climb via KRE R324 to 500FT,  
turn left HDG178° to intercept  
and proceed via KRE R223 to  
SUSAK and hold at 3000FT.  
Contact KANSAI APP.

Timing not authorized for defining the MAPt.



Missed APCH climb gradient MNM 4.5%

MINIMA THR elev. 18 AD elev. 29

CAT	CIRCLING		CIRCLING	
	MDA(H)	RVR/CMV	MDA(H)	VIS
A	360 (342)	1200	690 (661)	1600
B	400 (382)	1300		
C	430 (412)	1400	760 (731)	2400
D	450 (432)	1600	830 (801)	3200


Circling to EAST side of RWY only.

MINIMA with Missed APCH climb gradient of 2.5% are not established.

## INSTRUMENT APPROACH CHART

RJOK / KOCHI

RNAV(RNP) Z RWY14



## INSTRUMENT APPROACH CHART

RJOK / KOCHI

RNAV(RNP) Z RWY14

RNAV(RNP) Z RWY14Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	ANPAN	—	—	-6.9	—	—	+4000	—	—	—
002	TF	NOITI	—	343 (335.9)	-6.9	9.7	—	+4000	—	—	1.0
003	TF	IGENO	—	318 (310.7)	-6.9	4.2	—	3500	—	—	1.0
004	TF	OK451	—	318 (310.7)	-6.9	1.8	—	2922	-165	-3.00	0.14 0.30
005	RF Center: OKRF1 r=2.07NM	OK477	—	—	-6.9	6.5	L	856	—	-3.00	0.14 0.30
006	TF	RW14	Y	138 (130.6)	-6.9	2.4	—	92	—	-3.00/50	0.14 0.30
007	TF	ANPAN	—	138 (130.6)	-6.9	12.4	—	4000	—	—	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
ANPAN	332507.54N/1335048.52E	OKRF1	333620.13N/1333858.11E
NOITI	333400.03N/1334602.07E		
IGENO	333643.39N/1334213.86E		
OK451	333754.48N/1334034.43E		
OK477	333445.76N/1333721.85E		
RW14	333312.04N/1333932.98E		

## INSTRUMENT APPROACH CHART

RJOK / KOCHI

RNAV(RNP) Y RWY14



## INSTRUMENT APPROACH CHART

RJOK / KOCHI

RNAV(RNP) Y RWY14

RNAV(RNP) Y RWY14Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/RDH (°/FT)	RNP Value
001	IF	ANPAN	—	—	-6.9	—	—	+4000	—	—	—
002	TF	KATUO	—	292 (285.5)	-6.9	9.7	—	+4000	—	—	1.0
003	TF	TATKY	—	318 (310.6)	-6.9	4.2	—	3500	—	—	1.0
004	TF	OK481	—	318 (310.6)	-6.9	1.8	—	2922	-165	-3.00	0.14 0.30
005	RF Center: OKRF2 r=2.07NM	OK477	—	—	-6.9	6.5	R	856	—	-3.00	0.14 0.30
006	TF	RW14	Y	138 (130.6)	-6.9	2.4	—	92	—	-3.00/50	0.14 0.30
007	TF	ANPAN	—	138 (130.6)	-6.9	12.4	—	4000	—	—	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
ANPAN	332507.54N/1335048.52E	OKRF2	333311.37N/1333545.65E
KATUO	332742.79N/1333937.02E		
TATKY	333025.96N/1333548.91E		
OK481	333136.96N/1333409.51E		
OK477	333445.76N/1333721.85E		
RW14	333312.04N/1333932.98E		

RJOK / KOCHI

Visual REP



Call sign	BRG / DIST from ARP	Remarks
工 科 大 Koukadai	035° / 5.2NM	高知工科大学 Kochi University of Technology
芸 西 Geisei	113° / 5.9NM	観光ホテル Hotel
桂 浜 Katsurahama	248° / 6.0NM	浦戸大橋 Bridge
高 知 市 Kochi city	290° / 6.5NM	JR高知駅 Station
植 野 Ueno	355° / 5.0NM	ゴルフ場 Golf course
安 芸 Aki	110° / 12.5NM	安芸川河口 River mouth
横 浪 Yokonami	243° / 12.9NM	国民宿舎 Hotel





RJOK / KOCHI

Minimum Vectoring Altitude CHART

VAR 7°W (2009)



- ① 2000
- ② 2300
- ③ 2500
- ④ 3000
- ⑤ 3500
- ⑥ 4000
- ⑦ 4500



CENTER : 333245N/1334039E (RADAR SITE)