RJOW / IWAMI AD CHART



STANDARD DEPARTURE CHART-INSTRUMENT

RJOW / IWAMI SID and TRANSITION

SAMBA TWO DEPARTURE

RWY11：Climb RWY HDG to 800FT, turn left HDG351˚,...
RWY29：Climb RWY HDG to 700FT, turn right HDG081˚,...
...to intercept and proceed via IME R036 to SAMBA.
Cross SAMBA at or above 7000FT.

Note RWY11： 5.7% climb gradient required up to 1700FT.
OBST ALT 1177FT located at 4.83NM 093˚ FM end of RWY11.

IZUMO TRANSITION

From over SAMBA, via XZE R252 to XZE VOR/DME.
Cross CARNY at or below 13000FT, cross BAARU at or below FL230.



CHANGE : Update

STANDARD DEPARTURE CHART-INSTRUMENT

RJOW / IWAMI ➡ RNAV TRANSITION

VIBEL TRANSITION	RNAV1

Note 1) DME/DME/IRU or GNSS required.
2) RADAR service required.

VAR 8˚W (2017)



VIBEL TRANSITION

From SAMBA at or above 7000FT, to OSPEL at or below 13000FT, to VIBEL at or below FL230.

Critical DME	STD : SAMBA – VIBEL
DME GAP	–
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	SAMBA	–	–	-7.8	–	–	+7000	–	–	RNAV1
002	TF	OSPEL	–	077 (069.7)	-7.8	10.5	–	-13000	–	–	RNAV1
003	TF	VIBEL	–	078 (069.8)	-7.8	10.2	–	-FL230	–	–	RNAV1

CHANGE : New PROC

INSTRUMENT APPROACH CHART

RJOW / IWAMI — ILS or LOC RWY11

FUKUOKA CONTROL	ILS-LOC IWA 108.1	IWAMI REMOTE	NO RADAR
132.5–132.9 246.1–228.4	ILS–GP 334.7 ILS–DME CH–18X	122.2	



NM to IWA	FAF	7	6	5	4	3	2	1	MAPt
ALT (3.0˚ APCH Path)	2451	2407	2088	1770	1451	1133	814	495	–



MISSED APPROACH

Turn left, climb to 4000FT via IME R036 to BLUES and hold.
Contact IWAMI REMOTE.

Timing not authorized for definig the MAPt.

DME to IWA	13.1	7.1	1.0	0.6
NM to THR	13.0	7.0	0.8	0.5	0

Missed APCH climb gradient MNM 4.0%

MINIMA THR elev. 184 AD elev. 177

CAT	CAT I		LOC		CIRCLING	
	DA(H)	RVR/ CMV	MDA(H)	RVR/ CMV	MDA(H)	VIS
A	384 (200)	550	480 (303)	900	1000 (823)	1600
B				1000	1100 (923)	
C					1400 (1223)	2400
D				1400	1600 (1423)	3200

Circling to NORTH side of RWY only.
MINIMA with Missed APCH climb gradient of 2.5% are not established.

CHANGE : Editorial

INSTRUMENT APPROACH CHART

RJOW / IWAMI VOR RWY11

FUKUOKA CONTROL	IWAMI VOR/DME	IWAMI REMOTE	NO RADAR
132.5–132.9 246.1–228.4	115.05 IME CH–97Y *34˚40´34˝N/131˚46´48˝E*	122.2	



NM to IME	FAF	4	3	2	MAPt
ALT (3.0˚ APCH Path)	1810	1491	1173	855	–



MISSED APPROACH
Turn left, climb to 4000FT via IME R036 to BLUES and hold.
Contact IWAMI REMOTE.

VDP
D1.2 IME (CAT A, B, C)
D1.3 IME (CAT D)

Timing not authorized for definig the MAPt.

DME to IME	13.0	5.0	3.2	0
NM to THR	12.9	4.9	3.1	0

MINIMA THR elev. 184 AD elev. 177

CAT			CIRCLING	
	MDA(H)	RVR/ CMV	MDA(H)	VIS
A	590 (413)	900	1000 (823)	1600
B		1000	1100 (923)	
C			1400 (1223)	2400
D	610 (433)	1400	1600 (1423)	3200

Circling to NORTH side of RWY only

INSTRUMENT APPROACH CHART

RJOW / IWAMI VOR A

FUKUOKA CONTROL	IWAMI VOR/DME	IWAMI REMOTE	NO RADAR
132.5 - 132.9 246.1 - 228.4	115.05 IME CH-97Y *34˚40´34˝N/131˚46´48˝E*	122.2	



MISSED APPROACH

Turn right, climb to 4000FT via IME
R036 to BLUES and hold.
Contact IWAMI REMOTE.

Timing not authorized for definig the MAPt.



MINIMA	AD elev. 177	
CAT	CIRCLING	
	MDA(H)	VIS
A	1000 (823)	1600
B	1100 (923)	
C	1400 (1223)	2400
D	1600 (1423)	3200

Circling to NORTH side of RWY only

INSTRUMENT APPROACH CHART

RJOW / IWAMI

➡ RNAV(RNP) RWY11

FUKUOKA CONTROL 132.5 - 132.9 246.1 - 228.4	GNSS and RF required.	IWAMI REMOTE 122.2	NO RADAR

For uncompensated Baro-VNAV systems, procedure not authorized below -5 ℃ / above 45℃





MISSED APPROACH

From RW11 on track 113°, at or above 600FT turn left, direct to BLUES and hold at 4000FT.

Contact IWAMI REMOTE.

Missed APCH climb gradient MNM 5.0%

MINIMA THR elev. 184 AD elev. 177		
CAT	RNP 0.30	
	DA(H)	RVR/CMV
A	-	-
B		
C	484(300)	1000
D	-	-

MINIMA with Missed APCH climb gradient of 2.5% are not established.

RNP AR

Special Authorization Required

CHANGE : New PROC

INSTRUMENT APPROACH CHART

RJOW / IWAMI ➡ RNAV(RNP) RWY11

RNAV(RNP) RWY11

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/RDH (°/FT)	RNP Value
001	IF	BLUES	–	–	-7.8	–	–	+4000	–	–	1.0
002	TF	OW150	–	237 (229.3)	-7.8	9.8	–	2600	–	–	1.0
003	TF	OW151	–	237 (229.2)	-7.8	1.4	–	2139	-165	-3.00	0.3
004	RF Center: OWRF1 r=2.03NM	OW152	–	–	-7.8	4.4	L	736	–	-3.00	0.3
005	TF	RW11	Y	113 (104.8)	-7.8	1.6	–	238	–	-3.00/54	0.3
006	FA	–	–	113 (104.8)	-7.8	–	–	+600	–	–	1.0
007	DF	BLUES	–	–	-7.8	–	L	4000	–	–	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
BLUES	*345159.02N/1315423.09E*	OWRF1	*344304.90N/1314534.53E*
OW150	*344533.91N/1314518.52E*		
OW151	*344437.18N/1314358.51E*		
OW152	*344107.26N/1314456.99E*		
RW11	*344043.28N/1314647.11E*		

CHANGE : New PROC

INSTRUMENT APPROACH CHART

RJOW / IWAMI ➡ RNAV(RNP) RWY29

FUKUOKA CONTROL	GNSS and RF required.	IWAMI REMOTE	NO RADAR
132.5 - 132.9 246.1 - 228.4		122.2	

For uncompensated Baro-VNAV systems, procedure not authorized below -5 ℃ / above 39℃



MISSED APPROACH

From RW29 on track 293˚, at or above 600FT turn right, direct to BLUES and hold at 4000FT.

Contact IWAMI REMOTE.

PAPI not coincident with VPA.



Missed APCH climb gradient MNM 4.0%

MINIMA THR elev. 171 AD elev. 177

CAT	RNP 0.16		RNP 0.30	
	DA(H)	CMV	DA(H)	CMV
A	–	–	–	–
B				
C	471(300)	1400	489(318)	1400
D	–	–	–	–

RNP AR
Special Authorization Required

MINIMA with Missed APCH climb gradient of 2.5% are not established.

CHANGE : New PROC

INSTRUMENT APPROACH CHART

RJOW / IWAMI ➡ RNAV(RNP) RWY29

RNAV(RNP) RWY29

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/RDH (°/FT)	RNP Value
001	IF	BLUES	–	–	-7.8	–	–	+4000	–	–	1.0
002	TF	OW950	–	199 (191.5)	-7.8	6.0	–	3100	–	–	1.0
003	TF	OW951	–	199 (191.5)	-7.8	5.3	–	1374	-150	-3.10	0.16 0.3
004	RF Center: OWRF2 r=1.20NM	OW952	–	–	-7.8	2.0	R	731	–	-3.10	0.16 0.3
005	TF	RW29	Y	293 (284.9)	-7.8	1.5	–	221	–	-3.10/50	0.16 0.3
006	FA	–	–	293 (284.9)	-7.8	–	–	+600	–	–	1.0
007	DF	BLUES	–	–	-7.8	–	R	4000	–	–	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
BLUES	*345159.02N/1315423.09E*	OWRF2	*344112.62N/1315014.52E*
OW950	*344606.97N/1315256.13E*		
OW951	*344058.27N/1315140.08E*		
OW952	*344002.90N/1314952.21E*		
RW29	*344026.72N/1314803.07E*		

CHANGE : New PROC

RJOW / IWAMI

Visual REP



Call sign	BRG / DIST from ARP	Remarks
魚　待 Uomachi	038°/6.0NM	岬 Cape
高　山 Takayama	266°/8.9NM	岬 Cape
日　原 Nichihara	164°/8.0NM	JR日原駅 JR station

RJOW / IWAMI LDG CHART



*Note : RWY may be invisible on downwind leg of northside traffic pattern according to altitude.

CHANGE : Obstacle added

RJOW / IWAMI Minimum Vectoring Altitude CHART