


RJOI / IWAKUNI

AD CHART



NOTE: REPRINTING DOD FLIP

RJOI / IWAKUNI

Aircraft Parking / Docking Chart



RJOI / IWAKUNI MATSUYAMA SE THREE DEPARTURE(OBSTACLE) (RNAV)


Rwy	Knots	60	120	180	240	300	360
* 02 @	V/V(fpm)	230	460	690	920	1150	1650
† 02/20 (b)	V/V(fpm)	330	660	990	1320	1650	1980
† 20 ©	V/V(fpm)	204	408	612	816	1020	1224

* Minimum † ATC Climb Rate

Ⓐ to 2300

⑥ MALTA transtion to 15,000 from MYE to MALTA

(C) to 6000



RNAV1

DME/DME/IRU, DME/DME, GNSS, or RNP 2.0 REQUIRED

NOTE: Chart not to scale

TA 14,000

T

DEPARTURE ROUTE DESCRIPTION

TAKE-OFF RWY 02: Climb heading 015° to 511, then on depicted route.
Cross MATSUYAMA VOR/DME (MYE) at 6000 thence...

TAKE-OFF RWY 20: Climb heading 195° to 511, then on depicted route.
Cross MATSUYAMA VOR/DME (MYE) at 6000 thence...

KOCHI TRANSITION: As depicted. Cross KOCHI (KRE) at FL150. Maintain FL150 or higher as assigned.

MALTA TRANSITION: As depicted. Cross MALTA at FL150, maintain FL150 or higher as assigned.

CHANGE : Update.

NOTE: REPRINTING DOD FLIP

INSTRUMENT APPROACH CHART

RJOI / IWAKUNI

LOC/DME I-IJO 110.15 Chan 38(Y)	APCH CRS 014°	Rwy Idg 8006 TDZE 10 Arpt Elev 10
---	-------------------------	--

ILS RWY02

RADAR or MYE VOR/DME required.

▼ *When ALS inop, increase CAT ABCD vis to $\frac{3}{4}$ mile.
**When ALS inop, increase CAT AB vis to 1 mile,
CAT CD vis to $1\frac{1}{8}$ miles.
*** Circling not authorized W of Rwy 02-20. CAT D
remain within 2.8 NM.


ALSIF-1




MISSED APPROACH: Climb on heading 014° to 700,
then climbing right turn to 6000 heading 144° direct
MYE VOR/DME and hold.

ATIS★ 128.4 283.0	APP CON 131.4 236.2	TOWER★ 123.8 340.2	GND CON 121.3 360.2	CLNC DEL 135.7 310.6	ASR/PAR
-----------------------------	-------------------------------	------------------------------	-------------------------------	--------------------------------	---------


Knots	60	120	180	240	300	360
V/V(fpm)	210	420	630	840	1050	1260
Min climb of 210 ft/NM to 2100 - Controlling Obstacle 1457						



EMERG SAFE ALT 100 NM 8500



CATEGORY	A	B	C	D
S-ILS 02*	260- $\frac{1}{2}$	250	(300- $\frac{1}{2}$)	
S-LOC 02**	400- $\frac{1}{2}$	390 (400- $\frac{1}{2}$)	400- $\frac{5}{8}$	390 (400- $\frac{5}{8}$)
Ⓢ CIRCLING***	460-1	450 (500-1)	460-1 $\frac{1}{2}$ 450 (500-1 $\frac{1}{2}$)	560-2 550 (600-2)




CHANGE : Update.

NOTE: REPRINTING DOD FLIP

INSTRUMENT APPROACH CHART

RJOI / IWAKUNI



RJOI / IWAKUNI

LDG CHART

SEALANE PATTERNS & VFR ARR PATTERNS



IWAKUNI SEALANE(TOWER) :
122.0 - 123.1x - 228.2 - 319.0

IWAKUNI APP : WEST
131.4 - 236.2
EAST 128.0 - 250.6

IWAKUNI TWR :
123.8 - 340.2

RJOI / IWAKUNI

Minimum Vectoring Altitude CHART

Altitude MSL
S1 – 7400 ft
S2 – 5500 ft
S3 – 2300 ft
S4 – 4100 ft
S5 – 3400 ft
S6 – 2800 ft
S7 – 2700 ft
S8 – 2600 ft

- Centered on NEU (Iwakuni TACAN)
- Radials from NEU



CHANGE : Update.