

**AD 2 AERODROMES****RJDT AD 2.1 AERODROME LOCATION INDICATOR AND NAME****RJDT - TSUSHIMA****RJDT AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA**

1	ARP coordinates and site at AD	341706N 1291950E APRX 500m SE of AP administration office
2	Direction and distance from (city)	APRX 10km NE of Tsushima city office
3	Elevation/ Reference temperature	207ft / 33°C (2003-2007)
4	Geoid undulation at AD ELEV PSN	97ft
5	MAG VAR/ Annual change	7°W(2009) / 2.6'W
6	AD Administration, address, telephone, telefax, telex, AFS, e-mail and/or Web-site addresses	Tsushima Airport Administration Office, Nagasaki Prefectural Government Otsu-1725 Mitsushima-machi-kechi, Tsushima-city, Nagasaki, 817-0322 JAPAN Tel: 0920-54-2159      e-mail: s14080@pref.nagasaki.lg.jp
7	Types of traffic permitted (IFR/VFR)	IFR/VFR
8	Remarks	Nil

**RJDT AD 2.3 OPERATIONAL HOURS**

1	AD Administration	2230 -1200
2	Customs and immigration	On request Customs: 0920-52-1112 Immigration: 0920-52-0432
3	Health and sanitation	Quarantine (human): On request (0920-52-0089) Quarantine (animal, plant): Nil
4	AIS Briefing Office	Nil
5	ATS Reporting Office(ARO)	Nil
6	MET Briefing Office	H24 (FUKUOKA)
7	ATS	2230-1200 Remarks: AFIS provided by Fukuoka Airport Office.
8	Fuelling	Nil
9	Handling	Nil
10	Security	2230 - 1200
11	De-icing	Nil
12	Remarks	Nil

**RJDT AD 2.4 HANDLING SERVICES AND FACILITIES**

1	Cargo-handling facilities	Nil
2	Fuel/ oil types	JET A-1
3	Fuelling facilities/ capacity	By fueling truck, limitation 1kl, Ask AD administration
4	De-icing facilities	Nil
5	Hangar space for visiting aircraft	Nil
6	Repair facilities for visiting aircraft	Nil
7	Remarks	Nil

**RJDT AD 2.5 PASSENGER FACILITIES**

1	Hotels	in Tsushima city 4km
2	Restaurants	in Tsushima city 2km
3	Transportation	Busses and Taxis
4	Medical facilities	in Tsushima city 4km
5	Bank and Post Office	in Tsushima city 4km
6	Tourist Office	in Tsushima city 13km
7	Remarks	Nil

**RJDT AD 2.6 RESCUE AND FIRE FIGHTING SERVICES**

1	AD category for fire fighting	CAT 6
2	Rescue equipment	Chemical fire fighting truck x 1
3	Capability for removal of disabled aircraft	Nil
4	Remarks	Nil

**RJDT AD 2.7 SEASONAL AVAILABILITY-CLEARING**

1	Types of clearing equipment	Not AVBL
2	Clearance priorities	Nil
3	Remarks	Nil

**RJDT AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS DATA**

1	Apron surface and strength	Surface: Asphalt-concrete Strength: SPOT NR 1 PCN 17/F/C/Y/T SPOT NR 2 PCN 40/F/B/X/T SPOT NR 3, 5 PCN 36/R/B/X/T SPOT NR 6 PCN 48/R/B/X/T
2	Taxiway width, surface and strength	Surface: Asphalt T1 Width :23m Strength:PCN 52/F/A/X/T T2 Width :23m Strength: PCN 61/F/A/X/T
3	ACL and elevation	Not available
4	VOR checkpoints	Not available
5	INS checkpoints	Spot Nr 1 341715.17N 1291930.63E 2 341713.89N 1291932.12E 3 341712.23N 1291933.13E 5 341710.82N 1291934.76E 6 341709.43N 1291936.39E
6	Remarks	Nil

**RJDT AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS**

1	Use of aircraft stand ID signs, TWY guide lines and Visual docking/ parking guidance system of aircraft stands	Nil
2	RWY and TWY markings and LGT	RWY : RWY 14/32 (Marking) RWY designation, RWY CL, RWY THR, Aiming point, TDZ, RWY side stripe (LGT) RCLL, REDL, RTHL, RENL , RWY DIST markar LGT  TWY : T1, T2 (Marking) TWY CL, TWY side stripe (LGT)TWY edge LGT, Taxiing guidance sign, TWY CL LGT(T2)
3	Stop bars	Nil
4	Remarks	(Marking) Overrun area (LGT) Apron flood LGT

**RJDT AD 2.10 AERODROME OBSTACLES**

In approach/TKOF areas

RWY/Area affected	Obstacle type	Coordinates	Elevation	Markings/ LGT	Remarks
			Nil		

In circling area and at AD

Obstacle type	Coordinates	Elevation	Markings/ LGT	Remarks
Mountain	341657.4N/1292220.9E	689ft	- / LIM	above the horizontal surface

**RJDT AD 2.11 METEOROLOGICAL INFORMATION PROVIDED**

1	Associated MET Office	FUKUOKA
2	Hours of service MET Office outside hours	H24 (FUKUOKA)
3	Office responsible for TAF preparation Periods of validity	Nil
4	Trend forecast Interval of issuance	Nil
5	Briefing/ consultation provided	Briefing is available upon inquiry at FUKUOKA
6	Flight documentation Language(s) used	C En
7	Charts and other information available for briefing or consultation	S <sub>6</sub> , U <sub>85</sub> , U <sub>7</sub> , U <sub>5</sub> , U <sub>3</sub> , U <sub>25</sub> , U <sub>2</sub> /Tr, P <sub>S</sub> , P <sub>5</sub> , P <sub>3</sub> , P <sub>25</sub> , P <sub>SWE</sub> , P <sub>SWF</sub> , P <sub>SWG</sub> , P <sub>SWI</sub> , P <sub>SWM</sub> , P <sub>SW</sub> (domestic), E, C, W <sub>E</sub> , W <sub>F</sub> , W <sub>G</sub> , W <sub>I</sub> , W, N
8	Supplementary equipment available for providing information	Nil
9	ATS units provided with information	RADIO
10	Additional information (limitation of service, etc.)	Nil

**RJDT AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS**

Designations RWY NR	TRUE BRG	Dimensions of RWY(M)	Strength(PCN)and surface of RWY	THR coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
14	136.04°	1900x45	PCN 61/F/A/X/T Asphalt-Concrete	341727.79N 1291924.19E 303ft	THR ELEV : 205ft
32	316.04°	1900x45	PCN 61/F/A/X/T Asphalt-Concrete	341643.41N 1292015.77E 280ft	THR ELEV : 182ft
Slope of RWY	Strip Dimensions(M)		RESA(Overrun) Dimensions(M)		Remarks
7	10		11		14
SEE AD2.24 AD chart	2020x150 2020x150		40x150 125x(MNM:70 MAX:180)*		RWY Grooving:1900x30m
			*For detail, ask airport administrator		

**RJDT AD 2.13 DECLARED DISTANCES**

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)	Remarks
1	2	3	4	5	6
14	1900	1900	1900	1900	Nil
32	1900	1900	1900	1900	Nil

**RJDT AD 2.14 APPROACH AND RUNWAY LIGHTING**

RWY Designator	APCH LGT type LEN INTST	RTHL Color WBAR	PAPI (VASIS) Angle DIST FM THR MEHT	RTZL LEN	RCLL LEN Spacing Color INTST	REDL LEN Spacing Color INTST	RENL Color WBAR	STWL LEN Color
1	2	3	4	5	6	7	8	9
14	Nil	Green -	PAPI 3.0°/Left 342.8m 61ft	Nil	1900m 30m Coded color (White/Red) LIH	1900m 60m Coded color (White/Yellow) LIH	Red	Nil (*2)
32	Nil (*1)	Green -	PAPI 3.0°/Left 325.8m 61ft	Nil	1900m 30m Coded color (White/Red) LIH	1900m 60m Coded color (White/Yellow) LIH	Red	Nil (*2)
Remarks								
10								
APCH Guidance LGT (90m, 180m and 270m FM RWY THR ) (*1) Overrun area edge LGT (LEN: 60m Color: Red) CGL for RWY 14 RWY THR ID LGT for RWY 14/32 THR (Color: White)								

**RJDT AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY**

1	ABN/IBN location, characteristics and hours of operation	ABN: 341710N/1291929E, White/Green EV4.3sec, HO
2	LDI location and LGT Anemometer location and LGT	LDI: Nil Anemometer: RWY 14: 280m from RWY 14 THR, LGTD RWY 32: 370m from RWY 32 THR, LGTD
3	TWY edge and centerline lighting	TWY edge and center line lights installed, see AD2.9
4	Secondary power supply/ switch-over time	Within 15 sec: All lights
5	Remarks	WDI LGT

**RJDT AD 2.16 HELICOPTER LANDING AREA**

Nil
-----

**RJDT AD 2.17 ATS AIRSPACE**


Designation and lateral limits		Vertical limits (ft)	Airspace classification	ATS unit call sign Language	Remarks
1		2	3	4	6
Tsushima Information Zone	Area within a radius of 5nm(9km) of Tsushima ARP	3,000 or below	E	Tsushima Radio En	

## RJDT AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	Call sign	Frequency	Hours of operation	Remarks
1	2	3	4	5
AFIS	Tsushima Radio	124.3MHz	2230-1200	Operated by Fukuoka Airport Office.

## RJDT AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid (VOR declination)	ID	Frequency	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
VOR (7°W/2008)	VCE	111.45MHz	2230 - 1200	341653.43N 1292013.24E		VOR/DME unusable: 220°-230° beyond 15NM BLW 4000ft 230°-240° beyond 20NM BLW 4000ft
DME	VCE	1138MHz (CH-51Y)	2230 - 1200	341653.43N 1292013.24E	220ft	
LOC 32	IVC	108.7MHz	2230 - 1200	341731.34N 1291917.90E		LOC: 190m(623ft) away FM RWY14 THR, 40m(131ft) SW of RCL, BRG (MAG) 323° Offset angle 0.72°.
LOC-DME 32	IVC	985MHz	2230 - 1200	341731.38N 1291916.62E	215ft	DME: 213m(699ft) away FM RWY14 THR, 61m(200ft) SW of RCL.
MSAS		1575.42MHz	H24			Transmitting antennas are satellite based.



**RJDT AD 2.20 LOCAL TRAFFIC REGULATIONS**

1. Airport regulations

Nil

2. Taxiing to and from stands

Nil

3. Parking area for small aircraft(General aviation)

Nil

4. Parking area for helicopters

Nil

5. Apron - taxiing during winter conditions

Nil

6. Taxiing - limitations

Nil

7. School and training flights - technical test flights - use of runways

Nil

8. Helicopter traffic - limitation

Nil

9. Removal of disabled aircraft from runways

Nil

**RJDT AD 2.21 NOISE ABATEMENT PROCEDURES**

Nil

**RJDT AD 2.22 FLIGHT PROCEDURES****TAKE OFF MINIMA**

	RWY	ACFT CAT	REDL & RCLL		REDL or RCLL or RCL Marking		NII (DAYTIME ONLY)	
			RVR	VIS	RVR	VIS	RVR	VIS
Multi-Engine ACFT with TKOF ALTN AP FILED	14	A,B,C,D	-	400	-	400	-	500
	32							
OTHER	14	A,B,C,D	AVBL LDG MINIMA					
	32							

**RJDT AD 2.23 ADDITIONAL INFORMATION**

Nil

**RJDT AD 2.24 CHARTS RELATED TO AN AERODROME**

- Aerodrome/Heliport Chart
- Standard Departure Chart - Instrument (IKISHIMA, LAGER)
- Standard Departure Chart - Instrument (BAIRI-RNAV)
- Standard Departure Chart - Instrument (SIYAT-RNAV)
- Instrument Approach Chart (LOC Z RWY32)
- Instrument Approach Chart (LOC Y RWY32)
- Instrument Approach Chart (VOR RWY32)
- Instrument Approach Chart (VOR RWY14)
- Instrument Approach Chart (RNP RWY14)
- Other Chart (Visual REP)
- Other Chart (LDG CHART)
- Other Chart (MVA CHART)

**INTENTIONALLY LEFT BLANK**

RJDT / TSUSHIMA

AD CHART



**INTENTIONALLY LEFT BLANK**

STANDARD DEPARTURE CHART - INSTRUMENT

RJDT / TSUSHIMA

SID

IKISHIMA FIVE DEPARTURE

RWY 14 : Climb RWY HDG to 900FT,...

RWY 32 : Climb on HDG 338° to 900FT, turn right HDG 198°,...

...to intercept and proceed via VCE R153 to IKE VOR/DME.

Cross VCE R153/20.0DME at or above 4000FT.

Note RWY 32 : 3.9% climb gradient required up to 900FT.

OBST ALT 525FT located at 1.9NM 306° FM end of RWY 32.

LAGER TWO DEPARTURE

RWY 14 : Climb RWY HDG to 900FT, turn left,...

RWY 32 : Climb on HDG 338° to 900FT, turn right HDG 170°,...

...to intercept and proceed via VCE R125 to LAGER.

Note RWY 32 : 3.9% climb gradient required up to 900FT.

OBST ALT 525FT located at 1.9NM 306° FM end of RWY 32.

CHANGE : IKISHIMA FIVE DEPARTURE, LAGER TWO DEPARTURE



## STANDARD DEPARTURE CHART - INSTRUMENT

RJDT / TSUSHIMA


RNAV SID

## BAIRI ONE DEPARTURE

Basic RNP1

Note GNSS required.

VAR 8°W (2020)

BAIRI ONE DEPARTURE

CHANGE : FIX symbol(IKE).

RWY14 : Climb on HDG144° at or above 600FT, turn right direct to BAIRI at or above 4000FT, to IKE.

RWY32 : Climb on HDG324° at or above 900FT, turn right direct to DT200, to BAIRI at or above 4000FT,to IKE.

Note RWY32 :5.2% climb gradient required up to 900FT.

OBST ALT 262FT located at 0.2NM 292° FM end of RWY32.

STANDARD DEPARTURE CHART - INSTRUMENT

RJDT / TSUSHIMA

RNAV SID

BAIRI ONE DEPARTURE

RWY14

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	144 (136.2)	-7.9	—	—	+600	—	—	Basic RNP1
002	DF	BAIRI	—	—	-7.9	—	R	+4000	—	—	Basic RNP1
003	TF	IKE	—	154 (145.7)	-7.9	18.8	—	—	—	—	Basic RNP1

RWY32

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	324 (316.2)	-7.9	—	—	+900	—	—	Basic RNP1
002	DF	DT200	—	—	-7.9	—	R	—	—	—	Basic RNP1
003	TF	BAIRI	—	169 (161.3)	-7.9	22.0	—	+4000	—	—	Basic RNP1
004	TF	IKE	—	154 (145.7)	-7.9	18.8	—	—	—	—	Basic RNP1

CHANGE : New PROC

## STANDARD DEPARTURE CHART - INSTRUMENT

RJDT / TSUSHIMA


RNAV SID

SIYAT ONE DEPARTURE

Basic RNP1

Note GNSS required.

VAR 8°W (2020)

SIYAT ONE DEPARTURE

RWY14 : Climb on HDG144° at or above 900FT, turn left direct to SIYAT, to LAGER.

RWY32 : Climb on HDG324° at or above 900FT, turn right direct to DT200, to SIYAT, to LAGER.

Note RWY32 : 5.2% climb gradient required up to 900FT.

OBST ALT 262FT located at 0.2NM 292° FM end of RWY32.

CHANGE : FIX symbol(LAGER).

STANDARD DEPARTURE CHART - INSTRUMENT

RJDT / TSUSHIMA

RNAV SID

SIYAT ONE DEPARTURE

RWY14


Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	144 (136.2)	-7.9	—	—	+900	—	—	Basic RNP1
002	DF	SIYAT	—	—	-7.9	—	L	—	—	—	Basic RNP1
003	TF	LAGER	—	126 (118.0)	-7.9	36.8	—	—	—	—	Basic RNP1

RWY32

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	324 (316.2)	-7.9	—	—	+900	—	—	Basic RNP1
002	DF	DT200	—	—	-7.9	—	R	—	—	—	Basic RNP1
003	TF	SIYAT	—	150 (142.0)	-7.9	14.3	—	—	—	—	Basic RNP1
004	TF	LAGER	—	126 (118.0)	-7.9	36.8	—	—	—	—	Basic RNP1


CHANGE : New PROC

INSTRUMENT APPROACH CHART




## INSTRUMENT APPROACH CHART

RJDT / TSUSHIMA




CHANGE : Secondary FREQ abolished(TSUSHIMA RADIO).

INSTRUMENT APPROACH CHART




CHANGE : Secondary FREQ abolished(TSUSHIMA RADIO).

## INSTRUMENT APPROACH CHART



CHANGE : Secondary FREQ abolished(TSUSHIMA RADIO).

INSTRUMENT APPROACH CHART



**INTENTIONALLY LEFT BLANK**

RJDT / TSUSHIMA

Visual REP



CHANGE : Secondary FREQ abolished.

※図中に標高を示す数字がある場合、単位はメートル(m)である。The unit of measurement used to express elevation is meter(m).

Call sign	BRG / DIST from ARP	Remarks
長崎鼻 Nagasakihana	023°T / 8.3NM	灯台 Lighthouse
巣原 Izuhara	200°T / 5.7NM	港 Harbor
10NM SE	135°T / 10.0NM	海上 Over the Sea

RJDT / TSUSHIMA

LDG CHART



RJDT / TSUSHIMA

Minimum Vectoring Altitude CHART

