



AD CHART



STANDARD DEPARTURE CHART -INSTRUMENT



STANDARD DEPARTURE CHART -INSTRUMENT

RJOC / IZUMO

SID

IZUMO REVERSAL FOUR DEPARTURE

RWY07 : Climb RWY HDG to 500FT, turn left to intercept and proceed via XZE R032 to 3000FT, turn left direct to XZE VOR/DME.

Cross XZE VOR/DME at or above 7000FT.

RWY25 : Climb RWY HDG to 1700FT, turn right to intercept and proceed via XZE R260 to XZE 10.5DME, turn right direct to XZE VOR/DME.


Cross XZE VOR/DME at or above 7000FT.

Note RWY07: 4.6% climb gradient required up to 1300FT.


OBST ALT 1074FT located at 4.8NM 029° FM end of RWY07.

RWY25: 4.7% climb gradient required up to 2200FT.

OBST ALT 1838FT located at 6.3NM 280° FM end of RWY25.



STANDARD DEPARTURE CHART - INSTRUMENT



CHANGE : VAR. PROC renamed. PROC course.

STANDARD DEPARTURE CHART - INSTRUMENT

RJOC / IZUMO

RNAV SID and TRANSITION

MATSUE THREE DEPARTURE											
RWY07											
Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	068 (059.3)	-8.6	-	-	+500	-	-	RNP1
002	DF	MIHOU	-	-	-8.6	-	-	+3500	-	-	RNP1
RWY25											
Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	248 (239.3)	-8.6	-	-	+1700	-	-	RNP1
002	DF	OC511	-	-	-8.6	-	R	-	-	-	RNP1
003	TF	MIHOU	-	063 (054.5)	-8.6	6.8	-	+3500	-	-	RNP1
TSUNO TRANSITION											
Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	MIHOU	-	-	-8.6	-	-	+3500	-	-	RNP1
002	TF	KAIKE	-	111 (102.6)	-8.6	9.7	-	+6000	-	-	RNP1
003	TF	TSUNO	-	111 (102.7)	-8.6	43.5	-	+10000	-	-	RNP1

CHANGE : PROC renamed. PROC course. VAR.

STANDARD DEPARTURE CHART - INSTRUMENT

RJOC / IZUMO


RNAV SID

TAKHI TWO DEPARTURE

RNP1

Note GNSS required.

VAR 9°W



45(39) 39(33)
A A
A
33(27)
RWY 25
RWY25: See TAKE OFF MINIMA

CHANGE : PROC renamed. PROC course. VAR.

- RWY07 : Climb on HDG068° at or above 500FT, turn left direct to OC711,
to TAKHI at or above 3000FT.
- RWY25 : Climb on HDG248° at or above 1700FT, turn right direct to OC711,
to TAKHI at or above 3000FT.
- NOTE RWY07 : 4.6% climb gradient required up to 1300FT.
OBST ALT 1074FT located at 4.8NM 029° FM end of RWY07.
- RWY25 : 4.7% climb gradient required up to 2200FT.
OBST ALT 1838FT located at 6.3NM 280° FM end of RWY25.

STANDARD DEPARTURE CHART - INSTRUMENT


RJOC / IZUMO

RNAV SID

TAKHI TWO DEPARTURE											
RWY07											
Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	068 (059.3)	-8.6	-	-	+500	-	-	RNP1
002	DF	OC711	-	-	-8.6	-	L	-	-	-	RNP1
003	TF	TAKHI	-	021 (012.3)	-8.6	18.4	-	+3000	-	-	RNP1
RWY25											
Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	248 (239.3)	-8.6	-	-	+1700	-	-	RNP1
002	DF	OC711	-	-	-8.6	-	R	-	-	-	RNP1
003	TF	TAKHI	-	021 (012.3)	-8.6	18.4	-	+3000	-	-	RNP1

CHANGE : PROC renamed. PROC course. VAR.

STANDARD DEPARTURE CHART - INSTRUMENT



CHANGE : PROC renamed. PROC course. VAR.

STANDARD DEPARTURE CHART - INSTRUMENT

RJOC / IZUMO

RNAV SID

SAIGO TWO DEPARTURE

RWY07


Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	068 (059.3)	-8.6	-	-	+500	-	-	RNP1
002	DF	OC712	-	-	-8.6	-	L	-	-	-	RNP1
003	TF	OC713	-	042 (033.7)	-8.6	17.2	-	-	-	-	RNP1
004	TF	SAIGO	-	042 (033.8)	-8.6	18.2	-	+6000	-	-	RNP1

RWY25

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	248 (239.3)	-8.6	-	-	+1700	-	-	RNP1
002	DF	OC713	-	-	-8.6	-	R	-	-	-	RNP1
003	TF	SAIGO	-	042 (033.8)	-8.6	18.2	-	+6000	-	-	RNP1

CHANGE : PROC renamed. PROC course. VAR.

STANDARD DEPARTURE CHART - INSTRUMENT



STANDARD DEPARTURE CHART - INSTRUMENT

RJOC / IZUMO

RNAV SID and TRANSITION

KYOKA TWO DEPARTURE

RWY07

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	068 (059.3)	-8.6	-	-	+500	-	-	RNP1
002	DF	OC715	-	-	-8.6	-	L	-	-	-	RNP1
003	TF	OC716	-	248 (239.3)	-8.6	4.0	-	-	-	-	RNP1
004	TF	KYOKA	-	162 (153.6)	-8.6	16.4	-	+5000	-	-	RNP1

RWY25


Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	248 (239.3)	-8.6	-	-	+1600	-	-	RNP1
002	DF	KYOKA	-	-	-8.6	-	L	+5000	-	-	RNP1

CARPS TRANSITION

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	KYOKA	-	-	-8.6	-	-	+5000	-	-	RNP1
002	TF	CARPS	-	217 (208.4)	-8.6	52.7	-	+7000	-	-	RNP1

CHANGE : PROC renamed. PROC course. VAR.

STANDARD ARRIVAL CHART - INSTRUMENT




STANDARD ARRIVAL CHART - INSTRUMENT

RJOC / IZUMO

RNAV STAR RWY07

OKUNI ARRIVAL	RNP1
---------------	------

Note GNSS required.



From RAKDA, to YOKAI at or above 7000FT, to WATCH, to OKUNI at or above 4000FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	RAKDA	—	—	-8.6	—	—	—	—	—	RNP1
002	TF	YOKAI	—	286 (277.8)	-8.6	20.1	—	+7000	—	—	RNP1
003	TF	WATCH	—	286 (277.6)	-8.6	12.2	—	—	—	—	RNP1
004	TF	OKUNI	—	246 (237.3)	-8.6	20.7	—	+4000	—	—	RNP1

CHANGE : PROC course. VAR.


STANDARD ARRIVAL CHART - INSTRUMENT

RJOC / IZUMO

RNAV STAR RWY25

NAKAU ARRIVAL	RNP1
---------------	------

Note GNSS required.



From RAKDA, to NAKAU at or above 4000FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	RAKDA	—	—	-8.6	—	—	—	—	—	RNP1
002	TF	NAKAU	—	282 (273.9)	-8.6	23.4	—	+4000	—	—	RNP1


CHANGE : VAR.

RJOC / IZUMO

LOC Z RWY25



INSTRUMENT APPROACH CHART




CHANGE : VAR.


INSTRUMENT APPROACH CHART

RJOC / IZUMO

VOR RWY25



INSTRUMENT APPROACH CHART



INSTRUMENT APPROACH CHART

RJOC / IZUMO

RNP RWY07

FAS DATA BLOCK

Operation type	0	LTP/FTP ellipsoidal height	+00360
SBAS service provider identifier	2	FPAP latitude	352505.7945N
Airport identifier	RJOC	FPAP longitude	1325358.0770E
Runway	07	Threshold crossing height	00015.0
Approach performance designator	0	TCH units selector	1
Route indicator		Glide path angle	03.00
Reference path data selector	0	Course width at threshold	105.00
Reference path ID	M07A	∟ length offset	0000
LTP/FTP latitude	352432.8070N	HAL	40.0
LTP/FTP longitude	1325249.8095E	VAL	50.0
CRC remainder	30102B24		

Required additional data


LTP/FTP orthometric height	1.4
----------------------------	-----

CHANGE : FAS DATA BLOCK, Required additional data established.

INSTRUMENT APPROACH CHART

RJOC / IZUMO


RNP RWY25



MISSED APPROACH

Direct to OC553, turn right,
direct to XZE and hold at 3000FT.
Contact IZUMO RADIO.

VDP
2.0NM to THR (CAT A, B, C)
2.1NM to THR (CAT D)



Missed APCH climb gradient MNM 5.0%

MINIMA			THR elev. 15				AD elev. 6	
CAT	LPV		LNAV/VNAV		LNAV		CIRCLING	
	DA(H)	CMV	DA(H)	CMV	MDA(H)	CMV	MDA(H)	VIS
A	265 (250)	800	370 (355)	900	670 (664)	1200	670 (664)	1600
B				1000		1400		
C								2400
D		1200	405 (390)	1400	710 (704)	1800	710 (704)	3200

Circling to NORTH side of RWY only.

MINIMA with Missed APCH climb gradient of 2.5% are not established.

CHANGE : DIST FM FUMAI to RWY25 in plan view.

INSTRUMENT APPROACH CHART

RJOC / IZUMO

RNP RWY25


FAS DATA BLOCK			
Operation type	0	LTP/FTP ellipsoidal height	+00389
SBAS service provider identifier	2	FPAP latitude	352432.8070N
Airport identifier	RJOC	FPAP longitude	1325249.8095E
Runway	25	Threshold crossing height	00015.0
Approach performance designator	0	TCH units selector	1
Route indicator		Glide path angle	03.00
Reference path data selector	0	Course width at threshold	105.00
Reference path ID	M25A	∠ length offset	0000
LTP/FTP latitude	352505.7945N	HAL	40.0
LTP/FTP longitude	1325358.0770E	VAL	50.0
CRC remainder	F401BF48		

Required additional data	
LTP/FTP orthometric height	4.3

CHANGE : FAS DATA BLOCK, Required additional data established.

RJOC / IZUMO

Visual REP



※図中に標高を示す数字がある場合、単位はメートル(m)である。The unit of measurement used to express elevation is meter(m).


CHANGE : VAR.

Call sign	BRG / DIST from ARP	Remarks
一畑薬師 Ichibatayakushi	351°T / 5.0NM	寺 Temple
松江 Matsue	064°T / 8.7NM	城 Castle
日御碕 Hinomisaki	275°T / 12.8NM	灯台 Lighthouse
出雲市駅 Izumoshi Eki	244°T / 7.2NM	JR駅 Station
三刀屋木次 Mitoyakisuki	180°T / 7.0NM	IC Interchange



RJOC / IZUMO Minimum Vectoring Altitude CHART

VAR 9°W (2024)



CENTER: 353003N/1331413E (RJOC RADAR SITE)

CHANGE : VAR.