

## RJOC / IZUMO

## AD CHART



STANDARD DEPARTURE CHART -INSTRUMENT

RJOC / IZUMO

SID

DOZEN FOUR DEPARTURE

RWY07 : Climb RWY HDG to 500FT, turn left ...

RWY25 : Climb RWY HDG to 1700FT, turn right HDG077°...

... to intercept and proceed via XZE R032(OIE R213) to DOZEN.

Cross DOZEN at or above 5000FT.

Note RWY07: 4.6% climb gradient required up to 1300FT.

OBST ALT 1074FT located at 4.8NM 028° FM end of RWY07.

RWY25: 4.7% climb gradient required up to 2200FT.

OBST ALT 1838FT located at 6.3NM 279° FM end of RWY25.



## STANDARD DEPARTURE CHART -INSTRUMENT

RJOC / IZUMO

SID

IZUMO REVERSAL FOUR DEPARTURE

RWY07 : Climb RWY HDG to 500FT, turn left to intercept and proceed via XZE R032 to 3000FT, turn left direct to XZE VOR/DME.

Cross XZE VOR/DME at or above 7000FT.

RWY25 : Climb RWY HDG to 1700FT, turn right to intercept and proceed via XZE R260 to XZE 10.5DME, turn right direct to XZE VOR/DME.


Cross XZE VOR/DME at or above 7000FT.

Note RWY07: 4.6% climb gradient required up to 1300FT.


OBST ALT 1074FT located at 4.8NM 028° FM end of RWY07.

RWY25: 4.7% climb gradient required up to 2200FT.

OBST ALT 1838FT located at 6.3NM 279° FM end of RWY25.

IZUMO REVERSAL FOUR DEPARTURE

STANDARD DEPARTURE CHART - INSTRUMENT



## STANDARD DEPARTURE CHART - INSTRUMENT

## RJOC / IZUMO

## RNAV SID and TRANSITION

MATSUE TWO DEPARTURE

## RWY07

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	067 (059.3)	-7.6	—	—	+500	—	—	Basic RNP1
002	DF	MIHOU	—	—	-7.6	—	—	+3500	—	—	Basic RNP1

## RWY25

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	247 (239.3)	-7.6	—	—	+1700	—	—	Basic RNP1
002	DF	OC511	—	—	-7.6	—	R	—	—	—	Basic RNP1
003	TF	MIHOU	—	062 (054.5)	-7.6	6.8	—	+3500	—	—	Basic RNP1

TSUNO TRANSITION

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	MIHOU	—	—	-7.6	—	—	+3500	—	—	Basic RNP1
002	TF	KAIKE	—	110 (102.6)	-7.6	9.7	—	+6000	—	—	Basic RNP1
003	TF	TSUNO	—	110 (102.7)	-7.6	43.5	—	+10000	—	—	Basic RNP1

STANDARD DEPARTURE CHART - INSTRUMENT



CHANGE : FIX symbol(TAKHI).

## STANDARD DEPARTURE CHART - INSTRUMENT

RJOC / IZUMO

RNAV SID

TAKHI ONE DEPARTURE

## RWY07

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	067 (059.3)	-7.6	—	—	+500	—	—	Basic RNP1
002	DF	OC711	—	—	-7.6	—	L	—	—	—	Basic RNP1
003	TF	TAKHI	—	020 (012.3)	-7.6	18.4	—	+3000	—	—	Basic RNP1

## RWY25

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	247 (239.3)	-7.6	—	—	+1700	—	—	Basic RNP1
002	DF	OC711	—	—	-7.6	—	R	—	—	—	Basic RNP1
003	TF	TAKHI	—	020 (012.3)	-7.6	18.4	—	+3000	—	—	Basic RNP1

STANDARD DEPARTURE CHART - INSTRUMENT

RJOC / IZUMO


RNAV SID

SAIGO ONE DEPARTURE

Basic RNP1

Note GNSS required.

VAR 8°W (2014)



SAIGO ONE DEPARTURE

- RWY07 : Climb on HDG067° at or above 500FT, turn left direct to OC712, to OC713, to SAIGO at or above 6000FT.
- RWY25 : Climb on HDG247° at or above 1700FT, turn right direct to OC713, to SAIGO at or above 6000FT.
- NOTE RWY07 : 4.6% climb gradient required up to 800FT.  
OBST ALT 1214FT located at 6.8NM 044° FM end of RWY07.
- RWY25 : 4.7% climb gradient required up to 2200FT.  
OBST ALT 1838FT located at 6.3NM 279° FM end of RWY25.

CHANGE : FIX symbol(SAIGO).



## STANDARD DEPARTURE CHART - INSTRUMENT

RJOC / IZUMO

RNAV SID

SAIGO ONE DEPARTURE


## RWY07

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	067 (059.3)	-7.6	—	—	+500	—	—	Basic RNP1
002	DF	OC712	—	—	-7.6	—	L	—	—	—	Basic RNP1
003	TF	OC713	—	041 (033.7)	-7.6	17.2	—	—	—	—	Basic RNP1
004	TF	SAIGO	—	041 (033.8)	-7.6	18.2	—	+6000	—	—	Basic RNP1

## RWY25

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	247 (239.3)	-7.6	—	—	+1700	—	—	Basic RNP1
002	DF	OC713	—	—	-7.6	—	R	—	—	—	Basic RNP1
003	TF	SAIGO	—	041 (033.8)	-7.6	18.2	—	+6000	—	—	Basic RNP1

STANDARD DEPARTURE CHART - INSTRUMENT



CHANGE : FIX symbol(KYOKA).

## STANDARD DEPARTURE CHART - INSTRUMENT

## RJOC / IZUMO

## RNAV SID and TRANSITION

KYOKA ONE DEPARTURE

## RWY07

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	067 (059.3)	-7.6	—	—	+500	—	—	Basic RNP1
002	DF	OC715	—	—	-7.6	—	L	—	—	—	Basic RNP1
003	TF	OC716	—	247 (239.3)	-7.6	4.0	—	—	—	—	Basic RNP1
004	TF	KYOKA	—	161 (153.6)	-7.6	16.4	—	+5000	—	—	Basic RNP1

## RWY25

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	247 (239.3)	-7.6	—	—	+1600	—	—	Basic RNP1
002	DF	KYOKA	—	—	-7.6	—	L	+5000	—	—	Basic RNP1

CARPS TRANSITION

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	KYOKA	—	—	-7.6	—	—	+5000	—	—	Basic RNP1
002	TF	CARPS	—	216 (208.4)	-7.6	52.7	—	+7000	—	—	Basic RNP1

STANDARD ARRIVAL CHART - INSTRUMENT



STANDARD ARRIVAL CHART - INSTRUMENT

RJOC / IZUMO


RNAV STAR RWY07

OKUNI ARRIVAL

Basic RNP1

Note GNSS required.

VAR 8°W (2016)




OKUNI ARRIVAL

From RAKDA, to YOKAI at or above 7000FT, to WATCH, to OKUNI at or above 4000FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	RAKDA	—	—	-7.9	—	—	—	—	—	Basic RNP1
002	TF	YOKAI	—	286 (277.8)	-7.9	20.1	—	+7000	—	—	Basic RNP1
003	TF	WATCH	—	285 (277.6)	-7.9	12.2	—	—	—	—	Basic RNP1
004	TF	OKUNI	—	245 (237.3)	-7.9	20.7	—	+4000	—	—	Basic RNP1

CHANGE : FIX symbol(OKUNI).

STANDARD ARRIVAL CHART - INSTRUMENT



NAKAU ARRIVAL

From RAKDA, to NAKAU at or above 4000FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	RAKDA	—	—	-7.6	—	—	—	—	—	Basic RNP1
002	TF	NAKAU	—	282 (273.9)	-7.6	23.4	—	+4000	—	—	Basic RNP1

CHANGE : FIX symbol(NAKAU).

## INSTRUMENT APPROACH CHART

RJOC / IZUMO

LOC Z RWY25



## INSTRUMENT APPROACH CHART

RJOC / IZUMO

LOC Y RWY25



NM to IXZ	MAPt	2	3	4	5	6	FAF
ALT (3.0° APCH Path)	—	317	635	954	1272	1591	1751

## MISSED APPROACH

Climb on HDG247° to 1600FT,  
turn right direct to XZE  
VOR/DME and hold at 3000FT.  
Contact IZUMO RADIO.

Timing not authorized for defining the  
MAPt.



DME to IXZ	1.2	1.5	1.9	6.5	10.1
NM to THR	0	0.3	0.6	5.3	9.0

Missed APCH climb gradient MNM 5.0%

MINIMA		THR elev. 15	AD elev. 6	
CAT			CIRCLING	
	MDA(H)	CMV	MDA(H)	VIS
A	270 (264)	800	390 (384)	1600
B			460 (454)	
C			560 (554)	
D		1200	630 (624)	3200

Circling to NORTH side of RWY only.

MINIMA with Missed APCH climb gradient of 2.5% are not established.



## INSTRUMENT APPROACH CHART

RJOC / IZUMO

VOR RWY25



## RJOC / IZUMO

RNP RWY07

<b>MIHO APP</b> 120.1 – 125.4 258.2 – 317.8	<b>RNP APCH</b>	<b>IZUMO RADIO</b> 122.7 – 126.2	<b>RADAR AVBL</b>
---	-----------------	-------------------------------------	-------------------

Baro-VNAV not authorized below -10°C

**VAR 8°W (2016)**

OKUNI	352412.59N
(IAF)	1323743.79E
SUSAR	351355.52N
(IAF)	1325118.61E
ENMUH	351352.39N
	1324512.46E
OC750	351627.49N
	1324320.47E
SUBIE	351902.56N
(IF)	1324128.37E
ENYAH	352135.67N
(FAF)	1324643.83E
OC751	352255.02N
	1324927.62E
RW07	352432.83N
(MAPt)	1325249.80E
OC753	352751.24N
(MATF)	1325940.95E
XZE	352502.06N
(MAHF)	1325332.54E

**Using NAVAID**

MHA 4000  
Maximum holding altitude 6000  
MAX 210KIAS

**TACAN MIHO**  
1201 JET  
CH-114X  
35°31'52"N/133°05'39"E

**MATSUE CITY**  
1086

**MSA 25NM**  
5400  
ARP

ARP : 352449N/1325324E

**RNAV HLDG**

MHA 3000  
MAX 210KIAS

1MIN 242°

IZUMO (XZE)

NOT TO SCALE

**Using NAVAID**

MHA 4300  
Maximum holding altitude 7000  
MAX 210KIAS

**SUSAR (IAF) 4300**

R197/D11.3 XZE

NM to Next Fix	FAF	5	4	3	2	MAPt
ALT (3.0° APCH Path)	1900	1647	1329	1010	692	—

**MISSED APPROACH**

Climb direct to OC753, turn left direct to XZE and hold at 3000FT. Contact IZUMO RADIO.

(For using VOR/DME)

Climb to 1300FT via XZE R067, turn left, direct to XZE VOR/DME and hold at 3000FT. Contact IZUMO RADIO.

MINIMA		THR elev. 6		AD elev. 6	
CAT	LNAV/VNAV	LNAV	CIRCLING	MDA(H)	VIS
A	510 (504)	1500	510 (504)	1500	510 (504)
B					1600
C					2400
D					3200

Circling to NORTH side of RWY only.

CHANGE:PROC renamed. Requirement for RNP.

## INSTRUMENT APPROACH CHART



RJOC / IZUMO

Visual REP



※図中に標高を示す数字がある場合、単位はメートル(m)である。The unit of measurement used to express elevation is meter(m).

Call sign	BRG / DIST from ARP	Remarks
一畑薬師 Ichibatayakushi	351°T / 5.0NM	寺 Temple
松江 Matsue	064°T / 8.7NM	城 Castle
日御碕 Hinomisaki	275°T / 12.8NM	灯台 Lighthouse
出雲市駅 Izumoshi Eki	244°T / 7.2NM	JR駅 Station
三刀屋木次 Mitoyakisuki	180°T / 7.0NM	IC Interchange

CHANGE : Map updated. BRG/DIST from ARP. Mitoyakisuki established. Kisuki abolished.

RJOC / IZUMO

LDG CHART



RJOC / IZUMO

Minimum Vectoring Altitude CHART

