

RJBD / NANKI-SHIRAHAMA

AD CHART



**INTENTIONALLY LEFT BLANK**

STANDARD DEPARTURE CHART - INSTRUMENT

RJBD / NANKI-SHIRAHAMA

SID

NANKI REVERSAL THREE DEPARTURE

RWY15 : Climb on HDG163° to NKE 4.0DME, turn right,...

RWY33 : Climb RWY HDG to 1500FT, turn left,....

...direct to NKE VOR/DME.

Cross NKE VOR/DME at or above 4000FT.

Note RWY15 : 5.8% climb gradient required up to 1300FT.

OBST ALT 984FT located at 3.1NM 139° FM end of RWY15.



## STANDARD DEPARTURE CHART - INSTRUMENT

RJBD / NANKI-SHIRAHAMA

RNAV SID

## KUSHIMOTO ONE DEPARTURE

Basic RNP1

Note GNSS required.



## KUSHIMOTO ONE DEPARTURE

RWY15 : Climb on HDG148° at or above 2100FT, turn left direct to KEC.

RWY33 : Climb on HDG328° at or above 800FT, turn left direct to BD300, to BD301 at or above 5000FT, to KEC.

Note RWY15 : 6.1% climb gradient required up to 2100FT.

OBST ALT 1641FT located at 4.3NM 138° FM end of RWY15.

OBST ALT 1903FT located at 4.2NM 119° FM end of RWY15.

## RWY15

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	148 (140.1)	-7.3	—	—	+2100	—	—	Basic RNP1
002	DF	KEC	—	—	-7.3	—	L	—	—	—	Basic RNP1

## RWY33

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	328 (321.1)	-7.3	—	—	+800	—	—	Basic RNP1
002	DF	BD300	—	—	-7.3	—	L	—	—	—	Basic RNP1
003	TF	BD301	—	116 (108.7)	-7.3	7.3	—	+5000	—	—	Basic RNP1
004	TF	KEC	—	116 (108.8)	-7.3	20.3	—	—	—	—	Basic RNP1

STANDARD ARRIVAL CHART - INSTRUMENT

RJBD / NANKI-SHIRAHAMA


RNAV STAR

RAYJO NORTH ARRIVAL / RAYJO SOUTH ARRIVAL

Basic RNP1

Note GNSS required.

VAR 7° W(2017)



RAYJO NORTH ARRIVAL

From RAYJO, to YATAR at or above 7000FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	RAYJO	—	—	-7.3	—	—	—	—	—	Basic RNP1
002	TF	YATAR	—	276 (268.6)	-7.3	26.7	—	+7000	—	—	Basic RNP1

RAYJO SOUTH ARRIVAL

From RAYJO, to MUROH at or above 7000FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	RAYJO	—	—	-7.3	—	—	—	—	—	Basic RNP1
002	TF	MUROH	—	249 (241.5)	-7.3	19.1	—	+7000	—	—	Basic RNP1

CHANGE : FIX symbol(MUROH, YATAR).

**INTENTIONALLY LEFT BLANK**

INSTRUMENT APPROACH CHART

RJBD / NANKI-SHIRAHAMA

LOC RWY15



## RJBD / NANKI-SHIRAHAMA

VOR RWY15


Civil Aviation Bureau, Japan (EFF:8 OCT 2020)



INSTRUMENT APPROACH CHART

RJBD / NANKI-SHIRAHAMA

VOR A



## INSTRUMENT APPROACH CHART

RJBD / NANKI-SHIRAHAMA

RNP RWY15



CHANGE:PROC renamed. Requirement for RNP.

## RJBD / NANKI-SHIRAHAMA

RNP RWY33




Figure 1 is a graph showing the relationship between the number of nodes (N) and the number of hops (H) for various network topologies. The x-axis represents the number of nodes (N) on a logarithmic scale from 10<sup>0</sup> to 10<sup>4</sup>. The y-axis represents the number of hops (H) on a linear scale from 0 to 10. The graph includes data for NKE, VDP (1.0NM to MAPt), BD351 (IF), BD350, BD352 PANDA (LNAV) (FAF), BD353 (LNAV) (LNAV), BD354 (MAPt), RDH50, and MUROH (IAF). A dashed line indicates a 249-degree angle, and a solid line indicates a 313-degree angle. A shaded area represents the range of hops for a given number of nodes.

MINIMA		THR elev. 274		AD elev. 293		
CAT	LNAV/VNAV		LNAV		CIRCLING	
	DA(H)	CMV	MDA(H)	CMV	MDA(H)	VIS
A	Not applicable		860 (586)	1500	860 (567)	1600
B						
C					2400	
D				2000	1150 (857)	3200

Circling to WEST side of RWY only.

**INTENTIONALLY LEFT BLANK**

RJBD / NANKI SHIRAHAMA


Visual REP



※図中に標高を示す数字がある場合、単位はメートル(m)である。The unit of measurement used to express elevation is meter(m).

CHANGE : Map updated. BRG/DIST from ARP.

Call sign	BRG / DIST from ARP	Remarks
切目 Kirime	318°T / 9.9NM	岬 Cape
南部 Minabe	342°T / 6.6NM	JR駅 Station
生馬 Ikuma	062°T / 3.8NM	橋 Truss-bridge
合川 Gogawa	083°T / 10.0NM	ダム Dam
10NM W	270°T / 10.0NM	海上 Over the Sea
椿 Tsubaki	161°T / 3.7NM	高層ビル High Building
日置 Hiki	143°T / 7.2NM	日置川河口中洲 River-mouth



注：南紀白浜空港の西側に廃止された滑走路が(なお、禁止標識が5カ所設置されている)視認できる状態にあるので、南紀白浜空港に着陸する航空機は当該滑走路と誤認しないように注意すること。

NOTE : There is remained the abolished runway with 5 cross[×] markings at west side of Nanki-Shirahama Airport. As the abolished runway in shape is visible, the aircraft which will land on Nanki-Shirahama Airport shall pay a special attention not to confuse the runway.

RJBD / NANKI-SHIRAHAMA

Minimum Vectoring Altitude CHART



**INTENTIONALLY LEFT BLANK**