

AD CHART

MINAMIDAITO AP



REMARKS :	WIDTH OF RWY	1500m x 45m
	WIDTH OF TWY	18m x 77.5m
	RWY GROOVING	1500m x 30m
	STRENGTH OF RWY	PCN 19/F/B/Y/T
	STRENGTH OF TWY	PCN 19/F/B/Y/T
	STRENGTH OF APRON	PCN 19/F/B/Y/T

LONGITUDINAL PROFILE OF RWY



STANDARD DEPARTURE CHART -INSTRUMENT

ROMD / MINAMIDAITO

SID

TOPAT THREE DEPARTURE

RWY02 : Climb RWY HDG to 600FT, turn left HDG234°...
RWY20 : Climb RWY HDG to 600FT, turn right HDG324°...
... to intercept and proceed via MDE R279 to TOPAT.
Cross TOPAT at or above 8000FT.



TOPAT THREE DEPARTURE

8000

△ ← 279°
TOPAT
R279/D97.8 MDE
R103/D98.8 NHC

HDG234°

R279

HDG324°

VOR/DME
MINAMIDAITO
117.8 MDE
CH-125X
25°51'16"N/131°15'50"E
200FT

600

600



STANDARD DEPARTURE CHART -INSTRUMENT

ROMD / MINAMIDAITO

SID

MINAMIDAITO REVERSAL FOUR DEPARTURE

RWY 02 : Climb RWY HDG to 1000FT, turn right...
RWY 20 : Climb RWY HDG to 1000FT, turn left...
... direct to MDE VOR/DME.
Cross MDE VOR/DME at or above 2000FT.

MINAMIDAITO REVERSAL FOUR DEPARTURE

STANDARD DEPARTURE CHART - INSTRUMENT

ROMD / MINAMIDAITO

RNAV SID

CORCO SOUTH ONE DEPARTURE

Basic RNP1

Note GNSS required.

VAR 5°W (2015)

CORCO SOUTH ONE DEPARTURE

RWY02 : Climb on HDG021° at or above 600FT, turn left direct to CORCO at or above 5000FT.

RWY20 : Climb on HDG201° at or above 600FT, turn right direct to CORCO at or above 5000FT.

RWY02

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	021 (015.6)	-4.9	—	—	+600	—	—	Basic RNP1
002	DF	CORCO	—	—	-4.9	—	L	+5000	—	—	Basic RNP1

RWY20

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	201 (195.6)	-4.9	—	—	+600	—	—	Basic RNP1
002	DF	CORCO	—	—	-4.9	—	R	+5000	—	—	Basic RNP1

ROMD / MINAMIDAITO

VOR RWY02




MINIMA					THR elev. 167	AD elev. 158
CAT			CIRCLING			
	MDA(H)	CMV	MDA(H)	VIS		
A	550 (392)	1500	600 (442)	1600		
B			610 (452)			
C			1800	620 (462)	2400	
D	—	—	—	—		

INSTRUMENT APPROACH CHART

ROMD / MINAMIDAITO

VOR RWY20



NM to MDE	MAPt	2	FAF
ALT (3.0° APCH Path)	—	851	1169

MISSED APPROACH

Climb via MDE R209 to 1500FT,
turn left, direct to MDE VOR/DME
and hold at 2000FT.
Contact DAITO REMOTE

Timing not authorized for defining the MAPt.



DME to/from MDE	0.1 0	3.0
NM to THR	0 0.1	3.1

MINIMA THR elev. 149 AD elev. 158


CAT	CIRCLING		CIRCLING	
	MDA(H)	CMV	MDA(H)	VIS
A	550 (401)	1500	600 (442)	1600
B			610 (452)	
C	560 (411)	1800	620 (462)	2400
D	—	—	—	—

CHANGE : COM

INSTRUMENT APPROACH CHART

ROMD / MINAMIDAITO

RNAV(GNSS) RWY02



CHANGE : COM

INSTRUMENT APPROACH CHART

ROMD / MINAMIDAITO

RNAV(GNSS) RWY20



CHANGE : COM

ROMD / MINAMI DAITO

Visual REP



Call sign	BRG / DIST from ARP	Remarks
10NM N	000°/10NM	海上 Over the sea
10NM W	270°/10NM	海上 Over the sea
北大東島 Kitadaitojima	035°/6.7NM	北大東空港 Kitadaito Airport

Minimum Vectoring Altitude CHART

