



RODN / KADENA

AD CHART



STANDARD DEPARTURE CHART -INSTRUMENT

RODN / KADENA



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWY 05L/05R: Climb heading 055° to KAD VORTAC 5 DME then turn right to intercept the KAD R-066 outbound to JILEE. Cross JILEE at or below 10,000 or altitude specified by ATC.

CHANGE : Update.

NOTE: REPRINTING DOD FLIP

STANDARD DEPARTURE CHART -INSTRUMENT

RODN / KADENA

ATIS ★ 124.2 280.5
CLNC DEL
123.3 235.0
GND CON
118.5 275.8
TOWER
134.1 315.8
NAHA DEP CON
119.1 335.8 (NW)
126.5 258.3 (SE)



TUCOF THREE DEPARTURE

Rwy	Knots	60	120	180	240	300	360
23L	V/V(fpm)	491	982	1473	1964	2455	2946
23R	V/V(fpm)	499	998	1497	1996	2495	2994

ATC Climb Rate to 2700 at 6.4 DME

666

KADENA
112.0 KAD
Chan 57



TLv FL140
TA 14,000

CHANGE : Update.



DEPARTURE ROUTE DESCRIPTION

TAKEOFF Rwy 23L/23R: Climb on KAD R-235 to 10,000, cross SNUUP at or above 2700 and TUCOF at or below 10,000 or altitude specified by ATC.

NOTE: REPRINTING DOD FLIP

STANDARD DEPARTURE CHART -INSTRUMENT

RODN/KADENA



ATIS★ 124.2 280.5
CLNC DEL
123.3 235.0
GND CON
118.5 275.8
TOWER
134.1 315.8
NAHA DEP CON
119.1 335.8 (NW)
126.5 258.3 (SW)

EKOLU THREE DEPARTURE

Rwy	Knots	60	120	180	240	300	360
23L ㊤	V/V(fpm)	205	410	615	820	1025	1230
23L ㊦	V/V(fpm)	455	910	1365	1820	2275	2730
23R ㊤	V/V(fpm)	206	412	618	824	1030	1236
23R ㊦	V/V(fpm)	460	920	1380	1840	2300	2760

ATC Climb Rate
㊤ to EKOLU to 2700
㊦ to EKAHI to 2200

1194



TLv FL140
TA 14,000

CHANGE : Update



DEPARTURE ROUTE DESCRIPTION


TAKEOFF RWY 23L/23R: Climb left turn to intercept KAD VORTAC R-224 to EKOLU. Cross EKAHI at or above 2200 not to exceed 10,000, cross EKOLU at or above 2700 not to exceed 10,000, or altitude specified by ATC.

NOTE: REPRINTING DOD FLIP

STANDARD DEPARTURE CHART -INSTRUMENT

RODN / KADENA

CUNЕК FOUR DEPARTURE(RNAV1)




STANDARD DEPARTURE CHART -INSTRUMENT

RODN / KADENA

ATIS ★ 124.2 280.5
CLNC DEL
123.3 235.0
GND CON
118.5 275.8
TOWER
134.1 315.8
NAHA DEP CON
119.1 335.8 (NW)
126.5 258.3 (SE)

HIVAS FOUR DEPARTURE (RNAV1)

RNAV1 - GPS
RADAR required (for non-GPS acft)



TLv FL140
TA 14,000



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWY 05R: Climb direct CAMDA, then track 073° to HIVAS. Cross HIVAS at or above 2800 not to exceed 10,000, or altitude assigned by ATC.

CHANGE : Update.

NOTE: REPRINTING DOD FLIP

INTENTIONALLY LEFT BLANK


RODN / KADENA

CHANGE : Update.

NOTE: REPRINTING DOD FLIP

INSTRUMENT APPROACH CHART

RODN / KADENA



CHANGE : Update.

NOTE: REPRINTING DOD FLIP


RODN / KADENA

VOR or TACAN RWY05R

MISSED APPROACH: Climb to 6000 on KAD VORTAC R-055 to IMONO and hold.

ASR

ATC climb of 260 ft/NM to 6000



6000
↑
KAD
R-055

IMONO
KAD
20

TLv FL140
TA 14 000





Diagram illustrating the layout of HIRL (High Intensity Runway Lighting) and REIL (Runway End Identifier Lights) for runways 05L, 05R, 23L, and 23R. The diagram shows the runway alignment, lighting systems, and associated towers (TWR 312 and 321). The runways are labeled with their dimensions: 12,101 x 300 and 12,101 x 200. The diagram also indicates the heading of 050° and the presence of a 241° heading.

NOTE: REPRINTING DOD FLIP

INSTRUMENT APPROACH CHART



RODN / KADENA



NOTE: REPRINTING DOD FLIP

INSTRUMENT APPROACH CHART

RODN / KADENA

APCH CRS 056°		Rwy Idg 12,101 TDZE 93 Arprt Elev 143	RNAV(GPS) RWY05L			
RNP APCH - GPS			SSALR 	MISSED APPROACH: Climbing right turn to 6000 direct BYYRD and hold. Continue climb-in-hold to 6000.		
RADAR required						
 * When ALS inop increase CAT A RVR to 40, vis to 3/4 mile; CAT B RVR to 45, vis to 7/8 mile; CAT C RVR to 50, vis to 1 mile; CAT D RVR to 55, vis to 1 mile; CAT E RVR to 60, vis to 1 1/8 miles.						
ATIS★ 124.2 280.5		NAHA APP CON/DEP CON 119.1 335.8 (NW) 126.5 258.3 (SE)	TOWER 134.1 315.8	GND CON 118.5 275.8	CLNC DEL 123.3 235.0	ASR


** When ALS inop increase CAT AB RVR to 55, vis to 1 mile; CAT CDE RVR to 60, vis to 1 1/8 miles.

*** Circling not authorized NW of Rwy 05L-23R

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 7° C or above 54° C.

RADAR required for holding at BYYRD above 10,000 when W178/178A is active.

RADAR required for holding at ADYEK above 10,000 when W174 is active.



EMERG SAFE ALT 100 NM 2700

CIRUG		TLv FL140 TA 14,000	6000	BYYRD	ELEV 143	TDZE 93
3000		052°	WITOT	2200	GP 2.88° TCH 56	1.3 NM to RWY05L
		056°			6.8 NM	
CATEGORY	A	B	C	D	E	
LNAV/VNAV DA*	353/24 260 (300-½)	384/24 291 (300-½)	421/26 328 (300-½)	439/30 346 (300-¾)	476/35 383 (400-¾)	
LNAV MDA**	500/24	407 (400-½)	500/40	407	(400-¾)	
■ CIRCLING***	780-1 637 (700-1)	920-1 777 (800-1)	940-2¼ 797 (800-2¼)	940-2½ 797 (800-2½)	1000-3 857 (900-3)	

CHANGE : Update.

NOTE: REPRINTING DOD FLIP

INSTRUMENT APPROACH CHART

RODN / KADENA


APCH CRS	Rwy ldg	12,101
055°	TDZE	106
	Arpt Elev	143

RNAV (GPS) RWY05R

RNP APCH - GPS	MISSED APPROACH: Climb to 6000 direct BYYRD and hold. Continue climb-in-hold to 6000.
RADAR required	
* Circling not authorized NW of RWY 05L-23R.	

ATIS★ 124.2 280.5	NAHA APP CON/DEP CON 119.1 335.8 (NW) 126.5 258.3 (SE)	TOWER 134.1 315.8	GND CON 118.5 275.8	CLNC DEL 123.3 235.0	ASR
----------------------	--	----------------------	------------------------	-------------------------	-----

For uncompensated
Baro-VNAV systems,
LNAV/VNAV NA below
7° C or above 54° C.



EMERG SAFE ALT 100 NM 2700

CIRUG	VGSi and RNAV glidepath not coincident (VGSi angle 3.00/TCH 60).		TLv FL140 TA 14,000	6000	BYYRD	ELEV 143	TDZE 106
3000	055°		COUCH	2200	1.6 NM to RWY05R	RWY05R	
GP 2.86° TCH 60					6.8 NM		
CATEGORY	A	B	C	D	E		
LNAV/VNAV DA	479/55 373 (400-1)	490/60 384 (400-1½)	498/60 392 (400-1½)	509/60	403 (400-1½)		
LNAV MDA	640/55	534 (500-1)	640-1½	534	(500-1½)		
CIRCLING*	780-1 637 (700-1)	920-1 777 (800-1)	940-2¼ 797 (800-2¼)	940-2½ 797 (800-2½)	1000-3 857 (900-3)		

NOTE: REPRINTING DOD FLIP

INSTRUMENT APPROACH CHART

RODN / KADENA

APCH CRS 235°	Rwy ldg 12,101
	TDZE 143
	Arpt Elev 143

RNAV (GPS) RWY23L

RNP APCH - GPS

RADAR required. DME/DME RNP - 0.3 NA.

* Circling not authorized NW of Rwy 05L-23R.


MISSED APPROACH: Climb to 6000 direct IGPUM, cross IGPUM at or above 2200, track 235° to ADYEK and hold, continue climb-in-hold to 6000.

ATIS★ 124.2 280.5	NAHA APP CON/DEP CON 119.1 335.8 (NW) 126.5 258.3 (SE)	TOWER 134.1 315.8	GND CON 118.5 275.8	CLNC DEL 123.3 235.0	ASR
----------------------	--	----------------------	------------------------	-------------------------	-----

For uncompensated
Baro-VNAV systems,
LNAV/VNAV not authorized
below 7°C or above 54°C.


RADAR required for holding
at ADYEK above 10,000
when W174 is active.

RADAR required for holding
at BYYRD above 10,000
when W178/178A is active.




EMERG SAFE ALT 100 NM 2700

6000	IGPUM	tr 235°	ADYEK	TLv FL140 TA 14,000	VGSI and Descent angles not coincident (VGSI Angle 3.00/TCH 55).	CITIK	ELEV 143	TDZE 143
------	-------	------------	-------	------------------------	--	-------	----------	----------



CATEGORY	A	B	C	D	E
LNAV/VNAV DA	669-1½	526	(600-1½)		
LNAV MDA	740/55 597 (600-1)	740-1¾ 597 (600-1¾)			
CIRCLING*	780-1 637 (700-1)	920-1 777 (800-1)	940-2¼ 797 (800-2¼)	940-2½ 797 (800-2½)	1000-3 857 (900-3)



CHANGE : Update.


NOTE: REPRINTING DOD FLIP

RODN / KADENA

RNAV (GPS) RWY23R

<p>ATIS★</p> <p>124.2 280.5</p>	<p>NAHA APP CON/DEP CON</p> <p>119.1 335.8 (NW)</p> <p>126.5 258.3 (SE)</p>	<p>TOWER</p> <p>134.1 315.8</p>	<p>GND CON</p> <p>118.5 275.8</p>	<p>CLNC DEL</p> <p>123.3 235.0</p>	<p>ASR</p>
--	---	--	--	---	------------

For uncompensated
Baro-VNAV systems,
LNAV/VNAV NA below
7° C or above 54° C.



CATEGORY	A	B	C	D	E
LNAV/VNAV DA*	482/40		353	(400-¾)	
LNAV MDA**	740/40	611 (600-¾)	740-1½	611	(600-1½)
CIRCLING***	780-1 637 (700-1)	920-1 777 (800-1)	940-2¼ 797 (800-2¼)	940-2½ 797 (800-2½)	1000-3 857 (900-3)

HIRL all Rwys
 REIL Rwy 05R, 23L

HIRL all Rwys
REIL Rwys 05R, 23L

20/2/25