

AD 2 AERODROMES

RJFO AD 2.1 AERODROME LOCATION INDICATOR AND NAME

RJFO - OITA

RJFO AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

| | | |
|---|--|---|
| 1 | ARP coordinates and site at AD | 332846N/1314414E 007 Degrees /1.5KM FM RWY 01 THR |
| 2 | Direction and distance from (city) | 16NM NE FM OITA City |
| 3 | Elevation/ Reference temperature | 17FT / 30°C |
| 4 | Geoid undulation at AD ELEV PSN | 104FT |
| 5 | MAG VAR/ Annual change | 7°W(2009) / 2'W |
| 6 | AD Administration, address, telephone, telefax, telex, AFS, e-mail and/or Web-site addresses | JCAB Aza Omida, Itoharu, Musashi-machi, Kunisaki-shi, Oita Pref. 873-0421 JAPAN. Tel:0978(67)3771, 0978(67)3773 Fax:0978(67)3780, 0978(67)3781(AIS) AFS:RJFOYFYX |
| 7 | Types of traffic permitted (IFR/VFR) | IFR/VFR |
| 8 | Remarks | Nil |

RJFO AD 2.3 OPERATIONAL HOURS

| | | |
|----|---------------------------|---|
| 1 | AD Administration | 2230 - 1330 |
| 2 | Customs and immigration | Customs:2330-0815 Immigration:INTL SKED FLT hours only |
| 3 | Health and sanitation | INTL SKED FLT hours only |
| 4 | AIS Briefing Office | 2230 - 1330 |
| 5 | ATS Reporting Office(ARO) | Nil |
| 6 | MET Briefing Office | H24 (FUKUOKA) |
| 7 | ATS | 2230 - 1330 |
| 8 | Fuelling | 2230 - 1330 |
| 9 | Handling | 2230 - 1330 |
| 10 | Security | 2230 - 1330 |
| 11 | De-icing | Nil |
| 12 | Remarks | Nil |

RJFO AD 2.4 HANDLING SERVICES AND FACILITIES

| | | |
|---|---|--|
| 1 | Cargo-handling facilities | All the modern institutions that with the weight thing to Boeing 747 type freighter. |
| 2 | Fuel/ oil types | JET A-1 |
| 3 | Fuelling facilities/ capacity | Fuel Truck / Not Limitation |
| 4 | De-icing facilities | Nil |
| 5 | Hangar space for visiting aircraft | Nil |
| 6 | Repair facilities for visiting aircraft | Nil |
| 7 | Remarks | Nil |

RJFO AD 2.5 PASSENGER FACILITIES

| | | |
|---|----------------------|--------------------------|
| 1 | Hotels | Near FM Airport |
| 2 | Restaurants | At Airport |
| 3 | Transportation | Buses and Taxis |
| 4 | Medical facilities | Hospital in Aki-town 3km |
| 5 | Bank and Post Office | BANK ATM at Airport |
| 6 | Tourist Office | At Airport |
| 7 | Remarks | Nil |

RJFO AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

| | | |
|---|---|--|
| 1 | AD category for fire fighting | CAT 9 |
| 2 | Rescue equipment | Chemical fire fighting truck x 3 Water-supply truck Lighting power supply truck Emergency medical equipments conveyance truck |
| 3 | Capability for removal of disabled aircraft | Ask AD Administration |
| 4 | Remarks | Nil |

RJFO AD 2.7 SEASONAL AVAILABILITY-CLEARING

| | | |
|---|-----------------------------|--|
| 1 | Types of clearing equipment | Clearing equipments: Sweeper x 1 Snow removal equipments: NIL(commission) |
| 2 | Clearance priorities | (1) RWY, TWY T0 T6 P, Spot 7-9 (2) TWY T1 T5, Spot 5-6 (3) TWY T2 T3 T4, Spot 1-3 10 11 |
| 3 | Remarks | Snow removal will be commenced when the RWY and TWY are covered with snow its depth 3cm or more(Ask AD administration for details) |

RJFO AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS DATA

| | | |
|---|-------------------------------------|---|
| 1 | Apron surface and strength | Surface: Asphalt-concrete and Cement-concrete Strength : Spot NR1A, 1B, 2, 3 : PCR 640/F/D/X/T Spot NR5, 6 : PCR 797/R/B/W/T Spot NR7, 8, 9, 10 : PCR 925/R/B/W/T Spot NR11 : PCR 1132/R/B/W/T |
| 2 | Taxiway width, surface and strength | Surface: Asphalt-concrete and Cement-concrete Strength : TWY T0, T1, T2, T3, T4, T5, T6: PCR 1041/F/C/X/T TWY P0, P1, P3, P4, P5: PCR 1041/F/C/X/T TWY P2: PCR 1132/R/B/W/T Width: TWY T1, T2, T3, T4, T5: 34m TWY T0, T6: 28.5m TWY P0, P1, P2, P3, P4, P5: 23m |
| 3 | ACL and elevation | Not Available |
| 4 | VOR checkpoints | Not Available |
| 5 | INS checkpoints | (Spot NR) 2 : 332844.43N,1314403.07E 3 : 332842.98N,1314403.05E 5 : 332841.51N,1314403.02E 6 : 332840.05N,1314403.01E 7 : 332837.39N,1314359.83E 8 : 332835.12N,1314359.81E 9 : 332832.85N,1314359.79E 10 : 332830.58N,1314359.77E 11 : 332828.47N,1314359.71E |
| 6 | Remarks | Nil |

RJFO AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

| | | |
|---|--|--|
| 1 | Use of aircraft stand ID signs, TWY guide lines and Visual docking/ parking guidance system of aircraft stands | ACFT stand ID signs: Spot 1-11 |
| 2 | RWY and TWY markings and LGT | <p>RWY:RWY01/19(SEE RJFO AD2.24) (Marking) RWY designation, RWY CL, RWY THR, RWY middle point, Aiming point, TDZ, RWY side stripe (LGT) RCLL, REDL, RTHL, RENL, RTZL(RWY01), WBAR(RWY01)</p> <p>TWY:ALL TWY (Marking) TWY CL, RWY HLDG PSN, TWY side stripe (LGT) TWY edge LGT, TWY CL LGT, RWY guard LGT, Taxiing guidance sign</p> |
| 3 | Stop bars | Nil |
| 4 | Remarks | <p>(Marking) Overrun area (LGT) Apron flood LGT</p> |

RJFO AD 2.10 AERODROME OBSTACLES

■ In Area2 See Obstacle data

■ In Area3 To be developed

RJFO AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

| | | |
|----|--|---|
| 1 | Associated MET Office | FUKUOKA |
| 2 | Hours of service MET Office outside hours | H24 (FUKUOKA) |
| 3 | Office responsible for TAF preparation Periods of validity | FUKUOKA 30 Hours |
| 4 | Trend forecast Interval of issuance | Nil |
| 5 | Briefing/ consultation provided | Briefing is available upon inquiry at FUKUOKA |
| 6 | Flight documentation Language(s) used | C En |
| 7 | Charts and other information available for briefing or consultation | S ₆ , U ₈₅ , U ₇ , U ₅ , U ₃ , U ₂₅ , U ₂ /Tr, P _S , P ₅ , P ₃ , P ₂₅ , P _{SWE} , P _{SWF} , P _{SWG} , P _{SWI} , P _{SWM} , P _{SW} (domestic), E, C, W _E , W _F , W _G , W _I , W, N |
| 8 | Supplementary equipment available for providing information | Nil |
| 9 | ATS units provided with information | TWR, APP, ATIS |
| 10 | Additional information(limitation of service, etc.) | Nil |

RJFO AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

| Designations RWY NR | TRUE BRG | Dimensions of RWY(M) | Strength(PCR) and surface of RWY | THR coordinates THR geoid undulation | THR elevation and highest elevation of TDZ of precision APP RWY |
|--|----------|-------------------------|--------------------------------------|---|---|
| 1 | 2 | 3 | 4 | 5 | 6 |
| 01 | 000° | 3000×45 | PCR 1041/F/C/X/T Asphalt-Concrete | 332757.53N 1314413.22E 104FT | THR ELEV:19FT TDZ ELEV:19FT |
| 19 | 180° | 3000×45 | PCR 1041/F/C/X/T Asphalt-Concrete | 332934.89N 1314414.08E 104FT | THR ELEV:17FT |
| | | | | | |
| Slope of RWY | | Strip Dimensions(M) | RESA (Overrun) Dimensions (M) | | Remarks |
| 7 | | 10 | 11 | | 14 |
| See AD CHART | | 3120×300 | 190×(MNM:152 MAX:300)* | | RWY Grooving 3000m × 30m |
| | | 3120×300 | 40×300 | | |
| *For detail, ask airport administrator | | | | | |

RJFO AD 2.13 DECLARED DISTANCES

| RWY Designator | TORA (m) | TODA (m) | ASDA (m) | LDA (m) | Remarks |
|----------------|-------------|-------------|-------------|------------|---------|
| 1 | 2 | 3 | 4 | 5 | 6 |
| 01 | 3000 | 3000 | 3000 | 3000 | Nil |
| 19 | 3000 | 3000 | 3000 | 3000 | Nil |

RJFO AD 2.14 APPROACH AND RUNWAY LIGHTING

| RWY Designator | APCH LGT type LEN INTST | RTHL Color WBAR | PAPI (VASIS) Angle DIST FM THR MEHT | RTZL LEN | RCLL LEN Spacing Color INTST | REDL LEN Spacing Color INTST | RENL Color WBAR | STWL LEN Color |
|---|-------------------------------------|-----------------------|---|-------------|---|--|-----------------------|----------------------|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| 01 | PALS (CAT I) 900M LIH | Green Green | PAPI 3.0°/LEFT 413M 66FT | 900M | 3000M 30M Coded color (White/Red) LIH | 3000M 60M Coded color (White/Yellow) LIH | Red | Nil (*2) |
| 19 | SALS (*1) 420M LIH | Green - | PAPI 3.0°/LEFT 457M 74FT | Nil | 3000M 30M Coded color (White/Red) LIH | 3000M 60M Coded color (White/Yellow) LIH | Red | Nil (*2) |
| Remarks | | | | | | | | |
| 10 | | | | | | | | |
| SALS with APCH LGT beacon(600m and 900m FM RWY THR)(*1) Overrun area edge LGT(LEN:60m Color:Red)(*2) CGL for RWY 19 | | | | | | | | |

RJFO AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY


| | | |
|---|--|---|
| 1 | ABN/IBN location, characteristics and hours of operation | ABN: 332833N/1314353E, White/Green EV4.3sec, HO Operating in night, IMC, and when requested |
| 2 | LDI location and LGT Anemometer location and LGT | LDI:Nil Anemometer: RWY01: 355m from RWY 01 THR, LGTD RWY19: 300m from RWY 19 THR, LGTD |
| 3 | TWY edge and center line lighting | TWY edge and center line lights installed, see AD2.9 |
| 4 | Secondary power supply / switch-over time | Within 1 sec : REDL, RENL, RTHL, WBAR, RCLL, Overrun area edge LGT Within 15 sec : Other LGT |
| 5 | Remarks | WDI LGT |

RJFO AD 2.16 HELICOPTER LANDING AREA

| |
|-----|
| Nil |
|-----|

RJFO AD 2.17 ATS AIRSPACE

| Designation and lateral limits | | Vertical limits (ft) | Airspace classification | ATS unit call sign Language | Remarks |
|--------------------------------|---|----------------------|-------------------------|-----------------------------|---------|
| 1 | | 2 | 3 | 4 | 6 |
| OITA CTR | Area within a radius of 5nm of OITA ARP | 3000 or below | D | OITA TOWER | |
| OITA ACA | SEE RJFO ATTACHED CHART | | | | |

大分進入管制区
Oita Approach Control Area

Point list

| | |
|----------------------|----------------------|
| (1) 334923N1315428E | (11) 334410N1320642E |
| (2) 333820N1313835E | (12) 340827N1321357E |
| (3) 333112N1313754E | (13) 331313N1314212E |
| (4) 331835N1313643E | (14) 335858N1315956E |
| (5) 331513N1312903E | (15) 334822N1320757E |
| (6) 330719N1312355E | (16) 335336N1321117E |
| (7) 325619N1311408E | |
| (8) 332346N1321425E | |
| (9) 332258N1320939E | |
| (10) 333116N1320253E | |

RJFO AD 2.18 ATS COMMUNICATION FACILITIES

| Service designation | Call sign | Frequency | Hours of operation | Remarks |
|---------------------|----------------|--|--------------------|------------|
| 1 | 2 | 3 | 4 | 5 |
| APP | Oita Approach | 120.6MHz(1) 127.7MHz 119.05MHz 261.2MHz 121.5MHz(E) 243.0MHz(E) | 2230 - 1330 | (1)Primary |
| ASR | Oita Radar | 119.05MHz 120.6MHz 127.7MHz 261.2MHz 121.5MHz(E) 243.0MHz(E) | 2230 - 1330 | |
| DEP | Oita Departure | 127.7MHz 120.6MHz 119.05MHz 261.2MHz 121.5MHz(E) 243.0MHz(E) | 2230 - 1330 | |
| TWR | Oita Tower | 118.8MHz(1) 126.2MHz 261.2MHz 121.5MHz(E) 243.0MHz(E) | 2230 - 1330 | |
| GND | Oita Ground | 121.6MHz | 2230 - 1330 | |
| ATIS | Oita Airport | 127.8MHz | 2230 - 1330 | |


RJFO AD 2.19 RADIO NAVIGATION AND LANDING AIDS

| Type of aid (VOR declination) | ID | Frequency | Hours of operation | Position of transmitting antenna coordinates | Elevation of DME transmitting antenna | Remarks |
|-------------------------------------|-----|----------------------|-----------------------|---|--|---|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 |
| ILS-LOC 01 | ITF | 111.5MHz | 2230 - 1330 | 332942.19N/ 1314414.15E | | LOC:225m(738ft) away FM RWY19 THR, BRG(MAG)007°. Unusable beyond 16nm. |
| ILS-GP 01 | - | 332.9MHz | 2230 - 1330 | 332807.70N/ 1314417.95E | | GP:315m (1034ft) inside FM RWY 01 THR,120m(394ft) E of RCL. HGT of ILS Ref datum16.5m (54ft) GP angle 3.0°. |
| ILS-DME 01 | ITF | 1013MHz (CH-52X) | 2230 - 1330 | 332808.01N/ 1314418.31E | 37ft | DME: 325m(1066ft) inside FM RWY 01 THR, 130m(427ft) E of RCL. |
| VOR (7°W/2016) | TFE | 117.7MHz | H24 | 332922.97N/ 1314343.52E | | VOR Unusable: 210°-220° beyond 35NM below 8,000FT. 240°-260° beyond 35NM below 8,000FT. 270°-330° beyond 30NM below 6,000FT. |
| DME | TFE | 1211MHz (CH-124X) | H24 | 332922.97N/ 1314343.52E | 100ft | DME Unusable: 260°-270° beyond 35NM below 8,000FT. 270°-290° beyond 15NM below 6,000FT. 290°-330° beyond 30NM below 6,000FT. 330°-340° beyond 30NM below 5,000FT. |
| MSAS | | 1575.42MHz | H24 | | | Transmitting antennas are satellite based. |


RJFO / OITA

ILS

ILS



REMARKS : 1. LOC beam BRG(MAG) 007°
 2. HGT of ILS REF datum 16.5m(54ft)
 3. GP angle 3.0°
 4. ELEV of ILS-DME 11.2m(37ft)



LOC UNUSABLE : BEYOND 16NM.

RJFO AD 2.20 LOCAL TRAFFIC REGULATIONS

1. Airport regulations

| |
|--|
| On use of this airport by transient ACFT, the operator is required to obtain the prior permission of the airport administrator in order to adjust of parking area, except scheduled flight and ACFT in an emergency. |
|--|

2. Taxiing to and from stands

| |
|-----|
| Nil |
|-----|

3. Parking area for small aircraft(General aviation)

| |
|-----|
| Nil |
|-----|

4. Parking area for helicopters

| |
|-----|
| Nil |
|-----|

5. Apron - taxiing during winter conditions

| |
|-----|
| Nil |
|-----|

6. Taxiing - limitations

| |
|-----|
| Nil |
|-----|

7. School and training flights - technical test flights - use of runways

| |
|-----|
| Nil |
|-----|

8. Helicopter traffic - limitation

| |
|-----|
| Nil |
|-----|

9. Removal of disabled aircraft from runways

| |
|-----|
| Nil |
|-----|

RJFO AD 2.21 NOISE ABATEMENT PROCEDURES

| |
|-----|
| Nil |
|-----|

RJFO AD 2.22 FLIGHT PROCEDURES

1. TAKE OFF MINIMA

| | RWY | ACFT CAT | REDL & RCLL | | REDL or RCLL or RCL marking | | NIL (DAYTIME ONLY) | |
|--|-----|-------------|-----------------|-----|-----------------------------------|-----|-----------------------|-----|
| | | | RVR | VIS | RVR | VIS | RVR | VIS |
| Multi-Engine ACFT with TKOF ALTN AP Filed | 01 | A,B,C,D | 400 | 400 | 400 | 400 | - | 500 |
| | 19 | A,B,C,D | - | 400 | - | 400 | - | 500 |
| OTHER | 01 | A,B,C,D | AVBL LDG MINIMA | | | | | |
| | 19 | A,B,C,D | | | | | | |

2. Lost Communication Procedures for Arrival Aircraft under radar navigational guidance

If radio Communications with Oita Approach/Radar are lost for 30 seconds,
squawk Mode A/3 Code 7600 and;

- I
 1. Contact Oita Tower.
 2. If unable, proceed in accordance with Visual Flight Rules.
 3. If unable, proceed to Musashi VOR/DME at last assigned altitude or 3500 feet whichever is higher and execute Instrument Approach.
- II Procedures other than above will be issued when situation required.

3. Trajectory-based Airport Traffic Data Processing System (TAPS)

Aircraft flying in Oita approach control area under its control will be instructed to reply with discrete code on Mode A/3 and Mode C.

If an aircraft has no capability of replying with discrete code, the pilot shall report ATC if so instructed.

大分アプローチの指示のもとに、当該進入管制区を飛行する航空機は、モード A/3 の二次レーダー個別コード及びモード C による応答を指示される。
二次レーダー個別コードを搭載していない航空機が当該コードによる応答を指示された場合は、管制機関に対しその旨通報すること。

RJFO AD 2.23 ADDITIONAL INFORMATION


Nil

RJFO AD 2.24 CHARTS RELATED TO AN AERODROME

Aerodrome Chart
Aerodrome Obstacle Chart-ICAO type A (RWY01/19)
Aerodrome Obstacle Chart-ICAO type B
Standard Departure Chart-Instrument (MUSASHI)
Standard Departure Chart-Instrument (EBOSHI-RNAV)
Standard Departure Chart-Instrument (TOYO-RNAV)
Standard Departure Chart-Instrument (FUSHA-RNAV)
Standard Departure Chart-Instrument (TRANSITION-RNAV)
Standard Arrival Chart-Instrument (JEWEL)
Standard Arrival Chart-Instrument (KAGEX, BAIEN, NOLEL, TANSO, OOTA-RNAV)
Instrument Approach Chart (ILS Z RWY01)
Instrument Approach Chart (ILS Y or LOC RWY01)
Instrument Approach Chart (ILS X RWY01)
Instrument Approach Chart (VOR RWY01)
Instrument Approach Chart (VOR A)
Instrument Approach Chart (RNP Z RWY19)
Instrument Approach Chart (RNP RWY01(AR))
Instrument Approach Chart (RNP Y RWY19(AR))
Other Chart (Visual REP)
Other Chart (MVA CHART)

RJFO / OITA

AD CHART



DIMENSIONS AND ELEVATIONS IN FEET BEARINGS ARE MAGNETIC

OITA AIRPORT
RWY : 01/19

DECLARED DISTANCES

| RWY 01 | | RWY 19 |
|--------|------------------------------------|--------|
| 3000m | TAKE OFF RUN AVAILABLE | 3000m |
| 3000m | TAKE OFF DISTANCE AVAILABLE | 3000m |
| 3000m | ACCELERATE STOP DISTANCE AVAILABLE | 3000m |
| 3000m | LANDING DISTANCE AVAILABLE | 3000m |

LEGEND

| LEGEND | |
|--------|-------------------------------------|
| ① | IDENTIFICATION NUMBER |
| ⊙ | POLE, TOWER, SPIRE, ANTENNA, ETC |
| ✱ | TREE |
| ⋯⋯⋯ | RAILROAD |
| ⋯⋯⋯ | TRANSMISSION LINE OR OVERHEAD CABLE |
| △ | TRIANGULATION POINT |
| ★ | AERONAUTICAL GROUND LIGHT |
| ⋯⋯⋯ | LEVEE |
| ⋯⋯⋯ | RIVER |


AMENDMENT RECORD

| Nr | DATE | ENTERED BY |
|----|------|------------|
| | | |

HORIZONTAL SCALE

FEET
0 1000 2000 3000 4000 5000 6000 7000 8000

METRES
0 500 1000 1500 2000 2500

AERODROME OBSTACLE CHART-ICAO
TYPE B

STANDARD DEPARTURE CHART - INSTRUMENT

RJFO / OITA

SID


MUSASHI REVERSAL TWO DEPARTURE

RWY01 : Climb RWY HDG to 500FT, turn right HDG177° to intercept and proceed via TFE R132 to TFE 10.0DME,...


RWY19 : Turn left, climb via TFE R132 to TFE 10.0DME,...
...turn right, direct to TFE VOR/DME.
Cross TFE VOR/DME at or above 4000FT.

Note RWY01 : 5.0% climb gradient required up to 500FT.
OBST ALT 321FT located at 2.5NM 352° FM end of RWY01.

CHANGE : OBST.



STANDARD DEPARTURE CHART - INSTRUMENT



STANDARD DEPARTURE CHART - INSTRUMENT

RJFO / OITA

RNAV SID

EBOSHI THREE DEPARTURE

RWY01

| Serial Number | Path Descriptor | Waypoint Identifier | Fly Over | Course °M(°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed (KIAS) | Vertical Angle | Navigation Specification |
|---------------|-----------------|---------------------|----------|----------------|--------------------|---------------|----------------|---------------|--------------|----------------|--------------------------|
| 001 | VA | — | — | 008 (000.4) | -8.0 | — | — | +500 | — | — | RNAV1 |
| 002 | DF | YANAI | — | — | -8.0 | — | R | — | — | — | RNAV1 |

RWY19


| Serial Number | Path Descriptor | Waypoint Identifier | Fly Over | Course °M(°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed (KIAS) | Vertical Angle | Navigation Specification |
|---------------|-----------------|---------------------|----------|----------------|--------------------|---------------|----------------|---------------|--------------|----------------|--------------------------|
| 001 | VA | — | — | 188 (180.4) | -8.0 | — | — | +500 | — | — | RNAV1 |
| 002 | DF | YANAI | — | — | -8.0 | — | L | — | — | — | RNAV1 |

Waypoint Coordinates

| Waypoint Identifier | Coordinates |
|---------------------|------------------------|
| YANAI | 334622.9N / 1315917.1E |

CHANGE : PROC renamed. PROC course. Waypoint Coordinates added.

STANDARD DEPARTURE CHART- INSTRUMENT



STANDARD DEPARTURE CHART- INSTRUMENT

RJFO / OITA

RNAV SID

TOYO FOUR DEPARTURE

RWY01

| Serial Number | Path Descriptor | Waypoint Identifier | Fly Over | Course °M(°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed (KIAS) | Vertical Angle | Navigation Specification |
|---------------|-----------------|---------------------|----------|----------------|--------------------|---------------|----------------|---------------|--------------|----------------|--------------------------|
| 001 | VA | — | — | 008 (000.4) | -8.0 | — | — | +500 | — | — | RNAV1 |
| 002 | DF | AKNIS | — | — | -8.0 | — | R | — | — | — | RNAV1 |
| 003 | TF | OOITA | — | 216 (208.1) | -8.0 | 13.8 | — | +4000 | — | — | RNAV1 |

RWY19


| Serial Number | Path Descriptor | Waypoint Identifier | Fly Over | Course °M(°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed (KIAS) | Vertical Angle | Navigation Specification |
|---------------|-----------------|---------------------|----------|----------------|--------------------|---------------|----------------|---------------|--------------|----------------|--------------------------|
| 001 | VA | — | — | 188 (180.4) | -8.0 | — | — | +500 | — | — | RNAV1 |
| 002 | DF | FO901 | — | — | -8.0 | — | — | — | — | — | RNAV1 |
| 003 | TF | OOITA | — | 198 (189.8) | -8.0 | 9.8 | — | +4000 | — | — | RNAV1 |

Waypoint Coordinates

| Waypoint Identifier | Coordinates |
|---------------------|------------------------|
| AKNIS | 332524.3N / 1314958.2E |
| FO901 | 332251.1N / 1314410.5E |
| OOITA | 331313.2N / 1314211.7E |

CHANGE : AKNIS established. TACHI abolished. PROC course. Waypoint Coordinates added.

STANDARD DEPARTURE CHART - INSTRUMENT



CHANGE : PROC renamed. VAR. PROC course. OBST.

STANDARD DEPARTURE CHART - INSTRUMENT

RJFO / OITA

RNAV SID

FUSHA TWO DEPARTURE

RWY01

| Serial Number | Path Descriptor | Waypoint Identifier | Fly Over | Course °M(°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed (KIAS) | Vertical Angle | Navigation Specification |
|---------------|-----------------|---------------------|----------|----------------|--------------------|---------------|----------------|---------------|--------------|----------------|--------------------------|
| 001 | VA | — | — | 008 (000.4) | -8.0 | — | — | +500 | — | — | RNAV1 |
| 002 | DF | FUSHA | — | — | -8.0 | — | R | — | — | — | RNAV1 |

RWY19


| Serial Number | Path Descriptor | Waypoint Identifier | Fly Over | Course °M(°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed (KIAS) | Vertical Angle | Navigation Specification |
|---------------|-----------------|---------------------|----------|----------------|--------------------|---------------|----------------|---------------|--------------|----------------|--------------------------|
| 001 | VA | — | — | 188 (180.4) | -8.0 | — | — | +500 | — | — | RNAV1 |
| 002 | DF | FUSHA | — | — | -8.0 | — | L | — | — | — | RNAV1 |

Waypoint Coordinates

| Waypoint Identifier | Coordinates |
|---------------------|------------------------|
| FUSHA | 331737.7N / 1320814.6E |

CHANGE : PROC renamed. PROC course. VAR. Waypoint Coordinates added.

STANDARD DEPARTURE CHART - INSTRUMENT



CHANGE : VAR. PROC course.

STANDARD DEPARTURE CHART - INSTRUMENT

RJFO / OITA

RNAV TRANSITION

DONAR TRANSITION

| Serial Number | Path Descriptor | Waypoint Identifier | Fly Over | Course °M(°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed (KIAS) | Vertical Angle | Navigation Specification |
|---------------|-----------------|---------------------|----------|----------------|--------------------|---------------|----------------|---------------|--------------|----------------|--------------------------|
| 001 | IF | FUSHA | — | — | -8.0 | — | — | — | — | — | RNAV1 |
| 002 | TF | DONAR | — | 087 (078.7) | -8.0 | 17.8 | — | +FL160 | — | — | RNAV1 |

DOUGO TRANSITION

| Serial Number | Path Descriptor | Waypoint Identifier | Fly Over | Course °M(°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed (KIAS) | Vertical Angle | Navigation Specification |
|---------------|-----------------|---------------------|----------|----------------|--------------------|---------------|----------------|---------------|--------------|----------------|--------------------------|
| 001 | IF | FUSHA | — | — | -8.0 | — | — | — | — | — | RNAV1 |
| 002 | TF | DONAR | — | 087 (078.7) | -8.0 | 17.8 | — | +FL160 | — | — | RNAV1 |
| 003 | TF | MYE | — | 028 (019.8) | -8.0 | 30.6 | — | — | — | — | RNAV1 |

FIATO TRANSITION

| Serial Number | Path Descriptor | Waypoint Identifier | Fly Over | Course °M(°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed (KIAS) | Vertical Angle | Navigation Specification |
|---------------|-----------------|---------------------|----------|----------------|--------------------|---------------|----------------|---------------|--------------|----------------|--------------------------|
| 001 | IF | FUSHA | — | — | -8.0 | — | — | — | — | — | RNAV1 |
| 002 | TF | DONAR | — | 087 (078.7) | -8.0 | 17.8 | — | +FL160 | — | — | RNAV1 |
| 003 | TF | SALTY | — | 044 (036.1) | -8.0 | 37.3 | — | — | — | — | RNAV1 |
| 004 | TF | FIATO | — | 044 (036.3) | -8.0 | 11.8 | — | — | — | — | RNAV1 |

SALTY TRANSITION

| Serial Number | Path Descriptor | Waypoint Identifier | Fly Over | Course °M(°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed (KIAS) | Vertical Angle | Navigation Specification |
|---------------|-----------------|---------------------|----------|----------------|--------------------|---------------|----------------|---------------|--------------|----------------|--------------------------|
| 001 | IF | FUSHA | — | — | -8.0 | — | — | — | — | — | RNAV1 |
| 002 | TF | DONAR | — | 087 (078.7) | -8.0 | 17.8 | — | +FL160 | — | — | RNAV1 |
| 003 | TF | SALTY | — | 044 (036.1) | -8.0 | 37.3 | — | — | — | — | RNAV1 |

CHANGE : PROC course. VAR.

STANDARD DEPARTURE CHART - INSTRUMENT

RJFO / OITA

RNAV TRANSITION

SPIDE TRANSITION

| Serial Number | Path Descriptor | Waypoint Identifier | Fly Over | Course °M(°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed (KIAS) | Vertical Angle | Navigation Specification |
|---------------|-----------------|---------------------|----------|----------------|--------------------|---------------|----------------|---------------|--------------|----------------|--------------------------|
| 001 | IF | FUSHA | — | — | -8.0 | — | — | — | — | — | RNAV1 |
| 002 | TF | DONAR | — | 087 (078.7) | -8.0 | 17.8 | — | +FL160 | — | — | RNAV1 |
| 003 | TF | SPIDE | — | 062 (054.1) | -8.0 | 30.1 | — | — | — | — | RNAV1 |

ASHIZURI TRANSITION

| Serial Number | Path Descriptor | Waypoint Identifier | Fly Over | Course °M(°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed (KIAS) | Vertical Angle | Navigation Specification |
|---------------|-----------------|---------------------|----------|----------------|--------------------|---------------|----------------|---------------|--------------|----------------|--------------------------|
| 001 | IF | FUSHA | — | — | -8.0 | — | — | — | — | — | RNAV1 |
| 002 | TF | SUC | — | 135 (126.5) | -8.0 | 54.0 | — | — | — | — | RNAV1 |

Waypoint Coordinates

| Waypoint Identifier | Coordinates |
|---------------------|------------------------|
| FUSHA | 331737.7N / 1320814.6E |
| DONAR | 332105.1N / 1322904.7E |
| MYE | 334948.4N / 1324132.0E |
| SALTY | 335109.7N / 1325530.8E |
| FIATO | 340037.4N / 1330354.6E |
| SPIDE | 333840.2N / 1325818.0E |
| SUC | 324521.5N / 1325947.9E |

CHANGE : PROC course. VAR. Waypoint Coordinates added.

STANDARD ARRIVAL CHART- INSTRUMENT


RJFO / OITA

STAR


JEWEL ARRIVAL

From over DONKO, via TFE R038 to JEWEL.

Cross DONKO at or above 5000FT, cross JEWEL at or above 3000FT.



STANDARD ARRIVAL CHART- INSTRUMENT



STANDARD ARRIVAL CHART - INSTRUMENT

RJFO / OITA

RNAV STAR

KAGEX ARRIVAL

From YANAI at or above 5000FT, to KAGEX at or above 3000FT.

| | |
|------------------------|---|
| Critical DME | — |
| DME GAP | — |
| Inappropriate Nav aids | See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1 |

| Serial Number | Path Descriptor | Waypoint Identifier | Fly Over | Course °M(°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed (KIAS) | Vertical Angle | Navigation Specification |
|---------------|-----------------|---------------------|----------|----------------|--------------------|---------------|----------------|---------------|--------------|----------------|--------------------------|
| 001 | IF | YANAI | — | — | -8.0 | — | — | +5000 | — | — | RNAV1 |
| 002 | TF | KAGEX | — | 244 (236.2) | -8.0 | 9.0 | — | +3000 | — | — | RNAV1 |

BAIEN ARRIVAL

From YANAI at or above 5000FT, to BAIEN at or above 3000FT.

| | |
|------------------------|---|
| Critical DME | — |
| DME GAP | — |
| Inappropriate Nav aids | See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1 |

| Serial Number | Path Descriptor | Waypoint Identifier | Fly Over | Course °M(°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed (KIAS) | Vertical Angle | Navigation Specification |
|---------------|-----------------|---------------------|----------|----------------|--------------------|---------------|----------------|---------------|--------------|----------------|--------------------------|
| 001 | IF | YANAI | — | — | -8.0 | — | — | +5000 | — | — | RNAV1 |
| 002 | TF | BAIEN | — | 225 (217.4) | -8.0 | 11.4 | — | +3000 | — | — | RNAV1 |

TANSO ARRIVAL

From YANAI at or above 5000FT, to FO162 at or above 3000FT, to TANSO at or above 2400FT.

| | |
|------------------------|---|
| Critical DME | — |
| DME GAP | — |
| Inappropriate Nav aids | See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1 |

| Serial Number | Path Descriptor | Waypoint Identifier | Fly Over | Course °M(°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed (KIAS) | Vertical Angle | Navigation Specification |
|---------------|-----------------|---------------------|----------|----------------|--------------------|---------------|----------------|---------------|--------------|----------------|--------------------------|
| 001 | IF | YANAI | — | — | -8.0 | — | — | +5000 | — | — | RNAV1 |
| 002 | TF | FO162 | — | 207 (199.4) | -8.0 | 7.2 | — | +3000 | — | — | RNAV1 |
| 003 | TF | TANSO | — | 207 (199.4) | -8.0 | 12.2 | — | +2400 | — | — | RNAV1 |

CHANGE : KAGEX ARRIVAL established. PROC course. VAR.

STANDARD ARRIVAL CHART - INSTRUMENT

RJFO / OITA

RNAV STAR

NOLEL ARRIVAL
From YANAI at or above 5000FT, to FO161 at or above 3000FT, to SELEN, to METAL, to NOLEL at or above 1800FT.

| | |
|-----------------------|---|
| Critical DME | — |
| DME GAP | — |
| Inappropriate Navaids | See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1 |

| Serial Number | Path Descriptor | Waypoint Identifier | Fly Over | Course °M(°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed (KIAS) | Vertical Angle | Navigation Specification |
|---------------|-----------------|---------------------|----------|----------------|--------------------|---------------|----------------|---------------|--------------|----------------|--------------------------|
| 001 | IF | YANAI | — | — | -8.0 | — | — | +5000 | — | — | RNAV1 |
| 002 | TF | FO161 | — | 204 (196.4) | -8.0 | 7.4 | — | +3000 | — | — | RNAV1 |
| 003 | TF | SELEN | — | 204 (196.4) | -8.0 | 21.9 | — | — | -220 | — | RNAV1 |
| 004 | TF | METAL | — | 278 (270.5) | -8.0 | 3.1 | — | — | -220 | — | RNAV1 |
| 005 | TF | NOLEL | — | 339 (330.5) | -8.0 | 2.6 | — | +1800 | — | — | RNAV1 |

Waypoint Coordinates


| Waypoint Identifier | Coordinates |
|---------------------|------------------------|
| YANAI | 334622.9N / 1315917.1E |
| KAGEX | 334121.2N / 1315016.7E |
| BAIEN | 333720.4N / 1315059.8E |
| FO162 | 333936.2N / 1315624.8E |
| TANSO | 332806.6N / 1315133.7E |
| FO161 | 333918.2N / 1315646.6E |
| SELEN | 331818.8N / 1314923.1E |
| METAL | 331820.3N / 1314541.2E |
| NOLEL | 332036.2N / 1314409.4E |

CHANGE : NOLEL ARRIVAL established. Waypoint Coordinates added. .

STANDARD ARRIVAL CHART - INSTRUMENT

RJFO / OITA

RNAV STAR RWY01



STANDARD ARRIVAL CHART - INSTRUMENT

RJFO / OITA

RNAV STAR

OOITA ARRIVAL

From OOITA at or above 4000FT, to LUISU at or above 2900FT, to NOLEL at or above 1800FT.

| | |
|------------------------|---|
| Critical DME | — |
| DME GAP | — |
| Inappropriate Nav aids | See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1 |

| Serial Number | Path Descriptor | Waypoint Identifier | Fly Over | Course °M(°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed (KIAS) | Vertical Angle | Navigation Specification |
|---------------|-----------------|---------------------|----------|----------------|--------------------|---------------|----------------|---------------|--------------|----------------|--------------------------|
| 001 | IF | OOITA | — | — | -8.0 | — | — | +4000 | — | — | RNAV1 |
| 002 | TF | LUISU | — | 028 (020.2) | -8.0 | 4.7 | — | +2900 | — | — | RNAV1 |
| 003 | TF | NOLEL | — | 009 (000.5) | -8.0 | 3.0 | — | +1800 | — | — | RNAV1 |


| Path | Waypoint Identifier | Inbound Course °M(°T) | Magnetic Variation | Outbound Time (MIN) | Turn Direction | Minimum Altitude (FT) | Maximum Altitude (FT) | Speed (KIAS) | Navigation Specification |
|------|---------------------|-----------------------|--------------------|---------------------|----------------|-----------------------|-----------------------|--------------|--------------------------|
| Hold | LUISU | 009 (000.5) | -8.0 | 1.0(-14000) | R | 3000 | FL140 | -210(-14000) | RNAV1 |

Waypoint Coordinates

| Waypoint Identifier | Coordinates |
|---------------------|------------------------|
| OOITA | 331313.2N / 1314211.7E |
| LUISU | 331735.8N / 1314407.5E |
| NOLEL | 332036.2N / 1314409.4E |

CHANGE : New PROC.



INSTRUMENT APPROACH CHART



INSTRUMENT APPROACH CHART

RJFO / OITA

ILS Y or LOC RWY01



Missed APCH climb gradient MNM 4.0%.

| MINIMA | | THR elev. 19 | | AD elev. 17 | | |
|--------|-----------|--------------|-----------|-------------|-----------|------|
| CAT | CAT I | | LOC | | CIRCLING | |
| | DA(H) | RVR/ CMV | MDA(H) | RVR/ CMV | MDA(H) | VIS |
| A | 219 (200) | 550 | 300 (283) | 800 | 430 (413) | 1600 |
| B | | | | | 470 (453) | |
| C | | | | 660 (643) | 2400 | |
| D | | | | 1200 | 760 (743) | 3200 |

MINIMA with Missed APCH climb gradient of 2.5% are not established.
Circling to EAST side of RWY only.

CHANGE : PROC renamed.

RJFO / OITA

ILS X RWY01

VAR 8°W

MSA 25NM

6300

ARP

ARP : 332846N/1314414E

EQPT REQUIRED
DME

RNP1
RF required.

090°

180°

10NM

BAIEN(MAHF)

MINIR (MATF)

007°

007°

IKOKU(FAF)
D4.0 ITF

NINEN
D5.5 ITF

007°

7.4

FO153 (IF)
MAX 200KIAS

6.1 200°

TANSO (IAF)

RNAV HLDG

MHA 3000
MAX 210KIAS

BAIEN

243°

063°

1MIN

NOT TO SCALE

270°

RNAV HLDG

MHA 2400
MAX 210KIAS

TANSO


198°

018°

1MIN

NOT TO SCALE

IKOKU(FAF) : 332408.45N/1314411.21E



CHANGE : PROC renamed. MINIR, FO153 established. RNAV HLDG established. PROC course. Missed APCH course. DME to ITF. NM to THR. Missed APCH climb gradient MNM. MINIMA for CIRCLING CAT C.

INSTRUMENT APPROACH CHART

RJFO / OITA

ILS X RWY01

Coding Table

| Serial Number | Path Descriptor | Waypoint Identifier | Fly Over | Course °M(°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed (KIAS) | Vertical Angle | Navigation Specification |
|---------------|------------------------------------|---------------------|----------|----------------|--------------------|---------------|----------------|---------------|--------------|----------------|--------------------------|
| 001 | IF | TANSO | - | - | -8.0 | - | - | +2400 | - | - | RNP1 |
| 002 | TF | FO153 | - | 200 (191.7) | -8.0 | 6.1 | - | +1300 | -200 | - | RNP1 |
| 003 | RF Center: FORF3 r=2.50NM | NINEN | - | - | -8.0 | 7.4 | R | 1300 | - | - | RNP1 |

| | | | | | | | | | | | |
|-----|----|-------|---|---|------|---|---|------|---|---|------|
| 001 | DF | MINIR | Y | - | -8.0 | - | - | - | - | - | RNP1 |
| 002 | DF | BAIEN | - | - | -8.0 | - | R | 3000 | - | - | RNP1 |


| Path | Waypoint Identifier | Inbound Course °M(°T) | Magnetic Variation | Outbound Time (MIN) | Turn Direction | Minimum Altitude (FT) | Maximum Altitude (FT) | Speed (KIAS) | Navigation Specification |
|------|---------------------|-----------------------|--------------------|---------------------|----------------|-----------------------|-----------------------|--------------|--------------------------|
| Hold | TANSO | 198 (190.0) | -8.0 | 1.0(-14000) | L | 2400 | FL140 | -210(-14000) | RNP1 |
| Hold | BAIEN | 243 (234.9) | -8.0 | 1.0(-14000) | L | 3000 | FL140 | -210(-14000) | RNP1 |

Waypoint Coordinates

| Waypoint Identifier | Coordinates | RF Arc Center Identifier | Coordinates |
|---------------------|--------------------------|--------------------------|--------------------------|
| TANSO | 332806.56N / 1315133.74E | FORF3 | 332237.18N / 1314709.46E |
| FO153 | 332206.75N / 1315004.78E | | |
| NINEN | 332238.32N / 1314410.42E | | |
| MINIR | 333001.00N / 1314414.31E | | |
| BAIEN | 333720.39N / 1315059.77E | | |

CHANGE : PROC renamed. MINIR, FO153 established. HLDG pattern. Waypoint Coordinates added.

INSTRUMENT APPROACH CHART




CHANGE : PATRO established. MONKY abolished. MINIMA for CIRCLING CAT C.

INSTRUMENT APPROACH CHART


RJFO / OITA

VOR A

**MISSED APPROACH**

Climb to 3000FT via TFE R218 to TFE 1.1DME, turn left HDG046° to intercept and proceed via TFE R091 to TFE 13.0DME, turn left, via TFE 13.0DME counterclockwise ARC to intercept and proceed via TFE R038 to JEWEL and hold. Contact OITA APP.

Timing not authorized for defining the MAPt.



Missed APCH climb gradient MNM 5.0%.

| MINIMA AD elev. 17 | | |
|--------------------|-----------|------|
| CAT | CIRCLING | |
| | MDA(H) | VIS |
| A | 440 (423) | 1600 |
| B | 480 (463) | |
| C | 660 (643) | 2400 |
| D | 760 (743) | 3200 |

MINIMA with Missed APCH climb gradient of 2.5% are not established.
Circling to EAST side of RWY only.

CHANGE : IGMAN established. MELDY abolished. VAR.


CHANGE : KAGEX, AKILU established. KABOS, KUROSZ abolished. PROC course. VAR. HLDG pattern at TFE. ALT restriction at KAREI.
NIM to THR. Missed APCH climb gradient MNM. MINIMA.



INSTRUMENT APPROACH CHART


RJFO / OITA

RNP RWY01(AR)



MISSED APPROACH

From RW01 on track 008°, at or above 500FT turn right, direct to BAIEN and hold at 3000FT.
Contact OITA APP.



Missed APCH climb gradient MNM 5.0%

| MINIMA | THR elev. 19 | AD elev. 17 |
|--------|--------------|-------------|
| CAT | RNP 0.30 | |
| | DA(H) | RVR/CMV |
| A | - | - |
| B | - | - |
| C | 326(307) | 1000 |
| D | 326(307) | 1400 |

Authorization Required

MINIMA with Missed APCH climb gradient of 2.5% are not established.

INSTRUMENT APPROACH CHART

RJFO / OITA

RNP RWY01(AR)

Coding Table

| Serial Number | Path Descriptor | Waypoint Identifier | Fly Over | Course °M(°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed (KIAS) | VPA/ RDH (°/FT) | RNP Value |
|---------------|---------------------------|---------------------|----------|---------------|--------------------|---------------|----------------|---------------|--------------|-----------------|-----------|
| 001 | IF | TANSO | - | - | -8.0 | - | - | +2400 | -220 | - | - |
| 002 | TF | FO151 | - | 222 (214.2) | -8.0 | 3.6 | - | 2400 | -165 | - | 1.0 |
| 003 | RF Center: FORF1 r=2.25NM | FO152 | - | - | -8.0 | 5.7 | R | 570 | - | -3.00 | 0.3 |
| 004 | TF | RW01 | Y | 008 (000.4) | -8.0 | 1.6 | - | 73 | - | -3.00/54 | 0.3 |
| 005 | FA | - | - | 008 (000.4) | -8.0 | - | - | +500 | - | - | 1.0 |
| 006 | DF | BAIEN | - | - | -8.0 | - | R | 3000 | - | - | 1.0 |

| Path | Waypoint Identifier | Inbound Course °M(°T) | Magnetic Variation | Outbound Time (MIN) | Turn Direction | Minimum Altitude (FT) | Maximum Altitude (FT) | Speed (KIAS) | RNP Value |
|------|---------------------|-----------------------|--------------------|---------------------|----------------|-----------------------|-----------------------|--------------|-----------|
| Hold | TANSO | 198 (190.0) | -8.0 | 1.0 (-14000) | L | 2400 | FL140 | -210(-14000) | 1.0 |
| Hold | BAIEN | 243 (234.9) | -8.0 | 1.0 (-14000) | L | 3000 | FL140 | -210(-14000) | 1.0 |

Waypoint Coordinates



| Waypoint Identifier | Coordinates | RF Arc Center Identifier | Coordinates |
|---------------------|--------------------------|--------------------------|--------------------------|
| TANSO | 332806.56N / 1315133.74E | FORF1 | 332622.64N / 1314653.79E |
| FO151 | 332506.40N / 1314907.12E | | |
| FO152 | 332623.67N / 1314412.39E | | |
| RW01 | 332757.53N / 1314413.22E | | |
| BAIEN | 333720.39N / 1315059.77E | | |

CHANGE : PROC course. VAR. HLDG pattern added.

INSTRUMENT APPROACH CHART

RJFO / OITA

RNP Y RWY19(AR)



Missed APCH climb gradient MNM 5.0%

| MINIMA | THR elev. 17 | AD elev. 17 |
|--------|--------------|-------------|
| CAT | RNP 0.30 | |
| | DA(H) | CMV |
| A | - | - |
| B | - | - |
| C | 357(340) | 1400 |
| D | | 1600 |

MINIMA with Missed APCH climb gradient of 2.5% are not established.

Authorization Required

CHANGE : DA(H). OBST.

INSTRUMENT APPROACH CHART

RJFO / OITA

RNP Y RWY19(AR)

| Coding Table | | | | | | | | | | | |
|---------------|---------------------------|---------------------|----------|---------------|--------------------|---------------|----------------|---------------|--------------|-----------------|-----------|
| Serial Number | Path Descriptor | Waypoint Identifier | Fly Over | Course °M(°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed (KIAS) | VPA/ RDH (°/FT) | RNP Value |
| 001 | IF | BAIEN | - | - | -8.0 | - | - | +3000 | -210 | - | - |
| 002 | TF | FO951 | - | 235 (226.8) | -8.0 | 5.0 | - | 1700 | - | - | 1.0 |
| 003 | TF | FO952 | - | 235 (226.8) | -8.0 | 1.9 | - | 1101 | -165 | -3.00 | 0.3 |
| 004 | RF Center: FORF2 r=2.02NM | FO953 | - | - | -8.0 | 1.6 | L | 578 | - | -3.00 | 0.3 |
| 005 | TF | RW19 | Y | 188 (180.4) | -8.0 | 1.6 | - | 67 | - | -3.00/50 | 0.3 |
| 006 | FA | - | - | 188 (180.4) | -8.0 | - | - | +500 | - | - | 1.0 |
| 007 | DF | BAIEN | - | - | -8.0 | - | L | 3000 | - | - | 1.0 |

| Path | Waypoint Identifier | Inbound Course °M(°T) | Magnetic Variation | Outbound Time (MIN) | Turn Direction | Minimum Altitude (FT) | Maximum Altitude (FT) | Speed (KIAS) | RNP Value |
|------|---------------------|-----------------------|--------------------|---------------------|----------------|-----------------------|-----------------------|--------------|-----------|
| Hold | BAIEN | 243 (234.9) | -8.0 | 1.0 (-14000) | L | 3000 | FL140 | -210(-14000) | 1.0 |

| Waypoint Coordinates | | | | | | | | | | | |
| Waypoint Identifier | | Coordinates | | RF Arc Center Identifier | | Coordinates | | | | | |
| BAIEN | | 333720.39N / 1315059.77E | | FORF2 | | 333110.65N / 1314640.11E | | | | | |
| FO951 | | 333356.67N / 1314639.45E | | | | | | | | | |
| FO952 | | 333239.42N / 1314500.88E | | | | | | | | | |
| FO953 | | 333111.58N / 1314414.94E | | | | | | | | | |
| RW19 | | 332934.89N / 1314414.08E | | | | | | | | | |

CHANGE : PROC course. VAR. HLDG pattern added.

RJFO / OITA

Visual REP



※図中に標高を示す数字がある場合、単位はメートル(m)である。The unit of measurement used to express elevation is meter(m).


CHANGE : Map updated. BRG/DIST from ARP.

| Call sign | BRG / DIST from ARP | Remarks |
|------------------------|---------------------|-----------------------------------|
| 姫島 Himeshima | 346°T / 15.3NM | 島 Island |
| ゴルフコース Golf course | 345°T / 9.7NM | ゴルフ場 Golf course |
| 行入ダム Gyonyu dam | 321°T / 7.0NM | ダム Dam |
| イーストポイント East point | 090°T / 10.0NM | 海上 Over the sea |
| 杵築 Kitsuki | 232°T / 6.7NM | 八坂川河口 River mouth (The Yasaka) |
| 佐賀関 Saganoseki | 152°T / 15.0NM | 精錬所煙突 Chimney |

RJFO / OITA

Minimum Vectoring Altitude CHART

VAR 7°W (2008)



CENTER : 332842N/1314351E (RADAR SITE)