

AD 2 AERODROMES

RJSM AD 2.1 AERODROME LOCATION INDICATOR AND NAME

RJSM - MISAWA

RJSM AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	ARP coordinates and site at AD	404211N 1412206E
2	Direction and distance from (city)	3nm NE of Misawa Railway Station
3	Elevation/ Reference temperature	119ft / -
4	Geoid undulation at AD ELEV PSN	Nil
5	MAG VAR/ Annual change	9°W(2021)/ 6°W
6	AD Administration, address, telephone, telefax, telex, AFS, e-mail and/or Web-site addresses	USAF 35 OSS/OSAA Unit 5011 APO AP 96319-5011 Tel: 0176-77-1110 ext.226.3110 e-mail: 35oss.amops@us.af.mil www.misawa.af.mil
7	Types of traffic permitted(IFR/VFR)	IFR/VFR
8	Remarks	Misawa Airport Office(Civil Aviation Bureau) Shimotazawa, Misawa, Aomori Prefecture TEL:0176-53-2461, 53-2463

RJSM AD 2.3 OPERATIONAL HOURS

1	AD Administration	H24
2	Customs and immigration	On request Customs: 0178-33-0423 Immigration: 017-777-2939
3	Health and sanitation	Quarantine(human): On request(017-722-7687) Quarantine(animal, plant): Nil
4	AIS Briefing Office	Nil
5	ATS Reporting Office(ARO)	Nil
6	MET Briefing Office	H24(SENDAL)
7	ATS	H24
8	Fuelling	Nil
9	Handling	Nil
10	Security	Nil
11	De-icing	Nil
12	Remarks	HR of service at CAB OPS section 2330 - 1100

RJSM AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	Nil
2	Fuel/ oil types	JET A-1 (For CIV ACFT) , JET A-1 PLUS (For JSDF ACFT)
3	Fuelling facilities/ capacity	Fuel truck refueling(For CIV ACFT)
4	De-icing facilities	Nil
5	Hangar space for visiting aircraft	Nil
6	Repair facilities for visiting aircraft	Nil
7	Remarks	Nil

RJSM AD 2.5 PASSENGER FACILITIES

1	Hotels	In Misawa city
2	Restaurants	At the Airport, not continuous
3	Transportation	Buses, Taxis and Rent-a-car
4	Medical facilities	Hospitals in Misawa city
5	Bank and Post Office	In Misawa city
6	Tourist Office	In Misawa city
7	Remarks	Nil

RJSM AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD category for fire fighting	CAT 10
2	Rescue equipment	(CAB) Emergency medical equipments conveyance truck x 1 Lighting power supply truck x 1
3	Capability for removal of disabled aircraft	Available via GOJ IAW Support Agreements
4	Remarks	Nil

RJSM AD 2.7 SEASONAL AVAILABILITY-CLEARING

1	Types of clearing equipment	Snow remove equipments *(CAB) : Rotary x 1, Loader x 2, Motor grader x 1, Anti-freezing sprayer x 1, Dump trucks, etc.
2	Clearance priorities	Nil
3	Remarks	*For Civil apron and TWY A8

RJSM AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS DATA

1	Apron surface and strength	Civil apron : Surface : Cement Concrete, Strength : PCN 50/R/C/X/T
2	Taxiway width, surface and strength	A: Width 23m Surface: Concrete Strength: PCN 42/R/B/W/T A1: Width 96m Surface: Concrete Strength: PCN 57/R/B/W/T A2: Width 66m Surface: Concrete Strength: PCN 71/R/B/W/T A3: Width 23m Surface: Concrete Strength: PCN 35/R/B/W/T A4: Width 23m Surface: Asphalt Strength: PCN 40/F/C/W/T A5: Width 55m Surface: Concrete Strength: PCN 44/R/B/W/T B1: Width 91m Surface: Concrete Strength: PCN 44/R/C/W/T B2: Width 23m Surface: Asphalt Strength: PCN 88/R/C/W/T B3: Width 23m Surface: Asphalt Strength: PCN 46/R/B/W/T B5: Width 23m Surface: Concrete Strength: PCN 67/R/C/W/T BRAVO: Width 23m Surface: Concrete Strength: PCN 39/R/B/W/T Civil TWY A8 : Width 23m Surface : Cement Concrete, Strength : PCN 50/R/C/X/T Surface : Asphalt Concrete, Strength : PCN 48/F/B/X/T
3	ACL and elevation	Not available
4	VOR checkpoints	TWY A1, A2, B1
5	INS checkpoints	Nil
6	Remarks	Nil

RJSM AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand ID signs, TWY guide lines and Visual docking / parking guidance system of aircraft stands	Nil
2	RWY and TWY markings and LGT	RWY: RWY10/28 (Marking): RWY designation, RWY CL, RWY THR, RWY THR stripe, Fixed DIST, TDZ, RWY Side stripe, RWY lead-on/lead-off lines, RWY Shoulder (LGT): RTHL, REDL, RENL, RWY DIST marker LGT, Arresting gear marker (AGM), RWY guard LGT (elev WIG-WAG) TWY: ALL TWY (EXC A8) (Marking): TWY side stripe, TWY CL (LGT): TWY edge LGT, TWY end LGT, Taxiing Guidance Sign Civil TWY: A8 (Marking): TWY side stripe, TWY CL (LGT): TWY edge LGT, TWY CL LGT
3	Stop bars	Nil
4	Remarks	Civil apron: (LGT): Apron flood LGT

RJSM AD 2.10 AERODROME OBSTACLES

In circling area and at AD

Obstacle type	Coordinates	Elevation	Markings/ LGT	Remarks
Airfield Beacon/Water Tower	404115.9N 1412138.3E	293FT MSL		

RJSM AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Associated MET Office	SENDAI
2	Hours of service MET Office outside hours	H24(SENDAI)
3	Office responsible for TAF preparation Periods of validity	Nil
4	Trend forecast Interval of issuance	Nil
5	Briefing/ consultation provided	Briefing is available upon inquiry at SENDAI
6	Flight documentation Language(s) used	C En
7	Charts and other information available for briefing or consultation	S ₆ , U ₈₅ , U ₇ , U ₅ , U ₃ , U ₂₅ , U ₂ /T _r , P _S , P ₅ , P ₃ , P ₂₅ , P _{SWE} , P _{SWF} , P _{SWG} , P _{SWI} , P _{SWM} , P _{SW} (domestic), E, C, W _E , W _F , W _G , W _I , W _N
8	Supplementary equipment available for providing information	Doppler Radar for Airport Weather (See below figure)
9	ATS units provided with information	TWR, APP, ATIS
10	Additional information (limitation of service, etc.)	Observation is made by the Ministry of Defence.

Airspace for the advisory service concerning low level wind shear

UPPER LIMIT: 1600ft above FIELD ELEV LEVEL
 LOWER LIMIT: FIELD ELEV LEVEL

RJSM AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY(M)	Strength(PCN) and surface of RWY	THR coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
10	to be issued later	3047×45	PCN 46/R/B/W/T Asphalt Concrete	404215.991N 1412101.361E	THR 114FT TDZ 116FT
28	to be issued later	3047×45	PCN 46/R/B/W/T Asphalt Concrete	404207.194N 1412310.850E	THR 94FT TDZ 98FT
Slope of RWY			Strip Dimensions(M)	Remarks	
7			10	12	
from the crown of the RWY -0.26			3650×600	RWY Grooving: 3047×42m	
from the crown of the RWY -0.148			3650×600		

RJSM AD 2.13 DECLARED DISTANCES

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)	Remarks
1	2	3	4	5	6

RJSM AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	APCH LGT type LEN INTST	RTHL Color WBAR	PAPI (VASIS) Angle DIST FM THR MEHT	RTZL LEN	RCLL LEN Spacing Color INTST	REDL LEN Spacing Color INTST	RENL Color WBAR	STWL LEN Color
1	2	3	4	5	6	7	8	9
10	ALSF-1 900m	Green Green	PAPI 3.00°/Left 947ft	Nil	Nil	2440m 60m coded color Yellow/White LIH	Red Red	Nil
28	ALSF-1 900m	Green Green	PAPI 2.37°/Left 1113ft	Nil	Nil	2440m 60m coded color Yellow/White LIH	Red Red	Nil
Remarks								
10								
RWY28 PAPI and ILS GS not coincidental. PAPI for RWY28 unuse beyond 8° right of RWY CL.								

RJSM AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	ABN/IBN location, characteristics and hours of operation	ABN: 404108N/1412145E , White/Green EV10sec, HN&HO
2	LDI location and LGT Anemometer location and LGT	Nil
3	TWY edge and centerline lighting	TWY edge LGT for A8:AVBL TWY CL LGT for A8:AVBL
4	Secondary power supply/ switch-over time	Nil
5	Remarks	Nil

RJSM AD 2.16 HELICOPTER LANDING AREA

Nil

RJSM AD 2.17 ATS AIRSPACE

Designation and lateral limits		Vertical limits (ft)	Airspace classification	ATS unit call sign Language	Remarks
1		2	3	4	6
MISAWA CTR	Area within a radius of 5nm of MISAWA ARP (40°42'N/141°22'E)	6000 or below	D	MISAWA TOWER En	
MISAWA PCA	SEE ATTACHED CHART		C	SEE ATTACHED CHART	
MISAWA ACA	SEE ATTACHED CHART		E		
MISAWA TCA	SEE ATTACHED CHART		E		

Misawa Positive Control Area

NAME	LATERAL LIMITS	UPPER LIMIT (AMSL)	UNIT PROVIDING SERVICE	REMARKS
		LOWER LIMIT (AMSL) M(ft)		
1	2	3	4	5
三沢 Misawa	下記に示される区域 The area shown below (1) 三沢第一特別管制区 Misawa NR 1 Positive Control Air Space		札幌ACC Sapporo ACC 124.5 MHz 303.8 MHz	当該空域を飛行しようとする VFR機は、札幌ACCに連絡し、 飛行の許可を求めること。 VFR aircraft operating which will fly in the airspace above should contact Sapporo ACC and obtain the permission.
	(2) 三沢第二特別管制区 Misawa NR 2 Positive Control Air Space		三沢アプローチ Misawa APP RADAR Primary 120.7 MHz 317.8 MHz Secondary 261.2MHz	当該空域を飛行しようとする VFR機は、三沢アプローチ又 はレーダーに連絡し、飛行の 許可を求めること。 VFR aircraft operating which will fly in the airspace above should contact Misawa APP/RADAR and obtain the permission.



Misawa Approach Control Area



Misawa Terminal Control Area



RJSM AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	Call sign	Frequency	Hours of operation	Remarks
1	2	3	4	5
APP/ASR	Misawa Approach/ Misawa Radar	317.8MHz(1) 261.2MHz(1) 362.3MHz(2) 120.7MHz(1) 120.1MHz(2) 243.0MHz(E) 121.5MHz(E)	H24	(1) VFR Radar advisory SER all ALT. (2) AVBL on request. (3) CLR delivery. (4) For rescue only.
TCA	Misawa TCA	124.05MHz 288.1MHz	2300 - 1100 SUN-THU (EXC HOL)	(5) Secondary.
DEP	Misawa Departure	363.8MHz(1) 125.3MHz(1)	H24	
TWR	Misawa Tower	315.8MHz 236.8MHz(5) 236.6MHz(2) 126.2MHz(5) 118.1MHz 138.05MHz(4) 247.0MHz(2)(4) 123.1MHz(2)(4) 121.5MHz(E) 243.0MHz(E)	H24	
GCA-ASR -PAR	Misawa Radar	258.2MHz 261.0MHz 270.8MHz 289.4MHz 335.8MHz 335.6MHz 134.1MHz 139.4MHz 125.15MHz 127.95MHz 121.5MHz(E) 243.0MHz(E)	H24	ASR, PAR RWY 10/28 Glide path 3.0° RWY10 Glide path 2.5° RWY28 if COM is lost on westerly HDG on downwind leg of radar APCH to RWY10, do not exceed 12 DME of MIS.
GND	Misawa Ground	275.8MHz(3) 126.2MHz(2) 118.65MHz(3)	H24	
ATIS	Misawa Airport	128.4MHz 315.35MHz	2200 - 1100 MON-FRI	
MET	Misawa Metro	344.6MHz	H24	PFSV

RJSM AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid	ID	Frequency	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
VOR (8° 00.0' W)	MIS	115.4MHz	H24	404213.76N 1412251.99E		VOR Unusable: (1) R050-100 beyond 25nm BLW 5500ft. (2) R135-200 WI 20nm BLW 5500ft beyond 20nm BLW 15000ft. (3) R240-280 beyond 30nm BLW 9500ft. (4) R310-350 beyond 20nm all ALT. VOR Maintenance period: 1500-2200Z(SUN-THU)
TACAN (8° 00.0' W)	MIS	Tx1188MHz (CH-101)	H24	404213.76N 1412251.99E	142ft	TACAN AZM and DME Unusable: 050°-065° beyond 25nm BLW 3000ft. TACAN DME unusable: 260°-275° beyond 39nm. TACAN Maintenance period: 1500-2200Z(SUN-THU)
ILS-LOC 28	I-MIS	109.7MHz	H24	-		LOC back course unusable for course guidance.
ILS-GP 28	-	333.2MHz	H24	-		ILS RWY 10/28 Maintenance period: 1500-2200Z(SUN-THU)
ILS-LOC10	I-MAS	109.7MHz	H24			
ILS-GP10		333.2MHz	H24			

RJSM AD 2.20 LOCAL TRAFFIC REGULATIONS

1. Airport regulations

1. Do not overfly Misawa City located S of AB below 3000FT VMC.
2. Do not overfly school building located APRX 1.5NM ESE of AB.
3. On take off all ACFT (including radar vectored ACFT) must MNTN RWY HDG at or below 1600FT until 3 DME for RWY28 or 2 DME for RWY10 unless otherwise cleared by ATC.

2. Taxiing to and from stands

TKOF restriction:
To prevent jet blast damage to over run, all TKOF and ENG run by jet ACFT shall be performed at least 200ft FM RWY THR.

3. Parking area for small aircraft(General aviation)

Nil

4. Parking area for helicopters

Nil

5. Apron - taxiing during winter conditions

Nil

6. Taxiing - limitations

1. Alpha Taxilane is located between TWY A1 and A4 and is restricted to aircraft with wingspans of 170ft (C-17) or smaller. Aircraft with wingspans larger than 170ft requiring the use of Alpha Taxilane must receive approval from the AFM prior to use.
 2. TWY B between B2 and B5 restricted to C130, P8, CH-47 or smaller aircraft. B-737 operations authorized on full length of TWY B. Any other use requires coordination with the AFM and/or CES pavement engineer.
- NOTE: Intersection of TWY B and C3/B3 unrestricted.

7. School and training flights - technical test flights - use of runways

Nil

8. Helicopter traffic - limitation

Nil

9. Removal of disabled aircraft from runways

Nil

RJSM AD 2.21 NOISE ABATEMENT PROCEDURES

1. Local established ACFT quiet HR at Misawa 1300-2100Z DLY. No ENG runs, ARR or DEP WO prior COOR approval; policy strictly enforced.
2. The south departure ACFT will delay turns until 3.5 DME for RWY28 and 2.5 DME for RWY10.

RJSM AD 2.22 FLIGHT PROCEDURES

1. Automated Radar Terminal System (ARTS)

三沢進入管制所の指示のもとに、当該進入管制区を飛行する航空機は、モード A/3 の二次レーダー個別コード及びモード C による応答を指示される。
二次レーダー個別コードを搭載していない航空機が当該コードによる応答を指示された場合は、管制官に対し、その旨通報すること。

Aircraft flying within the approach control area under the control of Misawa approach control will be instructed to reply with discrete code on Mode A/3 and Mode C.

If an aircraft with non-discrete code capability be instructed to reply with the discrete code, it shall report a controller accordingly.

2. WX MINIMA CONCERNING PAR/ASR APCH PROCEDURE

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/HATh HAA</u>	<u>CEIL-VIS</u>
PAR ②	28 ④	3°/-/-	ABCDE	209/18	100	(100-¼)
	10 ⑤	3°/-/-	ABCDE	219/24	100	(100-¼)
ASR ②	10 ⑥		ABCDE	480/40	371	(400-¾)
	28 ⑦		ABC	540/40	431	(500-¾)
			DE	540/50	431	(500-1)
CIR ③	10-28		A	540-1¼	421	(500-1¼)
			B	580-1¼	461	(500-1¼)
			C	580-1½	461	(500-1½)
			DE	680-2	561	(600-2)

① a. LOST COMMUNICATIONS: If no transmissions are received for more than 30 seconds for Rwy 10 (1 minute for Rwy 28) during radar vectors to final, or for more than 5 seconds/15 seconds once established on PAR/ASR final approach, the pilot shall maintain VMC and attempt to contact Misawa Tower. If unable to maintain VMC, the pilot shall proceed to SHOJU IAF for the runway of departure, at last assigned alt or 9000, whichever is higher, and execute instrument approach or previously coordinated instruction.


① b. If com is lost on westerly hdg on downwind leg of radar apch to Rwy 10, do not exceed 10.7 mile fix of MISAWA VORTAC. CAUTION: Possible interference on freq 270.8 from Chitose. ② MP 2300-0300Z Fri.

③ Cir not auth S of Rwy 10-28. ④ When ALS inop, increase RVR to 24, vis to ½. ⑤ When ALS inop, increase RVR to 40, vis to ¾. ⑥ When ALS inop, increase vis CAT ABC RVR to 50, vis to 1 mile, CAT DE RVR to 60, vis to 1¼. ⑦ When ALS inop, increase CAT AB RVR to 50, vis to 1 mile, CAT C RVR to 60, vis to 1¼, CAT DE vis to 1½.

NOTE: REPRINTING DOD FLIP

RJSM AD 2.23 ADDITIONAL INFORMATION

1. 無操縦者航空機の飛行について 1.1 三沢飛行場周辺の空域において、無操縦者航空機の飛行が次のとおり実施される。		1.Unmanned aircraft operations 1.1 Unmanned aircraft operations will take place in the vicinity of Misawa aerodrome as follows	
航空機	RQ-4(グローバル・ホーク) : unmanned aircraft の用語が使用される。	Aircraft	RQ-4(Global Hawk) : Term "unmanned aircraft" is used.
区域	添付図参照	AREA	See attached chart
飛行方式	計器飛行方式	Flight Rules	IFR
高度	1,000ft から 29,000ft まで	Altitude	1,000ft to 29,000ft
期間	飛行予定時間はノータムにより通知される	Period	Expected date and time for the operations will be notified by NOTAM.
1.2 三沢飛行場周辺の空域において飛行する航空機は次の対応が求められる。 (1) 有視界飛行方式により当該空域に入域する際は、事前に ATIS の聴取又は管制機関 (20,000 フィート以下の場合は三沢進入管制所、20,000 フィートを超える場合は札幌管制部) との通信設定を行い、無操縦者航空機の運航の有無を確認すること。(“unmanned aircraft operations are in progress” の用語が三沢 ATIS の備考に追加される。) (2) 無操縦者航空機が運航される場合、有視界飛行方式により当該空域に入域する際は、ATC トランスポンダーの VFR コード (飛行高度 10,000 フィート未満は 1200、10,000 フィート以上は 1400) を発信するとともに、管制機関 (20,000 フィート以下の場合は三沢進入管制所、20,000 フィートを超える場合は札幌管制部) と無線電話により通信設定を行い、積極的に、自機の位置等運航情報を連絡し、また、管制機関によるレーダー業務 (レーダー・サービス) の提供を求める等により、無操縦者航空機の動向についてモニターを実施すること。 ※ 三沢 ATIS 運用時間外に無操縦者航空機が運用される場合、臨時に ATIS 放送が実施される。 ※ 三沢進入管制所 (120.7MHz) ※ 札幌管制部 (124.5MHz)		1.2 The aircraft flying in the vicinity of Misawa aerodrome will be required following action. (1) A VFR aircraft should monitor Misawa ATIS or contact Misawa APP/ASR at or below 20,000 feet or SAPPORO-ACC above 20,000 feet before entering the area and check the unmanned aircraft operations.(Misawa ATIS will broadcast "unmanned aircraft operations are in progress" in the remark section.) (2) During the unmanned aircraft operations, an aircraft mentioned above should squawk SSR code 1200 below 10,000 feet or 1400 at or above 10,000 feet, contact Misawa APP/ASR at or below 20,000 feet or SAPPORO-ACC above 20,000 feet, make position report proactively, and request radar services or take other suitable measures to monitor the movement of the unmanned aircraft. *Misawa ATIS temporarily opens and broadcasts the above information when the unmanned aircraft operations take place beyond Misawa ATIS service hours. *Frequency for Misawa APP/ASR is 120.7MHz *Frequency for SAPPORO-ACC is 124.5MHz	




RJSM AD 2.24 CHARTS RELATED TO AN AERODROME

Aerodrome/Heliport Chart
Aircraft Parking/Docking Chart (for civil)
Standard Departure Chart - Instrument
Instrument Approach Chart (HI-ILS Y or LOC Y RWY28)
Instrument Approach Chart (ILS Z or LOC Z RWY28)
Instrument Approach Chart (HI-VOR Y or TACAN Y RWY28)
Instrument Approach Chart (VOR Z or TACAN Z RWY28)
Instrument Approach Chart (HI-ILS Z or LOC Z RWY10)
Instrument Approach Chart (HI-VOR Y or TACAN Y RWY10)
Other Chart (MVA CHART)

INTENTIONALLY LEFT BLANK

RJSM / MISAWA


AD CHART



NOTE: REPRINTING DOD FLIP

RJSM / MISAWA

Aircraft Parking / Docking Chart



STANDARD DEPARTURE CHART - INSTRUMENT


RJSM / MISAWA

ENKAI TWO DEPARTURE

ATIS ★ 128.4 315.35
CLNC DEL
118.65 275.8
TOWER
118.1 315.8
DEP CON
125.3 363.8

Rwy	Knots	60	120	180	240	300	360
10	V/V(fpm)	350	700	1050	1400	1750	2100

ATC Climb Rate to 3500



DEPARTURE ROUTE DESCRIPTION

TAKE-OFF RWY 10: Climb on MIS VORTAC R-105 to ENKAI.
Cross ENKAI at or above 3500.


CHANGE : Update.

NOTE: REPRINTING DOD FLIP

STANDARD DEPARTURE CHART - INSTRUMENT

RJSM / MISAWA

KOSUI TWO DEPARTURE



▼


DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWY 28: Climb on MIS VORTAC R-282 to KOSUI.
Cross KOSUI at or above 3600.

CHANGE : Update.

NOTE: REPRINTING DOD FLIP

STANDARD DEPARTURE CHART - INSTRUMENT



CHANGE : Update.

STANDARD DEPARTURE CHART - INSTRUMENT

RJSM / MISAWA

MISAWA SIX DEPARTURE



(CONTINUED)

HANAMAKI TRANSITION:

TAKEOFF RWY 10: ...turn right to intercept MIS TACAN R-196 (HPE VOR/DME R-017) to HANAMAKI VOR/DME. Cross OMBOE at or above 10,000. Maintain ATC assigned altitude.

TAKEOFF RWY 28: ...turn left to intercept MIS R-196 (HPE R-017) to HANAMAKI VOR/DME. Cross OMBOE at or above 10,000. Maintain ATC assigned altitude.

JYONA TRANSITION:

TAKEOFF RWY 10: ...continue climb to 2000, then turn right and climb via MIS VORTAC to intercept MIS R-310 direct to JYONA. Cross JYONA at or above 3500. Maintain ATC assigned altitude.

TAKE-OFF RWY 28: ...then turn right to intercept MIS R-310 to JYONA. Cross JYONA at or above 3500. Maintain ATC assigned altitude.

MIYAKO TRANSITION:

TAKEOFF RWY 10: ...turn right to intercept MIS R-161 (MQE VOR/DME R-340) to MIYAKO VOR/DME. Cross the SESEA at or above 8000. Maintain ATC assigned altitude.

TAKEOFF RWY 28: ...turn left to intercept MIS R-161 (MQE R-340) to MIYAKO VOR/DME. Cross the SESEA at or above 8000. Maintain ATC assigned altitude.

OLSAE TRANSITION:

TAKEOFF RWY 10: ...turn right to intercept MIS R-233 to OLSAE (MIS R-233/40 DME). Cross OLSAE at or above 9000. Maintain ATC assigned altitude.

TAKEOFF RWY 28: ...turn left to intercept MIS R-233 to OLSAE (MIS R-233/40 DME). Cross OLSAE at or above 9000. Maintain ATC assigned altitude.

SAMBO TRANSITION:

TAKEOFF RWY 10: ...turn right to intercept MIS R-221 to SAMBO (MIS R-221/36.7 DME). Cross SAMBO at or above 13,000. Maintain ATC assigned altitude.

TAKEOFF RWY 28: ...turn left to intercept MIS R-221 to SAMBO (MIS R-221/36.7 DME). Cross SAMBO at or above 13,000. Maintain ATC assigned altitude.

CHANGE : Update.

NOTE: REPRINTING DOD FLIP

STANDARD DEPARTURE CHART - INSTRUMENT


RJSM / MISAWA

ATIS★128.4 315.35
CLNC DEL
118.65 275.8
TOWER
118.1 315.8
DEP CON
125.3 363.8

REIWA ONE DEPARTURE

Rwy	Knots	60	120	180	240	300	360
10	V/V(fpm)	289	578	867	1156	1445	1734
28	V/V(fpm)	249	498	747	996	1245	1494


ATC Climb Rate to 10,000



INTENTIONALLY LEFT BLANK

INSTRUMENT APPROACH CHART


RJSM / MISAWA



NOTE: REPRINTING DOD FLIP

INSTRUMENT APPROACH CHART


RJSM / MISAWA



NOTE: REPRINTING DOD FLIP

INSTRUMENT APPROACH CHART

RJSM / MISAWA



NOTE: REPRINTING DOD FLIP

INSTRUMENT APPROACH CHART

RJSM / MISAWA

VORTAC MIS 115.4 Chan 101	APCH CRS 290°	Rwy ldg 9999 TDZE 109 Arpt Elev 119
---	-------------------------	--

VOR Z or TACAN Z RWY28

RADAR or DME required.

▼ * When ALS inop, increase CAT AB RVR to 55 vis to 1 mile, CAT CDE vis to 1¼ miles.
** Circling S of Rwy 10-28 not authorized.


ALSF-1



MISSED APPROACH: Climb to 7000 on MIS VORTAC R-280 to KISSA, then climbing left direct SHOJU and hold. Continue climb in holding to 7000.


ATIS ★ 128.4 315.35	APP CON 120.7 317.8	TOWER 118.1 315.8	GND CON 118.65 275.8	CLNC DEL 118.65 275.8	ASR/PAR
-------------------------------	-------------------------------	-----------------------------	--------------------------------	---------------------------------	---------

Missed approach requires use of RNAV or ATC RADAR.



EMERG SAFE ALT 100 NM 8700


7000 MIS R-280	KISSA MIS 8	SHOJU MIS R-200 20
----------------------	-------------------	-----------------------------

TLv FL140
TA 14,000VGSI and descent
angles not coincident

CATEGORY	A	B	C	D	E
S-28 *	540/24 431 (500-½)	540/40 431 (500-¾)			
CIRCLING **	580-1 461 (500-1)	580-1½ 461 (500-1½)	680-2 561 (600-2)		

ELEV 119

TDZE 109



HIRL Rwy 10-28

NOTE: REPRINTING DOD FLIP

RJSM / MISAWA

CHANGE · Update

11/8/22

INSTRUMENT APPROACH CHART

RJSN / MISAWA

VORTAC MIS	APCH CRS	Rwy ldg
115.4	101°	TDZE 119
Chan 101		Arpt Elev 119

HI-VOR Y or TACAN Y RWY10


RADAR or DME required.

* When ALS inop, increase RVR CAT AB to 55 and vis to 1 mile,
CAT CDE vis to 1½ miles.
** Circling S of Rwy 10-28 not authorized.

ALSF-1

MISSED APPROACH: Climb to 4000 on MIS
VORTAC R-106 to STICK and hold. Continue
climb in holding to 4000.


ATIS ★	APP CON	TOWER	GND CON	CLNC DEL	ASR/PAR
128.4 315.35	120.7 317.8	118.1 315.8	118.65 275.8	118.65 275.8	



EMERG SAFE ALT 100 NM 8700

VGS and descent
angles not coincidentTLv FL140
TA 14,0004000
MIS
R-106STICK
MIS
14


CHANGE: New PROC.



CATEGORY	A	B	C	D	E
S-10 *	620/24	501 (600-½)	620/55	501	(600-1)
CIRCLING **	620-1	501 (600-1)	620-1½ 501 (600-1½)	680-2	561 (600-2)

ELEV 119

TDZE 119



NOTE: REPRINTING DOD FLIP

RJSM / MISAWA

Minimum Vectoring Altitude CHART

