


RJOS / TOKUSHIMA


AD CHART

CHANGE : Description of strength of pavement.



INTENTIONALLY LEFT BLANK

STANDARD DEPARTURE CHART-INSTRUMENT



STANDARD DEPARTURE CHART-INSTRUMENT

CHANGE : PROC course. PROC renamed(HONMA TWO DEPARTURE). Navigation Specification(RNAV1 → RNP1). VAR.

RJOS / TOKUSHIMA RNAV SID and TRANSITION

HONMA TWO DEPARTURE

RWY11

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	111 (102.6)	-8.0	-	-	+500	-	-	RNP1
002	DF	HATIS	-	-	-8.0	-	R	-	-	-	RNP1
003	TF	SIJIL	-	145 (136.9)	-8.0	3.6	-	3000	-	-	RNP1
004	TF	HONMA	-	145 (136.9)	-8.0	13.0	-	+5000	-	-	RNP1

RWY29

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	291 (282.6)	-8.0	-	-	+500	-	-	RNP1
002	DF	HATIS	-	-	-8.0	-	L	-	-	-	RNP1
003	TF	SIJIL	-	145 (136.9)	-8.0	3.6	-	3000	-	-	RNP1
004	TF	HONMA	-	145 (136.9)	-8.0	13.0	-	+5000	-	-	RNP1

KILAP TRANSITION

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	HONMA	-	-	-8.0	-	-	+5000	-	-	RNP1
002	TF	KMANO	-	113 (105.2)	-8.0	8.9	-	-	-	-	RNP1
003	TF	KILAP	-	104 (095.9)	-8.0	82.2	-	-	-	-	RNP1

STANDARD DEPARTURE CHART-INSTRUMENT


RJOS / TOKUSHIMA

RNAV SID

KAGAWA ONE DEPARTURE

RNP1

Note GNSS required.



RWY11 : Climb on HDG111° at or above 500FT, turn right direct to OBDED at or above 5000FT, to KTE.
 RWY29 : Climb on HDG291° at or above 500FT, direct to OBDED at or above 5000FT, to KTE.

Note RWY11 : 5.0% climb gradient required up to 1700FT.

OBST ALT 2494FT located at 11.5NM 288° FM end of RWY11.

RWY29 : 5.0% climb gradient required up to 2800FT.

OBST ALT 2494FT located at 10.2NM 288° FM end of RWY29.

RWY11

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	111 (102.6)	-8.0	-	-	+500	-	-	RNP1
002	DF	OBDED	-	-	-8.0	-	R	+5000	-	-	RNP1
003	TF	KTE	-	293 (284.7)	-8.0	14.8	-	-	-	-	RNP1

RWY29

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	291 (282.6)	-8.0	-	-	+500	-	-	RNP1
002	DF	OBDED	-	-	-8.0	-	-	+5000	-	-	RNP1
003	TF	KTE	-	293 (284.7)	-8.0	14.8	-	-	-	-	RNP1

CHANGE : New PROC.

STANDARD DEPARTURE CHART-INSTRUMENT

RJOS / TOKUSHIMA

SID

TOSAR SIX DEPARTURE

RWY11 : Climb RWY HDG to 500FT, turn right HDG232°...

RWY29 : Climb RWY HDG to 600FT, turn left HDG142°...


...to intercept and proceed via TSC R187 to TOSAR.

Cross TSC R187/13.0DME at 3000FT, cross TSC R187/20.0DME at 6000FT, cross TOSAR at assigned altitude.

NOTE RWY29 : 4.0% climb gradient required up to 800FT.

OBST ALT 1105FT located at 5.0NM 224° FM end of RWY29.

CHANGE : PROC course. PROC renamed(TOSAR SIX DEPARTURE). Note.



STANDARD DEPARTURE CHART-INSTRUMENT

RJOS / TOKUSHIMA

SID

TOKUSHIMA REVERSAL SEVEN DEPARTURE

RWY11 : Climb RWY HDG to 500FT, turn right HDG205°...

RWY29 : Climb RWY HDG to 600FT, turn left HDG115°...


...to intercept and proceed via TSC R160 to 13.0DME, turn right, direct to TSC VORTAC.

Cross TSC R160/13.0DME at 3000FT, cross TSC VORTAC at or above 6000FT.

NOTE RWY29 : 4.0% climb gradient required up to 800FT.

OBST ALT 1105FT located at 5.0NM 224° FM end of RWY29.

CHANGE : PROC course. PROC renamed(TOKUSHIMA REVERSAL SEVEN DEPARTURE). Note.



STANDARD DEPARTURE CHART -INSTRUMENT

RJOS / TOKUSHIMA

SID and TRANSITION

MISAKI FOUR DEPARTURE

RWY11 : Climb RWY HDG to 500FT, turn right,...

RWY29 : Climb RWY HDG to 600FT, turn left HDG098° to intercept and proceed...
...via TSC R143 to HONMA.Cross TSC R143/12.0DME at 3000FT, cross HONMA at or above 8000FT.
(Cross HONMA at or above 9000FT when using KEC TACAN only).


NOTE RWY29 : 4.0% climb gradient required up to 800FT.

OBST ALT 1105FT located at 5.0NM 224° FM end of RWY29.

CHANGE : PROC renamed. PROC course. ALT restriction at HONMA when using KEC TACAN only.

KUSHIMOTO TRANSITION

From over HONMA, via KEC R306 to KEC VORTAC.



STANDARD ARRIVAL CHART-INSTRUMENT


RJOS / TOKUSHIMA

STAR

TOSAR ARRIVAL


From over TOSAR, via TSC R187 to TSC VORTAC.
Cross TSC VORTAC at 5000 FT.

CHANGE : Distance FM TSC to TOSAR added.




INTENTIONALLY LEFT BLANK

INSTRUMENT APPROACH CHART




INSTRUMENT APPROACH CAHRT


CHANGE : PROC course. Missed APCH PROC. MINIMA. ALT(3.0° APCH Path) established. HDG pattern. EQPT REQUIRED. PROC ALT established. OCA/H established. ALT restriction. GUNVI established. DME to ITS. NM to THR.




INSTRUMENT APPROACH CHART



INSTRUMENT APPROACH CHART




INSTRUMENT APPROACH CHART



INSTRUMENT APPROACH CHART


RJOS / TOKUSHIMA



MISSSED APPROACH

From RW11 on track 110°, at or above 500FT turn right, direct to DATIS and hold at 3000FT. Contact TOKUSHIMA APP.

CHANGE : Description of VAR.



Missed APCH climb gradient MNM 5.0%

MINIMA		THR elev. 6		AD elev. 37	
CAT	RNP 0.15		RNP 0.30		
	DA(H)	CMV	DA(H)	CMV	
A	-	-	-	-	
B					
C	306(300)	1400	362(356)	1400	
D		1600		1600	

MINIMA with Missed APCH climb gradient of 2.5% are not established.

Authorization Required

INSTRUMENT APPROACH CHART

RJOS / TOKUSHIMA

RNP Z RWY11(AR)

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	DATIS	-	-	-7.8	-	-	+3000	-	-	-
002	TF	AIZEN	-	292 (284.2)	-7.8	10.4	-	-	-	-	1.0
003	TF	OS150	-	292 (284.1)	-7.8	10.2	-	+3000	-180	-	0.3
004	RF Center: OSRF2 r=2.38NM	BIZAN	-	-	-7.8	3.2	R	2000	-	-	0.3
005	RF Center: OSRF2 r=2.38NM	OS151	-	-	-7.8	4.2	R	661	-	-3.00	0.15 0.30
006	TF	RW11	Y	110 (102.6)	-7.8	1.9	-	56	-	-3.00/50	0.15 0.30
007	FA	-	-	110 (102.6)	-7.8	-	-	+500	-	-	1.0
008	DF	DATIS	-	-	-7.8	-	R	3000	-	-	1.0


Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
DATIS	335851.96N / 1345613.14E	OSRF2	340610.26N / 1343254.26E
AIZEN	340123.97N / 1344405.59E		
OS150	340351.55N / 1343212.95E		
BIZAN	340613.12N / 1343002.50E		
OS151	340829.79N / 1343331.39E		
RW11	340804.98N / 1343545.74E		

CHANGE : PROC renamed.

INSTRUMENT APPROACH CHART

RJOS / TOKUSHIMA



INSTRUMENT APPROACH CHART

RJOS / TOKUSHIMA

RNP Y RWY11(AR)

Coding Table


Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	KULUL	-	-	-7.8	-	-	+5000	-210	-	-
002	TF	DOCHU	-	179 (171.2)	-7.8	2.7	-	+3100	-	-	0.3
003	TF	OS152	-	179 (171.2)	-7.8	2.0	-	-	-180	-	0.3
004	RF Center: OSRF1 r=2.88NM	OS153	-	-	-7.8	7.5	L	-	-	-	0.3
005	TF	FUDOU	-	030 (022.4)	-7.8	1.8	-	2000	-	-	0.3
006	TF	OS154	-	030 (022.4)	-7.8	0.9	-	1717	-	-3.00	0.15 0.30
007	RF Center: OSRF2 r=2.38NM	OS151	-	-	-7.8	3.3	R	661	-	-3.00	0.15 0.30
008	TF	RW11	Y	110 (102.6)	-7.8	1.9	-	56	-	-3.00/50	0.15 0.30
009	FA	-	-	110 (102.6)	-7.8	-	-	+500	-	-	1.0
010	DF	DATIS	-	-	-7.8	-	R	3000	-	-	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
KULUL	340954.74N / 1342131.22E	OSRF1	340544.73N / 1342549.48E
DOCHU	340716.80N / 1342200.89E	OSRF2	340610.26N / 1343254.26E
OS152	340517.99N / 1342223.19E		
OS153	340438.24N / 1342902.35E		
FUDOU	340615.76N / 1342950.98E		
OS154	340705.08N / 1343015.59E		
OS151	340829.79N / 1343331.39E		
RW11	340804.98N / 1343545.74E		
DATIS	335851.96N / 1345613.14E		


CHANGE : PROC renamed.

INSTRUMENT APPROACH CHART



INSTRUMENT APPROACH CHART

RJOS / TOKUSHIMA



INSTRUMENT APPROACH CHART

RJOS / TOKUSHIMA

RNP Y RWY29(AR)

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/RDH (°/FT)	RNP Value
001	IF	KULUL	-	-	-7.8	-	-	+5000	-	-	-
002	TF	OHASA	-	092 (083.7)	-7.8	8.6	-	-	-	-	1.0
003	TF	WAKME	-	092 (083.8)	-7.8	4.5	-	3500	-	-	0.7
004	TF	OS953	-	092 (083.8)	-7.8	1.9	-	2905	-165	-3.00	0.27 0.30
005	RF Center: OSRF3 r=2.08NM	OS954	-	-	-7.8	7.2	R	610	-	-3.00	0.27 0.30
006	TF	RW29	Y	290 (282.6)	-7.8	1.6	-	91	-	-3.00/54	0.27 0.30
007	FA	-	-	290 (282.6)	-7.8	-	-	+500	-	-	1.0
008	DF	DATIS	-	-	-7.8	-	L	3000	-	-	1.0


Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
KULUL	340954.74N / 1342131.22E	OSRF3	340928.04N / 1343948.74E
OHASA	341051.19N / 1343153.12E		
WAKME	341120.36N / 1343718.44E		
OS953	341132.33N / 1343932.73E		
OS954	340726.04N / 1343916.02E		
RW29	340747.36N / 1343720.97E		
DATIS	335851.96N / 1345613.14E		

CHANGE : PROC renamed.


RJOS / TOKUSHIMA

Visual REP



CHANGE : VAR.


Call sign	BRG / DIST from ARP	Remarks
福良 Fukura	037°T / 9.0NM	港 Harbor
岡崎 Okazaki	029°T / 3.3NM	灯台 Lighthouse
沼島 Nushima	079°T / 11.1NM	灯台 Lighthouse
吉野イニシャル Yoshino Initial	248°T / 4.5NM	鉄道橋中央 The center of iron bridge
吉野リバー Yoshino River	188°T / 3.3NM	吉野川河口 River mouth



RJOS / TOKUSHIMA

Minimum Vectoring Altitude CHART

VAR 8°W (2023)



- ① 2000
 - ② 3000
 - ③ 1700
 - ④ 2100
 - ⑤ 4500

CENTER : 340751N/1343552E (RADAR SITE)

CHANGE : VAR.

INTENTIONALLY LEFT BLANK