

AD 2 AERODROMES**RJTT AD 2.1 AERODROME LOCATION INDICATOR AND NAME****RJTT - TOKYO International****RJTT AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA**

1	ARP coordinates and site at AD	353312N/1394652E 301° /2.3km from RWY 34R THR
2	Direction and distance from (city)	14km (7.6nm) S of Tokyo Station (Japan Railway)
3	Elevation/ Reference temperature	21ft / 31°C (2004-2008)
4	Geoid undulation at AD ELEV PSN	117.6FT
5	MAG VAR/ Annual change	8°W (2021) /0.07'E
6	AD Administration, address, telephone, telefax, telex, AFS, e-mail and/or Web-site addresses	Civil Aviation Bureau, Ministry of Land, Infrastructure, Transport and Tourism. Tokyo International Airport, 3-1. 3-chome, Haneda-Kuko, Ota-ku, Tokyo, 144-0041 Japan. Tel : 03-5757-3000, Fax : 03-5756-1511 Tel(AD) : 03-5756-1531,1532, Tel(AIS) : 050-3198-2863, Fax : 03-5756-1528 AFS : RJTTYFYX
7	Types of traffic permitted (IFR/VFR)	IFR/VFR
8	Remarks	Nil

RJTT AD 2.3 OPERATIONAL HOURS

1	AD Administration	H24
2	Customs and immigration	H24
3	Health and sanitation	H24
4	AIS Briefing Office	H24
5	ATS Reporting Office(ARO)	Nil
6	MET Briefing Office	H24
7	ATS	H24
8	Fuelling	H24
9	Handling	H24
10	Security	H24
11	De-icing	Nil
12	Remarks	Nil

RJTT AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	All the modern institutions that deal with the weight thing to Boeing747-8F type freighter.
2	Fuel/ oil types	Fuel Grades : JET A-1 Oil grades : Turbine grades
3	Fuelling facilities / capacity	Hydrant refueling,fuel truck/Not limitation
4	De-icing facilities	Nil
5	Hangar space for visiting aircraft	Nil
6	Repair facilities for visiting aircraft	Nil
7	Remarks	Nil

RJTT AD 2.5 PASSENGER FACILITIES

1	Hotels	At Airport
2	Restaurants	At Airport
3	Transportation	Monorail, Railways, Busses and Taxis
4	Medical facilities	First aid treatment, ambulance
5	Bank and Post Office	At Airport
6	Tourist Office	At Airport
7	Remarks	Nil

RJTT AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD category for fire fighting	CAT 10
2	Rescue equipment	Chemical fire fighting truck x 6, Water-supply truck, Lighting power supply truck, Emergency medical equipments conveyance truck
3	Capability for removal of disabled aircraft	To be issued later
4	Remarks	Nil

RJTT AD 2.7 SEASONAL AVAILABILITY-CLEARING

1	Types of clearing equipment	Snow remove equipments: 1) 6 snow sweepers 2) 8 snow plows 3) 2 rotaries 4) 2 motor graders 5) 5 loaders
2	Clearance priorities	1) RWY16R/34L and 16L/34R, Taxiways attached to the RWY 2) RWY04/22 and 05/23, Taxiways attached to the RWY
3	Remarks	Seasonal availability : All seasons. Snow removal will be commenced, if the RWY and TWY are covered with a depth of 3cm snow or more.

RJTT AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS DATA

1	Apron surface and strength	Terminal 1, Terminal 2 Surface : Concrete Strength : PCN 74/R/B/X/T Terminal 3 Surface : Concrete Strength : PCN 78/R/B/X/T N Area Surface : Concrete Strength : PCN 48/R/B/X/T N Area Spot NR951-957, 961-969 Surface : Concrete Strength : PCN 91/R/B/X/T Compass Area Surface : Concrete Strength : PCN 74/R/B/X/T
2	Taxiway width, surface and strength	Surface : Asphalt-concrete, concrete Strength : PCN 75/F/B/X/T, PCN 74/R/B/X/T Width : 34m(111FT) : A6, A9, A11, B2, B5, B7, C8, C9, E3(between C and E), E4, E5, E8(between C and E), E9(between C and E), E12(between C and E), G(between C and E), H(between A and W), H(between C and E), J(between A and W), J(between C and E), K(between A and W), L4, L6, L9, L11, M2(between C and E), W6 THRU W10, W11(between A and W), W13 32m(105FT) : A1, A2, A4, B1, C1, E1, E2, E10(between C and E), G(between A and W), K(between C and E), L3, R(between G and H), R(between K and J), W1 30m(98FT) : A, A3, A5, A7, A8 THRU A10, A12 THRU A16, B, B3, B4, B6, B8 THRU B14, C, C2 THRU C7, C10 THRU C14, D, D1 THRU D7, E3(between E and R), E, E8(between E and R), E9(between E and R), E10(from spot NR55 to spot NR53), E12(between E and R), G(between E and W), H(between E and W), H1, H2, R1, J(between E and W), J1, J2, K(between E and W), L, L5, L10, L12 THRU L16, M, M1, M2(between E and R), N(between spot NR981 and N7), N1, N5, N7, P, P3 THRU P11, Q, Q1, Q2, R(between A and G), R(between E8 and E9), R(between E10 and J), R(between K and C), R(between A and S), S, S1 THRU S3, T, T1 THRU T9, T11, T12, T14, U2, U4, V, W, W11(between W and R1), Y1 15m(49FT) : N6(between spot NR961 and N3) 23m(75FT) : Other
3	ACL and elevation	Not available
4	VOR checkpoints	Not available

5	INS checkpoints	<p>Spot NR</p> <p>1 : 353244.87N/1394715.45E 2 : 353243.91N/1394713.19E 3 : 353242.77N/1394710.79E 4 : 353241.67N/1394708.47E 5R : 353240.61N/1394706.99E 5 : 353240.85N/1394707.04E 5L : 353240.41N/1394705.84E 6 : 353241.75N/1394705.46E 7 : 353243.30N/1394705.33E 8 : 353245.27N/1394705.86E 9 : 353248.11N/1394704.81E 10 : 353250.36N/1394703.25E 11 : 353252.33N/1394700.22E 12 : 353252.76N/1394658.54E 13 : 353254.41N/1394657.37E 14 : 353255.85N/1394657.64E 15 : 353258.98N/1394657.09E 16 : 353301.21N/1394655.50E 17 : 353303.24N/1394652.77E 18 : 353303.50N/1394650.89E 19 : 353304.80N/1394648.96E 20 : 353306.09N/1394648.17E 21 : 353306.70N/1394649.16E 22 : 353307.44N/1394651.14E 23 : 353308.19N/1394653.09E</p> <p>31 : 353313.19N/1394648.39E 32 : 353314.60N/1394647.42E 33 : 353316.57N/1394646.03E 34 : 353318.53N/1394644.64E 35 : 353320.50N/1394643.24E 36 : 353322.46N/1394641.85E 37 : 353324.18N/1394639.92E 38 : 353326.39N/1394639.06E 39 : 353328.36N/1394637.66E 40 : 353330.32N/1394636.27E 41 : 353332.28N/1394634.87E</p> <p>53 : 353319.25N/1394714.98E 54 : 353320.22N/1394717.28E 55 : 353321.20N/1394719.34E 56 : 353318.42N/1394721.31E 57 : 353317.26N/1394719.15E 58 : 353314.90N/1394715.68E 59 : 353311.22N/1394717.32E 60 : 353309.26N/1394718.72E 61 : 353307.29N/1394720.11E 62 : 353305.33N/1394721.51E 63 : 353303.36N/1394722.90E 64 : 353301.40N/1394724.30E 65 : 353259.43N/1394725.69E 66 : 353256.29N/1394729.18E 67R : 353257.40N/1394732.54E 67 : 353257.49N/1394732.99E 67L : 353258.73N/1394733.01E 68 : 353258.54N/1394734.99E 69 : 353255.82N/1394737.27E 70 : 353254.33N/1394735.67E 71 : 353253.92N/1394733.45E 72 : 353252.85N/1394731.08E 73 : 353251.67N/1394728.59E 81 : 353313.04N/1394725.84E 82 : 353311.01N/1394727.27E 83 : 353306.60N/1394730.41E 84 : 353304.57N/1394731.84E</p> <p>101 : 353235.61N/1394632.63E 102 : 353234.38N/1394630.02E 103 : 353233.14N/1394627.41E 104 : 353231.90N/1394624.80E 105F : 353230.68N/1394622.23E 105P : 353230.91N/1394620.33E 106 : 353233.11N/1394618.77E 106R : 353233.52N/1394618.36E 106L : 353233.25N/1394620.00E 107 : 353236.04N/1394617.83E 107R : 353236.45N/1394617.42E 107L : 353236.11N/1394619.13E 108 : 353238.48N/1394616.10E 108R : 353238.89N/1394615.69E 108L : 353238.58N/1394617.37E 109 : 353240.52N/1394614.66E 110 : 353242.55N/1394613.21E 111 : 353244.59N/1394611.77E 112 : 353246.90N/1394610.12E 113 : 353248.94N/1394608.68E 114 : 353250.97N/1394607.23E</p> <p>121 : 353240.65N/1394626.06E 122 : 353242.75N/1394624.57E 123 : 353247.53N/1394621.33E 124 : 353249.20N/1394620.14E</p> <p>131 : 353241.47N/1394627.80E 132 : 353243.58N/1394626.30E 133 : 353248.25N/1394622.84E 134 : 353249.91N/1394621.66E</p> <p>140 : 353254.40N/1394614.86E 141 : 353255.60N/1394617.04E 142 : 353300.16N/1394613.74E 143 : 353258.90N/1394611.08E 144 : 353257.70N/1394608.54E 145 : 353256.46N/1394605.92E 146 : 353255.26N/1394603.39E 147 : 353253.79N/1394600.30E 148 : 353252.61N/1394557.81E 149 : 353251.43N/1394555.32E</p> <p>151 : 353306.65N/1394610.75E 152 : 353305.54N/1394608.40E 153 : 353304.42N/1394606.05E 154 : 353303.31N/1394603.69E 155 : 353302.19N/1394601.34E</p> <p>201 : 353204.82N/1394732.11E 202 : 353206.22N/1394731.32E 203 : 353208.26N/1394730.08E 204 : 353210.22N/1394728.69E 205 : 353212.18N/1394727.29E 206 : 353214.15N/1394725.90E 207 : 353216.11N/1394724.51E 208 : 353218.08N/1394723.11E 209 : 353220.04N/1394721.72E 210 : 353222.10N/1394720.51E 211 : 353223.98N/1394718.93E 212 : 353226.39N/1394717.22E 213 : 353228.44N/1394716.01E 214 : 353230.32N/1394714.43E</p>
---	-----------------	---



5	INS checkpoints	<p><i>Spot NR</i></p> <p>301 : 353346.49N/1394639.93E 302 : 353347.63N/1394642.33E 303 : 353348.77N/1394644.73E 304 : 353349.54N/1394647.40E 305 : 353350.96N/1394649.27E 311 : 353345.88N/1394639.02E 312 : 353346.52N/1394641.55E 313 : 353347.66N/1394643.96E 314 : 353349.22N/1394646.06E 315 : 353349.85N/1394648.59E</p> <p>331 : 353359.72N/1394651.90E 332 : 353355.35N/1394656.39E 333 : 353353.78N/1394658.18E 341 : 353400.48N/1394651.39E 342 : 353359.07N/1394653.13E 343 : 353354.96N/1394657.15E 344 : 353353.92N/1394659.52E</p> <p>351 : 353354.90N/1394614.70E 352 : 353356.83N/1394616.35E 353 : 353358.76N/1394618.00E 354 : 353400.68N/1394619.66E 355 : 353403.34N/1394622.14E</p> <p>361 : 353355.47N/1394614.66E 362 : 353357.59N/1394616.49E 363 : 353359.52N/1394618.15E 364 : 353359.81N/1394616.36E 365 : 353402.73N/1394620.54E 366 : 353403.13N/1394624.24E</p> <p>401R : 353336.59N/1394658.56E 401 : 353335.21N/1394659.00E 402 : 353333.22N/1394700.44E</p> <p>406 : 353331.04N/1394702.17E 407 : 353329.08N/1394703.57E 408 : 353327.11N/1394704.96E 501 : 353345.29N/1394702.69E 502 : 353343.54N/1394704.16E 503 : 353341.52N/1394705.44E 504 : 353339.55N/1394706.83E 505 : 353334.60N/1394710.28E 506 : 353332.80N/1394711.63E 507 : 353330.89N/1394713.13E 508 : 353328.92N/1394714.53E 509 : 353326.96N/1394715.92E</p> <p>601 : 353238.52N/1394736.98E 602 : 353236.85N/1394738.16E 603 : 353235.18N/1394739.35E 604 : 353233.10N/1394740.97E 605 : 353231.06N/1394742.41E</p> <p>951 : 353333.71N/1394541.04E 952 : 353335.65N/1394539.40E 953 : 353337.58N/1394537.76E 954 : 353339.52N/1394536.13E 955 : 353339.98N/1394532.87E 956 : 353341.19N/1394531.83E 957 : 353342.53N/1394530.74E</p> <p>961 : 353343.77N/1394524.31E 962 : 353344.36N/1394525.56E 963 : 353344.95N/1394526.80E 964 : 353345.54N/1394528.05E 965 : 353346.13N/1394529.29E 966 : 353346.72N/1394530.54E 967 : 353347.31N/1394531.79E 968 : 353347.90N/1394533.03E 969 : 353348.59N/1394534.48E</p> <p>V1 : 353322.75N/1394707.47E V2 : 353324.85N/1394705.98E VN : 353341.08N/1394654.86E VS : 353338.04N/1394656.82E</p>
6	Remarks	<i>Nil</i>

RJTT AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand ID signs, TWY guide lines and Visual docking/ parking guidance system of aircraft stands	ACFT stand ID sign : NR1 THRU NR4, NR5, NR6 THRU NR23, NR53 THRU NR66, NR67, NR68 THRU NR73, NR105P, NR106, NR107, NR108, NR109 THRU NR114, NR140 THRU NR149, NR406 THRU NR408 ACFT stand taxi lane : E8(BTN E and R), E9(BTN E and R), R(from E8 to E9), N6(from spot NR964 to spot NR969) Visual docking guidance system : See below figure
2	RWY and TWY markings and LGT	<p>RWY: RWY 16L/34R, 16R/34L, 04/22, 05/23 (Marking) RWY designation, RWY CL, RWY THR, Aiming point, TDZ, RWY side stripe, RWY middle point, Displaced THR(RWY 16L/34R, 16R) (LGT) RCLL, REDL, RTHL, RENL, RTZL(RWY16L/34R, 16R/34L, 22, 23), WBAR(RWY16L/34R, 16R/34L, 22, 23)</p> <p>TWY: C10, D3 and D5 (LGT) Rapid exit taxiway indicator lights</p> <p>TWY: ALL TWY (Marking) TWY CL, RWY HLDG PSN, TWY side stripe (LGT) TWY edge LGT(except F), TWY CL LGT(except B12, D(between D7 and E), F, N1, N2, N3, N4, N5, N6, N, Y(between SPOT 312 and J2)), Taxiing guidance sign(except B12) TWY CL LGT on C4, C6, C7, C10, C11, B4, B6, T4, T6, A2, A5, A10, A12, L5 and L12 The intensity of the TWY CL LGT is more increased than that of other TWY CL LGT.</p> <p>TWY: C1 THRU C14 (LGT) Stop bar LGT, RWY guard LGT(90m off the runway center line)</p> <p>TWY: A1 THRU A16, C1, C2, C3, C5, C12, C13, C14, D1 THRU D5, L3 THRU L16 (LGT) RWY guard LGT(75m off the runway center line)</p> <p>TWY: A, E, M, R (Marking) Intermediate Holding Position (LGT) Intermediate Holding Position (see attached chart)</p> <p>TWY: A1, A3, A4, A6, A9, A11, A13, A14, A15, A16, B1, B2, B5, B7, B9, B10, B11, L3, L4, L6, L9, L11, L14, L15, L16, T1, T2, T5, T7, T9, T11 (LGT)Variable Message Signs (RWY status LGT) (see attached chart)</p> <p>SFC painted direction sign (See Figure "Type of Surface Painted Markings")</p>
3	Stop bars	<p>Stop Bar Lights Operations</p> <ol style="list-style-type: none"> 1) Stop Bar Lights are installed at each RWY holding position associated with RWY16L/34R 2) Stop Bar Lights will be operated when the visibility or the lowest RVR of the RWY16L/34R is at or less than 600m. 3) Stop Bar Lights on TWY C1, C2, C13 and C14 are controlled individually by ATC 4) Stop Bar Lights on TWY C3 THRU C12 are not controlled individually by ATC. 5) During the period Stop Bar Lights operated, TWY C3 THRU C12 are not available for departure aircraft.
4	Remarks	<p>(Marking) Overrun area, ACFT PRKG PSN, Apron TWY CL (LGT) Apron flood LGT</p> <p>Runway Guard Lights Operations: Either Runway Guard Lights of 75m off runway center line or Runway Guard Lights of 90m off runway center line turn on in the daytime regardless of visibility condition of TWY C1, C2, C3, C5, C12, C13, C14</p>

MARKING AIDS



MARKING AIDS


Intermediate Holding Position Marking and Intermediate Holding Position Lights

1. The Intermediate Holding Position Marking indicates the position where aircraft is to hold to prevent collision with other aircraft on the taxiway. The Intermediate Holding Position Lights are collocated with the Intermediate Holding Position Marking and synchronized with the taxiway center line lights. The Intermediate Holding Position Lights consist of 5 yellow lights and the Intermediate Holding Position Marking is a single broken line as illustrated in the figure below;



2. Operational procedure
See AD 2.20.6.4.

Variable Message Signs (VMS)



NOTE : The TWY names and RWY HLDG PSN markings in this ATTACHMENT are depicted only for the TWYs where VMS are installed.

Type of Surface Painted Markings

1. Type of Surface Painted Markings

- Surface Painted Direction Sign

This type of marking at a taxiway intersection indicates the designation and direction of the taxiway leading out of an intersection. Black inscriptions with an arrow with a yellow background.

- Surface Painted Location Sign

This type of marking indicates the designation of the taxiway on which the aircraft is located. Yellow inscriptions with a black background and yellow frame.

2. On each of the taxiways A, A14, A15, A16, B, B6, B7, B9, B10, F, H, J, K, L, L13, L15, L16, M, N, N2, N3, N4, N5, T, T7, T9, T11, U2, U4, W, surface painted markings are provided (refer attached drawing).






Fig.1





VISUAL DOCKING GUIDANCE SYSTEM

I. SAFEDOCK


1. General

- (1) Aircraft parking stands NR1 THRU NR4, NR5, NR6 THRU NR23, NR53 THRU NR66, NR67, NR68 THRU NR73, NR105P, NR106, NR107, NR108, NR109 THRU NR114, NR140 THRU NR149, NR406 THRU NR408 are equipped with a SAFEDOCK visual docking guidance system.
The pilots of an arriving aircraft assigned to park at one of these parking stands can use this system to be guided and stop the aircraft at the correct parking position.
- (2) This system is operational only in the automatic mode and in an event of a system failure, the aircraft shall be manually guided by a marshaller to the stopping position.
- (3) The SAFEDOCK visual docking system consists of a display screen for pilots and a laser scanner.
The system detects and analyses the aircraft type of an approaching aircraft, tracks it through the laser scanner, and displays these results on the display screen.
- (4) The display screen indicates the following information:
 - a) type of the approaching aircraft
 - b) deviation from the lead-in center line, and
 - c) distance to the stopping position.

The above information is provided equally to the pilots on both left seat and right seat.

2. Aircraft Type Indication


- (1) A message about the aircraft type from Spot Control System shall be confirmed and put into the system by ground operator.
The system then carries out internal calibration and starts laser scanning simultaneously.
The system shows the aircraft type on the display screen and then will begin to indicate yellow lead-in arrows scrolling upwards prompting the aircraft to proceed.(Fig.1)



- (2) When the laser scanner detects the approaching aircraft, the display screen will indicate the aircraft type, a "T" bar, and a lead-in upward arrow in yellow.(Fig.2)
- (3) At least until the approaching aircraft arrives at a point 12 meters before the stopping position, the system will identify the aircraft type and will compare with the previously input aircraft type, If these data match, the system will continue its operation. If they do not match, the display screen will repeatedly indicate "STOP", "ID" and "FAIL" in sequence and will indicate 2 illuminated red squares simultaneously.

NOTE:At this moment, the pilots must stop the aircraft immediately.

When the operator re-input the correct aircraft type into the system and the system finds it correct, it resumes normal operations indicating the correct aircraft type on its display screen



3.Taxiing and Lateral Center line Guidance

- (1) While taxiing the aircraft using the system, the pilots should maneuver the aircraft at a low speed to the stopping position. In an event when "SLOW" is indicated on the display screen, the pilots should further decelerate the taxiing speed to avoid overshooting.(Fig.6)



Fig.6

- (2) Deviation of an upward yellow arrow from the center line of "T" indicates the deviation of the approaching aircraft relative to the center line of the parking stand either to right or left. Further, an additional flashing red arrow on the either side indicates the required direction for the aircraft to turn.(Fig.7, Fig.8)



Fig.7

Fig.8

4.Stop Guidance

- (1) When the approaching aircraft is within 30 meters from the stopping position, display of digital countdown will start. As the aircraft approaches the stopping position, digital countdown is for every 1.0 meter(from 30.0 to 2.0 meters to the stop position) or for every 0.2 meters (from 2.0 to 0.0 meters to the stop position).

- (2) When the approaching aircraft is within 16 meters from the stopping position, the shaft of the illuminated "T" will start to reduce in its length from the bottom to indicate the approaching rate of the aircraft, indicating the remaining distance to the stopping position successively.(Fig.9, Fig.10)

As the aircraft approaches the stopping position, the shaft of the illuminated "T" retract one row for every 0.5 meters.



Fig.9



Fig.10

- (3) When the aircraft reaches the stopping position, a message "STOP" will be displayed on the screen together with two red squares, one each at the either side of the screen at the positions previously used for indication of a direction to turn. (Fig.11)



Fig.11

- (4) When the aircraft is stopped at the correct stopping position, a message "OK" will be displayed on the screen in several seconds.(Fig.12)



Fig.12



Fig.13

- (5) When the operator applies chocks, and switches on "CHOCK ON" switch, the display screen will display "CHOCK ON".(Fig.13)

- (6) If the aircraft stops at a position beyond the correct stopping position, a message "TOO FAR" will be displayed on the screen.(Fig 14).




Fig.14




Fig.15

5. Cautions and Safety

- (1) When the system displays an incorrect aircraft type, or when such a message as "STOP", "ID", "FAIL", or "WAIT" appears on the display screen, the pilots should stop the aircraft immediately. (Fig.3, Fig.4, Fig.5, Fig.11, Fig.15)
- (2) Bad weather condition, during heavy fog, rain or snow, the visibility for the docking system can be reduced. When the system is activated and in capture mode, the display screen will deactivate the floating arrows and indicate "Aircraft type" and "SLOW".

This message will be superseded by the "T" bar, as soon as the system detects the approaching aircraft.
The pilot must not proceed beyond the bridge, unless the "SLOW" text has been superseded by the "T" bar.



Fig.16

- (3) System breakdown, in case of a severe system failure, the display screen will go black, except for 2 red squares indicator. A manual backup procedure must be used for docking guidance.(Fig.17)



Fig.17

RJTT AD 2.10 AERODROME OBSTACLES

SEE RJTT AD2.24 AERODORME OBSTRUCTION CHART-ICAO

In approach / TKOF Areas

RWY/Area affected	Obstacle type	Coordinates	Elevation	Markings/LGT	Remarks
-	Lightning Rod	353218.52N 1394402.50E	217ft	-/-	above the conical surface
-	Lightning Rod	353218.50N 1394404.09E	220ft	-/LGTD	above the conical surface
-	Lightning Rod	353218.50N 1394404.56E	217ft	-/-	above the conical surface
-	Lightning Rod	353219.07N 1394404.53E	217ft	-/-	above the conical surface
-	Lightning Rod	353219.69N 1394404.53E	217ft	-/LGTD	above the conical surface
-	Lightning Rod	353220.08N 1394404.55E	217ft	-/-	above the conical surface
-	Chimney	353050.7N 1394547.4E	291ft	-/LGTD	above the conical surface
-	Building	353958.9N 1394459.0E	875ft	-/LGTD	above the conical surface
-	Building	353951.2N 1394415.7E	893ft	-/LGTD	above the conical surface


In circling area and at AD


Obstacle type	Coordinates	Elevation	Markings/ LGT	Remarks
Chimney	353107.42N 1394619.09E	177ft	-/LGTD	above the horizontal surface

RJTT AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Associated MET Office	TOKYO
2	Hours of service MET Office outside hours	H24
3	Office responsible for TAF preparation Periods of validity	TOKYO 30 Hours
4	Trend forecast Interval of issuance	TREND 30min
5	Briefing/ consultation provided	P, Ja, En
6	Flight documentation Language(s) used	C En
7	Charts and other information available for briefing or consultation	S ₆ , U ₈₅ , U ₇ , U ₅ , U ₃ , U ₂₅ , U ₂ /T _r , P _S , P ₅ , P ₃ , P ₂₅ , P _{SWE} , P _{SWF} , P _{SWG} , P _{SWI} , P _{SWM} , P _{SW} (domestic), E, C, W _E , W _F , W _G , W _I , W, N
8	Supplementary equipment available for providing information	Doppler Radar and Lidars for Airport Weather(see attached chart)
9	ATS units provided with information	TWR, APP, ATIS
10	Additional information(limitation of service, etc.)	Nil

Airspace for the advisory service concerning low level wind shear (RWY16L/34R)



Airspace for the advisory service concerning low level wind shear (RWY16R/34L)

Airspace for the advisory service concerning low level wind shear (RWY04/22)



UPPER LIMIT: 1600ft above FIELD ELEV LEVEL
LOWER LIMIT: FIELD ELEV LEVEL

Airspace for the advisory service concerning low level wind shear (RWY05/23)



UPPER LIMIT: 1600ft above FIELD ELEV LEVEL
LOWER LIMIT: FIELD ELEV LEVEL

RJTT AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY(M)	Strength(PCN) and surface of RWY	THR coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
16L	149.88°	3360x60	PCN 95/F/B/X/T Asphalt Concrete	353357.23N 1394711.59E 117.7FT (Displaced THR) 353346.27N 1394719.34E 117.8FT	THR ELEV : 21.8FT (Displaced THR) THR ELEV : 19.2FT TDZ ELEV : 19.2FT
34R	329.88°	3360x60	PCN 95/F/B/X/T Asphalt Concrete	353222.90N 1394818.49E 117.1FT (Displaced THR) 353233.02N 1394811.34E 117.2FT	THR ELEV : 27.8FT (Displaced THR) THR ELEV : 19.7FT TDZ ELEV : 21.0FT
16R	149.88°	3000x60	PCN85F/B/X/T Asphalt Concrete	353335.95N 1394608.64E 117.9FT (Displaced THR) 353322.47N 1394618.19E 117.9FT	THR ELEV : 20.5FT (Displaced THR) THR ELEV : 16.4FT TDZ ELEV : 16.4FT
34L	329.88°	3000x60	PCN 85/F/B/X/T Asphalt Concrete	353211.76N 1394708.41E 117.3FT	THR ELEV : 18.2FT TDZ ELEV : 18.4FT
04	035.01°	2500x60	PCN 85/F/B/X/T Asphalt Concrete	353256.47N 1394540.60E 117.8FT	THR ELEV : 19.0FT TDZ ELEV : 19.3FT
22	215.01°	2500x60	PCN 85/F/B/X/T Asphalt Concrete	353402.88N 1394637.61E 117.9FT	THR ELEV : 35.0FT TDZ ELEV : 35.0FT
05	042.56°	2500x60	PCN 102/F/B/X/T* Asphalt Concrete	353126.41N 1394812.47E 116.9FT	THR ELEV : 45.5FT TDZ ELEV : 45.5FT
23	222.56°	2500x60	PCN 102/F/B/X/T* Asphalt Concrete	353226.15N 1394919.61E 116.9FT	THR ELEV : 54.7FT TDZ ELEV : 54.7FT

Slope of RWY	Strip Dimensions(M)	RESA(Overrun) Dimensions(M)	Arresting System	Remarks
7	10	11	12	14
See below figure	3480x300	150x300		RWY grooving: RWY 16L/34R 3360mx40m RWY 16R/34L 3000mx40m RWY 04/22 2500mx40m RWY 05/23 2500mx40m *REF AD2.23.7
	3480x300	240x300		
	3120x300	40x(MNM:255 MAX:300)**	EMAS(84.5mx62.8m) *See RJTT AD2.23.8	CAUTION : THR of RWY 16L is displaced by 390m inward. In case of landing, the usable length of RWY 16L is 2,970m. In case of take-off, the usable length of RWY 16L is 3,360m. THR of RWY 34R is displaced by 360m inward. In case of landing, the usable length of RWY 34R is 3,000m. In case of take-off, the usable length of RWY 34R is 3,360m.
	3120x300	240x300		
	2620x300	186x(MNM:210 MAX:300)**		THR of RWY 16R is displaced by 480m inward. In case of landing, the usable length of RWY 16R is 2,520m. In case of take-off, the usable length of RWY 16R is 3,000m. Usable length of RWY 34L is 3,000m for both landing and take-off.
	2620x300	240x300		
	2620x300	240x300		
	2620x300	240x300 **For detail, ask airport administrator		

**RJTT AD 2.13 DECLARED DISTANCES**

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)	Remarks
1	2	3	4	5	6
16L 34R	3360 3360	3360 3360	3360 3360	2970 3000	Nil Nil
16R 34L	3000 3000	3000 3000	3000 3000	2520 3000	Nil Nil
04 22	2500 2500	2500 2500	2500 2500	2500 2500	Nil Nil
05 23	2500 2500	2500 2500	2500 2500	- 2500	Not usable for LDG Nil

RJTT AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	APCH type LEN INTST	LGT RTHL Color WBAR	PAPI (VASIS) Angle DIST FM THR MEHT	RTZL LEN	RCLL Spacing Color INTST	REDL Spacing Color INTST	RENL Color WBAR	STWL LEN Color
1	2	3	4	5	6	7	8	9
16L	PALS	Green Green	PAPI 3.0°/LEFT 900M 412M LIH 65FT	900M	3360M 15M Coded color (White/Red) LIH	3360M 30M Coded color (White/Yellow/Red) LIH	Red	Nil (*1)
			PAPI(*3) 3.25°/LEFT 378M 65FT					
34R	PALS (CAT III)	Green Green	PAPI 3.0°/RIGHT 900M 416M LIH 66FT	900M	3360M 15M Coded color (White/Red) LIH	3360M 30M Coded color (White/Yellow/Red) LIH	Red	Nil (*1)
16R	PALS	Green Green	PAPI 3.0°/LEFT 900M 434M LIH 65FT	900M	3000M 30M Coded color (White/Red) LIH	3000M 60M Coded color (White/Yellow/Red) LIH	Red	Nil (*1)
			PAPI(*3) 3.25°/LEFT 397M 65FT					
34L	PALS (CAT I)	Green Green	PAPI 3.0°/LEFT 900M 449M LIH 66FT	900M	3000M 30M Coded color (White/Red) LIH	3000M 60M Coded color (White/Yellow) LIH	Red	Nil (*1)
04	-	Green -	PAPI(*2) 3.0°/LEFT 369M 61FT	-	2500M 30M Coded color (White/Red) LIH	2500M 60M Coded color (White/Yellow) LIH	Red	Nil (*1)
22	PALS (CAT I)	Green Green	PAPI 3.0°/LEFT 900M 438M LIH 63FT	900M	2500M 30M Coded color (White/Red) LIH	2500M 60M Coded color (White/Yellow) LIH	Red	Nil (*1)
05	-	Green -	-	-	2500M 30M Coded color (White/Red) LIH	2500M 30M Coded color (White/Yellow) LIH	Red	Nil (*1)
23	PALS (CAT I)	Green Green	PAPI 3.0°/LEFT 870M 452M LIH 66FT	900M	2500M 30M Coded color (White/Red) LIH	2500M 30M Coded color (White/Yellow) LIH	Red	Nil (*1)
Remarks								
10								
Overrun area edge LGT(LEN:60M(RWY16L,34R,34L,04,22, 05, 23) 77M(RWY16R), Color:Red) (*1) CGL for RWY 16L APCH guidance LGT for RWY16L,16R RWY THR ID LGT for RWY04, RWY22 and RWY16L THR(Color:White) Rapid exit taxiway indicator lights prior to exit to TWY C10, D3 and D5(Color:Yellow) Usable area of PAPI for RWY04 is within 2.4NM FM RWY04 THR(*2) 3.25° PAPI(The angle is 3.25°) turn on and 3.0° PAPI(The angle is 3.0°) turn off only when RNP RWY16R and RNP RWY16L are in operation. See AIP RJTT AD2.20.1.8(*3)								

RJTT AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	ABN/IBN location, characteristics and hours of operation	ABN: 353238N/1394557E, White/Green EV4.3sec, HO
2	LDI location and LGT Anemometer location and LGT	LDI:Nil Anemometer: RWY16L: 358m from RWY16L THR, LGTD RWY34R: 710m from RWY34R THR, LGTD RWY16R: 226m from RWY16R THR, LGTD RWY34L: 270m from RWY34L THR, LGTD RWY04: 273m from RWY04 THR, LGTD RWY22: 400m from RWY22 THR, LGTD RWY05: 381m from RWY05 THR, LGTD RWY23: 319m from RWY23 THR, LGTD
3	TWY edge and center line lighting	TWY edge LGT: Blue TWY CL LGT: ALTN Green/Yellow FM RWY leaving report point, other Green
4	Secondary power supply / switch-over time	Within 1 sec: PALS(RWY34R), PAPI(RWY16L/34R), RCLL(RWY16L/34R), RTZL(RWY34R), RENL(RWY16L/34R), RTHL(RWY16L/34R), WBAR(RWY16L/34R), Overrun area edge LGT(RWY16L/34R), Stop Bar LGT Within 15 sec : PALS(RWY16L/16R/34L/22/23), CGL(RWY16L), PAPI(RWY16R/34L/04/22/23), REDL(RWY16L/34R/16R/34L/04/22/05/23), RCLL(RWY16R/34L/04/22/05/23), RTZL(RWY16L/16R/34L/22/23), RENL(RWY16R/34L/04/22/05/23), RTHL(RWY16R/34L/04/22/05/23), WBAR(RWY16R/34L/22/23), RWY THR ID LGT(RWY16L/04/22), Overrun area edge LGT(RWY16R/34L/04/22/05/23), RWY guard LGT, ABN, TWY edge LGT, TWY CL LGT, Intermediate Holding Position Light, Rapid exit taxiway indicator lights, Taxiing guidance sign, WDI LGT, Variable Message Signs
5	Remarks	WDI LGT

RJTT AD 2.16 HELICOPTER LANDING AREA


Nil

RJTT AD 2.17 ATS AIRSPACE


Designation and lateral limits		Vertical limits (ft)	Airspace classification	ATS unit call sign Language	Remarks
	1	2	3	4	6
TOKYO CTR	Area defined as follows. Area within a radius of 5nm of TOKYO INTERNATIONAL ARP (35°33'N/139°47'E).	3 000 or below (900)	D	TOKYO TOWER En	
TOKYO PCA	SEE RJTT ATTACHED CHART		C		
TOKYO ACA	SEE RJTT ATTACHED CHART		E		
TOKYO TCA	SEE RJTT ATTACHED CHART		E		

東京特別管制区
Tokyo Positive Control Area

NAME	LATERAL LIMITS	UPPER LIMIT (AMSL) ----- LOWER LIMIT (AMSL) M(ft)	UNIT PROVIDING SERVICE	REMARKS
1	2	3	4	5
Tokyo	下図に示される区域 The area shown below (1) 東京第一特別管制区 Tokyo NR1 Positive control Area (2) 東京第二特別管制区 Tokyo NR2 Positive control Area		Primary Tokyo TCA 124.75MHz (2300-1200) 119.7MHz Secondary Tokyo Tower 118.1MHz 124.35MHz	当該空域を飛行しようとする航空機は東京 TCA 又はタワーに連絡し、コールサイン、現在位置、高度及び意図を通報し指示を受けなければならない。なお、東京第一特別管制区にあっては 24 時間、東京第二特別管制区にあっては 0600UTC から 1000UTC の間とする。 Pilot requiring transit of Tokyo NR1/NR2 Positive Control Area must call Tokyo TCA or Tower prior to the point of entry to provide aircraft identification, position, altitude and intention. This rule is enforced 24 hours a day for Tokyo NR1 Positive Control Area and between 0600UTC and 1000UTC for Tokyo NR2 Positive Control Area.

東京特別管制区
Tokyo Positive Control Area


東京進入管制区
Tokyo Approach Control Area



Point list

- | | | | |
|-----------------------|-----------------------|-----------------------|-----------------------|
| (1) 343224N/1400724E | (18) 360419N/1414409E | (35) 361053N/1402147E | (52) 352343N/1392749E |
| (2) 342337N/1390033E | (19) 355600N/1411534E | (36) 361204N/1401853E | (53) 351301N/1392926E |
| (3) 341153N/1391255E | (20) 355600N/140841E | (37) 360407N/1403112E | (54) 362938N/1405126E |
| (4) 341141N/1395954E | (21) 355600N/1404746E | (38) 360250N/1403803E | (55) 363540N/1402812E |
| (5) 341614N/1401235E | (22) 355600N/1403828E | (39) 360503N/1410017E | (56) 355626N/1390939E |
| (6) 363429N/1401317E | (23) 355600N/1403535E | (40) 360500N/1403600E | (57) 354316N/1390433E |
| (7) 362515N/1395633E | (24) 355600N/1403154E | (41) 360858N/1402626E | (58) 352134N/1390812E |
| (8) 355918N/1394424E | (25) 355626N/1403002E | (42) 363752N/1401937E | (59) 360223N/1391842E |
| (9) 355339N/1394146E | (26) 355930N/1401651E | (43) 361152N/1402623E | |
| (10) 353325N/1393840E | (27) 360023N/1401723E | (44) 361619N/1402619E | |
| (11) 351136N/1394310E | (28) 360623N/1400824E | (45) 361628N/1402245E | |
| (12) 350019N/1393818E | (29) 361321N/1400930E | (46) 363547N/1402606E | |
| (13) 345811N/1392443E | (30) 355732N/1402939E | (47) 363611N/1402610E | |
| (14) 345614N/1391225E | (31) 360705N/1401514E | (48) 361913N/1404125E | |
| (15) 345412N/1385949E | (32) 360705N/1401134E | (49) 361630N/1403849E | |
| (16) 344816N/1414417E | (33) 360453N/1402703E | (50) 355218N/1392608E | |
| (17) 360500N/1414604E | (34) 360602N/1402056E | (51) 354715N/1392411E | |

東京ターミナルコントロールエリア
Tokyo Terminal Control Area



RJTT AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	Call sign	Frequency	Hours of operation	Remarks
1	2	3	4	5
APP	Tokyo Approach	119.1MHz(1) 119.4MHz 119.65MHz 119.7MHz 125.4MHz 232.2MHz 261.2MHz 121.5MHz(E) 243.0MHz(E)	121.275MHz 124.4MHz 125.2MHz 125.8MHz 127.7MHz 225.65MHz	H24 (1)Primary
ASR	Tokyo Radar	124.0MHz 126.5MHz 236.8MHz 261.2MHz 295.9MHz 121.5MHz(E) 243.0MHz(E) 120.2MHz	119.025MHz 120.9MHz 123.6MHz 125.1MHz 283.4MHz	H24
DEP	Tokyo Departure	126.0MHz(1) 120.8MHz 127.5MHz 127.6MHz 121.5MHz(E) 243.0MHz(E) 124.2MHz 119.6MHz 120.6MHz 125.525MHz		H24
TCA	Tokyo TCA	124.75MHz(1) 119.7MHz 256.1MHz 119.45MHz 246.1MHz		2300 - 1200 2300 - 1030
TWR	Tokyo Tower	118.1MHz(1) 118.575MHz 118.725MHz 124.35MHz 118.8MHz 126.2MHz 236.8MHz 121.5MHz(E) 243.0MHz(E)		H24
GND	Tokyo Ground	118.225MHz 121.625MHz 121.7MHz 121.975MHz 122.075MHz		H24 See RJTT AD2.20.1.2 (14) "GROUND CONTROL Frequency"
DLVRY	Tokyo Delivery	121.825MHz(1) 121.875MHz		H24
ATIS	Tokyo INTL Airport	128.8MHz		H24


RJTT AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid	ID	Frequency	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
VOR	HME	112.2MHz	H24	353344.34N/ 1394540.14E		VOR Unusable: 1) 230° -240° beyond 15nm BLW 8000ft. 2) 240° -260° beyond 10nm BLW 8000ft. VOR/DME Unusable: 1) 210° -230° beyond 20nm BLW 3000ft. 2) 330° -340° beyond 30nm BLW 3000ft. 3) 340° -020° beyond 20nm BLW 3000ft.
DME	HME	1020MHz (CH-59X)	H24	353344.34N/ 1394540.14E	63ft	
ILS-LOC 16L	IOC	111.95MHz	H24	353217.43N/ 1394822.37E		LOC: 195m(640ft) away FM RWY34R THR, BRG(MAG) 157.41°.
ILS-GP 16L	-	330.95MHz	H24	353335.57N/ 1394721.45E		GP: 312m(1024ft) inside FM RWY16L Displaced THR, 120m(394ft) SW of RCL. HGT of ILS Ref datum 16.3m(53ft). GP angle 3.0°.
ILS-DME 16L	IOC	1143MHz (CH-56Y)	H24	353335.08N/ 1394721.61E	34ft	DME: 320m(1050ft) inside FM RWY16L Displaced THR, 131.5m(431ft) SW of RCL.
ILS-LOC 34R	ITC	108.9MHz	H24	353403.81N/ 1394706.89E		LOC: (ITC) 235m(771ft) away FM RWY16L THR, BRG (MAG) 337°.
ILS-GP 34R	-	329.3MHz	H24	353243.92N/ 1394809.36E		GP: 316m(1037ft) inside FM RWY34R Displaced THR, 126m(413ft) NE of RCL. HGT of ILS Ref datum 16.5m(54ft). GP angle 3.0°.
ILS-DME 34R	ITC	987MHz (CH-26X)	H24	353244.02N/ 1394809.72E	35ft	DME: 314m(1030ft) inside FM RWY34R Displaced THR, 135m(443ft) NE of RCL.
IM 34R	-	75MHz	H24	353220.45N/ 1394820.26E		IM: 446m(1463ft) away FM RWY34R Displaced THR.
ILS-LOC 16R	ITA	111.55MHz	H24	353206.29N/ 1394712.30E		LOC: 195m(640ft) away FM RWY34L THR, BRG(MAG) 157.41°.
ILS-GP 16R	-	332.75MHz	H24	353315.14N/ 1394628.93E		GP: 326m(1070ft) inside FM RWY16R Displaced THR, 120m(394ft) NE of RCL. HGT of ILS Ref datum 16.3m(53ft). GP angle 3.0°.
ILS-DME 16R	ITA	1139MHz (CH-52Y)	H24	353315.97N/ 1394629.22E	31ft	DME: 334m(1096ft) inside FM RWY16L Displaced THR, 125m(410ft) NE of RCL.


Type of aid	ID	Frequency	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
ILS-LOC 34L	IHA	111.7MHz	H24	353343.81N/ 1394603.06E		LOC: (IHA) 280m(919ft) away FM RWY 16R THR, BRG(MAG)337°.
ILS-GP 34L	-	333.5MHz	H24	353223.19N/ 1394705.78E		GP: 338m(1109ft) inside FM RWY34L THR ,120m(394ft) NE of RCL. HGT of ILS Ref datum 16.5m (54ft). GP angle 3.0°.
ILS-DME 34L	IHA	1015MHz (CH-54X)	H24	353223.33N/ 1394706.14E	43ft	DME: 338m(1109ft) inside FM RWY34L THR, 130m (427ft) NE of RCL. DME Unusable: beyond 15° E side of LOC course.
ILS-LOC 22	IAD	108.1MHz	H24	353248.36N/ 1394533.62E		LOC: (IAD)305m (1001ft) away FM RWY04 THR, BRG(MAG) 222°.
ILS-GP 22	-	334.7MHz	H24	353351.52N/ 1394633.91E		GP: 339m(1112ft) inside FM RWY22 THR, 125m (410ft) S of RCL. HGT of ILS Ref datum 16.5m(54ft). GP angle 3.0°.
ILS-DME 22	IAD	979MHz (CH-18X)	H24	353351.23N/ 1394633.96E	44ft	DME: 346.4m(1137ft) inside FM RWY22 THR, 130.9m(429ft) S of RCL.
LDA-LOC 22	IKL	110.1MHz	H24	353613.77N/ 1394908.33E		LOC: (IKL) 5481m(17983ft) outside FM RWY22, 788m(2585ft) S of RCL, BRG(MAG) 277°.
LDA-DME 22	IKL	999MHz (CH-38X)	H24	353612.96N/ 1394908.33E	122ft	DME: 5460m(17914ft) outside FM RWY22, 803m(2635ft) S of RCL.
ILS-LOC 23	ITD	110.5MHz	H24	353151.24N/ 1394835.14E		LOC: (ITD) 950m(3117ft) inside FM RWY05 THR, 97m(318ft) N of RCL. LOC off-set angle 2.0°, BRG(MAG)232°.
ILS-GP 23	-	329.6MHz	H24	353220.86N/ 1394906.93E		GP: 336m(1102ft) inside FM RWY23 THR ,125m(410ft) N of RCL. HGT of ILS Ref datum 16.5m (54ft). GP angle 3.0°.
ILS-DME 23	ITD	1003MHz (CH-42X)	H24	353221.08N/ 1394906.64E	67ft	DME: 336m(1102ft) inside FM RWY23 THR, 135m (443ft) NE of RCL.
LDA-LOC 23	ITL	108.5MHz	H24	353410.37N/ 1394656.13E		LOC: (ITL) 79m(259ft) inside FM RWY23, 4834m(15860ft) N of RCL, BRG(MAG) 277°.
LDA-DME 23	ITL	983MHz (CH-22X)	H24	353411.11N/ 1394656.12E	34ft	DME: 62m(203ft) inside FM RWY23, 4849m(15910ft) N of RCL.
MSAS		1575.42MHz	H24			Transmitting antennas are satellite based.

ILS for RWY 34L

REMARKS : 1. LOC beam BRG (MAG) 337°
 2. HGT of ILS REF datum 16.5m(54ft)
 3. GP Angle 3.0°
 4. ELEV of ILS-DME 13.0m(43ft)

ILS for RWY 22

REMARKS : 1.LOC beam BRG(MAG) 222°
 2.HGT of ILS REF datum 16.5m(54ft)
 3.GP Angle 3.0°
 4.ELEV of ILS-DME 13.5m(44ft)

ILS for RWY 34R

REMARKS : 1.LOC BEAM BRG(MAG) 337°
 2.HGT of ILS REF datum 16.5m(54ft)
 3.GP Angle 3.0°
 4.ELEV of ILS-DME 10.6m(35ft)

LDA for RWY 22



ILS for RWY 23



LDA for RWY 23



ILS for RWY 16R

REMARKS : 1. LOC beam BRG (MAG) 157.41°
 2. HGT of ILS REF datum 16.3m(53ft)
 3. GP Angle 3.0°
 4. ELEV of ILS-DME 9.4m(31ft)

ILS for RWY 16L

REMARKS : 1. LOC beam BRG (MAG) 157.41°
 2. HGT of ILS REF datum 16.3m(53ft)
 3. GP Angle 3.0°
 4. ELEV of ILS-DME 10.1m(34ft)

RJTT AD 2.20 LOCAL TRAFFIC REGULATIONS

1. Airport regulations

1.1 Procedural Speed and Speedy Turn Off Procedure

In order to reduce runway occupancy time with the smooth traffic flow based on safety, arriving aircraft should operate as follows.

(1)Procedural Speed (for IFR)

(a)Unless otherwise instructed by ATC, arriving aircraft should cross each points at the speed listed below.

Approach	Point	Procedural Speed
ILS Z RWY34L LOC Z RWY34L	IHA 10.0DME	180 kt (IAS)
	IHA 5.0DME	160 kt (IAS)
ILS X RWY34L	KAIHO	180 kt (IAS)
	ALLIE	160 kt (IAS)
ILS Z RWY34R LOC Z RWY34R	ITC 10.0DME	180 kt (IAS)
	ITC 5.0DME	160 kt (IAS)
ILS RWY22 LOC RWY22	IAD 10.0DME	180 kt (IAS)
	IAD 5.0DME	160 kt (IAS)
LDA Z RWY22 LDA X RWY22 LDA W RWY22	IKL 8.0DME	180 kt (IAS)
	IKL 3.0DME	160 kt (IAS)
ILS Z RWY23 LOC Z RWY23	ITD 10.0DME	180 kt (IAS)
	ITD 5.0DME	160 kt (IAS)
LDA Z RWY23 LDA X RWY23 LDA W RWY23	ITL 12.0DME	180 kt (IAS)
	ITL 7.0DME	160 kt (IAS)
ILS RWY16R	ITA 10.0DME	180 kt (IAS)
	ITA 5.0DME	160 kt (IAS)
RNP RWY16R	10.2NM from THR	170 kt (IAS)
ILS RWY16L	IOC 10.0DME	180 kt (IAS)
	IOC 5.0DME	160 kt (IAS)
RNP RWY16L	9.2NM from THR	170 kt (IAS)

(b)

1)When speed adjustment is made after approach clearance issued, ATC will instruct to comply with Procedural Speed by the phrase as below instead of "RESUME PUBLISHED SPEED (ref. ENR1.6.1.8.7)".

(e.g.) COMPLY WITH PROCEDURAL SPEED.

2)Pilots should advise ATC when unable to comply with Procedural Speed due to an operational or a performance reason.

(e.g.) UNABLE TO COMPLY WITH PROCEDURAL SPEED ([number]KNOTS).

3)Pilots will be informed by ATC when there is no need to comply with Procedural Speed.

(e.g.) PROCEDURAL SPEED ([number]KNOTS) IS NOT REQUIRED.

(e.g.) MAINTAIN PROCEDURAL SPEED OR GREATER.

(2) Speedy Turn Off Procedure

(a)The exit taxiways, as a rule, from which arriving aircraft should plan to vacate the runway are listed below.

(b)Pilot should vacate the runway for which the nearest side of the arriving spot.

RWY	EXIT TAXIWAY	DISTANCE FROM THRESHOLD (m/ft)	REMARKS
34L	A10	1,500/4,920	for Terminal 1 and Terminal 2*
	A12	2,000/6,560	
	L10	1,320/4,330	for Terminal 3 and "N" Area*
	L12	1,800/5,900	
	L13	2,080/6,820	
16R	A5	1,530/5,020	for Terminal 1 and Terminal 2*
	A2	2,040/6,690	
	L5	1,500/4,920	for Terminal 3 and "N" Area*
34R	C9	1,290/4,230	
	C10	1,670/5,470	
	C11	2,120/6,950	
16L	C7	1,390/4,570	
	C6	1,710/5,640	
	C4	2,000/6,560	
22	B8	1,050/3,440	Except for "N" Area*
	B6	1,530/5,010	
	B4	1,800/5,900	
	B3	2,030/6,660	
	T8	1,050/3,440	for "N" Area*
	T6	1,530/5,010	
	T4	1,800/5,900	
	T3	2,030/6,660	
23	D5	1,500/4,920	
	D3	1,800/5,900	

*Except for Instructed by ATC when the Aircraft is on the air or on the ground

(c) Pilots should plan which exit taxiway to be used to vacate the runway in approach/landing briefing. Upon landing, pilots should vacate the runway without delay and pass the runway holding position marking on the exit taxiway. It is better, in terms of runway occupancy time, to aim for an exit which can be made, rather than to aim for an earlier one, just to miss it and then to roll slowly to the next.

Note ; The intensity of the taxiway center line lights listed below will be more increased than that of other taxiways to improve the recognition of these exit taxiways.

RWY	TAXIWAY
16L	C4, C6, C7
34R	C10, C11
22	B4
	B6
	T4
	T6
16R	A2, A5, L5
34L	A10, A12
	L12

1.2 Procedures other than 1.1 above and information

- (1) Aircraft operations other than scheduled or in emergency
On use of this airport, aircraft operator is required to obtain the prior permission of the airport administrator.
- (2) A380-800 is prohibited from operating between 2100UTC and 1400UTC.
- (3) When operating A380-800 between 1400UTC and 2100UTC, the aircraft weight restriction is imposed.
(see RJTT AD2.23.7)
- (4) A380-800 and B747-8 shall equip digital avionics that provide steering commands to maintain an established track during the go-around manoeuvre and they shall be utilized when landing to runway.
- (5) Aircraft without approvals of RNAV1 and RNAV5 is prohibited from operating.
- (6) RNP RWY16R/RWY16L are set for the purpose of noise reduction, and applied between 0600UTC and 1000UTC in southerly wind condition with good weather.
All landing aircraft are required to be ready to conduct RNP RWY16R/RWY16L during that period.
In case of aircraft which is not possible to conduct RNP RWY16R/RWY16L for inevitable reasons, it will be assigned another runway or type of approach with reasonable delay which depends on traffic flow at the time.
So, the pilot should notify at initial contact with Tokyo Approach.
- (7) Preflight call to control tower
IFR departing aircraft should notify TOKYO DELIVERY of their readiness five minutes prior to starting engines with following items for facilitating ATC service.
 - a. call sign
 - b. spot number
 - c. proposed flight level/altitude and route (only when changed from original Flight Plan)
- (8) Pilot should ensure that they are able to follow the clearance to the take-off position or the take-off clearance without delay to reduce runway occupancy time. Cockpit check should be completed prior to line-up and checks requiring completion on the runway should be kept to a minimum. If unable to do so, notify to Tokyo Tower.
- (9) Pilot should ensure that they are able to follow the instruction for runway crossing without delay. Upon runway crossing, pilot should vacate the runway as soon as possible and pass through the runway holding position marking on the exit taxiway.
- (10) Departure aircraft is required to take off with runway length 2500m except following (a) and (b).
 - (a) Between 2100UTC and 1400UTC : Departure aircraft(*) for North America, Europe and Turkey.
 - (b) Between 1400UTC and 2100 UTC : Departure specified and allowed in advance(see RJTT AD2.21 NOISE ABATEMENT PROCEDURES 2.Noise Preferential Runways)

(Note)*Between 0600UTC and 1000UTC, non-scheduled flight is required to take off with runway length 2500m,even though bound for North America, Europe and Turkey.
- (11) Predetermined Runway depend on the flight direction
During 2100UTC and 1400UTC, the aircraft will be assigned departure runway depending on the flight direction.

The Airway or Fix filed in Flight Plan (Reference AIC)	Departure Runway		
	North wind operation	South wind operation 1 (RWY22/23 approaches in progress)	South wind operation 2 (RWY16L/R approaches in progress between 0600UTC and 1000UTC)
ROVER, Y884, Y885	RWY34R	RWY16L	RWY16R ^(*1)
Y18 ^(*2)	RWY34R	RWY16L	RWY16R
	RWY05	RWY16R	RWY22
Y20 ^(*2)	RWY34R	RWY16L	RWY16R
	RWY05	RWY16R	RWY22
Y28, Y56, XAC	RWY05	RWY16R	RWY22

(Note1) *1 Scheduled flight only for North America, Europe and Turkey will be assigned RWY16L.

(Note2) *2 Departure runway will be assigned when Flight schedule is fixed.


(Note3) ATC may assign other runway that listed above, if required.

- (12) Runway is predetermined by flight direction.
Aircraft which uses RWY05 for take off shall comply with the aircraft weight restriction. Even though aircraft weight exceeds the restriction, the other runway shall not be used.(see RJTT AD2.23.7)
- (13) Prior notice of spot number before landing
All arriving aircraft should notify control tower of the parking spot number at initial contact.

(14) GROUND CONTROL Frequency

See attached chart

GROUND CONTROL Frequency



1.3 Intersection departure

- (1) When RWY 34R/16L, 05, 16R, 04/22 is in use, departing aircraft may be instructed intersection departure from C2, C3, C13, D2, A15/L15, A14/L14, B2/T2 or B13 without pilot's consent. Aircraft unable to depart from C2, C3, C13, D2, A15/L15, A14/L14, B2/T2 or B13 intersection shall advise "TOKYO GROUND/TOWER" accordingly.
- (2) Separation for departure as in AD1.1.6.3.2.2(2) will not be applied to aircraft departing from TWY C13, D2, B2/T2, B13, TWY C3 behind departing aircraft from C2 or A14/L14 behind departing aircraft from A15/L15. Aircraft requiring separation in AD1.1.6.3.2.2(2) shall advise "TOKYO GROUND/TOWER" accordingly.
- (3) The remaining runway length for intersection departures are as follows.

RWY	TWY	Remaining RWY length *
34R	C2	2,920m (9,590ft)
	C3	2,820m (9,250ft)
	C5	2,420m (7,930ft)
	C6	2,100m (6,880ft)
	C7	1,780m (5,830ft)
	C8	1,330m (4,360ft)
	C13	3,180m (10,440ft)
	C12	2,800m (9,190ft)
16L	C11	2,480m (8,160ft)
	C10	2,030m (6,680ft)
	C9	1,650m (5,430ft)
	A2	2,520m (8,260ft)
	A3/L3	2,420m (7,960ft)
	A4/L4	2,320m (7,630ft)
	A5	2,010m (6,590ft)
	L5	1,980m (6,490ft)
34L	A6/L6	1,890m (6,200ft)
	A7	1,570m (5,150ft)
	A9/L9	1,470m (4,820ft)
	RWY 04/22	2,770m (9,080ft)
	A15	2,600m (8,550ft)
	L15	2,550m (8,370ft)
	A14	2,490m (8,190ft)
	L14	2,440m (8,010ft)
16R	A13	2,310m (7,570ft)
	A12	2,000m (6,560ft)
	L13	2,080m (6,850ft)
	L12	1,800m (5,910ft)
	A11/L11	1,930m (6,350ft)
	A10	1,500m (4,920ft)
	B2/T2	2,310m (7,570ft)
	B3/T3	2,030m (6,670ft)
04	B4/T4	1,800m (5,900ft)
	B5/T5	1,810m (5,950ft)
	B6/T6	1,530m (5,030ft)
	B13	2,320m (7,620ft)
	B12	1,930m (6,340ft)
	T12	1,880m (6,170ft)
	B11	1,660m (5,460ft)
	T11	1,630m (5,370ft)
22	B10	1,580m (5,190ft)
	B9	1,470m (4,830ft)
	T9	1,520m (5,010ft)
	D2	2,320m (7,620ft)
	D3	1,800m (5,900ft)
05	D4	1,880m (6,170ft)
	D5	1,500m (4,920ft)

*Rounded down to the nearest 10m(10ft) from the measurement between the point where TWY CL meets RWY CL and RWY THR.

- 1.4 Pilot should hold at RWY-holding position markings beside RWY guard lights are turned on at the TWY C1, C2, C3, C5, C12, C13 and C14.

Remarks; RWY-holding position markings and RWY guard lights are located at 75m and 90m off the runway center line on those TWY.(see RJTT AD2.24-ADC-1)

1.5 機材制限

B747-100/100SR, -200/200SR, -300/300SR 及び -SP(いわゆる、「クラシックジャンボ」)については、緊急機または国の航空機を除き運航は許可されない。

1.6 補助動力装置 (APU) の使用制限

航空機が対象スポットを使用する場合は、管理者が特に認める場合を除き、次に掲げる時間を超えて補助動力装置を使用してはならない。

(1) 出発予定時刻前の 15 分間

(2) 到着後、地上からの動力設備が使用可能となるまでに必要とする最小限度の時間

(3) 航空機が点検整備のため補助動力装置を必要とする場合は最小限度の時間

注) 対象スポットは、1 ~ 5R、5、6 ~ 23、53 ~ 73、105P、106 ~ 114、142 ~ 149 とする。

1.5 Aircraft type restrictions

B747-100/100SR, -200/200SR, -300/300SR and -SP(so-called "B747 Classics") are not allowed to operate all day except in emergency or state aircraft.

1.6 Restrictions about the use of auxiliary power units(APU)

When an aircraft is using following aircraft parking stand, APU shall not be used outside the time periods specified below except when specifically acknowledged by the authority as necessary.

(1) Less than 15 minutes prior to the estimated time of departure.

(2) The minimum time required for switching over to the fixed power facilities, after arrival at the parking stand.

(3) For the minimum time required for aircraft maintenance purposes if needed.

NOTE) Aircraft parking stand: Spot NR1-5R, 5, 6-23, 53-73, 105P, 106-114, 142-149.

1.7 PDA (parts departing aircraft) reporting to Airport Administration

In order to secure the safety of aircraft operations and to rectify the issue of falling objects from aircraft operating in the vicinity of Tokyo International Airport, aircraft operators are required to notify Airport Administration (Tel 03-5756-1531) of any "Parts Departing Aircraft" from flights operating to/from Tokyo International Airport, without delay. This information shall be shared by relevant parties in order to prevent recurrence of such.

1.8 RWY16R/RWY16L における PAPI の運用

(1) RNP RWY16R 及び RNP RWY16L 運用時ののみ設定角 3.25° の PAPI(以下「3.25° PAPI」という。)が点灯し、設定角 3.0° の PAPI(以下「3.0° PAPI」という。)が消灯する。(図 1)

(2) 3.25° PAPI のオンコースは、3.0° から 3.5° となる。(図 2)

(3) 3.0° PAPI と 3.25° PAPI の同時点灯は行わない。

(4) PAPI の切替えは、原則として、航空機が滑走路進入端から 5NM の地点に到達するまでに行われる。

(5) 点灯している PAPI の角度に疑義がある場合は管制機関に確認すること。

(例) Pilot: Confirm PAPI angle.
ATC: PAPI angle 3.0/3.25.

(6) 進入方式の変更に伴い PAPI が切り替わる場合は必要に応じ管制機関から通報される。

(例) PAPI angle change to 3.0.

(7) 障害等により 3.25° PAPI が不点灯となっている場合、その代替措置として 3.0° PAPI が点灯される。その場合には必要に応じ管制機関から通報される。

(例) 3.25° PAPI unserviceable(due to trouble).

(例) Alternate PAPI angle 3.0 available.

注 RNP RWY16R/RWY16L 運用時以外において、3.0° PAPI が障害等により不点灯になった場合であっても、3.25° PAPI は点灯されない。

1.8 Operation of PAPI on RWY16R/RWY16L

(1) PAPI(The angle is 3.25°)(The PAPI is called "3.25° PAPI" hereafter.) is turned on and PAPI(The angle is 3.0°)(The PAPI is called "3.0° PAPI" hereafter.) turned off only when RNP RWY16R and RNP RWY16L are in operation.(Fig.1)

(2) The setting angles for a 3.25° PAPI on-course sector is between 3.0° and 3.5°.(Fig.2)

(3) 3.0° PAPI and 3.25° PAPI are not turned on simultaneously.

(4) A changeover between 3.0° PAPI and 3.25° PAPI will be accomplished before the aircraft reaches 5NM from runway threshold.

(5) When pilot is uncertain of an angle of the PAPI in operation, that pilot should contact ATC for confirmation.

(e.g.) Pilot: CONFIRM PAPI ANGLE.
ATC: PAPI ANGLE 3.0/3.25.

(6) When ATC intend to carry out a changeover between 3.0° PAPI and 3.25° PAPI in response to a change in approach procedure, ATC will inform pilots as necessary.

(e.g.) PAPI ANGLE CHANGE TO 3.0.

(7) When the outages of 3.25° PAPI occur due to the system failure, 3.0° PAPI will be turned on as an alternative guidance.

ATC will inform pilots about PAPI conditions as necessary.

(e.g.) 3.25° PAPI UNSERVICEABLE(DUE TO TROUBLE).

(e.g.) ALTERNATE PAPI ANGLE 3.0 AVAILABLE.

Note: When approach procedures except RNP RWY16R/RWY16L are in operation, 3.25° PAPI will not be turned on as an alternative guidance even if 3.0° PAPI becomes unserviceable due to system failure.

Fig.1



Fig.2



2. Taxiing to and from stands

2.1 スポット 33 ~ 41 からのスポットアウト手順

プッシュバック後に、プッシュバックレーンから誘導路 W へ自走を行う場合は、使用スポット導入線とプッシュバックレーンの交点付近から、隣接スポット導入線と誘導路 W の誘導路中心線との交点付近を会合点として実施すること。ただし、管制官からプッシュバックレーンの走行を指示された場合^{*1*2}は、プッシュバックレーンを走行した後、地上走行補助線を経由して誘導路 W へ自走すること。

プッシュバック後にプッシュバックレーンから誘導路 J 又は誘導路 J1 へ自走を行う場合は、プッシュバックレーンを走行した後、地上走行補助線を経由して誘導路 J 又は誘導路 J1 へ自走すること。

^{*1} 例：“TAXI VIA PUSHBACK-LANE TO W TWY”

^{*2} 例：“TAXI VIA PUSHBACK-LANE TO J TWY”


2.1 Spot OUT procedure from spot 33-41

After pushing back, ACFT taxiing from the Pushback-lane to TWY W, shall proceed to TWY W from the intersection of the Pushback-lane and the guide lane for the used spot, so as to intercept TWY W center line near the point crossing the guide lane for the next spot. However, when instructed to taxi via the Pushback-lane by ATC^{*1*2}, ACFT shall taxi on the Pushback-lane and then proceed via the auxiliary taxiing line to TWY W.

After pushing back, ACFT taxiing from the Pushback-lane to TWY J or TWY J1, shall taxi on the Pushback-lane and then proceed via the auxiliary taxiing line to TWY J or TWY J1.

^{*1} example: "TAXI VIA PUSHBACK-LANE TO W TWY"


^{*2} example: "TAXI VIA PUSHBACK-LANE TO J TWY"



2.2 Standard taxiing route(See attached chart RJTT AD2.20)

The standard taxiing routes for departure and arrival may be instructed by ATC, using route ID in the table below.

	Direction	Route ID	Routing Via
Departure	To RWY05	ROUTE 5	TWY A-R-S
Arrival	From RWY23		TWY S-R-A



3. Parking area for small aircraft(General aviation)

The following markings shown on the Fig.1 below are installed on the parking area for small aircraft.





Fig. 1



4. Parking area for helicopters

Nil

5. Apron - taxiing during winter conditions

Nil

6. Taxiing - limitations

6.1 Restricted taxiways

(a) The aircraft of which wing span (WS) listed below table shall not pass following TWY or ACFT stand taxilane.

Restricted TWY or ACFT stand taxilane	WS	REMARKS
A(BTN A1 and A3), A(BTN A1 and W)	WS >= 74m	
A2, A5(BTN RWY16R/34L and A4), A5(BTN A3 and A4), A7, A8, A10, A13(BTN A and A12), A13(BTN RWY16R/34L and A12), B8, B9, B10, B11, J1(BTN B and K), J1(BTN K and J), C(BTN K and R), C4, C8, C9, C10, C13, E(BTN J and K), E3(BTN E and R), E4, E8(BTN C and E), E9(BTN C and E), E10(BTN C and E), E12, L10, M2(BTN C and E), Y(BTN C and R), R(BTN A and G), R(BTN E10 and J), T8, T9, T11, A16, W10, W11(BTN A and W), W(BTN K and B), E(BTN H and J), W13, W(BTN K and J), W(BTN J and M1)	WS >= 69m	
E10(BTN E and spot NR53), R1, J2(BTN K and Y), F, N(BTN spot NR981 and N7), N1, N2, N5, N7, P11(BTN P and U2), U2, U4, W6, W9, W(BTN H and M1), W11(BTN W and R1), M1(BTN R1 and W)	WS >= 65m	
E8(BTN E and R)*, E9(BTN E and R)*, R(from E8 to E9)*, M2(BTN E and R)	WS >= 61m	*The restrictions are excepted for B77W. REF AD2.20. 6.1(e)
Q	WS >= 52m	*REF AD2.23. 7
M1(from spot NR21 to NR23), N6(from spot NR961 to NR969)*	WS >= 36m	*Except towed aircraft of which WS below 48m
N3, N4	WS >= 33m	
N6(BTN spot NR961 and N3)	WS > 28.5m	

(b) In order to keep clearance between other aircraft or obstacle, the aircraft of which wing span (WS) listed below table shall reduce taxi speed and shall strictly follow the taxiway center line as following TWY.

Restricted TWY	WS
A(from RU6 to RU7)	78m =< WS < 80m
A(from W to Hangar)	76m =< WS < 80m
E(from spot NR801 to NR807), E(from spot NR808 to NR811)	72m =< WS < 80m
W(from spot NR201 to NR214), P8(BTN P and V), P9(BTN P and V), P10(BTN P and V) and V	71m =< WS < 80m
C(BTN K and R), E3(BTN E and R), E12(BTN E and R), E(BTN H and J), Y(BTN C and R), R(BTN A and G), R(BTN E10 and J), W(BTN J and M1)	63m =< WS < 69m
W(from spot NR5 to NR20), E10(from spot NR55 to spot NR53), J2(BTN K and Y), P11(BTN P and U2) and F	55m =< WS < 65m
M2(BTN E and R)	55m =< WS < 61m

(c) All aircraft shall taxi with minimum power when taxiing on apron taxiways in order to avoid blast damage to vehicles running along apron taxiways.

(d) In order to keep clearance between aircrafts and the fence etc, (31.5m from taxiway center line, 1.1m/AGL) which is installed on the bridge of E, P and R taxiway, all aircrafts shall reduce taxiing speed and follow the taxiway center line strictly.(see below chart)

E, P 及び R 誘導路橋梁部に設置されるフェンス等(誘導路中心線から 31.5m, 地上高 1.1m)と機体との間のクリアランスを確保するために、すべての航空機は速度を減じて且つ誘導路中心線を走行することを厳守すること。(下図参照)




Fig.1








Fig.2




(e) Taxiway required to pay special attention are shown on attached chart.
(See RJTT AD2.20.6.1(a) and (b))

- 1) TWY required to pay special attention for A340-500




2) A340-600における注意して走行すべき誘導路

2) TWY required to pay special attention for A340-600




3) A350-900 における注意して走行すべき誘導路

3) TWY required to pay special attention for A350-900




4) A350-1000における注意して走行すべき誘導路

4) TWY required to pay special attention for A350-1000




5) A380-800における注意して走行すべき誘導路

5) TWY required to pay special attention for A380-800




6) B747-8における注意して走行すべき誘導路

6) TWY required to pay special attention for B747-8



7) B767-400ERにおける注意して走行すべき誘導路


7) TWY required to pay special attention for B767-400ER



8) B777-300 における注意して走行すべき誘導路


8) TWY required to pay special attention for B777-300

B777-300における注意して走行すべき誘導路
TWY required to pay special attention for B777-300




9) B777-300ER における注意して走行すべき誘導路

9) TWY required to pay special attention for B777-300ER




10) B787-8における注意して走行すべき誘導路

10) TWY required to pay special attention for B787-8




11) B787-9における注意して走行すべき誘導路

11) TWY required to pay special attention for B787-9



12) B787-10における注意して走行すべき誘導路

12) TWY required to pay special attention for B787-10



- 6.2 All aircraft shall hold at "GP HOLD LINE" on TWY A1, A12, A13, C12, B13, B14 until receiving further taxi clearance in order to protect ILS glide slope signal. (See RJTT AD2.24-APDC-1)

- 6.3 Wing tip clearance at the TWY intersection (REF. AD1.1.6.8)

Wing tip clearance at the TWY intersection between the ACFT holding at the stop marking on the TWY and the other ACFT taxiing behind it are as follows.

1) When B748 holding at the stop marking on TWY C1, C2, C3, C5, C12, C13, or C14

wing span (WS) of ACFT taxiing on TWY C ^{*1}	WS =< 28.8m	28.8m < WS =< 45.8m	WS > 45.8m
wing tip clearance	A	B	×
wing span (WS) of ACFT taxiing on TWY C ^{*2}		WS =< 15.8m	WS > 15.8m
wing tip clearance		B	×

^{*1} When B748 holding at the stop markings located at 75m off the RWY center line.
^{*2} When B748 holding at the stop markings located at 90m off the RWY center line.

2) When B748 holding at the stop marking on TWY T9

wing span (WS) of ACFT taxiing on TWY A16	WS =< 5.8m	WS > 5.8m
wing tip clearance	*B	*×

3) When B748 holding at the stop marking on TWY T7

wing span (WS) of ACFT taxiing on TWY T	WS =< 25.8m	WS > 25.8m
wing tip clearance	B	×

4) When B748 holding at the stop marking on TWY A14, A15, B9, B10, L14 or L15

wing span (WS) of ACFT taxiing on TWY B, L or TWY A	WS =< 21.3m	21.3m < WS =< 38.3m	WS > 38.3m
wing tip clearance	A	B	×

5) When B748 holding at the stop marking on TWY A3, A4, A6, A9, A11, A13, B2, B5, B7, B11, B13, B14, D1, D2, D4, D6, L3, L4, L6, L9 or L11

wing span (WS) of ACFT taxiing on TWY A, B, D or TWY L	WS =< 28.8m	28.8m < WS =< 45.8m	WS > 45.8m
wing tip clearance	A	B	×

6) When B748 holding at the stop marking on TWY B12


wing span (WS) of ACFT taxiing on TWY B	WS =< 17.9m	17.9m < WS =< 34.9m	WS > 34.9m
wing tip clearance	A	B	×

7) When B748 holding at the GP HOLD LINE on TWY A1

wing span (WS) of ACFT taxiing on TWY W	WS =< 24.6m	WS > 24.6m
wing tip clearance	B	×

Legend
A: wing tip clearance >= 15m
B: 6.5m =< wing tip clearance < 15m
×: wing tip clearance < 6.5m
*B: 10.5m =< wing tip clearance < 15m
*×: wing tip clearance < 10.5m

- | | | |
|-----|--|--|
| 6.4 | A 誘導路又は M 誘導路を西に向けて走行する航空機及び、R(A と S の間) 誘導路又は E 誘導路を南に向けて走行する航空機は、管制機間に指示された場合に限り、中間待機位置標識または中間待機位置灯で停止し待機する。(RJTT AD2.9.2 及び AD2.24 を参照) | 6.4 The aircraft taxiing to the west on TWY A or TWY M and taxiing to the south on TWY R(between A and S) or TWY E shall hold at Intermediate Holding Position Marking or Intermediate Holding Position Lights only when instructed by ATC.
(see RJTT AD2.9.2 and AD2.24) |
| 6.5 | (a) Spot NR104、NR105P、NR105F 及び NR106 へのスポットインの方法(添付図参照) | 6.5 (a) Procedures of taxiing to spot NR104, NR105P, NR105F and NR106(see attached chart) |




- (b) Spot NR5R のスポットインの方法(添付図参照)

W 誘導路を経由してスポット NR5R に入る航空機は、十分に減速して航空機導入線に沿ってスポットインすること。

(b) Procedure of taxiing to spot NR5R(see attached chart)

The aircraft should reduce taxi speed and should strictly follow the taxiing guide line of the spot NR5R via W-TWY.



7. School and training flights - technical test flights - use of runways

Nil

8. Helicopter traffic - limitation

Nil

9. Removal of disabled aircraft from runways

Nil


10. Hot spots

A "HOT SPOT" is a location on an aerodrome movement area with a history or potential risk of collision or runway incursion, and where heightened attention by pilots/drivers is necessary.

HS1

Intersection of taxiways of B7, L-TWY and L13


Pilots sometimes confuse L-TWY with L13, while taxiing from B7 to L-TWY.
Do not enter L13.



HS2

Intersection of taxiways of U4, B-TWY and B6


Pilots sometimes confuse B-TWY with B6, while taxiing from U4 to B-TWY.
Do not enter B6.



HS3

Runway crossing area of A16 and L16

Runway holding position markings are installed. ATC authorization shall be required for crossing the runway.



RJTT AD 2.21 NOISE ABATEMENT PROCEDURES**1. 騒音制限**

- 東京国際空港においては、以下の騒音軽減運航方式が適用される。
- ・優先滑走路方式
 - ・優先飛行経路及び騒音軽減運航方式
 - ・騒音軽減進入方式 (NAAP)

1. Noise restrictions

- Following noise abatement procedures on Tokyo INTL Airport are in force.
- Noise Preferential Runways
 - Preferential Routes and Aircraft Operating Procedures for Noise Abatement
 - Noise Abatement Approach Procedure(NAAP)

2. 優先滑走路方式

使用される滑走路は以下の通り。(滑走路閉鎖時又は緊急事態発生時を除く。)

2. Noise Preferential Runways

Runways described below are used except when those runways are not available or urgent situation exists.

(離陸)

(For Take off)

From 2100UTC to 1400UTC	1. 滑走路 05 及び 34R (北風運用時) 又は滑走路 16L 及び 16R (南風運用時) を優先的に使用する。ただし、0600UTC から 1000UTC の南風運用時は除く。(*1) 2. 滑走路 04 は、概ね 20 ノット以上の北東強風時又は滑走路 05 もしくは 34R の閉鎖時に使用する。	1. RWY05 and 34R(north wind operation applied) or, RWY16L and 16R(south wind operation applied) are preferentially used. Except during south wind operation from 0600UTC to 1000UTC.(*1) 2. RWY04 is used when northeast wind is about 20 knots or more, or, when RWY05 or RWY34R is closed.
----------------------------------	--	---

From 1400UTC to 2100UTC	<p>1. 滑走路 05（北風運用時）又は 16L（南風運用時）を優先的に使用する。</p> <p>2. 滑走路 05 及び 16L が使用できない場合は滑走路 16R を使用する。</p> <p>3. 滑走路 34R は、北風運用時、以下の a. 又は b. のいずれかの場合であって、加えて 16L 及び 16R のいずれの滑走路からも安全な離陸が不可能となつた場合に限り使用できるものとする。なお、滑走路 34R は、滑走路 05 の使用を前提に計画したものが、本条項に該当した場合に、使用するものであるから、滑走路 05/23 の航空機荷重制限 (RJTT AD2.23.7) を満たすとともに、滑走路 34R の南端から滑走路長 2500m での離陸を行うこと。ただし、機材性能及び路線距離等を考慮して、滑走路 34R の使用があらかじめ認められた便（以下「指定便」という。）はこの限りではない。この場合、滑走路 34R の南端から滑走路長 3000m での離陸を行うこと。</p> <p>a. 滑走路 05 が閉鎖中である場合</p> <p>b. 出発時において滑走路 05 では背風又は横風制限を超過する場合であって、安全な離陸が不可能な場合</p> <p>* 滑走路 05 からの離陸機又は滑走路 34R への着陸機と、上記 3.b. による滑走路 34R からの離陸機が競合する場合、前者が優先される。</p> <p>* 滑走路 05/23 の航空機荷重制限 (AIP RJTT AD2.23.7) の超過は、上記 3.b. による滑走路 34R の使用理由とはならない。</p> <p>* 上記 3.b. による滑走路 34R からの離陸について、やむを得ないと考えられる範囲を超えた運用がなされた場合、当該号については適用休止又は削除等の措置を執る場合がある。</p> <p>* 指定便以外により滑走路 34R からの離陸を行つた運航者は、以下の事項を東京空港事務所環境・地域振興課あてにFAX 又は E メールにより報告するものとする。</p> <p>a) 当該離陸の日時</p> <p>b) 航空機呼出符号及び航空機型式</p> <p>c) 当該離陸時のウエイト・アンド・バランスのデータ</p> <p>d) 当該離陸を行つた理由（滑走路 05 の閉鎖／背風／横風）</p> <p>e) 風向、風速</p> <p>f) 滑走路の状態（wet/dry 等）</p> <p>g) その他の関連情報</p> <p>当該離陸が上記 3.b. によるものである場合は、併せて以下の情報を報告すること。</p> <p>h) 出発時における風速の背風又は横風成分のうち、制限を超過しているものの当該制限値及び実際値</p> <p>東京空港事務所環境・地域振興課 FAX : 03-5756-1511(+81-3-5756-1511) E メール : hnd-kantika1596@mlit.go.jp</p> <p>4. 滑走路 04 は滑走路 05、滑走路 16L/16R 及び滑走路 34R が使用できない場合に使用する。</p>
----------------------------------	--

(着陸)

(For Landing)

From 2100UTC to 1400UTC	<ol style="list-style-type: none"> 滑走路 34L 及び 34R (北風運用時)、又は、滑走路 22 及び 23 (南風運用時) を優先的に使用する。ただし、0600UTC から 1000UTC の南風運用時は除く。(※1) 2100UTC から 0600UTC まで、及び 1000UTC から 1400UTC までは、滑走路 16L は、概ね 20 ノット以上の南東強風時、又は、滑走路 22 が使用できない場合 (滑走路 23 が使用できない場合であって、滑走路 22 では対応が不可能な場合を含む。) に使用する。 	<ol style="list-style-type: none"> RWY34L and 34R (north wind operation applied) or, RWY22 and 23 (south wind operation applied) are preferentially used. Except during south wind operation from 0600UTC to 1000UTC.(※1) From 2100UTC to 0600UTC and from 1000UTC to 1400UTC, RWY16L is used when southeast wind is about 20knots or more, or, when RWY22 is not available (including the case that RWY23 is not available and RWY22 is unsuitable.).
From 1400UTC to 2100UTC	<ol style="list-style-type: none"> 滑走路 34R (北風運用時) 又は滑走路 23 (南風運用時) を優先的に使用する 北風運用時において滑走路 34R が使用できない場合、滑走路 34L を使用する。 南風運用時において滑走路 23 が使用できない場合は、滑走路 16L、滑走路 22 の優先順位により滑走路を使用する。 	<ol style="list-style-type: none"> RWY34R(north wind operation applied) or RWY23(south wind operation applied) is preferentially used. When north wind operation is applied, and RWY34R is not available, RWY34L is used. When south wind operation is applied, and RWY23 is not available, RWY16L and RWY22 is used in this order.

3. 優先飛行経路及び騒音軽減運航方式

航空機が緊急状態又は避けがたい事態にある場合及びNOTAMに別段の定めがある場合を除き、次の運航方式がすべての航空機に適用される。ただし、航空機の安全な運航を確保するために必要な操縦者の職務権限と責任の遂行を妨げるものではない。

3. Preferential Routes and Aircraft Operating Procedures for Noise Abatement

Except in the event an aircraft is in an emergency, an unavoidable situation or unless otherwise specified by NOTAMs, the following procedures shall be adhered to by all aircraft. However, none of the procedures herein is intended, in any manner, to abrogate the responsibility of the pilot in command to assure the safe operations of the aircraft.

(離陸)

(For Take off)

From 2100UTC to 1400UTC	RWY 34R	<p>(右旋回離陸) 空港の北部、北西部及び北東部にある居住地域における航空機騒音を軽減するため、航空機は次のように従わなければならない。</p> <ol style="list-style-type: none"> 航空機は各航空会社のフライトマニュアルに規定されているバンク角及び速度により、できるだけ早く旋回を開始しなければならない。 2200UTC から 0230UTC 及び 0600UTC から 1000UTC において、TIARA/BEKLA/ROVER [number] B/C Departure が承認された場合、急上昇方式もしくは NADP2 が適用される。 	<p>(For right turn departure)</p> <p>In order to minimize public annoyance for aircraft noise in the residential areas located north, northwest and northeast of the airport, the aircraft should comply with following procedures.</p> <ol style="list-style-type: none"> Aircraft should commence turns as soon as practicable with bank angles and speeds as prescribed in each operator's flight manuals. From 2200UTC to 0230UTC and From 0600UTC to 1000UTC, when TIARA/BEKLA/ROVER [number] B/C Departure is cleared, Steepest Climb Procedure or NADP2 shall be applied.
	RWY 34L	<p>(左旋回離陸) 空港の北部、北西部及び西部にある居住地域における航空機騒音を軽減するため、航空機は次のように従わなければならない。</p> <ol style="list-style-type: none"> 航空機は各航空会社のフライトマニュアルに規定されているバンク角及び速度により、できるだけ早く旋回を開始しなければならない。 インターフェクションからの離陸は認められない。 	<p>(For left turn departure)</p> <p>In order to minimize public annoyance for aircraft noise in the residential areas located north, northwest and west of the airport, the aircraft should comply with following procedures.</p> <ol style="list-style-type: none"> Aircraft should commence turns as soon as practicable with bank angles and speeds as prescribed in each operator's flight manuals. Intersection departure is not permitted.
	RWY 05	なし	Nil
	RWY 16L	なし	Nil
	RWY 16R	なし	Nil

	RWY 04	(右旋回離陸) 空港の北部、北西部及び北東部にある居住地域における航空機騒音を軽減するため、各航空会社のフライトマニュアルに規定されているバンク角及び速度により、できるだけ早く旋回を開始するものとする。	(For right turn departure) In order to minimize public annoyance for aircraft noise in the residential areas located north, northwest and northeast of the airport, the aircraft should commence turns as soon as practicable with bank angles and speeds as prescribed in each operator's flight manuals.
From 2100UTC to 1400UTC	RWY 22	<p>空港の西部にある居住地域における航空機騒音を軽減するため、航空機は次のように従わなければならない。</p> <ol style="list-style-type: none"> 1. 航空機は各航空会社のフライトマニュアルに規定されているバンク角及び速度により、できるだけ早く旋回を開始しなければならない。 2. 急上昇方式が適用される。 3. 原則として主発動機が4発以上の航空機は運航が認められない。ただし、捜索救難及びVIP機を除く。 4. 以下の機種においては、可能な限り最大離陸推力を使用する。 B777, A330, MD11 5. B777, A330は、原則としてB14/T14からの離陸とする。 6. 使用する機材は、耐空証明における離陸測定点における離陸中の騒音値が89未満であること。(定期便を除く。) 	<p>In order to minimize public annoyance for aircraft noise in the residential areas located west of the airport, the aircraft should comply with following procedures.</p> <ol style="list-style-type: none"> 1. Aircraft should commence turns as soon as practicable with bank angles and speeds as prescribed in each operator's flight manual. 2. Steepest Climb Procedure shall be applied. 3. In principle, aircraft with 4 or more main engines are not allowed to operate. Excluding search and rescue and VIP aircraft. 4. In the following models, using the maximum takeoff thrust as much as possible. B777, A330, MD11 5. In principle, B777, A330 should use intersection B14/T14 for takeoff. 6. The noise level (EPNdB) during takeoff at flyover reference noise measurement point in the airworthiness certification shall be less than 89. (Excluding Scheduled flights.)
	RWY 05	空港の北部及び北東部にある居住地域における航空機騒音を軽減するため、各航空会社のフライトマニュアルに規定されているバンク角及び速度により、できるだけ早く旋回を開始するものとする。	In order to minimize public annoyance for aircraft noise in the residential areas located north and northeast of the airport, the aircraft should commence turns as soon as practicable with bank angles and speeds as prescribed in each operator's flight manuals.
	RWY 16L	なし	Nil
	RWY 16R	なし	Nil
From 1400UTC to 2100UTC	「OPPAR DEPARTURE」(代替方式無し) RWY 34R	空港の北部、北西部及び北東部にある居住地域における航空機騒音を軽減するため、各航空会社のフライトマニュアルに規定されているバンク角及び速度により、できるだけ早く旋回を開始するものとする。	[OPPAR DEPARTURE] (Not alternate procedures) In order to minimize public annoyance for aircraft noise in the residential areas located north, northwest and northeast of the airport, the aircraft should commence turns as soon as practicable with bank angles and speeds as prescribed in each operator's flight manuals.
	RWY 04	空港の北部、北西部及び北東部にある居住地域における航空機騒音を軽減するため、各航空会社のフライトマニュアルに規定されているバンク角及び速度により、できるだけ早く旋回を開始するものとする。	In order to minimize public annoyance for aircraft noise in the residential areas located north, northwest and northeast of the airport, the aircraft should commence turns as soon as practicable with bank angles and speeds as prescribed in each operator's flight manuals.

(着陸)

1. 住居地域における航空機騒音を軽減するため、脚下げは運航上可能な限り遅く操作するものとする。特に、滑走路 22ILS 進入を使用する場合は IAD から 6.3 海里の地点まで住居が密集していることに留意すること。

2. 1300UTC から 2200UTC まではディレイド・フラップ進入方式によるものとする。

(For Landing)

1. In order to reduce aircraft noise in the residential area, gear-down should be delayed as far as operationally practicable. Especially, when using RWY22 ILS approach, pay attention that residences are dense until 6.3NM from IAD.
2. Between the hours of 1300UTC and 2200UTC, aircraft should perform Delayed Flap Approach Procedure.

From 2100UTC to 1400UTC	RWY 34R	「HIGHWAY VISUAL RWY34R」が優先的に使用される。 「ILS Z or LOC Z RWY34R」は「HIGHWAY VISUAL RWY34R」が使用できない場合に限り使用される。	[HIGHWAY VISUAL RWY34R] is primarily applied. [ILS Z or LOC Z RWY34R] is applied only when [HIGHWAY VISUAL RWY34R] is not applicable.
	RWY 34L	「ILS X or LOC X RWY34L」が優先的に使用される。 「ILS Z or LOC Z RWY34L」は「ILS X or LOC X RWY34L」が使用できない場合に限り使用される。	[ILS X or LOC X RWY34L] is primarily applied. [ILS Z or LOC Z RWY34L] is applied only when [ILS X or LOC X RWY34L] is not applicable.
From 2100UTC to 1400UTC	RWY 22	「LDA W RWY22」が優先的に使用される。 (4. 騒音軽減進入方式を参照) 「LDA W RWY22」が使用できないときには、「LDA Z(X) RWY22」、「ILS RWY22」、「LOC RWY22」の順に使用される。	[LDA W RWY22] is primarily applied. (See 4.Noise Abatement Approach Procedure) When [LDA W RWY22] is not available, [LDA Z(X) RWY22], [ILS RWY22] and [LOC RWY22] is used in this order.
	RWY 23	「LDA W RWY23」が優先的に使用される。 (4. 騒音軽減進入方式を参照) 「LDA W RWY23」が使用できないときには、「LDA Z(X) RWY23」、「ILS Z RWY23」、「LOC Z RWY23」の順に使用される。	[LDA W RWY23] is primarily applied. (See 4.Noise Abatement Approach Procedure) When [LDA W RWY23] is not available, [LDA Z(X) RWY23], [ILS Z RWY23] and [LOC Z RWY23] is used in this order.
	RWY 16L	2100UTC から 0600UTC まで、及び 1000UTC から 1400UTC までは、空港の北部にある居住地域における航空機騒音を軽減するため、航空機は最終進入への旋回の間、付図に示すコースに沿って又はその内側を飛行しなければならない。 0600UTC から 1000UTC まで、「RNP RWY16L」が優先的に使用される。(*) 「ILS RWY16L」は「RNP RWY16L」が使用できない場合に限り使用される。	From 2100UTC to 0600UTC and From 1000UTC to 1400UTC, in order to minimize public annoyance for aircraft noise in the residential areas located north of the airport, aircraft should fly along or inside of the course shown in attached chart during the circling to final. From 0600UTC to 1000UTC, [RNP RWY16L] is primarily applied.(*) [ILS RWY16L] is applied only when [RNP RWY16L] is not applicable.
	RWY 16R	0600UTC から 1000UTC まで、「RNP RWY16R」が優先的に使用される。(*) 「ILS RWY16R」は「RNP RWY16R」が使用できない場合に限り使用される。	From 0600UTC to 1000UTC, [RNP RWY16R] is primarily applied.(*) [ILS RWY16R] is applied only when [RNP RWY16R] is not applicable.
From 1400UTC to 2100UTC	RWY 34R	「ILS Y or LOC Y RWY34R」(via OSHIMA NIGHT ARRIVAL, AKSEL NIGHT ARRIVAL, AROSA NIGHT ARRIVAL or MESSE NIGHT ARRIVAL)	[ILS Y or LOC Y RWY34R] (via OSHIMA NIGHT ARRIVAL, AKSEL NIGHT ARRIVAL, AROSA NIGHT ARRIVAL or MESSE NIGHT ARRIVAL)
	RWY 34L	「ILS Y or LOC Y RWY34L」(via OSHIMA NIGHT ARRIVAL, AKSEL NIGHT ARRIVAL, AROSA NIGHT ARRIVAL or MESSE NIGHT ARRIVAL) リバーススラスト 空港周辺の航空機騒音を軽減するため、滑走路 34L 着陸後のリバーススラスト使用についてはアイドルパワーまでとする。	[ILS Y or LOC Y RWY34L] (via OSHIMA NIGHT ARRIVAL, AKSEL NIGHT ARRIVAL, AROSA NIGHT ARRIVAL or MESSE NIGHT ARRIVAL) Reverse Thrust In order to reduce aircraft noise in the vicinity of the airport, pilots are requested to limit the use of reverse thrust to idle power after landing at RWY34L.
	RWY 22	「LDA Y RWY22」(via OSHIMA NIGHT ARRIVAL, AKSEL NIGHT ARRIVAL, AROSA NIGHT ARRIVAL or MESSE NIGHT ARRIVAL) リバーススラスト 空港周辺の航空機騒音を軽減するため、滑走路 22 着陸後のリバーススラスト使用についてはアイドルパワーまでとする。	[LDA Y RWY22] (via OSHIMA NIGHT ARRIVAL, AKSEL NIGHT ARRIVAL, AROSA NIGHT ARRIVAL or MESSE NIGHT ARRIVAL) Reverse Thrust In order to reduce aircraft noise in the vicinity of the airport, pilots are requested to limit the use of reverse thrust to idle power after landing at RWY22.

From 1400UTC to 2100UTC	RWY 23	「LDA Y RWY23」(via OSHIMA NIGHT ARRIVAL, AKSEL NIGHT ARRIVAL, AROSA NIGHT ARRIVAL or MESSE NIGHT ARRIVAL)が優先的に使用される。 「ILS Y or LOC Y RWY23」(via OSHIMA NIGHT ARRIVAL, AKSEL NIGHT ARRIVAL, AROSA NIGHT ARRIVAL or MESSE NIGHT ARRIVAL)は「LDA Y RWY23」が使用できない場合に限り使用される。	[LDA Y RWY23] (via OSHIMA NIGHT ARRIVAL, AKSEL NIGHT ARRIVAL, AROSA NIGHT ARRIVAL or MESSE NIGHT ARRIVAL) is primarily applied. [ILS Y or LOC Y RWY23] (via OSHIMA NIGHT ARRIVAL, AKSEL NIGHT ARRIVAL, AROSA NIGHT ARRIVAL or MESSE NIGHT ARRIVAL) is applied only when [LDA Y RWY23] is not applicable.
	RWY 16L	「VOR A」(via OSHIMA V ARRIVAL, AKSEL V ARRIVAL, AROSA V ARRIVAL or MESSE V ARRIVAL) 空港の北部にある居住地域における航空機騒音を軽減するため、航空機は最終進入への旋回の間、付図に示すコースに沿って又はその内側を飛行しなければならない。	[VOR A] (via OSHIMA V ARRIVAL, AKSEL V ARRIVAL, AROSA V ARRIVAL or MESSE V ARRIVAL) In order to minimize public annoyance for aircraft noise in the residential areas located north of the airport, aircraft should fly along or inside of the course shown in attached chart during the circling to final.

(*)1) 0600UTC から 1000UTC のうちの 3 時間程度にあっては、南風運用時において以下の滑走路が使用される。

(離陸) RWY16R, RWY16L, RWY22
(着陸) RWY16R, RWY16L

(*)2) 0600UTC から 1000UTC のうちの 3 時間程度であって、上記 (*)1) の滑走路が使用される場合に適用される。

(*)1) For about 3 hours from 0600UTC to 1000UTC, the following runway is used during the south wind operation.

(For Take off) RWY16R, RWY16L, RWY22
(For Landing) RWY16R, RWY16L

(*)2) Applicable when the runway (*)1) is used in about 3 hours from 0600UTC to 1000UTC.

4. 騒音軽減進入方式 (NAAP)

(1) 適用時間帯

2100UTC から 1400UTC の間

(2) 対象航空機

BACON 経由滑走路 22 及び DATUM 経由滑走路 23 に着陸する航空機
(レーダー誘導により LDA22 又は LDA23 ローカライザーコースへ会合するものを除く。)

(3) 対象経路

LDA W RWY22 及び LDA W RWY23

(4) 実施条件

台風等の悪天候、レーダー施設の障害等の重大な事象がないこと。

(5) NAAP の承認

管制機関は LDA W RWY22 又は LDA W RWY23 による進入を許可することにより、NAAP を承認する。

(6) 繙続的な降下 (LDA W RWY22 のみ)

NAAP 実施中は、不必要な TCAS-RA の発生を避けるとともに、騒音軽減のため、航空機は BACON と BEAST の間を 1500FT/min を超えない降下率で継続的に降下しなければならない。

(7) NAAP が実施できない場合

悪天候などの理由により NAAP が実施できない場合には、航空機は東京アプローチとの通信設定時に、その理由とともに LDA Z RWY22 又は LDA Z RWY23 若しくはその他の進入方式を要求しなければならない。

(8) NAAP の中止

交通状況等により、管制機関は承認した NAAP を中止することがある。その場合、代替指示が発出される。

(9) その他

交通状況もしくは気象状態等によって、管制機関は進入方式上の速度と異なる速度を指示することがある。

4. Noise Abatement Approach Procedure(NAAP)

1) Applicable time

Between 2100UTC and 1400UTC

2) Aircrafts NAAP is applied

All aircraft which land to RWY22 via BACON/RWY23 via DATUM of Tokyo INTL Airport. (except aircraft intercepting LDA22/LDA23 LOC course by RADAR vector)

3) Routes used for NAAP

LDA W RWY22 and LDA W RWY23

4) Conditions

No significant condition such as Typhoon, Severe WX conditions, or Malfunction of radar system etc. is observed.

5) Clearance for NAAP

ATC clears NAAP by assigning approach procedure of "LDA W RWY22" or "LDA W RWY23".

6) Continuous descent(only LDA W RWY22)

To avoid nuisance TCAS-RA and reduce noise, while conducting NAAP, pilot should make descent continuously with 1500FT/min or less descending rate between BACON and BEAST.

7) In case NAAP is not available


If NAAP is not available because of WX conditions etc, pilot should request LDA Z RWY22/LDA Z RWY23 or other approach with the reason at initial contact with Tokyo Approach.

8) Cancellation of NAAP

ATC may cancel NAAP due to traffic conditions even after NAAP is cleared. In this case, alternate instructions will be issued.

9) Remarks

Due to traffic or WX conditions, ATC may assign IAS differing from on attached.



RJTT AD 2.22 FLIGHT PROCEDURES**1. TAKE OFF MINIMA**

	RWY	ACFT CAT	REDL & RCLL		REDL or RCLL or RCL Marking		NIL (DAYTIME ONLY)	
			RVR	VIS	RVR	VIS	RVR	VIS
Multi-Engine ACFT with TKOF ALTN AP FILED	04	A,B,C,D	-	400m	-	400m	-	500m
	22	A,B,C,D	400m	400m	400m	400m		
	05	A,B,C,D	400m	400m	400m	400m		
	16R	A,B,C,D	400m	400m	400m	400m		
	34L	A,B,C,D	400m	400m	400m	400m		
	16L	A,B,C	400m *200m **150m	400m *200m	400m *250m	400m *250m		
		D	400m *250m **200m	400m *250m	400m *300m	400m *300m		
	34R	A,B,C	400m *200m **150m	400m *200m	400m *250m	400m *250m		
		D	400m *250m **200m	400m *250m	400m *300m	400m *300m		
OTHER	04 22 05 16R 34L 16L 34R	A,B,C,D	AVBL LDG MINIMA					

*APPLICABLE WHEN LVP/LVPD IN FORCE

**APPLICABLE WHEN LVP/LVPD INFORCE and MULTIPLE RVRs AVAILABLE

2. Trajectoryd Airport Traffic Data Processing System (TAPS)

東京アプローチの指示のもとに、当該進入管制区を飛行する航空機は、モード A/3 の二次レーダー個別コード及びモード C による応答を指示される。

二次レーダー個別コードを搭載していない航空機が当該コードによる応答を指示された場合は、管制官に対し、その旨通報すること。

Aircraft flying under control of Tokyo approach control in the approach control area will be instructed to reply with discrete code on Mode A/3 and Mode C.

If an aircraft with non-discrete code capability be instructed to reply with the discrete code, it shall report a controller accordingly.

3. Lost communication procedures for arrival aircraft under radar navigational guidance

If radio communications with Tokyo Approach/Radar are lost for 1 minute, squawk Mode A/3 Code 7600 and;

- (I)
 - 1) Contact TOKYO Tower.
 - 2) If unable, proceed in accordance with visual flight rules.
 - 3) If unable,
 - a) When RWY34L or RWY34R in use, proceed to SINGO at last assigned altitude or 4,000feet whichever is higher, and execute instrument approach for RWY34R.
 - b) When RWY22, RWY23, RWY16L or RWY16R in use, proceed to SMILE at last assigned altitude or 4,000feet whichever is higher, and execute instrument approach for RWY23.
- (II) Procedures other than above will be issued when situation required.

4. Flight restrictions


Unless otherwise authorized by ATC.

Aircraft other than the arriving at and/or departing from Tokyo International Airport are required not to fly over the Kawasaki Petrochemical Complex area, and even in case of flying over the area, not to fly below an altitude of 3,000feet.
(See AD2.24 OTHER CHART ATTACHMENT 1)

5. Special VFR flight route for helicopter (See below chart)**SPECIAL VFR FLIGHT ROUTE FOR HELICOPTER**

Special VFR flight route for helicopter in
the TOKYO Control ZONE

Daishibashi - (along the Tama River) - Marukobashi



6. SIMULTANEOUS INDEPENDENT LDA APPROACHES (SILA)

1) Applicable instrument approach procedures for SILA

LDA W RWY22(with VPT), LDA W RWY23(with VPT), LDA Z RWY22(with VPT), LDA Z RWY23(with VPT), LDA X RWY22(with VPT) and LDA X RWY23(with VPT)

Note: "VPT" stands for Visual maneuver with Prescribed Track that meets the criteria of ICAO PANS-OPS (Doc.8168). A specific track for visual maneuvering after the MAPt is prescribed in these procedures.

2) Conditions

SILA, where radar separation minima between aircrafts on adjacent localizer courses and VPTs are not prescribed, will be conducted when the following conditions are met. However, SILA shall not be applied under certain adverse weather conditions which might affect safe operations (e.g. windshear on the final approach course, etc.).

A. No Transgression Zone (NTZ) 610m wide is established equidistant between localizer courses and is depicted on the radar display.

B. LOC, radar, and appropriate frequencies are operating normally.

Note: Visual aids associated with the runway used for the prescribed track (i.e. ALS, PAPI) are shown on the chart with their main characteristics (i.e. slope of the PAPI).

3) Information of SILA

Aircraft shall be advised that SILA are in force. This information may be provided through the ATIS broadcasts.

"Simultaneous LDA approaches to RWY22 and RWY23 are in progress."

4) Radar monitoring

Radar monitoring is provided for each simultaneous LDA approach to ensure aircraft do not deviate from the localizer course as follows:

A. Aircraft shall be provided a minimum of 1,000ft vertical separation or a minimum of 3NM radar separation until intercepting localizer course.

The assigned altitude shall be maintained until final approach fix (FAF).

B. Radar monitoring is continued even after instructed to contact Tower frequency and instructions prescribed in C are provided on the frequency when necessary.

C. Aircraft observed to overshoot the turn-on or continue on a track which will penetrate the NTZ will be instructed to return to the correct localizer course. If a deviating aircraft fails to respond to such instructions or is observed penetrating the NTZ, the aircraft on the adjacent localizer course shall be instructed to avoid the deviating aircraft.

D. Radar monitoring will automatically be terminated when the aircraft has passed the coverage of NTZ (RWY22: IKL 2.7DME / RWY23: MAPt).

Note: ATC will not inform pilots when radar monitoring is terminated.

5) Go around procedure

When going around, pilot should report ATC as soon as practicable, and proceed in accordance with the go around procedure described on the chart until receiving ATC instructions.

6) Response to "TRAFFIC ALERT"

All breakouts in response to ATC's instructions shall be accomplished quickly. These instructions will be issued on TOWER FREQUENCY when situation required.

7. SIMULTANEOUS INDEPENDENT RNP APPROACHES (SIRA)

- 1) Applicable instrument approach procedures for SIRA

- RNP RWY16L, RNP RWY16R

- 2) Conditions

SIRA, where radar separation minima between aircrafts on adjacent approach courses are not prescribed, will be conducted when the following conditions are met. However, SIRA shall not be applied under certain adverse weather conditions which might affect safe operations (e.g. windshear on the final approach course, etc.).

- A. No Transgression Zone (NTZ) 610m wide is established equidistant between 16R final approach course and 16L final approach course is depicted on the radar display.
- B. Wide Area Multilateration (WAM), radar and appropriate frequencies are operating normally.
- C. Mode S transponder is activating normally. In case of Mode S transponder which has failed or be not equipped, the pilot should inform the ATC facility.

- 3) Information of SIRA

Aircraft shall be advised that SIRA are in force. This information may be provided through the ATIS broadcasts.

"Simultaneous RNP approaches to RWY16L and RWY16R are in progress."

- 4) Radar monitoring

Radar monitoring is provided for each simultaneous RNP approach to ensure aircraft do not deviate from the approach course as follows;

- A. Aircraft shall be provided a minimum of 1,000ft vertical separation or a minimum of 3NM radar separation until the following point;
: Intersection of an extension line of the north short side of NTZ with RWY 16L/R RNP approach courses.
- B. Radar monitoring is continued even after instructed to contact Tower frequency and instructions prescribed in C are provided on the frequency when necessary.
- C. Aircraft observed to deviate from the approach course or continue on a track which will penetrate the NTZ will be advised by ATC. If a deviating aircraft is observed penetrating the NTZ, the aircraft on the adjacent approach course shall be instructed to avoid the deviating aircraft.
- D. Radar monitoring will automatically be terminated when visual separation is applied by ATC.

Note: ATC will not inform pilots when radar monitoring is terminated.

- 5) Response to "TRAFFIC ALERT"

All breakouts in response to ATC's instructions shall be accomplished quickly. These instructions will be issued on TOWER FREQUENCY when situation required.

8. Category II / III Operations at Tokyo International Airport**1) Facilities**

The following facilities are available:

Runway 34R
(1) ILS Runway 34R-CAT III
(2) Lighting system Runway 34R-CAT III
(3) RVR by forward-scatter meters (the touchdown zone, the mid-point and stop-end of the runway)

2) Conditions

A. The following systems must be operative:

For ILS Z RWY34R approach (CAT II) For ILS Y RWY34R approach (CAT II)	For ILS Z RWY34R approach (CAT III) For ILS Y RWY34R approach (CAT III)
(1) ILS comprising: <ul style="list-style-type: none">• ILS-LOC 34R with standby transmitter• ILS-GP 34R with standby transmitter (When any standby transmitters unserviceable, downgrade ILS-CAT I.)• IM 34R (When IM unserviceable, RA could be used as an alternate method.)• ILS-DME 34R	(1) ILS comprising: <ul style="list-style-type: none">• ILS-LOC 34R with standby transmitter (including far field monitor)• ILS-GP 34R with standby transmitter (When any standby transmitters or far field monitor unserviceable, downgrade ILS-CAT I.)• ILS-DME 34R
(2) Lighting systems comprising: <ul style="list-style-type: none">• PALS 34R (including side row barrettes)• High INTST REDL• High INTST RTHL• RCLL and RTZL	(2) Lighting systems comprising: <ul style="list-style-type: none">• PALS 34R (including side row barrettes)• High INTST REDL• High INTST RTHL• RCLL and RTZL
(3) Secondary power supply	(3) Secondary power supply
(4) RVR by forward-scatter meters at the touchdown zone and either (the mid-point or stop-end of the runway).	(4) RVR by forward-scatter meters at the touchdown zone, mid-point and stop-end of the runway.

B. The following information must be currently available:

- 1) Surface wind speed and direction
- 2) RVR

C. ITEM A and/or B are not met, the relevant information will be notified to the pilots as soon as practicable.

3) Operating Minimum

Approach minima stated AD2.24 (Instrument Approach Chart) are observed.

4) LVP

LVP will be available when the following conditions are met:

- 1) Ceiling is at or less than 200ft and/or RVR is at or less than 600m.
- 2) Facilities listed 1) above are operational.
- 3) ILS Critical Area is protected.

In order to protect Critical Area for the succeeding arrival aircraft, an arrival aircraft may be given the following instruction by ATC:

"REPORT OUT OF ILS CRITICAL AREA"

The exit taxiway center line lights are fixed alternate green and yellow inside the ILS Critical Area. If an aircraft is given the above instruction, she is expected to advise the ATC when the taxiway center line lights change from alternate green and yellow to steady green.

5) Approval for CAT II / III Operations

Operators must obtain operational approval from the State of Registry or the State of Operator, as appropriate, to conduct CAT II / III Operations. (See GEN1.5)

9. LVTO at Tokyo International Airport**1) Facilities**

The following facilities are available:

RWY 16L	RWY 34R
<ul style="list-style-type: none"> • Lighting system RWY 16L for LVTO • RVR by forward-scatter meters (the touchdown zone, the mid-point and stop-end of the runway) 	<ul style="list-style-type: none"> • Lighting system RWY 34R for LVTO • RVR by forward-scatter meters (the touchdown zone, the mid-point and stop-end of the runway)

2) Conditions

A. The following systems must be operative:

For LVTO
(1) Lighting system comprising; <ul style="list-style-type: none"> • High INTST REDL • High INTST RENL • RCLL
(2) Secondary power supply

B. The following information must be currently available:

- a) Surface wind speed and direction
- b) RVR or VIS

C. ITEM A and/or B are not met, the relevant information will be notified to the pilots as soon as practicable.

3) Operating Minima

Take-off minima stated in AD2.22 (TAKE-OFF MINIMA) are observed.

4) LVP/LVPD

LVP/LVPD will be available when the following conditions are met:

- a) RVR is at or less than 600m.
- b) Facilities listed 1) above are operational.

RJTT AD 2.23 ADDITIONAL INFORMATION

1. TV tower
TV tower 1,148 feet MSL located 6NM NNW of HANEDA VOR/DME (HME)
2. Vehicle traffic line
White line markings on apron area.
3. Schedule maintenance on the runway
All RWY are subject to closing for maintenance purpose as follows. See NOTAM RJTT for further detailed information.

FACILITY	PLANNING PERIOD	REMARKS
RWY 16R/34L	MON, WED, THU, SAT, SUN 1400-2130	AVBL CROSS RWY 16R/34L VIA TWY OTHER THAN CLSD TWY
RWY 04/22	MON, TUE, THU, FRI, SUN 1430-2100	AVBL CROSS RWY 04/22 VIA TWY OTHER THAN CLSD TWY
RWY 16L/34R	TUE, FRI 1530-2130	
RWY 05/23	WED, SAT 1430-2100	

4. Bird-patrollers will patrol on perimeter and/or maintenance road around RWYs and occasionally use shotgun and shell crackers to get rid of birds harmful to air safety. Bird-patrollers may enter LDG strips not nearer than 50M FM RWY edges and 20M FM TWY edges to pick up birds being shot down HJ.
5. Positions not visible from control tower.
 - a) Aircraft stand
From NR201 to NR205.
 - b) Taxiway
A part of TWY A(from spot NR201 to spot RU6) and a part of TWY W(from spot NR201 to NR203).
6. 空港付近の船舶の航行
 - 6.1 RWY04/22 及び RWY05/23 の北東側に船舶高基準面と許容高が設定される。
 - 6.2 航空機の運航に影響がある高さの船舶が、RWY22 または RWY23 の進入表面下を航行することがあり、これらの船舶は空港当局により監視されている。必要に応じて以下の対応が取られる。
(添付図参照)
6. Passage of vessel in the vicinity of the airport
 - 6.1 Base level of Vessel height and Admissible height is set at Northeast side of RWY 04/22 or RWY 05/23.
 - 6.2 The Vessel with height which affects aircraft operations may pass across beneath the approach surface of RWY22 or RWY23, and those vessels are monitored by Airport authority. The following action will be taken when necessary.
(see attached chart)

東京西航路

- 1)当該進入表面下に設定された東京西航路を航行する船舶の情報は、RJTT NOTAM または ATC により提供される。
- 2)船舶が A 点と B 点または C 点と D 点の間を通過する間、下記の制限がかかる。
 - a) RWY04 及び RWY05 からの離陸は許可されない。
 - b) RWY22 及び RWY23 への到着機に対して空中待機または復行が指示されることがある。

側傍海域

- 船舶が、東京西航路と進入灯の間の進入表面下を通過する場合には、船舶の高さ及び位置により、以下の制限がかかる。
- a) RWY04 及び RWY05 からの離陸は許可されない。
 - b) RWY22 及び RWY23 への到着機に対して復行が指示されることがある。

Tokyo West Passage Route

- (1) The information of the vessel passing along the Tokyo West Passage Route, which is laid down beneath the approach surfaces, will be provided by NOTAM RJTT or ATC.
- (2) While the vessel is between point A and B or between point C and D, following restrictions are taken;
 - a) Take-off clearance is not issued for RWY04 or RWY05.
 - b) Holding or Go-around instruction may be issued for arrival aircraft for RWY22 or RWY23.

Adjacent sea area

When a vessel passes across beneath approach surface between approach lights and Tokyo West Passage Route, depending on height and position of the vessel, following restrictions are taken;


- a) Take-off clearance is not issued for RWY04 or RWY05.
- b) Go-around instruction may be issued for RWY22 or RWY23.

(断面図)

- 航空機の運航に影響がある高さの船舶：
側傍海域にあっては、N.H.H.W.L + 24.0m以上の船舶
東京西航路にあっては、N.H.H.W.L + 56.3m以上の船舶
- N.H.H.W.L：満潮時でこれより高くなないと想定される潮位

(profile view)

- The Vessel height which affects aircraft operations adjacent sea area:
Vessel height is at or above N.H.H.W.L + 24.0m
Tokyo West Passage Route:
Vessel height is at or above N.H.H.W.L + 56.3m
- N.H.H.W.L: Nearly Highest High Water Level




(断面図)


- 航空機の運航に影響がある高さの船舶：
側傍海域にあっては、N.H.H.W.L + 28.4m以上の船舶
東京西航路にあっては、N.H.H.W.L + 53.7m以上の船舶
- N.H.H.W.L：満潮時でこれより高くなないと想定される潮位

(profile view)

- The Vessel height which affects aircraft operations adjacent sea area:
Vessel height is at or above N.H.H.W.L + 28.4m
Tokyo West Passage Route:
Vessel height is at or above N.H.H.W.L + 53.7m
- N.H.H.W.L: Nearly Highest High Water Level



Tokyo West passage Route and Adjacent sea area



7. 航空機重量制限

滑走路 05/23 を使用する航空機においては、航空機重量、主脚荷重及び輪荷重の全てが下表の値を超えてはならない。

航空機重量		主脚荷重		輪荷重	
(lb)	(kg)	(lb/脚)	(kg/脚)	(lb/輪)	(kg/輪)
881,800	400,000	307,500	139,500	57,700	26,200

注) RJTT AD2.20.1.2 LOCAL TRAFFIC REGULATIONS (3), (12) 及び AD2.21.2 Noise Preferential Runways を参照

7. Aircraft weight restriction

When using RWY 05/23, all of the values of aircraft (aircraft weight, main gear load AND wheel load) shall not exceed the values listed in the table below.

Aircraft weight		Main gear load		Wheel load	
(lb)	(kg)	(lb/gear)	(kg/gear)	(lb/wheel)	(kg/wheel)
881,800	400,000	307,500	139,500	57,700	26,200

There are other restrictions for using runway(see RJTT AD2.20.1.2 LOCAL TRAFFIC REGULATIONS (3), (12) and RJTT AD2.21.2 Noise Preferential Runways.).

誘導路 Q を使用する航空機においては、コード Dまでの航空機（翼幅が 52m 未満）の使用に限ることとし、航空機重量、主脚荷重及び輪荷重の全てが下表の値を超えてはならない。

航空機重量		主脚荷重		輪荷重	
(lb)	(kg)	(lb/脚)	(kg/脚)	(lb/輪)	(kg/輪)
570,900	259,000	215,300	97,700	49,100	22,300

When passing TWY Q, the wing span of aircraft shall be less than 52m and all of the values of aircraft (aircraft weight, main gear load AND wheel load) shall not exceed the values listed in the table below.

Aircraft weight		Main gear load		Wheel load	
(lb)	(kg)	(lb/gear)	(kg/gear)	(lb/wheel)	(kg/wheel)
570,900	259,000	215,300	97,700	49,100	22,300

8. EMAS (Engineered Materials Arresting Systems)

EMAS, which has high energy-absorbing performance, is located in the overrun area and RESA of the runway. EMAS will exert deceleration force on the landing gear to reduce the damage in case of overrun of an airplane. EMAS is installed with overrun area marking. These systems do not affect the normal landing and takeoff of airplanes.

9. 双方向に設置されている ILS の輻射について

1) ILS 16L / 34R

LVP 適用時を除き、RWY16L および 34R ILS は同時に輻射する。
(RJTT AD2.22 8.Category II /III Operations at Tokyo International Airport を参照)

2) ILS 16R / 34L

RWY16R 運用時を除き、RWY16R および 34L ILS は同時に輻射する。

9. Two separate ILS radiate at opposite ends of a single runway

1) ILS 16L / 34R

RWY16L and 34R ILS radiate simultaneously except when LVP are applied.
(See RJTT AD2.22 8.Category II /III Operations at Tokyo International Airport)

2) ILS 16R / 34L

RWY16R and 34L ILS radiate simultaneously except when operating RWY16R.

RJTT AD 2.24 CHARTS RELATED TO AN AERODROME

Aerodrome Chart-1
Aerodrome Chart-2
Aircraft Parking/Docking Chart
Aerodrome Obstacle Chart-ICAO type A (RWY16R/34L)
Aerodrome Obstacle Chart-ICAO type A (RWY22)
Aerodrome Obstacle Chart-ICAO type A (RWY04)
Aerodrome Obstacle Chart-ICAO type A (RWY34R)
Aerodrome Obstacle Chart-ICAO type A (RWY16L)
Aerodrome Obstacle Chart-ICAO type A (RWY05/23)
Aerodrome Obstacle Chart-ICAO type B
Precision Approach Terrain Chart (RWY34R)
Standard Departure Chart - Instrument (SEKIYADO)
Standard Departure Chart - Instrument (VADAR)
Standard Departure Chart - Instrument (OPPAR)
Standard Departure Chart - Instrument (ISOGO)
Standard Departure Chart - Instrument (VAMOS-RNAV)
Standard Departure Chart - Instrument (LAXAS-RNAV)
Standard Departure Chart - Instrument (NINOX-RNAV)

Standard Departure Chart - Instrument (TIARA-A/B/C-RNAV)
Standard Departure Chart - Instrument (BEKLA-A/B/C-RNAV)
Standard Departure Chart - Instrument (ROVER-A/B/C-RNAV)
Standard Departure Chart - Instrument (RUTAS-RNAV)
Standard Departure Chart - Instrument (GUSRO-RNAV)


Standard Arrival Chart - Instrument (SINGO, DOYLE, ADDUM, BONUS)
Standard Arrival Chart - Instrument (OSHIMA-1A/1K/2C-RNAV)
Standard Arrival Chart - Instrument (AKSEL-1A/1K/2C-RNAV)
Standard Arrival Chart - Instrument (AROSA-1A/1K/2C-RNAV)
Standard Arrival Chart - Instrument (GODIN -2A/2K/1C-RNAV)
Standard Arrival Chart - Instrument (POLIX-2A/2K/1C-RNAV)
Standard Arrival Chart - Instrument (OSHIMA, AKSEL, AROSA-2H-RNAV)
Standard Arrival Chart - Instrument (GODIN, POLIX-1H-RNAV)
Standard Arrival Chart - Instrument (OSHIMA-1N/2N-RNAV)
Standard Arrival Chart - Instrument (OSHIMA-1B/2B-RNAV)
Standard Arrival Chart - Instrument (AKSEL-1N/2N-RNAV)
Standard Arrival Chart - Instrument (AKSEL-1B/2B-RNAV)
Standard Arrival Chart - Instrument (AROSA-1N/2N-RNAV)
Standard Arrival Chart - Instrument (AROSA-1B/2B-RNAV)
Standard Arrival Chart - Instrument (GODIN-1S/1D-RNAV)
Standard Arrival Chart - Instrument (POLIX-1S/1D-RNAV)
Standard Arrival Chart - Instrument (OSHIMA-L/R-RNAV)
Standard Arrival Chart - Instrument (AKSEL-L/R-RNAV)
Standard Arrival Chart - Instrument (AROSA-L/R-RNAV)
Standard Arrival Chart - Instrument (GODIN-L/R-RNAV)
Standard Arrival Chart - Instrument (POLIX-L/R-RNAV)
Standard Arrival Chart - Instrument (OSHIMA, AKSEL, AROSA, MESSE-NIGHT-RNAV)
Standard Arrival Chart - Instrument (OSHIMA, AKSEL, AROSA, MESSE-V-RNAV)

Instrument Approach Chart (ILS Z RWY34L)
Instrument Approach Chart (LOC Z RWY34L)
Instrument Approach Chart (ILS Y RWY34L)
Instrument Approach Chart (LOC Y RWY34L)
Instrument Approach Chart (ILS X RWY34L)
Instrument Approach Chart (LOC X RWY34L)
Instrument Approach Chart (VOR RWY34L)
Instrument Approach Chart (ILS Z RWY34R(CAT II & III))
Instrument Approach Chart (LOC Z RWY34R)
Instrument Approach Chart (ILS Y RWY34R(CAT II & III))
Instrument Approach Chart (LOC Y RWY34R)
Instrument Approach Chart (ILS RWY22)
Instrument Approach Chart (LOC RWY22)
Instrument Approach Chart (LDA Z RWY22)
Instrument Approach Chart (LDA Y RWY22)
Instrument Approach Chart (LDA X RWY22)
Instrument Approach Chart (LDA W RWY22)
Instrument Approach Chart (ILS Z RWY23)
Instrument Approach Chart (LOC Z RWY23)
Instrument Approach Chart (ILS Y or LOC Y RWY23)
Instrument Approach Chart (LDA Z RWY23)
Instrument Approach Chart (LDA Y RWY23)
Instrument Approach Chart (LDA X RWY23)

- Instrument Approach Chart (LDA W RWY23)
- Instrument Approach Chart (RNP RWY23 (AR))
- Instrument Approach Chart (ILS or LOC RWY16R)
- Instrument Approach Chart (RNP RWY16R)
- Instrument Approach Chart (ILS or LOC RWY16L)
- Instrument Approach Chart (RNP RWY16L)
- Instrument Approach Chart (VOR A)
- Other Chart (HIGHWAY VISUAL RWY34R)
- Other Chart (HOLDING PATTERN)
- Other Chart (HOLDING PATTERN-RNAV)
- Other Chart (Visual REP)
- Other Chart (MVA CHART)
- Other Chart (LDG CHART)
- Other Chart (Kawasaki Petrochemical Complex(ATTACHMENT-1))


AERODROME CHART

CHANGE: Spot24, Spot51, Spot52 abolished. Shape of APRON.





RJTT / TOKYO INTL

AD CHART



INTENTIONALLY LEFT BLANK






DIMENSIONS AND ELEVATIONS IN FEET BEARINGS ARE MAGNETIC Transverse Mercator Projection

AERODROME OBSTACLE CHART-ICA TYPE A (OPERATING LIMITATIONS)


MAGNETIC VARIATION 8°W - JUL 2022



CHANGE : Update.

DIMENSIONS AND ELEVATIONS IN FEET BEARINGS ARE MAGNETIC
Transverse Mercator Projection


AERODROME OBSTACLE CHART-ICAO
TYPE A (OPERATING LIMITATIONS)



CHANGE : Update.


DIMENSIONS AND ELEVATIONS IN FEET BEARINGS ARE MAGNETIC
Transverse Mercator Projection

AERODROME OBSTACLE CHART-ICAO
TYPE A (OPERATING LIMITATIONS)



DIMENSIONS AND ELEVATIONS IN FEET BEARINGS ARE MAGNETIC
Transverse Mercator Projection


AERODROME OBSTACLE CHART-ICAO
TYPE A (OPERATING LIMITATIONS)



CHANGE : Update.

DIMENSIONS AND ELEVATIONS IN FEET BEARINGS ARE MAGNETIC
Transverse Mercator Projection

AERODROME OBSTACLE CHART-ICAO
TYPE A (OPERATING LIMITATIONS)




DIMENSIONS AND ELEVATIONS IN FEET BEARINGS ARE MAGNETIC
Transverse Mercator Projection

AERODROME OBSTACLE CHART-ICAO
TYPE B



CHANGE : Obstruction added.

PRECISION APPROACH TERRAIN CHART



STANDARD DEPARTURE CHART-INSTRUMENT

RJTT / TOKYO INTL

SID


SEKIYADO THREE DEPARTURE

RWY04/34R/34L: Climb RWY HDG to 700FT, turn right HDG100° to HME 9.0DME, turn left HDG017° to intercept and proceed via SYE R167 to SYE VOR/DME.
Cross SYE VOR/DME between 12000FT and FL150.

RWY16R/16L: Climb RWY HDG to intercept and proceed via HME 11.8DME counterclockwise ARC to HME R065, turn right HDG017° to intercept and proceed via SYE R167 to SYE VOR/DME.
Cross HME R116 at or above 6000FT, cross SYE VOR/DME between 12000FT and FL150.

RWY05 : Climb on HDG059° to HME 10.0DME, turn left HDG017° to intercept and proceed via SYE R167 to SYE VOR/DME.
Cross SYE VOR/DME between 12000FT and FL150.

Note RWY34R/34L/04: 5.0% climb gradient required up to 700FT.
RWY05: 5.0% climb gradient required up to 500FT.



STANDARD DEPARTURE CHART-INSTRUMENT

RJTT / TOKYO INTL

SID

VADAR ONE DEPARTURE


RWY04/34R/34L: Climb RWY HDG to 700FT, turn right HDG100° to HME 9.0DME, turn right HDG222° to intercept and proceed via HME R177 to VADAR.
Cross HME R120 at or above 5000FT, cross VADAR at or above 9000FT.

RWY16R/16L: Climb RWY HDG to HME 7.0DME, turn right HDG207° to intercept and proceed via HME R177 to VADAR.
Cross VADAR at or above 9000FT.

RWY05: Climb RWY HDG to 1000FT, turn right HDG100° to HME 9.0DME, turn right HDG222° to intercept and proceed via HME R177 to VADAR.
Cross HME R120 at or above 5000FT, cross VADAR at or above 9000FT.

Note RWY04/34R/34L: 5.0% climb gradient required up to 700FT.

RWY05: 5.0% climb gradient required up to 1000FT.



STANDARD DEPARTURE CHART-INSTRUMENT

RJTT / TOKYO INTL

SID

OPPAR THREE DEPARTURE

RWY04/34R/34L: Climb RWY HDG to 700FT, turn right within 4NM, climb via HDG110° to HME 7.0DME, turn right, via HME 8.0DME clockwise ARC to intercept and proceed via HME R194 to OPPAR.

Cross HME 7.0DME at or above 3000FT, cross HME R120 at or above 5000FT, cross OPPAR at or above 9000FT.

RWY16R/16L: Climb RWY HDG to 500FT, turn left climb via HME R140 to 8.0DME, turn left HDG239° within HME 12.0DME to intercept and proceed via HME R194 to OPPAR.


Cross OPPAR at or above 9000FT.

RWY05: Climb RWY HDG to HME 5.0DME, turn right, via HME 8.0DME clockwise ARC to intercept and proceed via HME R194 to OPPAR.

Cross HME R120 at or above 5000FT, cross OPPAR at or above 9000FT.

Note Aircraft taking off from RWY16R/16L are required to complete left turns south of HME R080.

RWY34R/34L/04: 5.0% climb gradient required up to 700FT.




STANDARD DEPARTURE CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV TRANSITION

JYOGA TRANSITION UTIBO TRANSITION		RNAV1
Note 1) DME/DME/IRU or GNSS required.	Critical DME	-
2) RADAR service required.	DME GAP	-
	Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

VAR 7° W(2016)

JYOGA TRANSITION

From OPPAR at or above 9000FT, to JYOGA at or above FL150.

UTIBO TRANSITION

From OPPAR at or above 9000FT, to UTIBO at or above FL150.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV TRANSITION

JYOGA TRANSITION

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	OPPAR	—	—	-7.4	—	—	+9000	—	—	RNAV1
002	TF	JYOGA	—	224 (217.1)	-7.4	16.9	—	+FL150	—	—	RNAV1

UTIBO TRANSITION

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	OPPAR	—	—	-7.4	—	—	+9000	—	—	RNAV1
002	TF	UTIBO	—	170 (162.7)	-7.4	26.7	—	+FL150	—	—	RNAV1

INTENTIONALLY LEFT BLANK

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT / TOKYO INTL

SID

ISOGO TWO DEPARTURE (FOR PROP ONLY)


RWY04/34R/34L: Climb RWY HDG to 700FT or above, turn left within 4NM, climb via HME R177 to VADAR.

RWY16R/16L: Climb RWY HDG to HME 7.0DME, turn right HDG207° to intercept and proceed via HME R177 to VADAR.

RWY05: Climb RWY HDG to 1000FT, turn right HDG100° to HME 9.0DME, turn right HDG222° to intercept and proceed via HME R177 to VADAR.
Cross HME R120 at or above 5000FT.

Note RWY34R/34L/04: 5.0% climb gradient required up to 700FT.

RWY05: 5.0% climb gradient required up to 1000FT.



STANDARD DEPARTURE CHART-INSTRUMENT

RJTT / TOKYO INTL


TRANSITION

OSHIMA TRANSITION

From over VADAR, via HME R177 to intercept and proceed via XAC R058 to XAC VORTAC.

CHIKURA TRANSITION

From over VADAR, via HME R177 to UTIBO.



STANDARD DEPARTURE CHART-INSTRUMENT


RJTT/TOKYO INTL

RNAV SID

VAMOS THREE DEPARTURE		RNAV SID
Note 1) DME/DME/IRU or GNSS required. ※The aircraft equipped with only DME/DME/IRU must be able to update its position without delay at the starting point of take-off rolling. 2) RADAR service required.	Critical DME	RNAV1
DME GAP RWY16R:DER - 1.2NM FM DER RWY16L:DER - 1.0NM FM DER RWY34R:DER - 1.0NM FM DER RWY34L:DER - 0.5NM FM DER RWY04:DER - 1.7NM FM DER RWY22:DER - 1.4NM FM DER		RWY16R:HME 1.2NM FM DER - 1.9NM to T6R11 RWY16L:HME 1.0NM FM DER - 2.4NM to T6L21 RWY34R:HME 1.0NM FM DER - 2.5NM to TT502 RWY34L:HME 0.5NM FM DER - 2.5NM to TT502 RWY04:HME 1.7NM FM DER - 2.5NM to TT502 RWY05:HME DER - 2.7NM to TT502
Inappropriate Navaids See AD1.1.6.10.3.Inappropriate NAVAIDs for RNAV1		

VAR8°W(2020)

CHANGE : PROC renamed. VAR. HDG after DEP FM RWY04,22. Course FM TT502 to LOCUP.



STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

VAMOS THREE DEPARTURE

RWY16R : Climb on HDG 158° at or above 500FT, direct to T6R11, to VAMOS at or above 9000FT.

RWY16L : Climb on HDG 158° at or above 500FT, direct to T6L21, to VAMOS at or above 9000FT.

RWY34L/34R : Climb on HDG 338° at or above 700FT, turn right direct to TT502, to LOCUP at or above 5000FT, to VAMOS at or above 9000FT.

RWY04: Climb on HDG 043° at or above 700FT, turn right direct to TT502, to LOCUP at or above 5000FT, to VAMOS at or above 9000FT.

RWY05: Climb on HDG 050° at or above 500FT, direct to TT501, turn right direct to TT502, to LOCUP at or above 5000FT, to VAMOS at or above 9000FT.

RWY22: Climb on HDG 223° at or above 600FT, turn left direct to HOBBS, to BASSA, to VAMOS at or above 9000FT.

Note RWY34L/34R/04 : 5.0% climb gradient required up to 700FT.

RWY05 : 5.0% climb gradient required up to 500FT.

RWY22 : 5.0% climb gradient required up to 600FT.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

VAMOS THREE DEPARTURE

RWY16R

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	158 (150.0)	-7.6	—	—	+500	—	—	RNAV1
002	DF	T6R11	—	—	-7.6	—	—	—	—	—	RNAV1
003	TF	VAMOS	—	207 (199.5)	-7.6	14.5	—	+9000	—	—	RNAV1

RWY16L

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	158 (150.0)	-7.6	—	—	+500	—	—	RNAV1
002	DF	T6L21	—	—	-7.6	—	—	—	—	—	RNAV1
003	TF	VAMOS	—	208 (200.7)	-7.6	15.4	—	+9000	—	—	RNAV1

RWY34L/RWY34R

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	338 (330.0)	-7.6	—	—	+700	—	—	RNAV1
002	DF	TT502	—	—	-7.6	—	R	—	—	—	RNAV1
003	TF	LOCUP	—	199 (190.9)	-7.6	5.2	—	+5000	—	—	RNAV1
004	TF	VAMOS	—	217 (209.5)	-7.6	17.3	—	+9000	—	—	RNAV1

RWY04

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	043 (034.9)	-7.6	—	—	+700	—	—	RNAV1
002	DF	TT502	—	—	-7.6	—	R	—	—	—	RNAV1
003	TF	LOCUP	—	199 (190.9)	-7.6	5.2	—	+5000	—	—	RNAV1
004	TF	VAMOS	—	217 (209.5)	-7.6	17.3	—	+9000	—	—	RNAV1

CHANGE : PROC renamed. Magnetic Variation. RWY34L/RWY34R:NR003(Course), RWY04:NR001,003(Course).

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

RWY05

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M('T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	050 (042.4)	-7.6	—	—	+500	—	—	RNAV1
002	DF	TT501	Y	—	-7.6	—	—	—	—	—	RNAV1
003	DF	TT502	—	—	-7.6	—	R	—	—	—	RNAV1
004	TF	LOCUP	—	199 (190.9)	-7.6	5.2	—	+5000	—	—	RNAV1
005	TF	VAMOS	—	217 (209.5)	-7.6	17.3	—	+9000	—	—	RNAV1

RWY22

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M('T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	223 (214.9)	-7.6	—	—	+600	—	—	RNAV1
002	DF	HOBBS	—	—	-7.6	—	L	—	—	—	RNAV1
003	TF	BASSA	—	187 (179.9)	-7.6	5.8	—	—	—	—	RNAV1
004	TF	VAMOS	—	187 (179.9)	-7.6	8.9	—	+9000	—	—	RNAV1

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
BASSA	352108.8N / 1394542.2E	T6R11	352552.5N / 1395137.2E
HOBBS	352653.9N / 1394541.3E	TT501	353328.7N / 1395029.9E
LOCUP	352718.8N / 1395608.5E	TT502	353224.4N / 1395720.7E
T6L21	352639.1N / 1395222.0E	VAMOS	351215.5N / 1394543.6E

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL		RNAV TRANSITION			
TATEYAMA TRANSITION / DRAKY TRANSITION		RNAV1			
Note 1) DME/DME/IRU or GNSS required. 2) RADAR service required.	Critical DME	—			
DME GAP	—	—			
Inappropriate Navaids	See AD1.1.6.10.3.Inappropriate NAVAIDs for RNAV1	—			
VAR8°W(2019)					
<p>The chart shows a map of the Tokyo area with departure routes. The <u>DRAKY TRANSITION</u> route departs from OSHIMA (XAC) at 218° and 219°, leading to DRAKY. The <u>TATEYAMA TRANSITION</u> route departs from DRAKY at 222°, leading to TATEYAMA. From TATEYAMA, two routes lead to VAMOS (9000ft) and UTIBO. The RNAV1 route uses TACAN TATEYAMA (986, CH-25X, 500FT) and DME TATEYAMA (1159, CH-72X, 600FT). The VORTAC OSHIMA (113.1, CH-78X, 2100FT) is also indicated.</p> <table border="1"> <tr> <td>VORTAC OSHIMA 113.1 CH-78X 34°42'44"N/139°24'50"E 2100FT</td> <td>TACAN TATEYAMA 986 CH-25X 34°58'15"N/139°50'17"E 500FT</td> <td>DME TATEYAMA 1159 CH-72X 34°56'46"N/139°53'43"E 600FT</td> </tr> </table>			VORTAC OSHIMA 113.1 CH-78X 34°42'44"N/139°24'50"E 2100FT	TACAN TATEYAMA 986 CH-25X 34°58'15"N/139°50'17"E 500FT	DME TATEYAMA 1159 CH-72X 34°56'46"N/139°53'43"E 600FT
VORTAC OSHIMA 113.1 CH-78X 34°42'44"N/139°24'50"E 2100FT	TACAN TATEYAMA 986 CH-25X 34°58'15"N/139°50'17"E 500FT	DME TATEYAMA 1159 CH-72X 34°56'46"N/139°53'43"E 600FT			

CHANGE : New PROC

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV TRANSITION

TATEYAMA TRANSITION

From VAMOS at or above 9000FT, to UTIBO.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	VAMOS	–	–	-7.5	–	–	+9000	–	–	RNAV1
002	TF	UTIBO	–	165 (157.0)	-7.5	16.8	–	–	–	–	RNAV1

DRAKY TRANSITION

From VAMOS at or above 9000FT, to DRAKY, to XAC.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	VAMOS	–	–	-7.5	–	–	+9000	–	–	RNAV1
002	TF	DRAKY	–	218 (210.2)	-7.5	22.2	–	–	–	–	RNAV1
003	TF	XAC	–	218 (210.1)	-7.5	11.9	–	–	–	–	RNAV1

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
DRAKY	345301.7N / 1393205.5E	VAMOS	351215.5N / 1394543.6E
UTIBO	345647.0N / 1395343.9E	XAC	344244.1N / 1392450.5E

STANDARD DEPARTURE CHART-INSTRUMENT


RJTT/TOKYO INTL

RNAV SID

LAXAS THREE DEPARTURE		RNAV1
Note 1) DME/DME/IRU or GNSS required. ※The aircraft equipped with only DME/DME/IRU must be able to update its position without delay at the starting point of take-off rolling. 2) RADAR service required.	Critical DME	RWY16R: HME 1.2NM FM DER - 1.9NM to T6R11 HYD T6R11 - TAURA RWY16L: HME 1.0NM FM DER - 2.4NM to T6L21 HYD 9.0NM to TAURA - TAURA RWY34R: HME 1.0NM FM DER - 2.5NM to TT502 HYD 8.6NM to TAURA - TAURA RWY34L: HME 0.5NM FM DER - 2.5NM to TT502 HYD 8.6NM to TAURA - TAURA RWY04: HME 1.7NM FM DER - 2.5NM to TT502 HYD 8.6NM to TAURA - TAURA RWY05: HME DER - 2.7NM to TT502 HYD 8.6NM to TAURA - TAURA
DME GAP		RWY16R:DER - 1.2NM FM DER RWY16L:DER - 1.0NM FM DER RWY34R:DER - 1.0NM FM DER RWY34L:DER - 0.5NM FM DER RWY04:DER - 1.7NM FM DER RWY05:DER - 1.4NM FM DER
Inappropriate Navaids		See AD1.1.6.10.3.Inappropriate NAVAIDs for RNAV1

VAR8°W(2020)

CHANGE : PROC renamed. VAR. HDG after DEP FM RWY04,22. Course FM TT502 to LOCUP. Course FM BASSA to UMUKI.



STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

LAXAS THREE DEPARTURE

RWY16R : Climb on HDG 158° at or above 500FT, direct to T6R11, to TAURA at or above 9000FT, to IMOLA at or above FL150, to LAXAS at or above FL170.

RWY16L : Climb on HDG 158° at or above 500FT, direct to T6L21, to TAURA at or above 9000FT, to IMOLA at or above FL150, to LAXAS at or above FL170.

RWY34L/34R : Climb on HDG 338° at or above 700FT, turn right direct to TT502, to LOCUP at or above 5000FT, to TAURA at or above 9000FT, to IMOLA at or above FL150, to LAXAS at or above FL170.

RWY04 : Climb on HDG 043° at or above 700FT, turn right direct to TT502, to LOCUP at or above 5000FT, to TAURA at or above 9000FT, to IMOLA at or above FL150, to LAXAS at or above FL170.

RWY05 : Climb on HDG 050° at or above 500FT, direct to TT501, turn right direct to TT502, to LOCUP at or above 5000FT, to TAURA at or above 9000FT, to IMOLA at or above FL150, to LAXAS at or above FL170.

RWY22 : Climb on HDG 223° at or above 600FT, turn left direct to HOBBS, to BASSA, to UMUKI, to PIPER at or above 9000FT, to SATOL, to IMOLA at or above FL150, to LAXAS at or above FL170.

Note RWY34L/34R/04 : 5.0% climb gradient required up to 700FT.

RWY05 : 5.0% climb gradient required up to 500FT.

RWY22 : 5.0% climb gradient required up to 600FT.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

LAXAS THREE DEPARTURE

RWY16R

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	158 (150.0)	-7.6	—	—	+500	—	—	RNAV1
002	DF	T6R11	—	—	-7.6	—	—	—	—	—	RNAV1
003	TF	TAURA	—	226 (218.1)	-7.6	9.0	—	+9000	—	—	RNAV1
004	TF	IMOLA	—	228 (220.5)	-7.6	18.8	—	+FL150	—	—	RNAV1
005	TF	LAXAS	—	266 (258.6)	-7.6	12.8	—	+FL170	—	—	RNAV1

RWY16L

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	158 (150.0)	-7.6	—	—	+500	—	—	RNAV1
002	DF	T6L21	—	—	-7.6	—	—	—	—	—	RNAV1
003	TF	TAURA	—	226 (218.1)	-7.6	10.0	—	+9000	—	—	RNAV1
004	TF	IMOLA	—	228 (220.5)	-7.6	18.8	—	+FL150	—	—	RNAV1
005	TF	LAXAS	—	266 (258.6)	-7.6	12.8	—	+FL170	—	—	RNAV1

CHANGE : PROC renamed. Magnetic Variation. RWY34L/RWY34R.NR003(Course).

RWY34L/RWY34R

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	338 (330.0)	-7.6	—	—	+700	—	—	RNAV1
002	DF	TT502	—	—	-7.6	—	R	—	—	—	RNAV1
003	TF	LOCUP	—	199 (190.9)	-7.6	5.2	—	+5000	—	—	RNAV1
004	TF	TAURA	—	235 (227.3)	-7.6	12.6	—	+9000	—	—	RNAV1
005	TF	IMOLA	—	228 (220.5)	-7.6	18.8	—	+FL150	—	—	RNAV1
006	TF	LAXAS	—	266 (258.6)	-7.6	12.8	—	+FL170	—	—	RNAV1

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

RWY04

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	043 (034.9)	-7.6	—	—	+700	—	—	RNAV1
002	DF	TT502	—	—	-7.6	—	R	—	—	—	RNAV1
003	TF	LOCUP	—	199 (190.9)	-7.6	5.2	—	+5000	—	—	RNAV1
004	TF	TAURA	—	235 (227.3)	-7.6	12.6	—	+9000	—	—	RNAV1
005	TF	IMOLA	—	228 (220.5)	-7.6	18.8	—	+FL150	—	—	RNAV1
006	TF	LAXAS	—	266 (258.6)	-7.6	12.8	—	+FL170	—	—	RNAV1

RWY05

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	050 (042.4)	-7.6	—	—	+500	—	—	RNAV1
002	DF	TT501	Y	—	-7.6	—	—	—	—	—	RNAV1
003	DF	TT502	—	—	-7.6	—	R	—	—	—	RNAV1
004	TF	LOCUP	—	199 (190.9)	-7.6	5.2	—	+5000	—	—	RNAV1
005	TF	TAURA	—	235 (227.3)	-7.6	12.6	—	+9000	—	—	RNAV1
006	TF	IMOLA	—	228 (220.5)	-7.6	18.8	—	+FL150	—	—	RNAV1
007	TF	LAXAS	—	266 (258.6)	-7.6	12.8	—	+FL170	—	—	RNAV1

CHANGE : Magnetic Variation. RWY04:NR001,003(Course). RWY05:NR004(Course).

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

RWY22

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	223 (214.9)	-7.6	—	—	+600	—	—	RNAV1
002	DF	HOBBS	—	—	-7.6	—	L	—	—	—	RNAV1
003	TF	BASSA	—	187 (179.9)	-7.6	5.8	—	—	—	—	RNAV1
004	TF	UMUKI	—	172 (163.9)	-7.6	9.2	—	—	—	—	RNAV1
005	TF	PIPER	—	235 (227.4)	-7.6	3.5	—	+9000	—	—	RNAV1
006	TF	SATOL	—	235 (227.4)	-7.6	5.5	—	—	—	—	RNAV1
007	TF	IMOLA	—	266 (258.7)	-7.6	9.1	—	+FL150	—	—	RNAV1
008	TF	LAXAS	—	266 (258.6)	-7.6	12.8	—	+FL170	—	—	RNAV1

CHANGE : Magnetic Variation. RWY22:NR001,004(Course).

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
BASSA	352108.8N / 1394542.2E	T6L21	352639.1N / 1395222.0E
HOBBS	352653.9N / 1394541.3E	T6R11	352552.5N / 1395137.2E
IMOLA	350426.0N / 1392951.0E	TAURA	351846.1N / 1394447.3E
LAXAS	350153.1N / 1391432.8E	TT501	353328.7N / 1395029.9E
LOCUP	352718.8N / 1395608.5E	TT502	353224.4N / 1395720.7E
PIPER	350958.3N / 1394542.0E	UMUKI	351219.1N / 1394849.2E
SATOL	350613.3N / 1394043.4E		

STANDARD DEPARTURE CHART-INSTRUMENT

CHANGE : PROC renamed. VAR, HDG after DEP FM RWY04/22. Course FM TT502 to LOCUP. Course FM TT631 to BAYGE. Course FM BASSA to UMUKI.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

NINOX THREE DEPARTURE

RWY16R : Climb on HDG 158° at or above 500FT, direct to T6R12, to TT631, to BAYGE at or above 9000FT, to SEIKO at or above 13000FT, to NINOX at or above FL170.

RWY16L : Climb on HDG 158° at or above 500FT, direct to T6L22, to TT631, to BAYGE at or above 9000FT, to SEIKO at or above 13000FT, to NINOX at or above FL170.

RWY34L/34R : Climb on HDG 338° at or above 700FT, turn right direct to TT502, to LOCUP at or above 5000FT, to BAYGE at or above 9000FT, to SEIKO at or above 13000FT, to NINOX at or above FL170.

RWY04 : Climb on HDG 043° at or above 700FT, turn right direct to TT502, to LOCUP at or above 5000FT, to BAYGE at or above 9000FT, to SEIKO at or above 13000FT, to NINOX at or above FL170.

RWY05 : Climb on HDG 050° at or above 500FT, direct to TT501, turn right direct to TT502, to LOCUP at or above 5000FT, to BAYGE at or above 9000FT, to SEIKO at or above 13000FT, to NINOX at or above FL170.

RWY22 : Climb on HDG 223° at or above 600FT, turn left direct to HOBBS, to BASSA, to UMUKI, to PIPER at or above 9000FT, to SATOL, to CURVA at or above FL150, to NINOX at or above FL170.

Note RWY34L/34R/04 : 5.0% climb gradient required up to 700FT.

RWY05 : 5.0% climb gradient required up to 500FT.

RWY22 : 5.0% climb gradient required up to 600FT.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

NINOX THREE DEPARTURE

RWY16R

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	158 (150.0)	-7.6	—	—	+500	—	—	RNAV1
002	DF	T6R12	—	—	-7.6	—	—	—	—	—	RNAV1
003	TF	TT631	—	247 (239.8)	-7.6	5.6	—	—	—	—	RNAV1
004	TF	BAYGE	—	335 (327.0)	-7.6	5.0	—	+9000	—	—	RNAV1
005	TF	SEIKO	—	295 (287.8)	-7.6	11.4	—	+13000	—	—	RNAV1
006	TF	NINOX	—	281 (272.9)	-7.6	16.5	—	+FL170	—	—	RNAV1

RWY16L

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	158 (150.0)	-7.6	—	—	+500	—	—	RNAV1
002	DF	T6L22	—	—	-7.6	—	—	—	—	—	RNAV1
003	TF	TT631	—	247 (239.8)	-7.6	6.6	—	—	—	—	RNAV1
004	TF	BAYGE	—	335 (327.0)	-7.6	5.0	—	+9000	—	—	RNAV1
005	TF	SEIKO	—	295 (287.8)	-7.6	11.4	—	+13000	—	—	RNAV1
006	TF	NINOX	—	281 (272.9)	-7.6	16.5	—	+FL170	—	—	RNAV1

RWY34L/RWY34R

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	338 (330.0)	-7.6	—	—	+700	—	—	RNAV1
002	DF	TT502	—	—	-7.6	—	R	—	—	—	RNAV1
003	TF	LOCUP	—	199 (190.9)	-7.6	5.2	—	+5000	—	—	RNAV1
004	TF	BAYGE	—	268 (260.6)	-7.6	10.5	—	+9000	—	—	RNAV1
005	TF	SEIKO	—	295 (287.8)	-7.6	11.4	—	+13000	—	—	RNAV1
006	TF	NINOX	—	281 (272.9)	-7.6	16.5	—	+FL170	—	—	RNAV1

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

RWY04

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	043 (034.9)	-7.6	—	—	+700	—	—	RNAV1
002	DF	TT502	—	—	-7.6	—	R	—	—	—	RNAV1
003	TF	LOCUP	—	199 (190.9)	-7.6	5.2	—	+5000	—	—	RNAV1
004	TF	BAYGE	—	268 (260.6)	-7.6	10.5	—	+9000	—	—	RNAV1
005	TF	SEIKO	—	295 (287.8)	-7.6	11.4	—	+13000	—	—	RNAV1
006	TF	NINOX	—	281 (272.9)	-7.6	16.5	—	+FL170	—	—	RNAV1

RWY05

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	050 (042.4)	-7.6	—	—	+500	—	—	RNAV1
002	DF	TT501	Y	—	-7.6	—	—	—	—	—	RNAV1
003	DF	TT502	—	—	-7.6	—	R	—	—	—	RNAV1
004	TF	LOCUP	—	199 (190.9)	-7.6	5.2	—	+5000	—	—	RNAV1
005	TF	BAYGE	—	268 (260.6)	-7.6	10.5	—	+9000	—	—	RNAV1
006	TF	SEIKO	—	295 (287.8)	-7.6	11.4	—	+13000	—	—	RNAV1
007	TF	NINOX	—	281 (272.9)	-7.6	16.5	—	+FL170	—	—	RNAV1

CHANGE : Magnetic Variation. RWY04:NR001,003,006(Course). RWY05:NR004,007(Course).

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

RWY22

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M('T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	223 (214.9)	-7.6	—	—	+600	—	—	RNAV1
002	DF	HOBBS	—	—	-7.6	—	L	—	—	—	RNAV1
003	TF	BASSA	—	187 (179.9)	-7.6	5.8	—	—	—	—	RNAV1
004	TF	UMUKI	—	172 (163.9)	-7.6	9.2	—	—	—	—	RNAV1
005	TF	PIPER	—	235 (227.4)	-7.6	3.5	—	+9000	—	—	RNAV1
006	TF	SATOL	—	235 (227.4)	-7.6	5.5	—	—	—	—	RNAV1
007	TF	CURVA	—	300 (292.2)	-7.6	8.2	—	+FL150	—	—	RNAV1
008	TF	NINOX	—	327 (319.6)	-7.6	27.1	—	+FL170	—	—	RNAV1

CHANGE : Magnetic Variation. RWY22:NR001,004(Course).

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
BASSA	352108.8N / 1394542.2E	SEIKO	352904.5N / 1393005.0E
BAYGE	352535.4N / 1394327.4E	T6L22	352441.2N / 1395345.4E
CURVA	350919.0N / 1393124.4E	T6R12	352413.6N / 1395247.1E
HOBBS	352653.9N / 1394541.3E	TT501	353328.7N / 1395029.9E
LOCUP	352718.8N / 1395608.5E	TT502	353224.4N / 1395720.7E
NINOX	352953.4N / 1390953.1E	TT631	352123.4N / 1394648.6E
PIPER	350958.3N / 1394542.0E	UMUKI	351219.1N / 1394849.2E
SATOL	350613.3N / 1394043.4E		

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL


RNAV SID

TIARA ONE A DEPARTURE		RNAV SID
Note 1) DME/DME/IRU or GNSS required. ※The aircraft equipped with only DME/DME/IRU must be able to update its position without delay at the starting point of take-off rolling. 2) RADAR service required.		RNAV1
DME GAP	RNAV1 RWY16R : DER - 1.2NM FM DER RWY16L : DER - 1.0NM FM DER RWY34R : DER - 1.0NM FM DER RWY34L : DER - 0.5NM FM DER RWY04 : DER - 1.7NM FM DER RWY05 : 3.8NM to KAMAT - 1.8NM to KAMAT	Critical DME RWY16R : HME 1.2NM FM DER - HATBA HYD 2.8NM to HATBA - 1.6NM to HATBA PQD HATBA - 1.6NM to KAMAT RWY16L : HME 1.0NM FM DER - 3.5NM to T6L23 PQD 6.6NM to KAIJI - KAIJI NRE 6.9NM to INTEL - 6.9NM to LAYER RWY34R : HME 1.0NM FM DER - 1.1NM to PLUTO SND TORAM - 3.1NM to PLUTO PQD 6.6NM to KAIJI - KAIJI NRE 6.9NM to INTEL - 6.9NM to LAYER RWY34L : HME 0.5NM FM DER - 1.1NM to PLUTO SND TORAM - 3.1NM to PLUTO PQD 6.6NM to KAIJI - KAIJI NRE 6.9NM to INTEL - 6.9NM to LAYER RWY04 : HME 1.7NM FM DER - 1.1NM to PLUTO SND 2.2NM to TORAM - 3.1NM to PLUTO PQD 6.6NM to KAIJI - KAIJI NRE 6.9NM to INTEL - 6.9NM to LAYER RWY05 : HME DER - 2.7NM to TT502 TT503 - 3.8NM to KAMAT 1.8NM to KAMAT - KAMAT HYD 1.2NM to TT503 - TT503 4.8NM to KAMAT - 3.8NM to KAMAT
Inappropriate Navaids	See AD1.1.6.10.3.Inappropriate NAVAIDs for RNAV1	

VAR8°W

TIARA ONE A DEPARTURE RWY16R/16L

CHANGE : New PROC.




STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

VAR8°W

TIARA ONE A DEPARTURE RWY 34L/34R/04/05



CHANGE : New PROC.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

TIARA ONE A DEPARTURE

RWY16R : Climb on HDG 158° at or above 500FT, direct to T6R13, to HATBA, to KAMAT at or above 9000FT, to LAYER at or above 13000FT, to TIARA, to GUSRO at or above FL170.

RWY16L : Climb on HDG 158° at or above 500FT, turn left direct to T6L23, to WELDA at or above 6000FT, to PLUTO, to KAIJI, to INTEL at or above 9000FT, to LAYER at or above 13000FT, to TIARA, to GUSRO at or above FL170.

RWY34L/34R : Climb on HDG 338° at or above 700FT, turn right direct to TORAM, to PLUTO, to KAIJI, to INTEL at or above 9000FT, to LAYER at or above 13000FT, to TIARA, to GUSRO at or above FL170.

RWY04 : Climb on HDG 043° at or above 700FT, direct to TORAM, to PLUTO, to KAIJI, to INTEL at or above 9000FT, to LAYER at or above 13000FT, to TIARA, to GUSRO at or above FL170.

RWY05 : Climb on HDG 050° at or above 500FT, direct to TT501, turn right direct to TT502, to LOCUP at or above 5000FT, to TT503, to KAMAT at or above 9000FT, to LAYER at or above 13000FT, to TIARA, to GUSRO at or above FL170.

Note RWY34L/34R/04 : 5.0% climb gradient required up to 700FT.

RWY05 : 5.0% climb gradient required up to 500FT.

CHANGE : New PROC.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

TIARA ONE A DEPARTURE

RWY16R

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	158 (150.0)	-7.6	—	—	+500	—	—	RNAV1
002	DF	T6R13	—	—	-7.6	—	—	—	—	—	RNAV1
003	TF	HATBA	—	261 (253.8)	-7.6	5.8	—	—	—	—	RNAV1
004	TF	KAMAT	—	359 (351.1)	-7.6	7.6	—	+9000	—	—	RNAV1
005	TF	LAYER	—	305 (297.1)	-7.6	12.2	—	+13000	—	—	RNAV1
006	TF	TIARA	—	279 (271.2)	-7.6	7.0	—	—	—	—	RNAV1
007	TF	GUSRO	—	279 (271.1)	-7.6	9.5	—	+FL170	—	—	RNAV1

RWY16L

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	158 (150.0)	-7.6	—	—	+500	—	—	RNAV1
002	DF	T6L23	—	—	-7.6	—	L	—	—	—	RNAV1
003	TF	WELDA	—	055 (047.3)	-7.6	4.8	—	+6000	—	—	RNAV1
004	TF	PLUTO	—	352 (344.5)	-7.6	7.1	—	—	—	—	RNAV1
005	TF	KAIJI	—	011 (003.0)	-7.6	7.6	—	—	—	—	RNAV1
006	TF	INTEL	—	286 (278.4)	-7.6	11.9	—	+9000	—	—	RNAV1
007	TF	LAYER	—	250 (242.4)	-7.6	13.9	—	+13000	—	—	RNAV1
008	TF	TIARA	—	279 (271.2)	-7.6	7.0	—	—	—	—	RNAV1
009	TF	GUSRO	—	279 (271.1)	-7.6	9.5	—	+FL170	—	—	RNAV1

RWY34L/RWY34R

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	338 (330.0)	-7.6	—	—	+700	—	—	RNAV1
002	DF	TORAM	—	—	-7.6	—	R	—	—	—	RNAV1
003	TF	PLUTO	—	098 (090.7)	-7.6	6.0	—	—	—	—	RNAV1
004	TF	KAIJI	—	011 (003.0)	-7.6	7.6	—	—	—	—	RNAV1
005	TF	INTEL	—	286 (278.4)	-7.6	11.9	—	+9000	—	—	RNAV1
006	TF	LAYER	—	250 (242.4)	-7.6	13.9	—	+13000	—	—	RNAV1
007	TF	TIARA	—	279 (271.2)	-7.6	7.0	—	—	—	—	RNAV1
008	TF	GUSRO	—	279 (271.1)	-7.6	9.5	—	+FL170	—	—	RNAV1

CHANGE : New PROC.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

RWY04

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	043 (034.9)	-7.6	—	—	+700	—	—	RNAV1
002	DF	TORAM	—	—	-7.6	—	—	—	—	—	RNAV1
003	TF	PLUTO	—	098 (090.7)	-7.6	6.0	—	—	—	—	RNAV1
004	TF	KAIJI	—	011 (003.0)	-7.6	7.6	—	—	—	—	RNAV1
005	TF	INTEL	—	286 (278.4)	-7.6	11.9	—	+9000	—	—	RNAV1
006	TF	LAYER	—	250 (242.4)	-7.6	13.9	—	+13000	—	—	RNAV1
007	TF	TIARA	—	279 (271.2)	-7.6	7.0	—	—	—	—	RNAV1
008	TF	GUSRO	—	279 (271.1)	-7.6	9.5	—	+FL170	—	—	RNAV1

RWY05

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	050 (042.4)	-7.6	—	—	+500	—	—	RNAV1
002	DF	TT501	Y	—	-7.6	—	—	—	—	—	RNAV1
003	DF	TT502	—	—	-7.6	—	R	—	—	—	RNAV1
004	TF	LOCUP	—	199 (190.9)	-7.6	5.2	—	+5000	—	—	RNAV1
005	TF	TT503	—	288 (280.8)	-7.6	6.2	—	—	—	—	RNAV1
006	TF	KAMAT	—	322 (314.2)	-7.6	7.8	—	+9000	—	—	RNAV1
007	TF	LAYER	—	305 (297.1)	-7.6	12.2	—	+13000	—	—	RNAV1
008	TF	TIARA	—	279 (271.2)	-7.6	7.0	—	—	—	—	RNAV1
009	TF	GUSRO	—	279 (271.1)	-7.6	9.5	—	+FL170	—	—	RNAV1

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
GUSRO	353944.8N / 1390813.1E	T6L23	352627.6N / 1395539.1E
HATBA	352623.4N / 1394315.9E	T6R13	352800.8N / 1395006.4E
INTEL	354553.0N / 1394340.2E	TIARA	353934.0N / 1391954.2E
KAIJI	354409.6N / 1395806.6E	TORAM	353636.8N / 1395011.0E
KAMAT	353353.6N / 1394148.9E	TT501	353328.7N / 1395029.9E
LAYER	353925.4N / 1392829.5E	TT502	353224.4N / 1395720.7E
LOCUP	352718.8N / 1395608.5E	TT503	352828.0N / 1394840.4E
PLUTO	353632.1N / 1395736.8E	WELDA	352941.4N / 1395956.7E

CHANGE : New PROC.

STANDARD DEPARTURE CHART-INSTRUMENT


RJTT/TOKYO INTL

RNAV SID

TIARA ONE B DEPARTURE		RNAV1
Note 1) DME/DME/IRU or GNSS required. ※The aircraft equipped with only DME/DME/IRU must be able to update its position without delay at the starting point of take-off rolling. 2) RADAR service required.		
DME GAP	RWY16R : DER - 1.2NM FM DER RWY16L : DER - 1.0NM FM DER RWY34R : DER - 1.0NM FM DER RWY05 : 3.8NM to KAMAT - 1.8NM to KAMAT	Critical DME
Inappropriate Navaids	See AD1.1.6.10.3.Inappropriate NAVAIDs for RNAV1	

VAR8°W

TIARA ONE B DEPARTURE RWY16R/16L




STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

VAR8°W

TIARA ONE B DEPARTURE RWY 34R/05



CHANGE : New PROC.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

TIARA ONE B DEPARTURE

RWY16R : Climb on HDG 158° at or above 500FT, direct to T6R13, to HATBA, to KAMAT at or above 9000FT, to LAYER at or above 13000FT, to TIARA, to GUSRO at or above FL170.

RWY16L : Climb on HDG 158° at or above 500FT, turn left direct to T6L23, to WELDA at or above 6000FT, to PLUTO, to KAIJI, to INTEL at or above 9000FT, to LAYER at or above 13000FT, to TIARA, to GUSRO at or above FL170.

RWY34R : Climb on HDG 338° at or above 700FT, turn right direct to ARAKA, to EDOJO, to OHEDO, to INTEL at or above 9000FT, to LAYER at or above 13000FT, to TIARA, to GUSRO at or above FL170.

RWY05 : Climb on HDG 050° at or above 500FT, direct to TT501, turn right direct to TT502, to LOCUP at or above 5000FT, to TT503, to KAMAT at or above 9000FT, to LAYER at or above 13000FT, to TIARA, to GUSRO at or above FL170.

Note RWY34R : 5.0% climb gradient required up to 700FT.

RWY05 : 5.0% climb gradient required up to 500FT.

CHANGE : New PROC.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

TIARA ONE B DEPARTURE

RWY16R

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	158 (150.0)	-7.6	–	–	+500	–	–	RNAV1
002	DF	T6R13	–	–	-7.6	–	–	–	–	–	RNAV1
003	TF	HATBA	–	261 (253.8)	-7.6	5.8	–	–	–	–	RNAV1
004	TF	KAMAT	–	359 (351.1)	-7.6	7.6	–	+9000	–	–	RNAV1
005	TF	LAYER	–	305 (297.1)	-7.6	12.2	–	+13000	–	–	RNAV1
006	TF	TIARA	–	279 (271.2)	-7.6	7.0	–	–	–	–	RNAV1
007	TF	GUSRO	–	279 (271.1)	-7.6	9.5	–	+FL170	–	–	RNAV1

RWY16L

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	158 (150.0)	-7.6	–	–	+500	–	–	RNAV1
002	DF	T6L23	–	–	-7.6	–	L	–	–	–	RNAV1
003	TF	WELDA	–	055 (047.3)	-7.6	4.8	–	+6000	–	–	RNAV1
004	TF	PLUTO	–	352 (344.5)	-7.6	7.1	–	–	–	–	RNAV1
005	TF	KAIJI	–	011 (003.0)	-7.6	7.6	–	–	–	–	RNAV1
006	TF	INTEL	–	286 (278.4)	-7.6	11.9	–	+9000	–	–	RNAV1
007	TF	LAYER	–	250 (242.4)	-7.6	13.9	–	+13000	–	–	RNAV1
008	TF	TIARA	–	279 (271.2)	-7.6	7.0	–	–	–	–	RNAV1
009	TF	GUSRO	–	279 (271.1)	-7.6	9.5	–	+FL170	–	–	RNAV1

RWY34R

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	338 (330.0)	-7.6	–	–	+700	–	–	RNAV1
002	DF	ARAKA	–	–	-7.6	–	R	–	–	–	RNAV1
003	TF	EDOJO	–	018 (010.8)	-7.6	3.5	–	–	–	–	RNAV1
004	TF	OHEDO	–	331 (323.7)	-7.6	3.9	–	–	–	–	RNAV1
005	TF	INTEL	–	285 (277.0)	-7.6	4.1	–	+9000	–	–	RNAV1
006	TF	LAYER	–	250 (242.4)	-7.6	13.9	–	+13000	–	–	RNAV1
007	TF	TIARA	–	279 (271.2)	-7.6	7.0	–	–	–	–	RNAV1
008	TF	GUSRO	–	279 (271.1)	-7.6	9.5	–	+FL170	–	–	RNAV1

CHANGE : New PROC.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

RWY05

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	050 (042.4)	-7.6	—	—	+500	—	—	RNAV1
002	DF	TT501	Y	—	-7.6	—	—	—	—	—	RNAV1
003	DF	TT502	—	—	-7.6	—	R	—	—	—	RNAV1
004	TF	LOCUP	—	199 (190.9)	-7.6	5.2	—	+5000	—	—	RNAV1
005	TF	TT503	—	288 (280.8)	-7.6	6.2	—	—	—	—	RNAV1
006	TF	KAMAT	—	322 (314.2)	-7.6	7.8	—	+9000	—	—	RNAV1
007	TF	LAYER	—	305 (297.1)	-7.6	12.2	—	+13000	—	—	RNAV1
008	TF	TIARA	—	279 (271.2)	-7.6	7.0	—	—	—	—	RNAV1
009	TF	GUSRO	—	279 (271.1)	-7.6	9.5	—	+FL170	—	—	RNAV1

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
ARAKA	353848.8N / 1395041.9E	OHEDO	354523.4N / 1394838.6E
EDOJO	354214.0N / 1395129.9E	PLUTO	353632.1N / 1395736.8E
GUSRO	353944.8N / 1390813.1E	T6L23	352627.6N / 1395539.1E
HATBA	352623.4N / 1394315.9E	T6R13	352800.8N / 1395006.4E
INTEL	354553.0N / 1394340.2E	TIARA	353934.0N / 1391954.2E
KAIJI	354409.6N / 1395806.6E	TT501	353328.7N / 1395029.9E
KAMAT	353353.6N / 1394148.9E	TT502	353224.4N / 1395720.7E
LAYER	353925.4N / 1392829.5E	TT503	352828.0N / 1394840.4E
LOCUP	352718.8N / 1395608.5E	WELDA	352941.4N / 1395956.7E

CHANGE : New PROC.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

TIARA ONE C DEPARTURE

RNAV1

Note 1) DME/DME/IRU or GNSS required.

※The aircraft equipped with only DME/DME/IRU must be able to update its position without delay at the starting point of take-off rolling.

2) RADAR service required.

DME GAP

RWY16R : DER - 1.2NM FM DER
RWY16L : DER - 1.0NM FM DER
RWY34R : DER - 1.0NM FM DER
RWY05 : 3.8NM to KAMAT - 1.8NM to KAMAT

Critical DME

RWY16R : HME 1.2NM FM DER - 1.9NM to T6R11
PQD 6.6NM to KAIJI - KAIJI

NRE 6.9NM to INTEL - 6.9NM to LAYER
RWY16L : HME 1.0NM FM DER - 3.5NM to T6L23
PQD 6.6NM to KAIJI - KAIJI

NRE 6.9NM to INTEL - 6.9NM to LAYER
RWY05 : HME DER - 2.7NM to TT502

TT503 - 3.8NM to KAMAT

1.8NM to KAMAT - KAMAT

HYD 1.2NM to TT503 - TT503


4.8NM to KAMAT - 3.8NM to KAMAT

Inappropriate Navaids

See AD1.1.6.10.3.Inappropriate NAVAIDs for RNAV1

VAR8°W

TIARA ONE C DEPARTURE RWY16R/16L




STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

VAR8°W

TIARA ONE C DEPARTURE RWY 34R/05



CHANGE : Mew PROC.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

TIARA ONE C DEPARTURE

RWY16R : Climb on HDG 158° at or above 500FT, direct to T6R11, to WELDA at or above 6000FT, to PLUTO, to KAIJI, to INTEL at or above 9000FT, to LAYER at or above 13000FT, to TIARA, to GUSRO at or above FL170.

RWY16L : Climb on HDG 158° at or above 500FT, turn left direct to T6L23, to WELDA at or above 6000FT, to PLUTO, to KAIJI, to INTEL at or above 9000FT, to LAYER at or above 13000FT, to TIARA, to GUSRO at or above FL170.

RWY34R : Climb on HDG 338° at or above 700FT, turn right direct to ARAKA, to EDOJO, to OHEDO, to INTEL at or above 9000FT, to LAYER at or above 13000FT, to TIARA, to GUSRO at or above FL170.

RWY05 : Climb on HDG 050° at or above 500FT, direct to TT501, turn right direct to TT502, to LOCUP at or above 5000FT, to TT503, to KAMAT at or above 9000FT, to LAYER at or above 13000FT, to TIARA, to GUSRO at or above FL170.

Note RWY34R : 5.0% climb gradient required up to 700FT.

RWY05 : 5.0% climb gradient required up to 500FT.

CHANGE : New PROC.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

TIARA ONE C DEPARTURE

RWY16R

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	158 (150.0)	-7.6	—	—	+500	—	—	RNAV1
002	DF	T6R11	—	—	-7.6	—	—	—	—	—	RNAV1
003	TF	WELDA	—	068 (060.6)	-7.6	7.8	—	+6000	—	—	RNAV1
004	TF	PLUTO	—	352 (344.5)	-7.6	7.1	—	—	—	—	RNAV1
005	TF	KAIJI	—	011 (003.0)	-7.6	7.6	—	—	—	—	RNAV1
006	TF	INTEL	—	286 (278.4)	-7.6	11.9	—	+9000	—	—	RNAV1
007	TF	LAYER	—	250 (242.4)	-7.6	13.9	—	+13000	—	—	RNAV1
008	TF	TIARA	—	279 (271.2)	-7.6	7.0	—	—	—	—	RNAV1
009	TF	GUSRO	—	279 (271.1)	-7.6	9.5	—	+FL170	—	—	RNAV1

RWY16L

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	158 (150.0)	-7.6	—	—	+500	—	—	RNAV1
002	DF	T6L23	—	—	-7.6	—	L	—	—	—	RNAV1
003	TF	WELDA	—	055 (047.3)	-7.6	4.8	—	+6000	—	—	RNAV1
004	TF	PLUTO	—	352 (344.5)	-7.6	7.1	—	—	—	—	RNAV1
005	TF	KAIJI	—	011 (003.0)	-7.6	7.6	—	—	—	—	RNAV1
006	TF	INTEL	—	286 (278.4)	-7.6	11.9	—	+9000	—	—	RNAV1
007	TF	LAYER	—	250 (242.4)	-7.6	13.9	—	+13000	—	—	RNAV1
008	TF	TIARA	—	279 (271.2)	-7.6	7.0	—	—	—	—	RNAV1
009	TF	GUSRO	—	279 (271.1)	-7.6	9.5	—	+FL170	—	—	RNAV1

RWY34R

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	338 (330.0)	-7.6	—	—	+700	—	—	RNAV1
002	DF	ARAKA	—	—	-7.6	—	R	—	—	—	RNAV1
003	TF	EDOJO	—	018 (010.8)	-7.6	3.5	—	—	—	—	RNAV1
004	TF	OHEDO	—	331 (323.7)	-7.6	3.9	—	—	—	—	RNAV1
005	TF	INTEL	—	285 (277.0)	-7.6	4.1	—	+9000	—	—	RNAV1
006	TF	LAYER	—	250 (242.4)	-7.6	13.9	—	+13000	—	—	RNAV1
007	TF	TIARA	—	279 (271.2)	-7.6	7.0	—	—	—	—	RNAV1
008	TF	GUSRO	—	279 (271.1)	-7.6	9.5	—	+FL170	—	—	RNAV1

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

RWY05											
Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	050 (042.4)	-7.6	-	-	+500	-	-	RNAV1
002	DF	TT501	Y	-	-7.6	-	-	-	-	-	RNAV1
003	DF	TT502	-	-	-7.6	-	R	-	-	-	RNAV1
004	TF	LOCUP	-	199 (190.9)	-7.6	5.2	-	+5000	-	-	RNAV1
005	TF	TT503	-	288 (280.8)	-7.6	6.2	-	-	-	-	RNAV1
006	TF	KAMAT	-	322 (314.2)	-7.6	7.8	-	+9000	-	-	RNAV1
007	TF	LAYER	-	305 (297.1)	-7.6	12.2	-	+13000	-	-	RNAV1
008	TF	TIARA	-	279 (271.2)	-7.6	7.0	-	-	-	-	RNAV1
009	TF	GUSRO	-	279 (271.1)	-7.6	9.5	-	+FL170	-	-	RNAV1

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
ARAKA	353848.8N / 1395041.9E	PLUTO	353632.1N / 1395736.8E
EDOJO	354214.0N / 1395129.9E	T6L23	352627.6N / 1395539.1E
GUSRO	353944.8N / 1390813.1E	T6R11	352552.5N / 1395137.2E
INTEL	354553.0N / 1394340.2E	TIARA	353934.0N / 1391954.2E
KAIJI	354409.6N / 1395806.6E	TT501	353328.7N / 1395029.9E
KAMAT	353353.6N / 1394148.9E	TT502	353224.4N / 1395720.7E
LAYER	353925.4N / 1392829.5E	TT503	352828.0N / 1394840.4E
LOCUP	352718.8N / 1395608.5E	WELDA	352941.4N / 1395956.7E
OHEDO	354523.4N / 1394838.6E		

CHANGE : New PROC.

STANDARD DEPARTURE CHART-INSTRUMENT


RJTT/TOKYO INTL

RNAV SID

BEKLA TWO A DEPARTURE		RNAV SID
Note 1) DME/DME/IRU or GNSS required. ※The aircraft equipped with only DME/DME/IRU must be able to update its position without delay at the starting point of take-off rolling. 2) RADAR service required.		RNAV1
DME GAP	RWY16R : DER - 1.2NM FM DER RWY16L : DER - 1.0NM FM DER RWY34R : DER - 1.0NM FM DER RWY34L : DER - 0.5NM FM DER RWY04 : DER - 1.7NM FM DER RWY05 : 3.8NM to KAMAT - 1.8NM to KAMAT	Critical DME
Inappropriate Navaids	See AD1.1.6.10.3.Inappropriate NAVAIDs for RNAV1	RWY16R : HME 1.2NM FM DER - HATBA HYD 2.8NM to HATBA - 1.6NM to HATBA PQD HATBA - 1.6NM to KAMAT RWY16L : HME 1.0NM FM DER - 3.5NM to T6L23 PQD 6.6NM to KAIJI - KAIJI NRE 6.9NM to INTEL - INTEL RWY34R : HME 1.0NM FM DER - 1.1NM to PLUTO SND TORAM - 3.1NM to PLUTO PQD 6.6NM to KAIJI - KAIJI NRE 6.9NM to INTEL - INTEL RWY34L : HME 0.5NM FM DER - 1.1NM to PLUTO SND TORAM - 3.1NM to PLUTO PQD 6.6NM to KAIJI - KAIJI NRE 6.9NM to INTEL - INTEL RWY04 : HME 1.7NM FM DER - 1.1NM to PLUTO SND 2.2NM to TORAM - 3.1NM to PLUTO PQD 6.6NM to KAIJI - KAIJI NRE 6.9NM to INTEL - INTEL RWY05 : HME DER - 2.7NM to TT502 TT503 - 3.8NM to KAMAT 1.8NM to KAMAT - KAMAT HYD 1.2NM to TT503 - TT503 4.8NM to KAMAT - 3.8NM to KAMAT

VAR8°W(2020)

CHANGE : PROC renamed. VAR. RTE after KAMAT.



STANDARD DEPARTURE CHART-INSTRUMENT


RJTT/TOKYO INTL

RNAV SID

VAR8°W(2020)

BEKLA TWO A DEPARTURE RWY34L/34R/04/05

CHANGE : PROC renamed. VAR. RTE after KAMAT. Course FM TT502 to LOCUP. HDG after DEP FM RWY04.



STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

BEKLA TWO A DEPARTURE

RWY16R : Climb on HDG 158° at or above 500FT, direct to T6R13, to HATBA, to KAMAT at or above 9000FT, to LAYER at or above 13000FT, to BEKLA at or above FL170.

RWY16L : Climb on HDG 158° at or above 500FT, turn left direct to T6L23, to WELDA at or above 6000FT, to PLUTO, to KAIJI, to INTEL at or above 9000FT, to RAGOS at or above 13000FT, to BEKLA at or above FL170.

RWY34L/34R : Climb on HDG 338° at or above 700FT, turn right direct to TORAM, to PLUTO, to KAIJI, to INTEL at or above 9000FT, to RAGOS at or above 13000FT, to BEKLA at or above FL170.

RWY04 : Climb on HDG 043° at or above 700FT, direct to TORAM, to PLUTO, to KAIJI, to INTEL at or above 9000FT, to RAGOS at or above 13000FT, to BEKLA at or above FL170.

RWY05 : Climb on HDG 050° at or above 500FT, direct to TT501, turn right direct to TT502, to LOCUP at or above 5000FT, to TT503, to KAMAT at or above 9000FT, to LAYER at or above 13000FT, to BEKLA at or above FL170.

Note RWY34L/34R/04 : 5.0% climb gradient required up to 700FT.

RWY05 : 5.0% climb gradient required up to 500FT.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

BEKLA TWO A DEPARTURE

RWY16R

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	158 (150.0)	-7.6	—	—	+500	—	—	RNAV1
002	DF	T6R13	—	—	-7.6	—	—	—	—	—	RNAV1
003	TF	HATBA	—	261 (253.8)	-7.6	5.8	—	—	—	—	RNAV1
004	TF	KAMAT	—	359 (351.1)	-7.6	7.6	—	+9000	—	—	RNAV1
005	TF	LAYER	—	305 (297.1)	-7.6	12.2	—	+13000	—	—	RNAV1
006	TF	BEKLA	—	313 (305.4)	-7.6	18.3	—	+FL170	—	—	RNAV1

RWY16L

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	158 (150.0)	-7.6	—	—	+500	—	—	RNAV1
002	DF	T6L23	—	—	-7.6	—	L	—	—	—	RNAV1
003	TF	WELDA	—	055 (047.3)	-7.6	4.8	—	+6000	—	—	RNAV1
004	TF	PLUTO	—	352 (344.5)	-7.6	7.1	—	—	—	—	RNAV1
005	TF	KAIJI	—	011 (003.0)	-7.6	7.6	—	—	—	—	RNAV1
006	TF	INTEL	—	286 (278.4)	-7.6	11.9	—	+9000	—	—	RNAV1
007	TF	RAGOS	—	295 (287.2)	-7.6	13.0	—	+13000	—	—	RNAV1
008	TF	BEKLA	—	279 (271.2)	-7.6	14.8	—	+FL170	—	—	RNAV1

RWY34L/RWY34R

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	338 (330.0)	-7.6	—	—	+700	—	—	RNAV1
002	DF	TORAM	—	—	-7.6	—	R	—	—	—	RNAV1
003	TF	PLUTO	—	098 (090.7)	-7.6	6.0	—	—	—	—	RNAV1
004	TF	KAIJI	—	011 (003.0)	-7.6	7.6	—	—	—	—	RNAV1
005	TF	INTEL	—	286 (278.4)	-7.6	11.9	—	+9000	—	—	RNAV1
006	TF	RAGOS	—	295 (287.2)	-7.6	13.0	—	+13000	—	—	RNAV1
007	TF	BEKLA	—	279 (271.2)	-7.6	14.8	—	+FL170	—	—	RNAV1

CHANGE : PROC renamed. Magnetic Variation. RWY16R; RTE after KAMAT.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

RWY04											
Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	043 (034.9)	-7.6	—	—	+700	—	—	RNAV1
002	DF	TORAM	—	—	-7.6	—	—	—	—	—	RNAV1
003	TF	PLUTO	—	098 (090.7)	-7.6	6.0	—	—	—	—	RNAV1
004	TF	KAIJI	—	011 (003.0)	-7.6	7.6	—	—	—	—	RNAV1
005	TF	INTEL	—	286 (278.4)	-7.6	11.9	—	+9000	—	—	RNAV1
006	TF	RAGOS	—	295 (287.2)	-7.6	13.0	—	+13000	—	—	RNAV1
007	TF	BEKLA	—	279 (271.2)	-7.6	14.8	—	+FL170	—	—	RNAV1

RWY05											
Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	050 (042.4)	-7.6	—	—	+500	—	—	RNAV1
002	DF	TT501	Y	—	-7.6	—	—	—	—	—	RNAV1
003	DF	TT502	—	—	-7.6	—	R	—	—	—	RNAV1
004	TF	LOCUP	—	199 (190.9)	-7.6	5.2	—	+5000	—	—	RNAV1
005	TF	TT503	—	288 (280.8)	-7.6	6.2	—	—	—	—	RNAV1
006	TF	KAMAT	—	322 (314.2)	-7.6	7.8	—	+9000	—	—	RNAV1
007	TF	LAYER	—	305 (297.1)	-7.6	12.2	—	+13000	—	—	RNAV1
008	TF	BEKLA	—	313 (305.4)	-7.6	18.3	—	+FL170	—	—	RNAV1

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
BEKLA	354958.7N / 1391009.5E	RAGOS	354942.2N / 1392821.2E
HATBA	352623.4N / 1394315.9E	T6L23	352627.6N / 1395539.1E
INTEL	354553.0N / 1394340.2E	T6R13	352800.8N / 1395006.4E
KAIJI	354409.6N / 1395806.6E	TORAM	353636.8N / 1395011.0E
KAMAT	353353.6N / 1394148.9E	TT501	353328.7N / 1395029.9E
LAYER	353925.4N / 1392829.5E	TT502	353224.4N / 1395720.7E
LOCUP	352718.8N / 1395608.5E	TT503	352828.0N / 1394840.4E
PLUTO	353632.1N / 1395736.8E	WELDA	352941.4N / 1395956.7E

CHANGE : Magnetic Variation. RWY04:NR004(Course), RWY05:NR004(Course), RTE after KAMAT. Waypoint Coordinates(LAYER added).

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

BEKLA TWO B DEPARTURE

RNAV1

Note 1) DME/DME/IRU or GNSS required.

※The aircraft equipped with only DME/DME/IRU must be able to update its position without delay at the starting point of take-off rolling.

2) RADAR service required.

DME GAP

RWY16R : DER - 1.2NM FM DER
RWY16L : DER - 1.0NM FM DER
RWY34R : DER - 1.0NM FM DER
RWY05 : 3.8NM to KAMAT - 1.8NM to KAMAT

Critical DME

RWY16R : HME 1.2NM FM DER - HATBA
HYD 2.8NM to HATBA - 1.6NM to HATBA
PQD HATBA - 1.6NM to KAMAT
RWY16L : HME 1.0NM FM DER - 3.5NM to T6L23
PQD 6.6NM to KAIJI - KAIJI
NRE 6.9NM to INTEL - INTEL
RWY05 : HME DER - 2.7NM to TT502
TT503 - 3.8NM to KAMAT
1.8NM to KAMAT - KAMAT
HYD 1.2NM to TT503 - TT503
4.8NM to KAMAT - 3.8NM to KAMAT

Inappropriate Navaids

See AD1.1.6.10.3.Inappropriate NAVAIDs for RNAV1

VAR8°W(2020)

BEKLA
FL170


RAGOS
13000

BEKLA TWO B DEPARTURE

RWY16R/16L

VOR/DME
HANEDA
112.2 HME
CH-59X :::
35°33'44"N/139°45'40"E
100FT

CHANGE : PROC renamed. VAR. RTE after KAMAT.




STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

VAR8°W(2020)

BEKLA TWO B DEPARTURE RWY34R/05

CHANGE : PROC renamed. VAR RTE after KAMAT. Course FM TT502 to LOCUP.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

BEKLA TWO B DEPARTURE

RWY16R : Climb on HDG 158° at or above 500FT, direct to T6R13, to HATBA, to KAMAT at or above 9000FT, to LAYER at or above 13000FT, to BEKLA at or above FL170.

RWY16L : Climb on HDG 158° at or above 500FT, turn left direct to T6L23, to WELDA at or above 6000FT, to PLUTO, to KAIJI, to INTEL at or above 9000FT, to RAGOS at or above 13000FT, to BEKLA at or above FL170.

RWY34R : Climb on HDG 338° at or above 700FT, turn right direct to ARAKA, to EDOJO, to OHEDO, to INTEL at or above 9000FT, to RAGOS at or above 13000FT, to BEKLA at or above FL170.

RWY05 : Climb on HDG 050° at or above 500FT, direct to TT501, turn right direct to TT502, to LOCUP at or above 5000FT, to TT503, to KAMAT at or above 9000FT, to LAYER at or above 13000FT, to BEKLA at or above FL170.

Note RWY34R : 5.0% climb gradient required up to 700FT.

RWY05 : 5.0% climb gradient required up to 500FT.

CHANGE : PROC renamed. RTE after KAMAT (RWY16R,05).

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

BEKLA TWO B DEPARTURE

RWY16R

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	158 (150.0)	-7.6	—	—	+500	—	—	RNAV1
002	DF	T6R13	—	—	-7.6	—	—	—	—	—	RNAV1
003	TF	HATBA	—	261 (253.8)	-7.6	5.8	—	—	—	—	RNAV1
004	TF	KAMAT	—	359 (351.1)	-7.6	7.6	—	+9000	—	—	RNAV1
005	TF	LAYER	—	305 (297.1)	-7.6	12.2	—	+13000	—	—	RNAV1
006	TF	BEKLA	—	313 (305.4)	-7.6	18.3	—	+FL170	—	—	RNAV1

RWY16L

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	158 (150.0)	-7.6	—	—	+500	—	—	RNAV1
002	DF	T6L23	—	—	-7.6	—	L	—	—	—	RNAV1
003	TF	WELDA	—	055 (047.3)	-7.6	4.8	—	+6000	—	—	RNAV1
004	TF	PLUTO	—	352 (344.5)	-7.6	7.1	—	—	—	—	RNAV1
005	TF	KAIJI	—	011 (003.0)	-7.6	7.6	—	—	—	—	RNAV1
006	TF	INTEL	—	286 (278.4)	-7.6	11.9	—	+9000	—	—	RNAV1
007	TF	RAGOS	—	295 (287.2)	-7.6	13.0	—	+13000	—	—	RNAV1
008	TF	BEKLA	—	279 (271.2)	-7.6	14.8	—	+FL170	—	—	RNAV1

RWY34R

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	338 (330.0)	-7.6	—	—	+700	—	—	RNAV1
002	DF	ARAKA	—	—	-7.6	—	R	—	—	—	RNAV1
003	TF	EDOJO	—	018 (010.8)	-7.6	3.5	—	—	—	—	RNAV1
004	TF	OHEDO	—	331 (323.7)	-7.6	3.9	—	—	—	—	RNAV1
005	TF	INTEL	—	285 (277.0)	-7.6	4.1	—	+9000	—	—	RNAV1
006	TF	RAGOS	—	295 (287.2)	-7.6	13.0	—	+13000	—	—	RNAV1
007	TF	BEKLA	—	279 (271.2)	-7.6	14.8	—	+FL170	—	—	RNAV1

CHANGE : PROC renamed. Magnetic Variation. RWY16R,RTE after KAMAT.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

RWY05

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	050 (042.4)	-7.6	—	—	+500	—	—	RNAV1
002	DF	TT501	Y	—	-7.6	—	—	—	—	—	RNAV1
003	DF	TT502	—	—	-7.6	—	R	—	—	—	RNAV1
004	TF	LOCUP	—	199 (190.9)	-7.6	5.2	—	+5000	—	—	RNAV1
005	TF	TT503	—	288 (280.8)	-7.6	6.2	—	—	—	—	RNAV1
006	TF	KAMAT	—	322 (314.2)	-7.6	7.8	—	+9000	—	—	RNAV1
007	TF	LAYER	—	305 (297.1)	-7.6	12.2	—	+13000	—	—	RNAV1
008	TF	BEKLA	—	313 (305.4)	-7.6	18.3	—	+FL170	—	—	RNAV1

CHANGE : Magnetic Variation. RWY05:NR004(Course), RTE after KAMAT. Waypoint Coordinates(LAYER added).

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
ARAKA	353848.8N / 1395041.9E	OHEDO	354523.4N / 1394838.6E
BEKLA	354958.7N / 1391009.5E	PLUTO	353632.1N / 1395736.8E
EDOJO	354214.0N / 1395129.9E	RAGOS	354942.2N / 1392821.2E
HATBA	352623.4N / 1394315.9E	T6L23	352627.6N / 1395539.1E
INTEL	354553.0N / 1394340.2E	T6R13	352800.8N / 1395006.4E
KAIJI	354409.6N / 1395806.6E	TT501	353328.7N / 1395029.9E
KAMAT	353353.6N / 1394148.9E	TT502	353224.4N / 1395720.7E
LAYER	353925.4N / 1392829.5E	TT503	352828.0N / 1394840.4E
LOCUP	352718.8N / 1395608.5E	WELDA	352941.4N / 1395956.7E

STANDARD DEPARTURE CHART-INSTRUMENT


RJTT/TOKYO INTL

RNAV SID

BEKLA TWO C DEPARTURE		RNAV1
Note 1) DME/DME/IRU or GNSS required. ※The aircraft equipped with only DME/DME/IRU must be able to update its position without delay at the starting point of take-off rolling. 2) RADAR service required.		
DME GAP	RWY16R : DER - 1.2NM FM DER RWY16L : DER - 1.0NM FM DER RWY34R : DER - 1.0NM FM DER RWY05 : 3.8NM to KAMAT - 1.8NM to KAMAT	Critical DME
Inappropriate Navaids	See AD1.1.6.10.3.Inappropriate NAVAIDs for RNAV1	

VAR8°W(2020)

CHANGE : PROC renamed. VAR.




STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

VAR8°W(2020)

BEKLA TWO C DEPARTURE RWY34R/05



STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

BEKLA TWO C DEPARTURE

RWY16R : Climb on HDG 158° at or above 500FT, direct to T6R11, to WELDA at or above 6000FT, to PLUTO, to KAIJI, to INTEL at or above 9000FT, to RAGOS at or above 13000FT, to BEKLA at or above FL170.

RWY16L : Climb on HDG 158° at or above 500FT, turn left direct to T6L23, to WELDA at or above 6000FT, to PLUTO, to KAIJI, to INTEL at or above 9000FT, to RAGOS at or above 13000FT, to BEKLA at or above FL170.

RWY34R : Climb on HDG 338° at or above 700FT, turn right direct to ARAKA, to EDOJO, to OHEDO, to INTEL at or above 9000FT, to RAGOS at or above 13000FT, to BEKLA at or above FL170.

RWY05 : Climb on HDG 050° at or above 500FT, direct to TT501, turn right direct to TT502, to LOCUP at or above 5000FT, to TT503, to KAMAT at or above 9000FT, to LAYER at or above 13000FT, to BEKLA at or above FL170.

Note RWY34R : 5.0% climb gradient required up to 700FT.

RWY05 : 5.0% climb gradient required up to 500FT.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

BEKLA TWO C DEPARTURE

RWY16R

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	158 (150.0)	-7.6	–	–	+500	–	–	RNAV1
002	DF	T6R11	–	–	-7.6	–	–	–	–	–	RNAV1
003	TF	WELDA	–	068 (060.6)	-7.6	7.8	–	+6000	–	–	RNAV1
004	TF	PLUTO	–	352 (344.5)	-7.6	7.1	–	–	–	–	RNAV1
005	TF	KAIJI	–	011 (003.0)	-7.6	7.6	–	–	–	–	RNAV1
006	TF	INTEL	–	286 (278.4)	-7.6	11.9	–	+9000	–	–	RNAV1
007	TF	RAGOS	–	295 (287.2)	-7.6	13.0	–	+13000	–	–	RNAV1
008	TF	BEKLA	–	279 (271.2)	-7.6	14.8	–	+FL170	–	–	RNAV1

RWY16L

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	158 (150.0)	-7.6	–	–	+500	–	–	RNAV1
002	DF	T6L23	–	–	-7.6	–	L	–	–	–	RNAV1
003	TF	WELDA	–	055 (047.3)	-7.6	4.8	–	+6000	–	–	RNAV1
004	TF	PLUTO	–	352 (344.5)	-7.6	7.1	–	–	–	–	RNAV1
005	TF	KAIJI	–	011 (003.0)	-7.6	7.6	–	–	–	–	RNAV1
006	TF	INTEL	–	286 (278.4)	-7.6	11.9	–	+9000	–	–	RNAV1
007	TF	RAGOS	–	295 (287.2)	-7.6	13.0	–	+13000	–	–	RNAV1
008	TF	BEKLA	–	279 (271.2)	-7.6	14.8	–	+FL170	–	–	RNAV1

RWY34R

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	338 (330.0)	-7.6	–	–	+700	–	–	RNAV1
002	DF	ARAKA	–	–	-7.6	–	R	–	–	–	RNAV1
003	TF	EDOJO	–	018 (010.8)	-7.6	3.5	–	–	–	–	RNAV1
004	TF	OHEDO	–	331 (323.7)	-7.6	3.9	–	–	–	–	RNAV1
005	TF	INTEL	–	285 (277.0)	-7.6	4.1	–	+9000	–	–	RNAV1
006	TF	RAGOS	–	295 (287.2)	-7.6	13.0	–	+13000	–	–	RNAV1
007	TF	BEKLA	–	279 (271.2)	-7.6	14.8	–	+FL170	–	–	RNAV1

CHANGE : PROC renamed. Magnetic Variation.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

RWY05

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	050 (042.4)	-7.6	-	-	+500	-	-	RNAV1
002	DF	TT501	Y	-	-7.6	-	-	-	-	-	RNAV1
003	DF	TT502	-	-	-7.6	-	R	-	-	-	RNAV1
004	TF	LOCUP	-	199 (190.9)	-7.6	5.2	-	+5000	-	-	RNAV1
005	TF	TT503	-	288 (280.8)	-7.6	6.2	-	-	-	-	RNAV1
006	TF	KAMAT	-	322 (314.2)	-7.6	7.8	-	+9000	-	-	RNAV1
007	TF	LAYER	-	305 (297.1)	-7.6	12.2	-	+13000	-	-	RNAV1
008	TF	BEKLA	-	313 (305.4)	-7.6	18.3	-	+FL170	-	-	RNAV1

CHANGE : Magnetic Variation. RWY05:NR004(Course), RTE after KAMAT. Waypoint Coordinates(LAYER added).

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
ARAKA	353848.8N / 1395041.9E	PLUTO	353632.1N / 1395736.8E
BEKLA	354958.7N / 1391009.5E	RAGOS	354942.2N / 1392821.2E
EDOJO	354214.0N / 1395129.9E	T6L23	352627.6N / 1395539.1E
INTEL	354553.0N / 1394340.2E	T6R11	352552.5N / 1395137.2E
KAIJI	354409.6N / 1395806.6E	TT501	353328.7N / 1395029.9E
KAMAT	353353.6N / 1394148.9E	TT502	353224.4N / 1395720.7E
LAYER	353925.4N / 1392829.5E	TT503	352828.0N / 1394840.4E
LOCUP	352718.8N / 1395608.5E	WELDA	352941.4N / 1395956.7E
OHEDO	354523.4N / 1394838.6E		

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL


RNAV SID

ROVER TWO A DEPARTURE		RNAV1
Note 1) DME/DME/IRU or GNSS required. ※The aircraft equipped with only DME/DME/IRU must be able to update its position without delay at the starting point of take-off rolling. 2) RADAR service required.		
DME GAP	RWY16R: DER - 1.2NM FM DER RWY16L: DER - 1.0NM FM DER RWY34R: DER - 1.0NM FM DER RWY34L: DER - 0.5NM FM DER RWY04: DER - 1.7NM FM DER	Critical DME
Inappropriate Navaids	See AD1.1.6.10.3.Inappropriate NAVAIDs for RNAV1	RWY16R : HME 1.2NM FM DER - 1.9NM to T6R11 PQD 6.6NM to KAIJI - KAIJI RWY16L : HME 1.0NM FM DER - 3.5NM to T6L23 PQD 6.6NM to KAIJI - KAIJI RWY34R : HME 1.0NM FM DER - 1.1NM to PLUTO SND TORAM - 3.1NM to PLUTO PQD 6.6NM to KAIJI - KAIJI RWY34L : HME 0.5NM FM DER - 1.1NM to PLUTO SND TORAM - 3.1NM to PLUTO PQD 6.6NM to KAIJI - KAIJI RWY04 : HME 1.7NM FM DER - 1.1NM to PLUTO SND 2.2NM to TORAM - 3.1NM to PLUTO PQD 6.6NM to KAIJI - KAIJI RWY05 : HME DER - 2.2NM to PLUTO PQD 6.6NM to KAIJI - KAIJI

VAR8°W(2020)

ROVER TWO A DEPARTURE

CHANGE : PROC renamed. VAR. HDG after DEP FM RWY04.



STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

ROVER TWO A DEPARTURE

RWY16R : Climb on HDG 158° at or above 500FT, direct to T6R11,
to WELDA at or above 6000FT, to PLUTO, to KAIJI,
to SPOON at or below FL150, to ROVER at or above 12000FT.

RWY16L : Climb on HDG 158° at or above 500FT, turn left direct to T6L23,
to WELDA at or above 6000FT, to PLUTO, to KAIJI,
to SPOON at or below FL150, to ROVER at or above 12000FT.

RWY34L/34R : Climb on HDG 338° at or above 700FT, turn right direct to
TORAM, to PLUTO, to KAIJI, to SPOON at or below FL150,
to ROVER at or above 12000FT.

RWY04 : Climb on HDG 043° at or above 700FT, direct to TORAM, to PLUTO,
to KAIJI, to SPOON at or below FL150, to ROVER at or above
12000FT.

RWY05 :Climb on HDG 050° at or above 500FT, turn right direct to PLUTO,
to KAIJI, to SPOON at or below FL150, to ROVER at or above
12000FT.

Note RWY34L/34R/04 : 5.0% climb gradient required up to 700FT.

RWY05 : 5.0% climb gradient required up to 500FT.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

ROVER TWO A DEPARTURE

RWY16R

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	158 (150.0)	-7.6	–	–	+500	–	–	RNAV1
002	DF	T6R11	–	–	-7.6	–	–	–	–	–	RNAV1
003	TF	WELDA	–	068 (060.6)	-7.6	7.8	–	+6000	–	–	RNAV1
004	TF	PLUTO	–	352 (344.5)	-7.6	7.1	–	–	–	–	RNAV1
005	TF	KAIJI	–	011 (003.0)	-7.6	7.6	–	–	–	–	RNAV1
006	TF	SPOON	–	347 (339.2)	-7.6	11.0	–	-FL150	–	–	RNAV1
007	TF	ROVER	–	347 (339.1)	-7.6	5.2	–	+12000	–	–	RNAV1

RWY16L

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	158 (150.0)	-7.6	–	–	+500	–	–	RNAV1
002	DF	T6L23	–	–	-7.6	–	L	–	–	–	RNAV1
003	TF	WELDA	–	055 (047.3)	-7.6	4.8	–	+6000	–	–	RNAV1
004	TF	PLUTO	–	352 (344.5)	-7.6	7.1	–	–	–	–	RNAV1
005	TF	KAIJI	–	011 (003.0)	-7.6	7.6	–	–	–	–	RNAV1
006	TF	SPOON	–	347 (339.2)	-7.6	11.0	–	-FL150	–	–	RNAV1
007	TF	ROVER	–	347 (339.1)	-7.6	5.2	–	+12000	–	–	RNAV1

RWY34L/RWY34R

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	338 (330.0)	-7.6	–	–	+700	–	–	RNAV1
002	DF	TORAM	–	–	-7.6	–	R	–	–	–	RNAV1
003	TF	PLUTO	–	098 (090.7)	-7.6	6.0	–	–	–	–	RNAV1
004	TF	KAIJI	–	011 (003.0)	-7.6	7.6	–	–	–	–	RNAV1
005	TF	SPOON	–	347 (339.2)	-7.6	11.0	–	-FL150	–	–	RNAV1
006	TF	ROVER	–	347 (339.1)	-7.6	5.2	–	+12000	–	–	RNAV1

CHANGE : PROC renamed. Magnetic Variation.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

RWY04

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	043 (034.9)	-7.6	—	—	+700	—	—	RNAV1
002	DF	TORAM	—	—	-7.6	—	—	—	—	—	RNAV1
003	TF	PLUTO	—	098 (090.7)	-7.6	6.0	—	—	—	—	RNAV1
004	TF	KAIJI	—	011 (003.0)	-7.6	7.6	—	—	—	—	RNAV1
005	TF	SPOON	—	347 (339.2)	-7.6	11.0	—	-FL150	—	—	RNAV1
006	TF	ROVER	—	347 (339.1)	-7.6	5.2	—	+12000	—	—	RNAV1

RWY05

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	050 (042.4)	-7.6	—	—	+500	—	—	RNAV1
002	DF	PLUTO	—	—	-7.6	—	R	—	—	—	RNAV1
003	TF	KAIJI	—	011 (003.0)	-7.6	7.6	—	—	—	—	RNAV1
004	TF	SPOON	—	347 (339.2)	-7.6	11.0	—	-FL150	—	—	RNAV1
005	TF	ROVER	—	347 (339.1)	-7.6	5.2	—	+12000	—	—	RNAV1

CHANGE : Magnetic Variation. RWY04:NRW01(Course).

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
KAIJI	354409.6N / 1395806.6E	T6L23	352627.6N / 1395539.1E
PLUTO	353632.1N / 1395736.8E	T6R11	352552.5N / 1395137.2E
ROVER	355918.3N / 1395059.3E	TORAM	353636.8N / 1395011.0E
SPOON	355428.3N / 1395316.0E	WELDA	352941.4N / 1395956.7E

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL


RNAV SID

ROVER TWO B DEPARTURE			RNAV1
<p>Note 1) DME/DME/IRU or GNSS required. ※The aircraft equipped with only DME/DME/IRU must be able to update its position without delay at the starting point of take-off rolling.</p> <p>2) RADAR service required.</p>			
DME GAP	RWY16R: DER - 1.2NM FM DER RWY16L: DER - 1.0NM FM DER RWY34R: DER - 1.0NM FM DER	Critical DME	<p>RWY16R : HME 1.2NM FM DER - 1.9NM to T6R11 PQD 6.6NM to KAIJI - KAIJI</p> <p>RWY16L : HME 1.0NM FM DER - 3.5NM to T6L23 PQD 6.6NM to KAIJI - KAIJI</p> <p>RWY05 : HME DER - 2.2NM to PLUTO PQD 6.6NM to KAIJI - KAIJI</p>
Inappropriate Navaids	See AD1.1.6.10.3.Inappropriate NAVAIDs for RNAV1		

VAR8°W(2020)

ROVER TWO B DEPARTURE

CHANGE : PROC renamed.



STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

ROVER TWO B DEPARTURE

RWY16R : Climb on HDG 158° at or above 500FT, direct to T6R11, to WELDA at or above 6000FT, to PLUTO, to KAIJI, to SPOON at or below FL150, to ROVER at or above 12000FT.

RWY16L : Climb on HDG 158° at or above 500FT, turn left direct to T6L23, to WELDA at or above 6000FT, to PLUTO, to KAIJI, to SPOON at or below FL150, to ROVER at or above 12000FT.

RWY34R : Climb on HDG 338° at or above 700FT, turn right direct to ARAKA, to EDOJO, to OHEDO, to SPOON at or below FL150, to ROVER at or above 12000FT.

RWY05 :Climb on HDG 050° at or above 500FT, turn right direct to PLUTO, to KAIJI, to SPOON at or below FL150, to ROVER at or above 12000FT.

Note RWY34R : 5.0% climb gradient required up to 700FT.

RWY05 : 5.0% climb gradient required up to 500FT.

CHANGE : PROC renamed.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

ROVER TWO B DEPARTURE

RWY16R

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	158 (150.0)	-7.6	—	—	+500	—	—	RNAV1
002	DF	T6R11	—	—	-7.6	—	—	—	—	—	RNAV1
003	TF	WELDA	—	068 (060.6)	-7.6	7.8	—	+6000	—	—	RNAV1
004	TF	PLUTO	—	352 (344.5)	-7.6	7.1	—	—	—	—	RNAV1
005	TF	KAIJI	—	011 (003.0)	-7.6	7.6	—	—	—	—	RNAV1
006	TF	SPOON	—	347 (339.2)	-7.6	11.0	—	-FL150	—	—	RNAV1
007	TF	ROVER	—	347 (339.1)	-7.6	5.2	—	+12000	—	—	RNAV1

RWY16L

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	158 (150.0)	-7.6	—	—	+500	—	—	RNAV1
002	DF	T6L23	—	—	-7.6	—	L	—	—	—	RNAV1
003	TF	WELDA	—	055 (047.3)	-7.6	4.8	—	+6000	—	—	RNAV1
004	TF	PLUTO	—	352 (344.5)	-7.6	7.1	—	—	—	—	RNAV1
005	TF	KAIJI	—	011 (003.0)	-7.6	7.6	—	—	—	—	RNAV1
006	TF	SPOON	—	347 (339.2)	-7.6	11.0	—	-FL150	—	—	RNAV1
007	TF	ROVER	—	347 (339.1)	-7.6	5.2	—	+12000	—	—	RNAV1

RWY34R

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	338 (330.0)	-7.6	—	—	+700	—	—	RNAV1
002	DF	ARAKA	—	—	-7.6	—	R	—	—	—	RNAV1
003	TF	EDOJO	—	018 (010.8)	-7.6	3.5	—	—	—	—	RNAV1
004	TF	OHEDO	—	331 (323.7)	-7.6	3.9	—	—	—	—	RNAV1
005	TF	SPOON	—	030 (022.4)	-7.6	9.8	—	-FL150	—	—	RNAV1
006	TF	ROVER	—	347 (339.1)	-7.6	5.2	—	+12000	—	—	RNAV1

CHANGE : PROC renamed.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

RWY05

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	050 (042.4)	-7.6	—	—	+500	—	—	RNAV1
002	DF	PLUTO	—	—	-7.6	—	R	—	—	—	RNAV1
003	TF	KAIJI	—	011 (003.0)	-7.6	7.6	—	—	—	—	RNAV1
004	TF	SPOON	—	347 (339.2)	-7.6	11.0	—	-FL150	—	—	RNAV1
005	TF	ROVER	—	347 (339.1)	-7.6	5.2	—	+12000	—	—	RNAV1

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
ARAKA	353848.8N / 1395041.9E	ROVER	355918.3N / 1395059.3E
EDOJO	354214.0N / 1395129.9E	SPOON	355428.3N / 1395316.0E
KAIJI	354409.6N / 1395806.6E	T6L23	352627.6N / 1395539.1E
OHEDO	354523.4N / 1394838.6E	T6R11	352552.5N / 1395137.2E
PLUTO	353632.1N / 1395736.8E	WELDA	352941.4N / 1395956.7E

CHANGE : Magnetic Variation.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

ROVER TWO C DEPARTURE

RNAV1

Note 1) DME/DME/IRU or GNSS required.
 ※The aircraft equipped with only DME/DME/IRU must be able to update its position without delay at the starting point of take-off rolling.
 2) RADAR service required.

DME GAP
 RWY16R: DER - 1.2NM FM DER
 RWY16L: DER - 1.0NM FM DER
 RWY34R: DER - 1.0NM FM DER

Inappropriate Navaids
 See AD1.1.6.10.3.Inappropriate NAVAIDs for RNAV1

Critical DME


RWY16R : HME 1.2NM FM DER - 1.9NM to T6R11
 PQD 6.6NM to KAIJI - KAIJI

RWY05 : HME DER - 2.2NM to PLUTO
 PQD 6.6NM to KAIJI - KAIJI

VAR8°W(2020)

ROVER TWO C DEPARTURE

CHANGE : PROC renamed.



STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

ROVER TWO C DEPARTURE

RWY16R : Climb on HDG 158° at or above 500FT, direct to T6R11, to WELDA at or above 6000FT, to PLUTO, to KAIJI, to SPOON at or below FL150, to ROVER at or above 12000FT.

RWY16L : Climb on HDG 158° at or above 500FT, turn left direct to T6L31, to DAMBO, to T6L32, to LESMO at or above 8000FT, to KAIJI, to SPOON at or below FL150, to ROVER at or above 12000FT.

RWY34R : Climb on HDG 338° at or above 700FT, turn right direct to ARAKA, to EDOJO, to OHEDO, to SPOON at or below FL150, to ROVER at or above 12000FT.

RWY05 : Climb on HDG 050° at or above 500FT, turn right direct to PLUTO, to KAIJI, to SPOON at or below FL150, to ROVER at or above 12000FT.

Note RWY34R : 5.0% climb gradient required up to 700FT.

RWY05 : 5.0% climb gradient required up to 500FT.

CHANGE : PROC renamed.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

ROVER TWO C DEPARTURE

RWY16R

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	158 (150.0)	-7.6	—	—	+500	—	—	RNAV1
002	DF	T6R11	—	—	-7.6	—	—	—	—	—	RNAV1
003	TF	WELDA	—	068 (060.6)	-7.6	7.8	—	+6000	—	—	RNAV1
004	TF	PLUTO	—	352 (344.5)	-7.6	7.1	—	—	—	—	RNAV1
005	TF	KAIJI	—	011 (003.0)	-7.6	7.6	—	—	—	—	RNAV1
006	TF	SPOON	—	347 (339.2)	-7.6	11.0	—	-FL150	—	—	RNAV1
007	TF	ROVER	—	347 (339.1)	-7.6	5.2	—	+12000	—	—	RNAV1

RWY16L

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	158 (150.0)	-7.6	—	—	+500	—	—	RNAV1
002	DF	T6L31	—	—	-7.6	—	L	—	—	—	RNAV1
003	TF	DAMBO	—	055 (047.5)	-7.6	8.7	—	—	—	—	RNAV1
004	TF	T6L32	—	317 (309.4)	-7.6	6.2	—	—	—	—	RNAV1
005	TF	LESMO	—	002 (354.1)	-7.6	3.0	—	+8000	—	—	RNAV1
006	TF	KAIJI	—	002 (354.1)	-7.6	3.0	—	—	—	—	RNAV1
007	TF	SPOON	—	347 (339.2)	-7.6	11.0	—	-FL150	—	—	RNAV1
008	TF	ROVER	—	347 (339.1)	-7.6	5.2	—	+12000	—	—	RNAV1

RWY34R

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	338 (330.0)	-7.6	—	—	+700	—	—	RNAV1
002	DF	ARAKA	—	—	-7.6	—	R	—	—	—	RNAV1
003	TF	EDOJO	—	018 (010.8)	-7.6	3.5	—	—	—	—	RNAV1
004	TF	OHEDO	—	331 (323.7)	-7.6	3.9	—	—	—	—	RNAV1
005	TF	SPOON	—	030 (022.4)	-7.6	9.8	—	-FL150	—	—	RNAV1
006	TF	ROVER	—	347 (339.1)	-7.6	5.2	—	+12000	—	—	RNAV1

CHANGE : PROC renamed.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

RWY05

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	050 (042.4)	-7.6	—	—	+500	—	—	RNAV1
002	DF	PLUTO	—	—	-7.6	—	R	—	—	—	RNAV1
003	TF	KAIJI	—	011 (003.0)	-7.6	7.6	—	—	—	—	RNAV1
004	TF	SPOON	—	347 (339.2)	-7.6	11.0	—	-FL150	—	—	RNAV1
005	TF	ROVER	—	347 (339.1)	-7.6	5.2	—	+12000	—	—	RNAV1

Waypoint Coordinates


Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
ARAKA	353848.8N / 1395041.9E	ROVER	355918.3N / 1395059.3E
DAMBO	353416.5N / 1400443.4E	SPOON	355428.3N / 1395316.0E
EDOJO	354214.0N / 1395129.9E	T6L31	352822.8N / 1395648.0E
KAIJI	354409.6N / 1395806.6E	T6L32	353810.9N / 1395852.2E
LESMO	354110.3N / 1395829.4E	T6R11	352552.5N / 1395137.2E
OHEDO	354523.4N / 1394838.6E	WELDA	352941.4N / 1395956.7E
PLUTO	353632.1N / 1395736.8E		

CHANGE : Magnetic Variation.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL		RNAV TRANSITION
AKAGI TRANSITION / BRUCE TRANSITION/ INUBO TRANSITION		RNAV1
Note 1) DME/DME/IRU or GNSS required.		
2) RADAR service required.		
DME GAP	-	Critical DME
Inappropriate Navaids	See AD1.1.6.10.3.Inappropriate NAVAIDs for RNAV1	-

VAR8°W(2019)



STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV TRANSITION

AKAGI TRANSITION

From ROVER, to CLARK, to AKAGI.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	ROVER	—	—	-7.5	—	—	—	—	—	RNAV1
002	TF	CLARK	—	350 (342.7)	-7.5	8.1	—	—	—	—	RNAV1
003	TF	AKAGI	—	351 (343.4)	-7.5	17.2	—	—	—	—	RNAV1

BRUCE TRANSITION

From ROVER, to BRUCE at or above FL150, to AGRIS.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	ROVER	—	—	-7.5	—	—	—	—	—	RNAV1
002	TF	BRUCE	—	028 (020.7)	-7.5	13.6	—	+FL150	—	—	RNAV1
003	TF	AGRIS	—	006 (358.7)	-7.5	13.3	—	—	—	—	RNAV1

INUBO TRANSITION

From ROVER, to BRUCE at or above FL150, to LEWIS at FL170, to SILVA at FL170, to INUBO at or above FL250.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	ROVER	—	—	-7.5	—	—	—	—	—	RNAV1
002	TF	BRUCE	—	028 (020.7)	-7.5	13.6	—	+FL150	—	—	RNAV1
003	TF	LEWIS	—	086 (078.6)	-7.5	9.6	—	FL170	—	—	RNAV1
004	TF	SILVA	—	086 (078.8)	-7.5	7.3	—	FL170	—	—	RNAV1
005	TF	INUBO	—	149 (141.9)	-7.5	40.2	—	+FL250	—	—	RNAV1

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
AGRIS	362514.7N / 1395633.1E	INUBO	354335.3N / 1404757.9E
AKAGI	362328.3N / 1394156.3E	LEWIS	361353.2N / 1400834.7E
BRUCE	361200.4N / 1395655.9E	ROVER	355918.3N / 1395059.3E
CLARK	360702.0N / 1394800.5E	SILVA	361518.0N / 1401726.0E

STANDARD DEPARTURE CHART-INSTRUMENT


RJTT/TOKYO INTL

RNAV SID

RUTAS TWO DEPARTURE		RNAV1
Note 1) DME/DME/IRU or GNSS required. ※The aircraft equipped with only DME/DME/IRU must be able to update its position without delay at the starting point of take-off rolling. 2) RADAR service required.	Critical DME	RWY16R : HME 1.2NM FM DER - 1.9NM to T6R11 RWY16L : HME 1.0NM FM DER - 2.4NM to T6L21 RWY34R : HME 1.0NM FM DER - 2.5NM to TT502 RWY34L : HME 0.5NM FM DER - 2.5NM to TT502 RWY04 : HME 1.7NM FM DER - 2.5NM to TT502 RWY05 : HME DER - 2.7NM to TT502
DME GAP RWY16R:DER - 1.2NM FM DER RWY16L:DER - 1.0NM FM DER RWY34R:DER - 1.0NM FM DER RWY34L:DER - 0.5NM FM DER RWY04:DER - 1.7NM FM DER		
Inappropriate Navaids See AD1.1.6.10.3.Inappropriate NAVAIDs for RNAV1		

VAR8°W(2020)

CHANGE : PROC renamed. VAR. HDG after DEP FM RWY04. Course FM TT502 to LOCUP.



STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

RUTAS TWO DEPARTURE

RWY16R : Climb on HDG 158° at or above 500FT, direct to T6R11, to VAMOS, to UTIBO at 6000FT, to RUTAS.

RWY16L : Climb on HDG 158° at or above 500FT, direct to T6L21, to VAMOS, to UTIBO at 6000FT, to RUTAS.

RWY34L/34R : Climb on HDG 338° at or above 700FT, turn right direct to TT502, to LOCUP at or above 5000FT, to VAMOS, to UTIBO at 6000FT, to RUTAS.

RWY04: Climb on HDG 043° at or above 700FT, turn right direct to TT502, to LOCUP at or above 5000FT, to VAMOS, to UTIBO at 6000FT, to RUTAS.

RWY05: Climb on HDG 050° at or above 500FT, direct to TT501, turn right direct to TT502, to LOCUP at or above 5000FT, to VAMOS, to UTIBO at 6000FT, to RUTAS.

Note RWY34L/34R/04 : 5.0% climb gradient required up to 700FT.

RWY05 : 5.0% climb gradient required up to 500FT.

RWY16R

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	158 (150.0)	-7.6	—	—	+500	—	—	RNAV1
002	DF	T6R11	—	—	-7.6	—	—	—	—	—	RNAV1
003	TF	VAMOS	—	207 (199.5)	-7.6	14.5	—	—	—	—	RNAV1
004	TF	UTIBO	—	165 (157.0)	-7.6	16.8	—	6000	—	—	RNAV1
005	TF	RUTAS	—	116 (108.4)	-7.6	40.6	—	—	—	—	RNAV1

RWY16L

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	158 (150.0)	-7.6	—	—	+500	—	—	RNAV1
002	DF	T6L21	—	—	-7.6	—	—	—	—	—	RNAV1
003	TF	VAMOS	—	208 (200.7)	-7.6	15.4	—	—	—	—	RNAV1
004	TF	UTIBO	—	165 (157.0)	-7.6	16.8	—	6000	—	—	RNAV1
005	TF	RUTAS	—	116 (108.4)	-7.6	40.6	—	—	—	—	RNAV1

CHANGE : PROC renamed. Magnetic Variation. HDG after DEP FM RWY04.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

RNAV SID											
RWY34L/RWY34R											
Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	338 (330.0)	-7.6	–	–	+700	–	–	RNAV1
002	DF	TT502	–	–	-7.6	–	R	–	–	–	RNAV1
003	TF	LOCUP	–	199 (190.9)	-7.6	5.2	–	+5000	–	–	RNAV1
004	TF	VAMOS	–	217 (209.5)	-7.6	17.3	–	–	–	–	RNAV1
005	TF	UTIBO	–	165 (157.0)	-7.6	16.8	–	6000	–	–	RNAV1
006	TF	RUTAS	–	116 (108.4)	-7.6	40.6	–	–	–	–	RNAV1

RWY04

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	043 (034.9)	-7.6	–	–	+700	–	–	RNAV1
002	DF	TT502	–	–	-7.6	–	R	–	–	–	RNAV1
003	TF	LOCUP	–	199 (190.9)	-7.6	5.2	–	+5000	–	–	RNAV1
004	TF	VAMOS	–	217 (209.5)	-7.6	17.3	–	–	–	–	RNAV1
005	TF	UTIBO	–	165 (157.0)	-7.6	16.8	–	6000	–	–	RNAV1
006	TF	RUTAS	–	116 (108.4)	-7.6	40.6	–	–	–	–	RNAV1

RWY05

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	050 (042.4)	-7.6	–	–	+500	–	–	RNAV1
002	DF	TT501	Y	–	-7.6	–	–	–	–	–	RNAV1
003	DF	TT502	–	–	-7.6	–	R	–	–	–	RNAV1
004	TF	LOCUP	–	199 (190.9)	-7.6	5.2	–	+5000	–	–	RNAV1
005	TF	VAMOS	–	217 (209.5)	-7.6	17.3	–	–	–	–	RNAV1
006	TF	UTIBO	–	165 (157.0)	-7.6	16.8	–	6000	–	–	RNAV1
007	TF	RUTAS	–	116 (108.4)	-7.6	40.6	–	–	–	–	RNAV1

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
LOCUP	352718.8N / 1395608.5E	TT501	353328.7N / 1395029.9E
RUTAS	344349.3N / 1404034.2E	TT502	353224.4N / 1395720.7E
T6L21	352639.1N / 1395222.0E	UTIBO	345647.0N / 1395343.9E
T6R11	352552.5N / 1395137.2E	VAMOS	351215.5N / 1394543.6E

STANDARD DEPARTURE CHART-INSTRUMENT


RJTT/TOKYO INTL

RNAV SID

GUSRO ONE DEPARTURE		RNAV SID
Note 1) DME/DME/IRU or GNSS required. ※The aircraft equipped with only DME/DME/IRU must be able to update its position without delay at the starting point of take-off rolling. 2) RADAR service required.		RNAV1
DME GAP	RWY16R : DER - 1.2NM FM DER RWY16L : DER - 1.0NM FM DER RWY34R : DER - 1.0NM FM DER 3.8NM to KAMAT – 1.8NM to KAMAT RWY34L : DER - 0.5NM FM DER 3.8NM to KAMAT – 1.8NM to KAMAT RWY04 : DER - 1.7NM FM DER 3.8NM to KAMAT – 1.8NM to KAMAT RWY05 : 3.8NM to KAMAT - 1.8NM to KAMAT RWY22 : DER – 1.4NM FM DER	Critical DME RWY16R : HME 1.2NM FM DER – HATBA HYD 2.8NM to HATBA - 1.6NM to HATBA PQD HATBA - 1.6NM to KAMAT RWY16L : HME 1.0NM FM DER - HATBA HYD 2.8NM to HATBA - 1.6NM to HATBA PQD HATBA - 1.6NM to KAMAT RWY34R : HME 1.0NM FM DER - 2.5NM to TT502 TT503 – 3.8NM to KAMAT 1.8NM to KAMAT - KAMAT HYD 1.2NM to TT503 – TT503 4.8NM to KAMAT – 3.8NM to KAMAT RWY34L : HME 0.5NM FM DER - 2.5NM to TT502 TT503 – 3.8NM to KAMAT 1.8NM to KAMAT - KAMAT HYD 1.2NM to TT503 – TT503 4.8NM to KAMAT – 3.8NM to KAMAT RWY04 : HME 1.7NM FM DER - 2.5NM to TT502 TT503 – 3.8NM to KAMAT 1.8NM to KAMAT - KAMAT HYD 1.2NM to TT503 – TT503 4.8NM to KAMAT – 3.8NM to KAMAT RWY05 : HME DER - 2.7NM to TT502 TT503 - 3.8NM to KAMAT 1.8NM to KAMAT - KAMAT HYD 1.2NM to TT503 - TT503 4.8NM to KAMAT - 3.8NM to KAMAT
Inappropriate Navaids	See AD1.1.6.10.3.Inappropriate NAVAIDs for RNAV1	

VAR8°W

GUSRO ONE DEPARTURE RWY16R/16L




STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

VAR8°W

GUSRO ONE DEPARTURE RWY 34L/34R/04/05/22



CHANGE : New PROC.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

GUSRO ONE DEPARTURE

RWY16R : Climb on HDG 158° at or above 500FT, direct to T6R13, to HATBA, to KAMAT at or above 9000FT, to LAYER at or above 13000FT, to GUSRO at or above FL170.

RWY16L : Climb on HDG 158° at or above 500FT, direct to T6L43, to HATBA, to KAMAT at or above 9000FT, to LAYER at or above 13000FT, to GUSRO at or above FL170.

RWY34L/34R : Climb on HDG 338° at or above 700FT, turn right direct to TT502, to LOCUP at or above 5000FT, to TT503, to KAMAT at or above 9000FT, to LAYER at or above 13000FT, to GUSRO at or above FL170.

RWY04 : Climb on HDG 043° at or above 700FT, turn right direct to TT502, to LOCUP at or above 5000FT, to TT503, to KAMAT at or above 9000FT, to LAYER at or above 13000FT, to GUSRO at or above FL170.

RWY05 : Climb on HDG 050° at or above 500FT, direct to TT501, turn right direct to TT502, to LOCUP at or above 5000FT, to TT503, to KAMAT at or above 9000FT, to LAYER at or above 13000FT, to GUSRO at or above FL170.

RWY22 : Climb on HDG 223° at or above 600FT, turn left direct to HOBBS, to BASSA, to UMUKI, to PIPER at or above 9000FT, to SATOL, to CURVA at or above FL150, to GUSRO at or above FL170.

Note RWY34L/34R/04 : 5.0% climb gradient required up to 700FT.

RWY05 : 5.0% climb gradient required up to 500FT.

RWY22 : 5.0% climb gradient required up to 600FT.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

GUSRO ONE DEPARTURE

RWY16R

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	158 (150.0)	-7.8	—	—	+500	—	—	RNAV1
002	DF	T6R13	—	—	-7.8	—	—	—	—	—	RNAV1
003	TF	HATBA	—	262 (253.8)	-7.8	5.8	—	—	—	—	RNAV1
004	TF	KAMAT	—	359 (351.1)	-7.8	7.6	—	+9000	—	—	RNAV1
005	TF	LAYER	—	305 (297.1)	-7.8	12.2	—	+13000	—	—	RNAV1
006	TF	GUSRO	—	279 (271.2)	-7.8	16.5	—	+FL170	—	—	RNAV1

RWY16L

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	158 (150.0)	-7.8	—	—	+500	—	—	RNAV1
002	DF	T6L43	—	—	-7.8	—	—	—	—	—	RNAV1
003	TF	HATBA	—	260 (251.9)	-7.8	6.7	—	—	—	—	RNAV1
004	TF	KAMAT	—	359 (351.1)	-7.8	7.6	—	+9000	—	—	RNAV1
005	TF	LAYER	—	305 (297.1)	-7.8	12.2	—	+13000	—	—	RNAV1
006	TF	GUSRO	—	279 (271.2)	-7.8	16.5	—	+FL170	—	—	RNAV1

RWY34L/RWY34R

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	338 (330.0)	-7.8	—	—	+700	—	—	RNAV1
002	DF	TT502	—	—	-7.8	—	R	—	—	—	RNAV1
003	TF	LOCUP	—	199 (190.9)	-7.8	5.2	—	+5000	—	—	RNAV1
004	TF	TT503	—	289 (280.8)	-7.8	6.2	—	—	—	—	RNAV1
005	TF	KAMAT	—	322 (314.2)	-7.8	7.8	—	+9000	—	—	RNAV1
006	TF	LAYER	—	305 (297.1)	-7.8	12.2	—	+13000	—	—	RNAV1
007	TF	GUSRO	—	279 (271.2)	-7.8	16.5	—	+FL170	—	—	RNAV1

CHANGE : New PROC.

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

RWY04

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	043 (034.9)	-7.8	—	—	+700	—	—	RNAV1
002	DF	TT502	—	—	-7.8	—	R	—	—	—	RNAV1
003	TF	LOCUP	—	199 (190.9)	-7.8	5.2	—	+5000	—	—	RNAV1
004	TF	TT503	—	289 (280.8)	-7.8	6.2	—	—	—	—	RNAV1
005	TF	KAMAT	—	322 (314.2)	-7.8	7.8	—	+9000	—	—	RNAV1
006	TF	LAYER	—	305 (297.1)	-7.8	12.2	—	+13000	—	—	RNAV1
007	TF	GUSRO	—	279 (271.2)	-7.8	16.5	—	+FL170	—	—	RNAV1

RWY05

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	050 (042.4)	-7.8	—	—	+500	—	—	RNAV1
002	DF	TT501	Y	—	-7.8	—	—	—	—	—	RNAV1
003	DF	TT502	—	—	-7.8	—	R	—	—	—	RNAV1
004	TF	LOCUP	—	199 (190.9)	-7.8	5.2	—	+5000	—	—	RNAV1
005	TF	TT503	—	289 (280.8)	-7.8	6.2	—	—	—	—	RNAV1
006	TF	KAMAT	—	322 (314.2)	-7.8	7.8	—	+9000	—	—	RNAV1
007	TF	LAYER	—	305 (297.1)	-7.8	12.2	—	+13000	—	—	RNAV1
008	TF	GUSRO	—	279 (271.2)	-7.8	16.5	—	+FL170	—	—	RNAV1

RWY22

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	223 (214.9)	-7.8	—	—	+600	—	—	RNAV1
002	DF	HOBBS	—	—	-7.8	—	L	—	—	—	RNAV1
003	TF	BASSA	—	188 (179.9)	-7.8	5.8	—	—	—	—	RNAV1
004	TF	UMUKI	—	172 (163.9)	-7.8	9.2	—	—	—	—	RNAV1
005	TF	PIPER	—	235 (227.4)	-7.8	3.5	—	+9000	—	—	RNAV1
006	TF	SATOL	—	235 (227.4)	-7.8	5.5	—	—	—	—	RNAV1
007	TF	CURVA	—	300 (292.2)	-7.8	8.2	—	+FL150	—	—	RNAV1
008	TF	GUSRO	—	336 (328.3)	-7.8	35.8	—	+FL170	—	—	RNAV1

STANDARD DEPARTURE CHART-INSTRUMENT

RJTT/TOKYO INTL

RNAV SID

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
BASSA	352108.8N / 1394542.2E	PIPER	350958.3N / 1394542.0E
CURVA	350919.0N / 1393124.4E	SATOL	350613.3N / 1394043.4E
GUSRO	353944.8N / 1390813.1E	T6L43	352828.4N / 1395104.6E
HATBA	352623.4N / 1394315.9E	T6R13	352800.8N / 1395006.4E
HOBBS	352653.9N / 1394541.3E	TT501	353328.7N / 1395029.9E
KAMAT	353353.6N / 1394148.9E	TT502	353224.4N / 1395720.7E
LAYER	353925.4N / 1392829.5E	TT503	352828.0N / 1394840.4E
LOCUP	352718.8N / 1395608.5E	UMUKI	351219.1N / 1394849.2E

CHANGE : New PROC.

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

STAR

SINGO ARRIVAL

From over STONE, via HME R036 to HME 22.2DME, via HME 22.2DME clockwise ARC to SINGO.

Cross STONE at 11000FT, cross HME R036/28.0DME at or above 8000FT.

DOYLE ARRIVAL

From over STONE, via HME R036 to HME 22.2DME, via HME 22.2DME clockwise ARC to intercept and proceed via ITL LOC course to DOYLE.

Cross STONE at 11000FT, cross HME R036/28.0DME at or above 8000FT.

ADDUM ARRIVAL

From over ADDUM, via HME R157 to HME 25.0DME, turn right, via IHA LOC course to ARLON.


Cross ADDUM at 10000FT.

BONUS ARRIVAL

From over ADDUM, via HME R157 to HME 22.2DME, via HME 22.2DME counterclockwise ARC to intercept and proceed via IKL LOC course to BONUS.

Cross ADDUM at 10000FT.

STANDARD ARRIVAL CHART-INSTRUMENT



STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY34R/34L

OSHIMA 1A ARRIVAL / OSHIMA 1K ARRIVAL
OSHIMA 2C ARRIVAL

RNAV 1

Note 1) DME/DME/IRU or GNSS required.


2) RADAR service required.

VAR 8° W(2019)

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)



MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)



MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)


WEDGE MHA 4000



TACAN TATEYAMA
986 CH-25X
34°58'15"N/139°50'17"E
500FT

VORTAC OSHIMA
113.1 CH-78X
34°42'44"N/139°24'50"E
2100FT

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)





VOR/DME HANEDA
112.2 CH-59X
35°33'44"N/139°45'40"E
100FT

HME

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)


CREAM MHA 4000



CHANGE : ACORN abolished. ANZAC established.

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

CIVIC MHA 4000



MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

ANZAC MHA 5000



STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY34R/34L

OSHIMA 1A ARRIVAL

From XAC, to ANZAC at 13000FT, to TT450, to TT451, to TT452, to TT453, to WANDA at 13000FT, to WEDGE at 8000FT, to ARLON.

Critical DME	—
DME GAP	—
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	XAC	—	—	-7.5	—	—	—	—	—	RNAV1
002	TF	ANZAC	—	068 (060.8)	-7.5	15.9	—	13000	230	—	RNAV1
003	TF	TT450	—	069 (061.0)	-7.5	5.0	—	—	—	—	RNAV1
004	TF	TT451	—	114 (106.9)	-7.5	9.0	—	—	—	—	RNAV1
005	TF	TT452	—	090 (082.2)	-7.5	7.0	—	—	—	—	RNAV1
006	TF	TT453	—	068 (060.7)	-7.5	7.0	—	—	—	—	RNAV1
007	TF	WANDA	—	044 (036.0)	-7.5	9.0	—	13000	230	—	RNAV1
008	TF	WEDGE	—	300 (292.4)	-7.5	18.7	—	8000	—	—	RNAV1
009	TF	ARLON	—	009 (001.6)	-7.5	6.4	—	—	—	—	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	XAC	098 (090.3)	-7.5	1.0(-14000) 1.5(+14001)	—	R	5000	—	-230(-14000) -240(+14001)	RNAV1
Hold	ANZAC	068 (060.8)	-7.5	1.0(-14000) 1.5(+14001)	—	L	5000	—	-230(-14000) -240(+14001)	RNAV1
Hold	WEDGE	300 (292.4)	-7.5	1.0(-14000) 1.5(+14001)	—	L	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	ARLON	009 (001.6)	-7.5	1.0(-14000) 1.5(+14001)	—	L	4000	—	-230(-14000) -240(+14001)	RNAV1

CHANGE : ACORN abolished. ANZAC established.

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY34R/34L

OSHIMA 1K ARRIVAL

From XAC, to ANZAC at 13000FT, to TT450, to TT451, to TT452, to TT453, to WANDA at 13000FT, to WEDGE at 8000FT, to UMUKI at or above 6000FT, to KAIHO.

Critical DME	—
DME GAP	—
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	XAC	—	—	-7.5	—	—	—	—	—	RNAV1
002	TF	ANZAC	—	068 (060.8)	-7.5	15.9	—	13000	230	—	RNAV1
003	TF	TT450	—	069 (061.0)	-7.5	5.0	—	—	—	—	RNAV1
004	TF	TT451	—	114 (106.9)	-7.5	9.0	—	—	—	—	RNAV1
005	TF	TT452	—	090 (082.2)	-7.5	7.0	—	—	—	—	RNAV1
006	TF	TT453	—	068 (060.7)	-7.5	7.0	—	—	—	—	RNAV1
007	TF	WANDA	—	044 (036.0)	-7.5	9.0	—	13000	230	—	RNAV1
008	TF	WEDGE	—	300 (292.4)	-7.5	18.7	—	8000	—	—	RNAV1
009	TF	UMUKI	—	300 (292.2)	-7.5	8.8	—	+6000	—	—	RNAV1
010	TF	KAIHO	—	353 (345.5)	-7.5	6.9	—	—	—	—	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	XAC	098 (090.3)	-7.5	1.0(-14000) 1.5(+14001)	—	R	5000	—	-230(-14000) -240(+14001)	RNAV1
Hold	ANZAC	068 (060.8)	-7.5	1.0(-14000) 1.5(+14001)	—	L	5000	—	-230(-14000) -240(+14001)	RNAV1
Hold	WEDGE	300 (292.4)	-7.5	1.0(-14000) 1.5(+14001)	—	L	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	KAIHO	353 (345.5)	-7.5	1.0(-14000) 1.5(+14001)	—	R	4000	—	-230(-14000) -240(+14001)	RNAV1

CHANGE : ACCORN abolished. ANZAC established.

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY34R/34L

OSHIMA 2C ARRIVAL

From XAC, to CLONE, to TT460, to TT461, to CIVIC at 7000FT, to TT462, to TT463, to TT464, to EPSON at 7000FT, to CREAM.

Critical DME	—
DME GAP	—
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	XAC	—	—	-7.5	—	—	—	—	—	RNAV1
002	TF	CLONE	—	095 (087.8)	-7.5	36.3	—	—	—	—	RNAV1
003	TF	TT460	—	068 (060.7)	-7.5	10.1	—	—	—	—	RNAV1
004	TF	TT461	—	044 (036.1)	-7.5	14.4	—	—	—	—	RNAV1
005	TF	CIVIC	—	345 (337.7)	-7.5	8.8	—	7000	210	—	RNAV1
006	TF	TT462	—	345 (337.7)	-7.5	6.4	—	—	—	—	RNAV1
007	TF	TT463	—	006 (358.0)	-7.5	6.9	—	—	—	—	RNAV1
008	TF	TT464	—	341 (333.5)	-7.5	5.4	—	—	—	—	RNAV1
009	TF	EPSON	—	317 (309.0)	-7.5	6.9	—	7000	210	—	RNAV1
010	TF	CREAM	—	211 (203.6)	-7.5	14.1	—	—	—	—	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	XAC	098 (090.3)	-7.5	1.0(-14000) 1.5(+14001)	—	R	5000	—	-230(-14000) -240(+14001)	RNAV1
Hold	CIVIC	345 (337.7)	-7.5	1.0(-14000) 1.5(+14001)	—	R	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	CREAM	291 (283.1)	-7.5	1.0(-14000) 1.5(+14001)	—	R	4000	—	-230(-14000) -240(+14001)	RNAV1

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
ANZAC	345028.8N / 1394146.7E	TT453	345438.5N / 1401325.9E
ARLON	351525.3N / 1395859.8E	TT460	344852.6N / 1401936.8E
CIVIC	350840.6N / 1402552.1E	TT461	350030.2N / 1402957.9E
CLONE	344357.8N / 1400856.0E	TT462	351433.3N / 1402254.8E
CREAM	351743.4N / 1400612.4E	TT463	352125.4N / 1402237.1E
EPSON	353036.2N / 1401305.9E	TT464	352617.6N / 1401938.6E
KAIHO	351857.8N / 1394642.4E	UMUKI	351219.1N / 1394849.2E
TT450	345254.0N / 1394706.0E	WANDA	350155.3N / 1401954.1E
TT451	345016.8N / 1395734.3E	WEDGE	350900.4N / 1395846.5E
TT452	345113.2N / 1400600.1E	XAC	344244.1N / 1392450.5E

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

AKSEL 1A ARRIVAL / AKSEL 1K ARRIVAL
AKSEL 2C ARRIVAL

RNAV STAR RWY34R/34L

RNAV 1

- Note 1) DME/DME/IRU or GNSS required.
2) RADAR service required.

VAR 8° W(2019)

VOR/DME
HANEDA
112.2 HME
CH-59X \cdots
35°33'44"N/139°45'40"E
100FT

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

KAIHO
MHA 4000
 173°
 353°

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

ARLON
MHA 4000
 600°
 68°

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

WEDGE
MHA 4000
 300°
 120°

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

AKSEL
MHA 5000
 039°
 219°

EPSON
7000
210KIAS

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

CREAM
MHA 4000

AKSEL 2C ARRIVAL

UMUKI
6000

WEDGE
8000

AKSEL1A ARRIVAL

DME
TATEYAMA
1159 PQD
CH-72X \cdots
34°56'46"N/139°53'43"E
600FT

TT454

TT455

TT456

TT457

TT458

TT459

TT460

TT461

TT462

TT463

TT464

TT465

TT466

TT467

TT468

TT469

TT470

TT471

TT472

TT473

TT474

TT475

TT476

TT477

TT478

TT479

TT480

TT481

TT482

TT483

TT484

TT485

TT486

TT487

TT488

TT489

TT490

TT491

TT492

TT493

TT494

TT495

TT496

TT497

TT498

TT499

TT500

TT501

TT502

TT503

TT504

TT505

TT506

TT507

TT508

TT509

TT510

TT511

TT512

TT513

TT514

TT515

TT516

TT517

TT518

TT519

TT520

TT521

TT522

TT523

TT524

TT525

TT526

TT527

TT528

TT529

TT530

TT531

TT532

TT533

TT534

TT535

TT536

TT537

TT538

TT539

TT540

TT541

TT542

TT543

TT544

TT545

TT546

TT547

TT548

TT549

TT550

TT551

TT552

TT553

TT554

TT555

TT556

TT557

TT558

TT559

TT560

TT561

TT562

TT563

TT564

TT565

TT566

TT567

TT568

TT569

TT570

TT571

TT572

TT573

TT574

TT575

TT576

TT577

TT578

TT579

TT580

TT581

TT582

TT583

TT584

TT585

TT586

TT587

TT588

TT589

TT590

TT591

TT592

TT593

TT594

TT595

TT596

TT597

TT598

TT599

TT600

TT601

TT602

TT603

TT604

TT605

TT606

TT607

TT608

TT609

TT610

TT611

TT612

TT613

TT614

TT615

TT616

TT617

TT618

TT619

TT620

TT621

TT622

TT623

TT624

TT625

TT626

TT627

TT628

TT629

TT630

TT631

TT632

TT633

TT634

TT635

TT636

TT637

TT638

TT639

TT640

TT641

TT642

TT643

TT644

TT645

TT646

TT647

TT648

TT649

TT650

TT651

TT652

TT653

TT654

TT655

TT656

TT657

TT658

TT659

TT660

TT661

TT662

TT663

TT664

TT665

TT666

TT667

TT668

TT669

TT670

TT671

TT672

TT673

TT674

TT675

TT676

TT677

TT678

TT679

TT680

TT681

TT682

TT683

TT684

TT685

TT686

TT687

TT688

TT689

TT690

TT691

TT692

TT693

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY34R/34L

AKSEL 1A ARRIVAL

From AKSEL at 12000FT, to TT454, to TT455, to TT456, to WALLY at 12000FT, to WEDGE at 8000FT, to ARLON.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AKSEL	-	-	-7.5	-	-	12000	230	-	RNAV1
002	TF	TT454	-	039 (031.2)	-7.5	9.5	-	-	-	-	RNAV1
003	TF	TT455	-	090 (082.2)	-7.5	7.6	-	-	-	-	RNAV1
004	TF	TT456	-	068 (060.7)	-7.5	7.6	-	-	-	-	RNAV1
005	TF	WALLY	-	044 (036.0)	-7.5	9.7	-	12000	230	-	RNAV1
006	TF	WEDGE	-	300 (292.4)	-7.5	20.2	-	8000	-	-	RNAV1
007	TF	ARLON	-	009 (001.6)	-7.5	6.4	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	AKSEL	039 (031.2)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	WEDGE	300 (292.4)	-7.5	1.0(-14000) 1.5(+14001)	-	L	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	ARLON	009 (001.6)	-7.5	1.0(-14000) 1.5(+14001)	-	L	4000	-	-230(-14000) -240(+14001)	RNAV1

CHANGE : WALLY renamed

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY34R/34L

AKSEL 1K ARRIVAL

From AKSEL at 12000FT, to TT454, to TT455, to TT456, to WALLY at 12000FT, to WEDGE at 8000FT, to UMUKI at or above 6000FT, to KAIHO.

Critical DME	—
DME GAP	—
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AKSEL	—	—	-7.5	—	—	12000	230	—	RNAV1
002	TF	TT454	—	039 (031.2)	-7.5	9.5	—	—	—	—	RNAV1
003	TF	TT455	—	090 (082.2)	-7.5	7.6	—	—	—	—	RNAV1
004	TF	TT456	—	068 (060.7)	-7.5	7.6	—	—	—	—	RNAV1
005	TF	WALLY	—	044 (036.0)	-7.5	9.7	—	12000	230	—	RNAV1
006	TF	WEDGE	—	300 (292.4)	-7.5	20.2	—	8000	—	—	RNAV1
007	TF	UMUKI	—	300 (292.2)	-7.5	8.8	—	+6000	—	—	RNAV1
008	TF	KAIHO	—	353 (345.5)	-7.5	6.9	—	—	—	—	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	AKSEL	039 (031.2)	-7.5	1.0(-14000) 1.5(+14001)	—	R	5000	—	-230(-14000) -240(+14001)	RNAV1
Hold	WEDGE	300 (292.4)	-7.5	1.0(-14000) 1.5(+14001)	—	L	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	KAIHO	353 (345.5)	-7.5	1.0(-14000) 1.5(+14001)	—	R	4000	—	-230(-14000) -240(+14001)	RNAV1

CHANGE : WALLY renamed

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY34R/34L

AKSEL 2C ARRIVAL

From AKSEL, to CLONE, to TT460, to TT461, to CIVIC at 7000FT, to TT462, to TT463, to TT464, to EPSON at 7000FT, to CREAM.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AKSEL	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	CLONE	-	085 (077.0)	-7.5	14.8	-	-	-	-	RNAV1
003	TF	TT460	-	068 (060.7)	-7.5	10.1	-	-	-	-	RNAV1
004	TF	TT461	-	044 (036.1)	-7.5	14.4	-	-	-	-	RNAV1
005	TF	CIVIC	-	345 (337.7)	-7.5	8.8	-	7000	210	-	RNAV1
006	TF	TT462	-	345 (337.7)	-7.5	6.4	-	-	-	-	RNAV1
007	TF	TT463	-	006 (358.0)	-7.5	6.9	-	-	-	-	RNAV1
008	TF	TT464	-	341 (333.5)	-7.5	5.4	-	-	-	-	RNAV1
009	TF	EPSON	-	317 (309.0)	-7.5	6.9	-	7000	210	-	RNAV1
010	TF	CREAM	-	211 (203.6)	-7.5	14.1	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	AKSEL	039 (031.2)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	CIVIC	345 (337.7)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	CREAM	291 (283.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
AKSEL	344039.5N / 1395126.9E	TT456	345329.3N / 1401440.2E
ARLON	351525.3N / 1395859.8E	TT460	344852.6N / 1401936.8E
CIVIC	350840.6N / 1402552.1E	TT461	350030.2N / 1402957.9E
CLONE	344357.8N / 1400856.0E	TT462	351433.3N / 1402254.8E
CREAM	351743.4N / 1400612.4E	TT463	352125.4N / 1402237.1E
EPSON	353036.2N / 1401305.9E	TT464	352617.6N / 1401938.6E
KAIHO	351857.8N / 1394642.4E	UMUKI	351219.1N / 1394849.2E
TT454	344844.8N / 1395725.3E	WALLY	350120.1N / 1402138.6E
TT455	344946.2N / 1400635.3E	WEDGE	350900.4N / 1395846.5E

CHANGE : WALLY renamed

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY34R/34L


AROSA 1A ARRIVAL / AROSA 1K ARRIVAL
AROSA 2C ARRIVAL

RNAV 1

Note 1) DME/DME/IRU or GNSS required.

2) RADAR service required.

VAR 8° W(2019)



STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY34R/34L

AROSA 1A ARRIVAL

From AROSA, to AVEEY at 11000FT, to TT457, to TT458, to TT459, to WALTZ at 11000FT, to WEDGE at 8000FT, to ARLON.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AROSA	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	AVEEY	-	277 (269.8)	-7.5	16.4	-	11000	230	-	RNAV1
003	TF	TT457	-	325 (317.5)	-7.5	7.2	-	-	-	-	RNAV1
004	TF	TT458	-	286 (278.5)	-7.5	7.4	-	-	-	-	RNAV1
005	TF	TT459	-	270 (262.3)	-7.5	8.2	-	-	-	-	RNAV1
006	TF	WALTZ	-	295 (287.0)	-7.5	10.4	-	11000	230	-	RNAV1
007	TF	WEDGE	-	038 (030.6)	-7.5	21.8	-	8000	-	-	RNAV1
008	TF	ARLON	-	009 (001.6)	-7.5	6.4	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	AVEEY	314 (306.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	WEDGE	300 (292.4)	-7.5	1.0(-14000) 1.5(+14001)	-	L	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	ARLON	009 (001.6)	-7.5	1.0(-14000) 1.5(+14001)	-	L	4000	-	-230(-14000) -240(+14001)	RNAV1

CHANGE : AVEEY renamed

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY34R/34L

AROSA 1K ARRIVAL

From AROSA, to AVEEY at 11000FT, to TT457, to TT458, to TT459, to WALTZ at 11000FT, to WEDGE at 8000FT, to UMUKI at or above 6000FT, to KAIHO.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AROSA	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	AVEEY	-	277 (269.8)	-7.5	16.4	-	11000	230	-	RNAV1
003	TF	TT457	-	325 (317.5)	-7.5	7.2	-	-	-	-	RNAV1
004	TF	TT458	-	286 (278.5)	-7.5	7.4	-	-	-	-	RNAV1
005	TF	TT459	-	270 (262.3)	-7.5	8.2	-	-	-	-	RNAV1
006	TF	WALTZ	-	295 (287.0)	-7.5	10.4	-	11000	230	-	RNAV1
007	TF	WEDGE	-	038 (030.6)	-7.5	21.8	-	8000	-	-	RNAV1
008	TF	UMUKI	-	300 (292.2)	-7.5	8.8	-	+6000	-	-	RNAV1
009	TF	KAIHO	-	353 (345.5)	-7.5	6.9	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	AVEEY	314 (306.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	WEDGE	300 (292.4)	-7.5	1.0(-14000) 1.5(+14001)	-	L	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	KAIHO	353 (345.5)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1

CHANGE : AVEEY renamed

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY34R/34L

AROSA 2C ARRIVAL

From AROSA, to AVEEY at 11000FT, to TT460, to TT461, to CIVIC at 7000FT, to TT462, to TT463, to TT464, to EPSON at 7000FT, to CREAM.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AROSA	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	AVEEY	-	277 (269.8)	-7.5	16.4	-	11000	230	-	RNAV1
003	TF	TT460	-	352 (344.5)	-7.5	7.2	-	-	-	-	RNAV1
004	TF	TT461	-	044 (036.1)	-7.5	14.4	-	-	-	-	RNAV1
005	TF	CIVIC	-	345 (337.7)	-7.5	8.8	-	7000	210	-	RNAV1
006	TF	TT462	-	345 (337.7)	-7.5	6.4	-	-	-	-	RNAV1
007	TF	TT463	-	006 (358.0)	-7.5	6.9	-	-	-	-	RNAV1
008	TF	TT464	-	341 (333.5)	-7.5	5.4	-	-	-	-	RNAV1
009	TF	EPSON	-	317 (309.0)	-7.5	6.9	-	7000	210	-	RNAV1
010	TF	CREAM	-	211 (203.6)	-7.5	14.1	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	AVEEY	314 (306.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	CIVIC	345 (337.7)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	CREAM	291 (283.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
ARLON	351525.3N / 1395859.8E	TT459	344712.8N / 1395716.3E
AROSA	344201.7N / 1404157.3E	TT460	344852.6N / 1401936.8E
AVEEY	344155.9N / 1402158.0E	TT461	350030.2N / 1402957.9E
CIVIC	350840.6N / 1402552.1E	TT462	351433.3N / 1402254.8E
CREAM	351743.4N / 1400612.4E	TT463	352125.4N / 1402237.1E
EPSON	353036.2N / 1401305.9E	TT464	352617.6N / 1401938.6E
KAIHO	351857.8N / 1394642.4E	UMUKI	351219.1N / 1394849.2E
TT457	344714.3N / 1401602.7E	WALTZ	345014.4N / 1394510.7E
TT458	344819.1N / 1400710.5E	WEDGE	350900.4N / 1395846.5E

CHANGE : AVEEY renamed

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY34R/34L

GODIN 2A ARRIVAL / GODIN 2K ARRIVAL
GODIN 1C ARRIVAL

RNAV 1

Note 1) DME/DME/IRU or GNSS required.
2) RADAR service required.

VAR 8° W

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

KAIHO
MHA 4000

NOT TO SCALE

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

ARLON
MHA 4000

NOT TO SCALE

VOR/DME
HANEDA
112.2 HME
CH-59X :::
35°33'44"N/139°45'40"E
100FT

NOT TO SCALE

DME
MORIYA
1174 SND
CH-87X :::
35°56'06"N/139°58'52"E
100FT

NOT TO SCALE

TACAN
SHIMOFUSA
980 SHT
CH-19X :::
35°48'07"N/140°00'36"E
100FT

NOT TO SCALE

GODIN

11.8
197°

CHIPS
13000

11.7
197°

COLOR
11000

14.3
188°

COPSE

9.4
185°

COACH
8000

8.0
187°

TT465

6.4
336°

TT466

6.5
105°

TT467

6.0
291°

CREAM
MHA 4000

NOT TO SCALE

111°

COACH
MHA 4000

9.0
98°

EDDIE
8000

210KIAS

TT468

6.7
256°

ANDEN

13.0
291°

UMUKI
6000

6.9
278°

TT469

6.2
308°

ARLON

13.7
278°

KAIHO

6.9
353°

GODIN 2K ARRIVAL

CHANGE : ANDEN established. TT469 abolished.

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

NOT TO SCALE

GODIN
MHA 8000

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

NOT TO SCALE

COLOR
MHA 8000

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

NOT TO SCALE

COACH
MHA 4000

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

NOT TO SCALE

CREAM
MHA 4000

NOT TO SCALE

111°

TT469

TT467

TT466

TT465

TT468

TT469

TT468

TT469

TT468

TT469

TACAN
TATEYAMA
986 TET
CH-25X :::
34°58'15"N/139°50'17"E
500FT

NOT TO SCALE

DME
TATEYAMA
1159 PQD
CH-72X :::
34°56'46"N/139°53'43"E
600FT

NOT TO SCALE

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY34R/34L

GODIN 2A ARRIVAL

From GODIN, to CHIPS at or below 13000FT, to COLOR at or below 11000FT, to COPSE, to COACH at 8000FT, to TT465, to TT466, to TT467, to EDDIE at 8000FT, to TT468, to ANDEN, to ARLON.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	GODIN	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	CHIPS	-	197 (189.1)	-7.5	11.8	-	-13000	-	-	RNAV1
003	TF	COLOR	-	197 (189.1)	-7.5	11.7	-	-11000	-	-	RNAV1
004	TF	COPSE	-	188 (180.8)	-7.5	14.3	-	-	-	-	RNAV1
005	TF	COACH	-	185 (177.8)	-7.5	9.4	-	8000	210	-	RNAV1
006	TF	TT465	-	187 (179.6)	-7.5	8.0	-	-	-	-	RNAV1
007	TF	TT466	-	136 (128.9)	-7.5	6.4	-	-	-	-	RNAV1
008	TF	TT467	-	161 (153.5)	-7.5	5.0	-	-	-	-	RNAV1
009	TF	EDDIE	-	186 (178.0)	-7.5	6.4	-	8000	210	-	RNAV1
010	TF	TT468	-	256 (248.1)	-7.5	6.7	-	-	-	-	RNAV1
011	TF	ANDEN	-	278 (270.2)	-7.5	6.9	-	-	-	-	RNAV1
012	TF	ARLON	-	308 (300.2)	-7.5	6.2	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	GODIN	197 (189.2)	-7.5	1.0(-14000) 1.5(+14001)	-	R	8000	-	-230(-14000) -240(+14001)	RNAV1
Hold	COLOR	197 (189.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	8000	-	-230(-14000) -240(+14001)	RNAV1
Hold	COACH	185 (177.8)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	ARLON	009 (001.6)	-7.5	1.0(-14000) 1.5(+14001)	-	L	4000	-	-230(-14000) -240(+14001)	RNAV1

CHANGE : ANDEN established. TT469 abolished.

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY34R/34L

GODIN 2K ARRIVAL

From GODIN ,to CHIPS at or below 13000FT, to COLOR at or below 11000FT, to COPSE, to COACH at 8000FT, to TT465, to TT466, to TT467, to EDDIE at 8000FT, to TT468, to ANDEN, to UMUKI at or above 6000FT, to KAIHO.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	GODIN	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	CHIPS	-	197 (189.1)	-7.5	11.8	-	-13000	-	-	RNAV1
003	TF	COLOR	-	197 (189.1)	-7.5	11.7	-	-11000	-	-	RNAV1
004	TF	COPSE	-	188 (180.8)	-7.5	14.3	-	-	-	-	RNAV1
005	TF	COACH	-	185 (177.8)	-7.5	9.4	-	8000	210	-	RNAV1
006	TF	TT465	-	187 (179.6)	-7.5	8.0	-	-	-	-	RNAV1
007	TF	TT466	-	136 (128.9)	-7.5	6.4	-	-	-	-	RNAV1
008	TF	TT467	-	161 (153.5)	-7.5	5.0	-	-	-	-	RNAV1
009	TF	EDDIE	-	186 (178.0)	-7.5	6.4	-	8000	210	-	RNAV1
010	TF	TT468	-	256 (248.1)	-7.5	6.7	-	-	-	-	RNAV1
011	TF	ANDEN	-	278 (270.2)	-7.5	6.9	-	-	-	-	RNAV1
012	TF	UMUKI	-	278 (270.2)	-7.5	13.7	-	+6000	-	-	RNAV1
013	TF	KAIHO	-	353 (345.5)	-7.5	6.9	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	GODIN	197 (189.2)	-7.5	1.0(-14000) 1.5(+14001)	-	R	8000	-	-230(-14000) -240(+14001)	RNAV1
Hold	COLOR	197 (189.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	8000	-	-230(-14000) -240(+14001)	RNAV1
Hold	COACH	185 (177.8)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	KAIHO	353 (345.5)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1

CHANGE : ANDEN established. TT469 abolished.

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY34R/34L

GODIN 1C ARRIVAL

From GODIN ,to CHIPS at or below 13000FT, to COLOR at or below 11000FT, to COPSE, to COACH at 8000FT, to TT465, to TT466, to TT467, to EDDIE at 8000FT, to CREAM.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M('T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	GODIN	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	CHIPS	-	197 (189.1)	-7.5	11.8	-	-13000	-	-	RNAV1
003	TF	COLOR	-	197 (189.1)	-7.5	11.7	-	-11000	-	-	RNAV1
004	TF	COPSE	-	188 (180.8)	-7.5	14.3	-	-	-	-	RNAV1
005	TF	COACH	-	185 (177.8)	-7.5	9.4	-	8000	210	-	RNAV1
006	TF	TT465	-	187 (179.6)	-7.5	8.0	-	-	-	-	RNAV1
007	TF	TT466	-	136 (128.9)	-7.5	6.4	-	-	-	-	RNAV1
008	TF	TT467	-	161 (153.5)	-7.5	5.0	-	-	-	-	RNAV1
009	TF	EDDIE	-	186 (178.0)	-7.5	6.4	-	8000	210	-	RNAV1
010	TF	CREAM	-	291 (283.1)	-7.5	13.0	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M('T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	GODIN	197 (189.2)	-7.5	1.0(-14000) 1.5(+14001)	-	R	8000	-	-230(-14000) -240(+14001)	RNAV1
Hold	COLOR	197 (189.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	8000	-	-230(-14000) -240(+14001)	RNAV1
Hold	COACH	185 (177.8)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	CREAM	291 (283.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
ANDEN	351217.9N / 1400534.7E	GODIN	362425.3N / 1401655.9E
ARLON	351525.3N / 1395859.8E	KAIHO	351857.8N / 1394642.4E
CHIPS	361247.7N / 1401436.9E	TT465	352939.2N / 1401235.4E
COACH	353736.0N / 1401231.5E	TT466	352539.0N / 1401840.1E
COLOR	360116.3N / 1401219.8E	TT467	352110.2N / 1402124.4E
COPSE	354658.8N / 1401205.4E	TT468	351216.4N / 1401402.6E
CREAM	351743.4N / 1400612.4E	UMUKI	351219.1N / 1394849.2E
EDDIE	351447.4N / 1402140.9E		

CHANGE : ANDEN established. TT469 abolished.

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY34R/34L

POLIX 2A ARRIVAL / POLIX 2K ARRIVAL
POLIX 1C ARRIVAL

RNAV 1

Note 1) DME/DME/IRU or GNSS required.
2) RADAR service required.

VAR 8° W

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)


KAIHO
MHA 4000

NOT TO SCALE

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

ARLON
MHA 4000

NOT TO SCALE



STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY34R/34L

POLIX 2A ARRIVAL

From POLIX at FL150, to CHIPS at or below 13000FT, to COLOR at or below 11000FT, to COPSE, to COACH at 8000FT, to TT465, to TT466, to TT467, to EDDIE at 8000FT, to TT468, to ANDEN, to ARLON.

Critical DME	—
DME GAP	—
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	POLIX	—	—	-7.5	—	—	FL150	—	—	RNAV1
002	TF	CHIPS	—	279 (271.1)	-7.5	9.5	—	-13000	—	—	RNAV1
003	TF	COLOR	—	197 (189.1)	-7.5	11.7	—	-11000	—	—	RNAV1
004	TF	COPSE	—	188 (180.8)	-7.5	14.3	—	—	—	—	RNAV1
005	TF	COACH	—	185 (177.8)	-7.5	9.4	—	8000	210	—	RNAV1
006	TF	TT465	—	187 (179.6)	-7.5	8.0	—	—	—	—	RNAV1
007	TF	TT466	—	136 (128.9)	-7.5	6.4	—	—	—	—	RNAV1
008	TF	TT467	—	161 (153.5)	-7.5	5.0	—	—	—	—	RNAV1
009	TF	EDDIE	—	186 (178.0)	-7.5	6.4	—	8000	210	—	RNAV1
010	TF	TT468	—	256 (248.1)	-7.5	6.7	—	—	—	—	RNAV1
011	TF	ANDEN	—	278 (270.2)	-7.5	6.9	—	—	—	—	RNAV1
012	TF	ARLON	—	308 (300.2)	-7.5	6.2	—	—	—	—	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	POLIX	310 (302.3)	-7.5	1.0(-14000) 1.5(+14001)	—	L	11000	—	-230(-14000) -240(+14001)	RNAV1
Hold	COLOR	197 (189.1)	-7.5	1.0(-14000) 1.5(+14001)	—	R	8000	—	-230(-14000) -240(+14001)	RNAV1
Hold	COACH	185 (177.8)	-7.5	1.0(-14000) 1.5(+14001)	—	R	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	ARLON	009 (001.6)	-7.5	1.0(-14000) 1.5(+14001)	—	L	4000	—	-230(-14000) -240(+14001)	RNAV1

CHANGE : ANDEN established. TT469 abolished.

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY34R/34L

POLIX 2K ARRIVAL

From POLIX at FL150, to CHIPS at or below 13000FT, to COLOR at or below 11000FT, to COPSE, to COACH at 8000FT, to TT465, to TT466, to TT467, to EDDIE at 8000FT, to TT468, to ANDEN, to UMUKI at or above 6000FT, to KAIHO.

Critical DME	-		
DME GAP	-		
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1		

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	POLIX	-	-	-7.5	-	-	FL150	-	-	RNAV1
002	TF	CHIPS	-	279 (271.1)	-7.5	9.5	-	-13000	-	-	RNAV1
003	TF	COLOR	-	197 (189.1)	-7.5	11.7	-	-11000	-	-	RNAV1
004	TF	COPSE	-	188 (180.8)	-7.5	14.3	-	-	-	-	RNAV1
005	TF	COACH	-	185 (177.8)	-7.5	9.4	-	8000	210	-	RNAV1
006	TF	TT465	-	187 (179.6)	-7.5	8.0	-	-	-	-	RNAV1
007	TF	TT466	-	136 (128.9)	-7.5	6.4	-	-	-	-	RNAV1
008	TF	TT467	-	161 (153.5)	-7.5	5.0	-	-	-	-	RNAV1
009	TF	EDDIE	-	186 (178.0)	-7.5	6.4	-	8000	210	-	RNAV1
010	TF	TT468	-	256 (248.1)	-7.5	6.7	-	-	-	-	RNAV1
011	TF	ANDEN	-	278 (270.2)	-7.5	6.9	-	-	-	-	RNAV1
012	TF	UMUKI	-	278 (270.2)	-7.5	13.7	-	+6000	-	-	RNAV1
013	TF	KAIHO	-	353 (345.5)	-7.5	6.9	-	-	-	-	RNAV1

CHANGE : ANDEN established. TT469 abolished.

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	POLIX	310 (302.3)	-7.5	1.0(-14000) 1.5(+14001)	-	L	11000	-	-230(-14000) -240(+14001)	RNAV1
Hold	COLOR	197 (189.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	8000	-	-230(-14000) -240(+14001)	RNAV1
Hold	COACH	185 (177.8)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	KAIHO	353 (345.5)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY34R/34L

POLIX 1C ARRIVAL

From POLIX at FL150, to CHIPS at or below 13000FT, to COLOR at or below 11000FT, to COPSE, to COACH at 8000FT, to TT465, to TT466, to TT467, to EDDIE at 8000FT, to CREAM.

Critical DME	-		
DME GAP	-		
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1		

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	POLIX	-	-	-7.5	-	-	FL150	-	-	RNAV1
002	TF	CHIPS	-	279 (271.1)	-7.5	9.5	-	-13000	-	-	RNAV1
003	TF	COLOR	-	197 (189.1)	-7.5	11.7	-	-11000	-	-	RNAV1
004	TF	COPSE	-	188 (180.8)	-7.5	14.3	-	-	-	-	RNAV1
005	TF	COACH	-	185 (177.8)	-7.5	9.4	-	8000	210	-	RNAV1
006	TF	TT465	-	187 (179.6)	-7.5	8.0	-	-	-	-	RNAV1
007	TF	TT466	-	136 (128.9)	-7.5	6.4	-	-	-	-	RNAV1
008	TF	TT467	-	161 (153.5)	-7.5	5.0	-	-	-	-	RNAV1
009	TF	EDDIE	-	186 (178.0)	-7.5	6.4	-	8000	210	-	RNAV1
010	TF	CREAM	-	291 (283.1)	-7.5	13.0	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	POLIX	310 (302.3)	-7.5	1.0(-14000) 1.5(+14001)	-	L	11000	-	-230(-14000) -240(+14001)	RNAV1
Hold	COLOR	197 (189.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	8000	-	-230(-14000) -240(+14001)	RNAV1
Hold	COACH	185 (177.8)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	CREAM	291 (283.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
ANDEN	351217.9N / 1400534.7E	KAIHO	351857.8N / 1394642.4E
ARLON	351525.3N / 1395859.8E	POLIX	361237.1N / 1402622.5E
CHIPS	361247.7N / 1401436.9E	TT465	352939.2N / 1401235.4E
COACH	353736.0N / 1401231.5E	TT466	352539.0N / 1401840.1E
COLOR	360116.3N / 1401219.8E	TT467	352110.2N / 1402124.4E
COPSE	354658.8N / 1401205.4E	TT468	351216.4N / 1401402.6E
CREAM	351743.4N / 1400612.4E	UMUKI	351219.1N / 1394849.2E
EDDIE	351447.4N / 1402140.9E		

CHANGE : ANDEN established. TT469 abolished.

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY34R/34L

OSHIMA 2H ARRIVAL / AKSEL 2H ARRIVAL AROSA 2H ARRIVAL

RNAV 1

Note 1) DME/DME/IRU or GNSS required.

2) RADAR service required.

VAR 8° W(2019)

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

VOR/DME
HANEDA
112.2 HME
CH-59X \ddots
35°33'44"N/139°45'40"E

CACAO
D14.0 HME
(D12.1 ITC)

D19.0 HME

332°

133°

MHA 4000/MAX 230KIAS

MHA 4000/MAX 230KIAS

VORTAC
OSHIMA
113.1 XAC
CH-78X 
34°42'44"N/139°24'50"E
2100FT

OSHIMA 2H ARRIVAL

OSHIMA
(XAC)

36.3
095° ————— 14.8°
AKSEI 085°

CLONE

AVEEY
11000
230KIAS

 ABOSA

AKSEL 2H ARRIVAL

AROSA 2H ARRIVAL

CHANGE : AVEEY renamed

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

098° OSHIMA(XAC)
MHA 5000
187°

039°
219°

AVEEY
MHA 5000

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY34R/34L

OSHIMA 2H ARRIVAL

From XAC, to CLONE, to TT460, to TT461, to CIVIC at 7000FT, to TT462, to TT463, to TT464, to EPSON at 7000FT, to CREAM, to CLOAK, to CAMEL, to CACAO.

Note: When cleared HIGHWAY VISUAL RWY34R APPROACH, aircraft should fly via last routing cleared until CACAO.

Critical DME	—
DME GAP	—
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	XAC	—	—	-7.5	—	—	—	—	—	RNAV1
002	TF	CLONE	—	095 (087.8)	-7.5	36.3	—	—	—	—	RNAV1
003	TF	TT460	—	068 (060.7)	-7.5	10.1	—	—	—	—	RNAV1
004	TF	TT461	—	044 (036.1)	-7.5	14.4	—	—	—	—	RNAV1
005	TF	CIVIC	—	345 (337.7)	-7.5	8.8	—	7000	210	—	RNAV1
006	TF	TT462	—	345 (337.7)	-7.5	6.4	—	—	—	—	RNAV1
007	TF	TT463	—	006 (358.0)	-7.5	6.9	—	—	—	—	RNAV1
008	TF	TT464	—	341 (333.5)	-7.5	5.4	—	—	—	—	RNAV1
009	TF	EPSON	—	317 (309.0)	-7.5	6.9	—	7000	210	—	RNAV1
010	TF	CREAM	—	211 (203.6)	-7.5	14.1	—	—	—	—	RNAV1
011	TF	CLOAK	—	247 (240.0)	-7.5	3.8	—	—	—	—	RNAV1
012	TF	CAMEL	—	308 (300.1)	-7.5	3.0	—	—	—	—	RNAV1
013	TF	CACAO	—	338 (330.1)	-7.5	5.7	—	—	—	—	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	XAC	098 (090.3)	-7.5	1.0(-14000) 1.5(+14001)	—	R	5000	—	-230(-14000) -240(+14001)	RNAV1
Hold	CIVIC	345 (337.7)	-7.5	1.0(-14000) 1.5(+14001)	—	R	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	CREAM	291 (283.1)	-7.5	1.0(-14000) 1.5(+14001)	—	R	4000	—	-230(-14000) -240(+14001)	RNAV1

CHANGE : Note added.

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY34R/34L

AKSEL 2H ARRIVAL

From AKSEL, to CLONE, to TT460, to TT461, to CIVIC at 7000FT, to TT462, to TT463, to TT464, to EPSON at 7000FT, to CREAM, to CLOAK, to CAMEL, to CACAO.

Note: When cleared HIGHWAY VISUAL RWY34R APPROACH, aircraft should fly via last routing cleared until CACAO.

Critical DME	—
DME GAP	—
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AKSEL	—	—	-7.5	—	—	—	—	—	RNAV1
002	TF	CLONE	—	085 (077.0)	-7.5	14.8	—	—	—	—	RNAV1
003	TF	TT460	—	068 (060.7)	-7.5	10.1	—	—	—	—	RNAV1
004	TF	TT461	—	044 (036.1)	-7.5	14.4	—	—	—	—	RNAV1
005	TF	CIVIC	—	345 (337.7)	-7.5	8.8	—	7000	210	—	RNAV1
006	TF	TT462	—	345 (337.7)	-7.5	6.4	—	—	—	—	RNAV1
007	TF	TT463	—	006 (358.0)	-7.5	6.9	—	—	—	—	RNAV1
008	TF	TT464	—	341 (333.5)	-7.5	5.4	—	—	—	—	RNAV1
009	TF	EPSON	—	317 (309.0)	-7.5	6.9	—	7000	210	—	RNAV1
010	TF	CREAM	—	211 (203.6)	-7.5	14.1	—	—	—	—	RNAV1
011	TF	CLOAK	—	247 (240.0)	-7.5	3.8	—	—	—	—	RNAV1
012	TF	CAMEL	—	308 (300.1)	-7.5	3.0	—	—	—	—	RNAV1
013	TF	CACAO	—	338 (330.1)	-7.5	5.7	—	—	—	—	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	AKSEL	039 (031.2)	-7.5	1.0(-14000) 1.5(+14001)	—	R	5000	—	-230(-14000) -240(+14001)	RNAV1
Hold	CIVIC	345 (337.7)	-7.5	1.0(-14000) 1.5(+14001)	—	R	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	CREAM	291 (283.1)	-7.5	1.0(-14000) 1.5(+14001)	—	R	4000	—	-230(-14000) -240(+14001)	RNAV1

CHANGE : Note added

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY34R/34L

AROSA 2H ARRIVAL

From AROSA, to AVEEY at 11000FT, to TT460, to TT461, to CIVIC at 7000FT, to TT462, to TT463, to TT464, to EPSON at 7000FT, to CREAM, to CLOAK, to CAMEL, to CACAO.

Note: When cleared HIGHWAY VISUAL RWY34R APPROACH, aircraft should fly via last routing cleared until CACAO.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AROSA	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	AVEEY	-	277 (269.8)	-7.5	16.4	-	11000	230	-	RNAV1
003	TF	TT460	-	352 (344.5)	-7.5	7.2	-	-	-	-	RNAV1
004	TF	TT461	-	044 (036.1)	-7.5	14.4	-	-	-	-	RNAV1
005	TF	CIVIC	-	345 (337.7)	-7.5	8.8	-	7000	210	-	RNAV1
006	TF	TT462	-	345 (337.7)	-7.5	6.4	-	-	-	-	RNAV1
007	TF	TT463	-	006 (358.0)	-7.5	6.9	-	-	-	-	RNAV1
008	TF	TT464	-	341 (333.5)	-7.5	5.4	-	-	-	-	RNAV1
009	TF	EPSON	-	317 (309.0)	-7.5	6.9	-	7000	210	-	RNAV1
010	TF	CREAM	-	211 (203.6)	-7.5	14.1	-	-	-	-	RNAV1
011	TF	CLOAK	-	247 (240.0)	-7.5	3.8	-	-	-	-	RNAV1
012	TF	CAMEL	-	308 (300.1)	-7.5	3.0	-	-	-	-	RNAV1
013	TF	CACAO	-	338 (330.1)	-7.5	5.7	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	AVEEY	314 (306.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	CIVIC	345 (337.7)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	CREAM	291 (283.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1

CHANGE : Note added

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY34R/34L

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
AKSEL	344039.5N / 1395126.9E	CREAM	351743.4N / 1400612.4E
AROSA	344201.7N / 1404157.3E	EPSON	353036.2N / 1401305.9E
AVEEY	344155.9N / 1402158.0E	TT460	344852.6N / 1401936.8E
CACAO	352212.8N / 1395530.1E	TT461	350030.2N / 1402957.9E
CAMEL	351718.2N / 1395857.8E	TT462	351433.3N / 1402254.8E
CIVIC	350840.6N / 1402552.1E	TT463	352125.4N / 1402237.1E
CLOAK	351548.0N / 1400208.2E	TT464	352617.6N / 1401938.6E
CLONE	344357.8N / 1400856.0E	XAC	344244.1N / 1392450.5E

CHANGE : AVEEY renamed

INTENTIONALLY LEFT BLANK

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

GODIN 1H ARRIVAL
POLIX 1H ARRIVAL

RNAV STAR RWY34R/34L


RNAV 1

Note 1) DME/DME/IRU or GNSS required.

2) RADAR service required.

VAR 8° W(2019)

GODIN 1H ARRIVAL



POLIX 1H ARRIVAL

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)



POLIX MHA 11000
310°
730°

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)



VOR/DME
HANEDA
112.2 HME
CH-59X \cdots
 $35^{\circ}33'44"N/139^{\circ}45'40"E$
100FT

CHANGE : New PROC

CACAO
D14.0 HME
(D12.1 ITC)
332°
152°
D19.0 HME
MHA 4000/MAX 230KIAS

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

CREAM
MHA 4000

TACAN
ONJUKU
1191 OJT
CH-104X \cdots
 $35^{\circ}11'03"N/140^{\circ}22'17"E$
400FT

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY34R/34L

GODIN 1H ARRIVAL

From GODIN, to CHIPS at or below 13000FT, to COLOR at or below 11000FT, to COPSE, to COACH at 8000FT, to TT465, to TT466, to TT467, to EDDIE at 8000FT, to CREAM, to CLOAK, to CAMEL, to CACAO.

Note: When cleared HIGHWAY VISUAL RWY34R APPROACH, aircraft should fly via last routing cleared until CACAO.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	GODIN	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	CHIPS	-	197 (189.1)	-7.5	11.8	-	-13000	-	-	RNAV1
003	TF	COLOR	-	197 (189.1)	-7.5	11.7	-	-11000	-	-	RNAV1
004	TF	COPSE	-	188 (180.8)	-7.5	14.3	-	-	-	-	RNAV1
005	TF	COACH	-	185 (177.8)	-7.5	9.4	-	8000	210	-	RNAV1
006	TF	TT465	-	187 (179.6)	-7.5	8.0	-	-	-	-	RNAV1
007	TF	TT466	-	136 (128.9)	-7.5	6.4	-	-	-	-	RNAV1
008	TF	TT467	-	161 (153.5)	-7.5	5.0	-	-	-	-	RNAV1
009	TF	EDDIE	-	186 (178.0)	-7.5	6.4	-	8000	210	-	RNAV1
010	TF	CREAM	-	291 (283.1)	-7.5	13.0	-	-	-	-	RNAV1
011	TF	CLOAK	-	247 (240.0)	-7.5	3.8	-	-	-	-	RNAV1
012	TF	CAMEL	-	308 (300.1)	-7.5	3.0	-	-	-	-	RNAV1
013	TF	CACAO	-	338 (330.1)	-7.5	5.7	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	GODIN	197 (189.2)	-7.5	1.0(-14000) 1.5(+14001)	-	R	8000	-	-230(-14000) -240(+14001)	RNAV1
Hold	COLOR	197 (189.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	8000	-	-230(-14000) -240(+14001)	RNAV1
Hold	COACH	185 (177.8)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	CREAM	291 (283.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1

CHANGE : Note added.

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY34R/34L

POLIX 1H ARRIVAL

From POLIX at FL150, to CHIPS at or below 13000FT, to COLOR at or below 11000FT, to COPSE, to COACH at 8000FT, to TT465, to TT466, to TT467, to EDDIE at 8000FT, to CREAM, to CLOAK, to CAMEL, to CACAO.

Note: When cleared HIGHWAY VISUAL RWY34R APPROACH, aircraft should fly via last routing cleared until CACAO.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	POLIX	-	-	-7.5	-	-	FL150	-	-	RNAV1
002	TF	CHIPS	-	279 (271.1)	-7.5	9.5	-	-13000	-	-	RNAV1
003	TF	COLOR	-	197 (189.1)	-7.5	11.7	-	-11000	-	-	RNAV1
004	TF	COPSE	-	188 (180.8)	-7.5	14.3	-	-	-	-	RNAV1
005	TF	COACH	-	185 (177.8)	-7.5	9.4	-	8000	210	-	RNAV1
006	TF	TT465	-	187 (179.6)	-7.5	8.0	-	-	-	-	RNAV1
007	TF	TT466	-	136 (128.9)	-7.5	6.4	-	-	-	-	RNAV1
008	TF	TT467	-	161 (153.5)	-7.5	5.0	-	-	-	-	RNAV1
009	TF	EDDIE	-	186 (178.0)	-7.5	6.4	-	8000	210	-	RNAV1
010	TF	CREAM	-	291 (283.1)	-7.5	13.0	-	-	-	-	RNAV1
011	TF	CLOAK	-	247 (240.0)	-7.5	3.8	-	-	-	-	RNAV1
012	TF	CAMEL	-	308 (300.1)	-7.5	3.0	-	-	-	-	RNAV1
013	TF	CACAO	-	338 (330.1)	-7.5	5.7	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	POLIX	310 (302.3)	-7.5	1.0(-14000) 1.5(+14001)	-	L	11000	-	-230(-14000) -240(+14001)	RNAV1
Hold	COLOR	197 (189.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	8000	-	-230(-14000) -240(+14001)	RNAV1
Hold	COACH	185 (177.8)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	CREAM	291 (283.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1

CHANGE : Note added.

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY34R/34L

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
CACAO	352212.8N / 1395530.1E	CREAM	351743.4N / 1400612.4E
CAMEL	351718.2N / 1395857.8E	EDDIE	351447.4N / 1402140.9E
CHIPS	361247.7N / 1401436.9E	GODIN	362425.3N / 1401655.9E
CLOAK	351548.0N / 1400208.2E	POLIX	361237.1N / 1402622.5E
COACH	353736.0N / 1401231.5E	TT465	352939.2N / 1401235.4E
COLOR	360116.3N / 1401219.8E	TT466	352539.0N / 1401840.1E
COPSE	354658.8N / 1401205.4E	TT467	352110.2N / 1402124.4E

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY22/23


OSHIMA 1N ARRIVAL
OSHIMA 2N ARRIVAL

RNAV 1

Note 1) DME/DME/IRU or GNSS required.

2) RADAR service required.

VAR 8° W(2019)



STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY22/23

OSHIMA 1N ARRIVAL

From XAC, to ANZAC at 13000FT, to SOLAR at 13000FT, to SCOUT, to TT250, to TT251, to TT252, to STOCK at 13000FT, to SHAFT at 8000FT, to NYLON.

Critical DME	—
DME GAP	—
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	XAC	—	—	-7.5	—	—	—	—	—	RNAV1
002	TF	ANZAC	—	068 (060.8)	-7.5	15.9	—	13000	230	—	RNAV1
003	TF	SOLAR	—	026 (018.4)	-7.5	9.1	—	13000	230	—	RNAV1
004	TF	SCOUT	—	052 (044.3)	-7.5	10.1	—	—	—	—	RNAV1
005	TF	TT250	—	131 (123.1)	-7.5	9.0	—	—	—	—	RNAV1
006	TF	TT251	—	110 (102.5)	-7.5	7.1	—	—	—	—	RNAV1
007	TF	TT252	—	092 (084.3)	-7.5	7.1	—	—	—	—	RNAV1
008	TF	STOCK	—	071 (063.6)	-7.5	9.0	—	13000	230	—	RNAV1
009	TF	SHAFT	—	330 (322.4)	-7.5	22.5	—	8000	—	—	RNAV1
010	TF	NYLON	—	357 (350.0)	-7.5	18.1	—	—	—	—	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	XAC	098 (090.3)	-7.5	1.0(-14000) 1.5(+14001)	—	R	5000	—	-230(-14000) -240(+14001)	RNAV1
Hold	ANZAC	068 (060.8)	-7.5	1.0(-14000) 1.5(+14001)	—	L	5000	—	-230(-14000) -240(+14001)	RNAV1
Hold	SHAFT	330 (322.4)	-7.5	1.0(-14000) 1.5(+14001)	—	R	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	NYLON	357 (350.0)	-7.5	1.0(-14000) 1.5(+14001)	—	L	4000	—	-230(-14000) -240(+14001)	RNAV1

CHANGE : ACCORN abolished. ANZAC established.

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY22/23

OSHIMA 2N ARRIVAL

From XAC, to AKSEL at 12000FT, to LAFIT at or below 10000FT, to STING at or below 9000FT, to SPARK at or below 7000FT, to SHAFT at 5000FT, to NYLON.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	XAC	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	AKSEL	-	103 (095.3)	-7.5	22.0	-	12000	230	-	RNAV1
003	TF	LAFIT	-	067 (059.5)	-7.5	15.3	-	-10000	-	-	RNAV1
004	TF	STING	-	067 (059.6)	-7.5	7.0	-	-9000	-	-	RNAV1
005	TF	SPARK	-	005 (357.4)	-7.5	11.3	-	-7000	-	-	RNAV1
006	TF	SHAFT	-	005 (357.4)	-7.5	19.3	-	5000	-	-	RNAV1
007	TF	NYLON	-	357 (350.0)	-7.5	18.1	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	XAC	098 (090.3)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	AKSEL	039 (031.2)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	STING	067 (059.6)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	SHAFT	330 (322.4)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	NYLON	357 (350.0)	-7.5	1.0(-14000) 1.5(+14001)	-	L	4000	-	-230(-14000) -240(+14001)	RNAV1

CHANGE : ACCORN abolished. ANZAC established.


Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
AKSEL	344039.5N / 1395126.9E	SPARK	350312.0N / 1401416.7E
ANZAC	345028.8N / 1394146.7E	STOCK	350438.7N / 1403002.9E
LAFIT	344826.0N / 1400732.4E	STING	345157.9N / 1401453.4E
NYLON	354018.5N / 1400919.9E	TT250	350129.7N / 1400308.5E
SCOUT	350624.1N / 1395356.8E	TT251	345957.7N / 1401136.0E
SHAFT	352227.4N / 1401313.3E	TT252	350039.9N / 1402013.0E
SOLAR	345909.2N / 1394518.5E	XAC	344244.1N / 1392450.5E

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY22/23



CHANGE : ACCORN abolished ANZAC established

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY22/23

OSHIMA 1B ARRIVAL

From XAC, to ANZAC at 13000FT, to SOLAR at 13000FT, to SCOUT, to TT250, to TT251, to TT252, to STOCK at 13000FT, to SHAFT at 8000FT, to BACON.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	XAC	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	ANZAC	-	068 (060.8)	-7.5	15.9	-	13000	230	-	RNAV1
003	TF	SOLAR	-	026 (018.4)	-7.5	9.1	-	13000	230	-	RNAV1
004	TF	SCOUT	-	052 (044.3)	-7.5	10.1	-	-	-	-	RNAV1
005	TF	TT250	-	131 (123.1)	-7.5	9.0	-	-	-	-	RNAV1
006	TF	TT251	-	110 (102.5)	-7.5	7.1	-	-	-	-	RNAV1
007	TF	TT252	-	092 (084.3)	-7.5	7.1	-	-	-	-	RNAV1
008	TF	STOCK	-	071 (063.6)	-7.5	9.0	-	13000	230	-	RNAV1
009	TF	SHAFT	-	330 (322.4)	-7.5	22.5	-	8000	-	-	RNAV1
010	TF	BACON	-	003 (355.2)	-7.5	9.5	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	XAC	098 (090.3)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	ANZAC	068 (060.8)	-7.5	1.0(-14000) 1.5(+14001)	-	L	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	SHAFT	330 (322.4)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	BACON	003 (355.2)	-7.5	1.0(-14000) 1.5(+14001)	-	L	4000	-	-230(-14000) -240(+14001)	RNAV1

CHANGE : ACORN abolished. ANZAC established.

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY22/23

OSHIMA 2B ARRIVAL

From XAC, to AKSEL at 12000FT, to LAFIT at or below 10000FT, to STING at or below 9000FT, to SPARK at or below 7000FT, to SHAFT at 5000FT, to BACON.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	XAC	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	AKSEL	-	103 (095.3)	-7.5	22.0	-	12000	230	-	RNAV1
003	TF	LAFIT	-	067 (059.5)	-7.5	15.3	-	-10000	-	-	RNAV1
004	TF	STING	-	067 (059.6)	-7.5	7.0	-	-9000	-	-	RNAV1
005	TF	SPARK	-	005 (357.4)	-7.5	11.3	-	-7000	-	-	RNAV1
006	TF	SHAFT	-	005 (357.4)	-7.5	19.3	-	5000	-	-	RNAV1
007	TF	BACON	-	003 (355.2)	-7.5	9.5	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	XAC	098 (090.3)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	AKSEL	039 (031.2)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	STING	067 (059.6)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	SHAFT	330 (322.4)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	BACON	003 (355.2)	-7.5	1.0(-14000) 1.5(+14001)	-	L	4000	-	-230(-14000) -240(+14001)	RNAV1

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
AKSEL	344039.5N / 1395126.9E	SPARK	350312.0N / 1401416.7E
ANZAC	345028.8N / 1394146.7E	STOCK	350438.7N / 1403002.9E
BACON	353155.0N / 1401215.1E	STING	345157.9N / 1401453.4E
LAFIT	344826.0N / 1400732.4E	TT250	350129.7N / 1400308.5E
SCOUT	350624.1N / 1395356.8E	TT251	345957.7N / 1401136.0E
SHAFT	352227.4N / 1401313.3E	TT252	350039.9N / 1402013.0E
SOLAR	345909.2N / 1394518.5E	XAC	344244.1N / 1392450.5E

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY22/23

AKSEL 1N ARRIVAL
AKSEL 2N ARRIVAL


RNAV 1

Note 1) DME/DME/IRU or GNSS required.

2) RADAR service required.

VAR 8° W(2019)

VOR/DME
HANEDA
112.2 HME
CH-59X
35°33'44"N/139°45'40"E
100FT



NYLON

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

NYLON
MHA 4000

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

SHAFT
MHA 4000


SHAFT
8000
5000
for AKSEL 1N ARRIVAL only
for AKSEL 2N ARRIVAL only

TACAN
ONJUKU
1191 OJT
CH-104X
35°11'03"N/140°22'17"E
400FT

AKSEL 1N ARRIVAL

TACAN
TATEYAMA
986 TET
CH-25X
34°58'15"N/139°50'17"E
500FT

DME
TATEYAMA
1159 PQD
CH-72X
34°56'46"N/139°53'43"E
600FT



STOWE
12000
230KIAS

SPARK
7000

AKSEL 2N ARRIVAL

CHANGE : STOWE renamed

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

AKSEL
MHA 5000

039°
219°

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

STING
MHA 4000

067°
241°

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY22/23

AKSEL 1N ARRIVAL

From AKSEL at 12000FT, to SALLY at 12000FT, to TT253, to TT254, to TT255, to STOWE at 12000FT, to SHAFT at 8000FT, to NYLON.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AKSEL	-	-	-7.5	-	-	12000	230	-	RNAV1
002	TF	SALLY	-	023 (015.0)	-7.5	13.4	-	12000	230	-	RNAV1
003	TF	TT253	-	048 (040.5)	-7.5	8.5	-	-	-	-	RNAV1
004	TF	TT254	-	109 (102.0)	-7.5	7.6	-	-	-	-	RNAV1
005	TF	TT255	-	092 (084.4)	-7.5	7.6	-	-	-	-	RNAV1
006	TF	STOWE	-	071 (063.6)	-7.5	9.6	-	12000	230	-	RNAV1
007	TF	SHAFT	-	330 (322.4)	-7.5	24.0	-	8000	-	-	RNAV1
008	TF	NYLON	-	357 (350.0)	-7.5	18.1	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	AKSEL	039 (031.2)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	SHAFT	330 (322.4)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	NYLON	357 (350.0)	-7.5	1.0(-14000) 1.5(+14001)	-	L	4000	-	-230(-14000) -240(+14001)	RNAV1

CHANGE : STOWE renamed

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY22/23

AKSEL 2N ARRIVAL

From AKSEL at 12000FT, to LAFIT at or below 10000FT, to STING at or below 9000FT, to SPARK at or below 7000FT, to SHAFT at 5000FT, to NYLON.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AKSEL	-	-	-7.5	-	-	12000	230	-	RNAV1
002	TF	LAFIT	-	067 (059.5)	-7.5	15.3	-	-10000	-	-	RNAV1
003	TF	STING	-	067 (059.6)	-7.5	7.0	-	-9000	-	-	RNAV1
004	TF	SPARK	-	005 (357.4)	-7.5	11.3	-	-7000	-	-	RNAV1
005	TF	SHAFT	-	005 (357.4)	-7.5	19.3	-	5000	-	-	RNAV1
006	TF	NYLON	-	357 (350.0)	-7.5	18.1	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	AKSEL	039 (031.2)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	STING	067 (059.6)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	SHAFT	330 (322.4)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	NYLON	357 (350.0)	-7.5	1.0(-14000) 1.5(+14001)	-	L	4000	-	-230(-14000) -240(+14001)	RNAV1

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
AKSEL	344039.5N / 1395126.9E	STING	345157.9N / 1401453.4E
LAFIT	344826.0N / 1400732.4E	STOWE	350325.9N / 1403111.4E
NYLON	354018.5N / 1400919.9E	TT253	350001.4N / 1400224.6E
SALLY	345333.9N / 1395540.1E	TT254	345826.5N / 1401129.4E
SHAFT	352227.4N / 1401313.3E	TT255	345910.9N / 1402041.4E
SPARK	350312.0N / 1401416.7E		

CHANGE : STOWE renamed

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY22/23

AKSEL 1B ARRIVAL
AKSEL 2B ARRIVAL


RNAV 1

Note 1) DME/DME/IRU or GNSS required.

2) RADAR service required.

VAR 8° W(2019)

VOR/DME
HANEDA
112.2 HME
CH-59X
35°33'44"N/139°45'40"E
100FT



MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

BACON
MHA 4000
183° ↘ 003°

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

SHAFT
MHA 4000
150° ↘ 330°

SHAFT
8000 for AKSEL 1B ARRIVAL only
5000 for AKSEL 2B ARRIVAL only


TACAN
ONJUKU
1191 OJT
CH-104X
35°11'03"N/140°22'17"E
400FT

AKSEL 1B ARRIVAL

TACAN
TATEYAMA
986 TET
CH-25X
34°58'15"N/139°50'17"E
500FT

DME
TATEYAMA
1159 PQD
CH-72X
34°56'46"N/139°53'43"E
600FT

SALLY
12000
230KIAS



MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

AKSEL
MHA 5000
039° ↗ 219°

AKSEL 2B ARRIVAL

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

STING
MHA 4000
067° ↗ 241°

CHANGE : STOWE renamed

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY22/23

AKSEL 1B ARRIVAL

From AKSEL at 12000FT, to SALLY at 12000FT, to TT253, to TT254, to TT255, to STOWE at 12000FT, to SHAFT at 8000FT, to BACON.

Critical DME	—
DME GAP	—
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AKSEL	—	—	-7.5	—	—	12000	230	—	RNAV1
002	TF	SALLY	—	023 (015.0)	-7.5	13.4	—	12000	230	—	RNAV1
003	TF	TT253	—	048 (040.5)	-7.5	8.5	—	—	—	—	RNAV1
004	TF	TT254	—	109 (102.0)	-7.5	7.6	—	—	—	—	RNAV1
005	TF	TT255	—	092 (084.4)	-7.5	7.6	—	—	—	—	RNAV1
006	TF	STOWE	—	071 (063.6)	-7.5	9.6	—	12000	230	—	RNAV1
007	TF	SHAFT	—	330 (322.4)	-7.5	24.0	—	8000	—	—	RNAV1
008	TF	BACON	—	003 (355.2)	-7.5	9.5	—	—	—	—	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	AKSEL	039 (031.2)	-7.5	1.0(-14000) 1.5(+14001)	—	R	5000	—	-230(-14000) -240(+14001)	RNAV1
Hold	SHAFT	330 (322.4)	-7.5	1.0(-14000) 1.5(+14001)	—	R	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	BACON	003 (355.2)	-7.5	1.0(-14000) 1.5(+14001)	—	L	4000	—	-230(-14000) -240(+14001)	RNAV1

CHANGE : STOWE renamed

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY22/23

AKSEL 2B ARRIVAL

From AKSEL at 12000FT, to LAFIT at or below 10000FT, to STING at or below 9000FT, to SPARK at or below 7000FT, to SHAFT at 5000FT, to BACON.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AKSEL	-	-	-7.5	-	-	12000	230	-	RNAV1
002	TF	LAFIT	-	067 (059.5)	-7.5	15.3	-	-10000	-	-	RNAV1
003	TF	STING	-	067 (059.6)	-7.5	7.0	-	-9000	-	-	RNAV1
004	TF	SPARK	-	005 (357.4)	-7.5	11.3	-	-7000	-	-	RNAV1
005	TF	SHAFT	-	005 (357.4)	-7.5	19.3	-	5000	-	-	RNAV1
006	TF	BACON	-	003 (355.2)	-7.5	9.5	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	AKSEL	039 (031.2)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	STING	067 (059.6)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	SHAFT	330 (322.4)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	BACON	003 (355.2)	-7.5	1.0(-14000) 1.5(+14001)	-	L	4000	-	-230(-14000) -240(+14001)	RNAV1

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
AKSEL	344039.5N / 1395126.9E	STING	345157.9N / 1401453.4E
BACON	353155.0N / 1401215.1E	STOWE	350325.9N / 1403111.4E
LAFIT	344826.0N / 1400732.4E	TT253	350001.4N / 1400224.6E
SALLY	345333.9N / 1395540.1E	TT254	345826.5N / 1401129.4E
SHAFT	352227.4N / 1401313.3E	TT255	345910.9N / 1402041.4E
SPARK	350312.0N / 1401416.7E		

CHANGE : STOWE renamed

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL


AROSA 1N ARRIVAL
AROSA 2N ARRIVAL

RNAV STAR RWY22/23

RNAV 1

Note 1) DME/DME/IRU or GNSS required.
2) RADAR service required.

VAR 8° W(2019)



CHANGE : RTE FM AVEEY to TT256 (ALDEN established)

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY22/23

AROSA 1N ARRIVAL

From AROSA, to AVEEY at 11000FT, to ALDEN at 11000FT, to TT256, to TT257, to SLICK at 11000FT, to SHAFT at 8000FT, to NYLON.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AROSA	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	AVEEY	-	277 (269.8)	-7.5	16.4	-	11000	230	-	RNAV1
003	TF	ALDEN	-	337 (330.0)	-7.5	11.3	-	11000	230	-	RNAV1
004	TF	TT256	-	337 (329.9)	-7.5	6.1	-	-	-	-	RNAV1
005	TF	TT257	-	290 (282.4)	-7.5	8.1	-	-	-	-	RNAV1
006	TF	SLICK	-	311 (303.1)	-7.5	10.2	-	11000	230	-	RNAV1
007	TF	SHAFT	-	052 (044.3)	-7.5	25.6	-	8000	-	-	RNAV1
008	TF	NYLON	-	357 (350.0)	-7.5	18.1	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	AVEEY	314 (306.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	SHAFT	330 (322.4)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	NYLON	357 (350.0)	-7.5	1.0(-14000) 1.5(+14001)	-	L	4000	-	-230(-14000) -240(+14001)	RNAV1

CHANGE : RTE FM AVEEY to TT256 (ALDEN established). HLDG pattern at STING deleted.

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY22/23

AROSA 2N ARRIVAL

From AROSA, to AVEEY at 11000FT, to STING at or below 9000FT, to SPARK at or below 7000FT, to SHAFT at 5000FT, to NYLON.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AROSA	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	AVEEY	-	277 (269.8)	-7.5	16.4	-	11000	230	-	RNAV1
003	TF	STING	-	337 (330.0)	-7.5	11.6	-	-9000	-	-	RNAV1
004	TF	SPARK	-	005 (357.4)	-7.5	11.3	-	-7000	-	-	RNAV1
005	TF	SHAFT	-	005 (357.4)	-7.5	19.3	-	5000	-	-	RNAV1
006	TF	NYLON	-	357 (350.0)	-7.5	18.1	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	AVEEY	314 (306.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	STING	067 (059.6)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	SHAFT	330 (322.4)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	NYLON	357 (350.0)	-7.5	1.0(-14000) 1.5(+14001)	-	L	4000	-	-230(-14000) -240(+14001)	RNAV1

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
ALDEN	345141.1N / 1401505.3E	SLICK	350412.7N / 1395120.0E
AROSA	344201.7N / 1404157.3E	SPARK	350312.0N / 1401416.7E
AVEEY	344155.9N / 1402158.0E	STING	345157.9N / 1401453.4E
NYLON	354018.5N / 1400919.9E	TT256	345655.4N / 1401122.9E
SHAFT	352227.4N / 1401313.3E	TT257	345838.5N / 1400146.6E

CHANGE : ALDEN established

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL


RNAV STAR RWY22/23

AROSA 1B ARRIVAL
AROSA 2B ARRIVAL

RNAV 1

Note 1) DME/DME/IRU or GNSS required.

2) RADAR service required.



STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY22/23

AROSA 1B ARRIVAL

From AROSA, to AVEEY at 11000FT, to ALDEN at 11000FT, to TT256, to TT257, to SLICK at 11000FT, to SHAFT at 8000FT, to BACON.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AROSA	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	AVEEY	-	277 (269.8)	-7.5	16.4	-	11000	230	-	RNAV1
003	TF	ALDEN	-	337 (330.0)	-7.5	11.3	-	11000	230	-	RNAV1
004	TF	TT256	-	337 (329.9)	-7.5	6.1	-	-	-	-	RNAV1
005	TF	TT257	-	290 (282.4)	-7.5	8.1	-	-	-	-	RNAV1
006	TF	SLICK	-	311 (303.1)	-7.5	10.2	-	11000	230	-	RNAV1
007	TF	SHAFT	-	052 (044.3)	-7.5	25.6	-	8000	-	-	RNAV1
008	TF	BACON	-	003 (355.2)	-7.5	9.5	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	AVEEY	314 (306.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	SHAFT	330 (322.4)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	BACON	003 (355.2)	-7.5	1.0(-14000) 1.5(+14001)	-	L	4000	-	-230(-14000) -240(+14001)	RNAV1

CHANGE : RTE FM AVEEY to TT256 (ALDEN established). HLDG pattern at STING deleted.

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY22/23

AROSA 2B ARRIVAL

From AROSA, to AVEEY at 11000FT, to STING at or below 9000FT , to SPARK at or below 7000FT, to SHAFT at 5000FT, to BACON.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AROSA	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	AVEEY	-	277 (269.8)	-7.5	16.4	-	11000	230	-	RNAV1
003	TF	STING	-	337 (330.0)	-7.5	11.6	-	-9000	-	-	RNAV1
004	TF	SPARK	-	005 (357.4)	-7.5	11.3	-	-7000	-	-	RNAV1
005	TF	SHAFT	-	005 (357.4)	-7.5	19.3	-	5000	-	-	RNAV1
006	TF	BACON	-	003 (355.2)	-7.5	9.5	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	AVEEY	314 (306.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	STING	067 (059.6)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	SHAFT	330 (322.4)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	BACON	003 (355.2)	-7.5	1.0(-14000) 1.5(+14001)	-	L	4000	-	-230(-14000) -240(+14001)	RNAV1

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
ALDEN	345141.1N / 1401505.3E	SLICK	350412.7N / 1395120.0E
AROSA	344201.7N / 1404157.3E	SPARK	350312.0N / 1401416.7E
AVEEY	344155.9N / 1402158.0E	STING	345157.9N / 1401453.4E
BACON	353155.0N / 1401215.1E	TT256	345655.4N / 1401122.9E
SHAFT	352227.4N / 1401313.3E	TT257	345838.5N / 1400146.6E

CHANGE : ALDEN established

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

GODIN 1S ARRIVAL
GODIN 1D ARRIVAL


RNAV STAR RWY22/23

RNAV 1

Note 1) DME/DME/IRU or GNSS required.

2) RADAR service required.


VAR 8° W(2019)




MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)




MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)




MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)



MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)



MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)



STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY22/23

GODIN 1S ARRIVAL

From GODIN, to NOVEL at or above 8000FT, to SCREW, to STEAM.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	GODIN	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	NOVEL	-	264 (256.4)	-7.5	14.0	-	+8000	-	-	RNAV1
003	TF	SCREW	-	203 (195.2)	-7.5	18.8	-	-	-	-	RNAV1
004	TF	STEAM	-	168 (160.4)	-7.5	7.6	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	GODIN	197 (189.2)	-7.5	1.0(-14000) 1.5(+14001)	-	R	8000	-	-230(-14000) -240(+14001)	RNAV1
Hold	NOVEL	264 (256.4)	-7.5	1.0(-14000) 1.5(+14001)	-	L	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	SCREW	203 (195.2)	-7.5	1.0(-14000) 1.5(+14001)	-	L	4000	-	-230(-14000) -240(+14001)	RNAV1

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY22/23

GODIN 1D ARRIVAL

From GODIN, to NOVEL at or above 8000FT, to DREAD, to DENNY, to DATUM.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	GODIN	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	NOVEL	-	264 (256.4)	-7.5	14.0	-	+8000	-	-	RNAV1
003	TF	DREAD	-	191 (183.1)	-7.5	17.2	-	-	-	-	RNAV1
004	TF	DENNY	-	167 (159.9)	-7.5	16.5	-	-	-	-	RNAV1
005	TF	DATUM		167 (160.0)	-7.5	5.8	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	GODIN	197 (189.2)	-7.5	1.0(-14000) 1.5(+14001)	-	R	8000	-	-230(-14000) -240(+14001)	RNAV1
Hold	NOVEL	264 (256.4)	-7.5	1.0(-14000) 1.5(+14001)	-	L	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	DREAD	191 (183.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	DENNY	167 (159.9)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
DATUM	354259.6N / 1400824.3E	NOVEL	362106.9N / 1400004.9E
DENNY	354828.8N / 1400556.4E	SCREW	360301.2N / 1395400.4E
DREAD	360359.2N / 1395856.9E	STEAM	355553.3N / 1395708.4E
GODIN	362425.3N / 1401655.9E		

CHANGE : Restriction on NOVEL

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY22/23


POLIX 1S ARRIVAL
POLIX 1D ARRIVAL

RNAV 1

Note 1) DME/DME/IRU or GNSS required.

2) RADAR service required.

VAR 8° W(2019)



VOR/DME
SEKIYADO
117.0 CH-117X
36°00'39"N/139°50'21"E
100FT

DME
MORIYA
1174 CH-87X
35°56'06"N/139°58'52"E
100FT

TACAN
SHIMOFUSA
980 CH-19X
35°48'07"N/140°00'36"E
100FT

CHANGE : COORD of MORIYA DME(SND).

POLIX 1S ARRIVAL POLIX 1D ARRIVAL		RNAV 1
		Note 1) DME/DME/IRU or GNSS required. 2) RADAR service required.
<u>POLIX 1S ARRIVAL</u>	<u>POLIX 1D ARRIVAL</u>	
<p>MAX 230KIAS(at or below FL140) MAX 240KIAS(above FL140) 1MIN(at or below FL140) 1.5MIN(above FL140)</p> <p>SCREW MHA 4000</p>	<p>MAX 230KIAS(at or below FL140) MAX 240KIAS(above FL140) 1MIN(at or below FL140) 1.5MIN(above FL140)</p> <p>POLIX MHA 11000</p>	
<p>MAX 230KIAS(at or below FL140) MAX 240KIAS(above FL140) 1MIN(at or below FL140) 1.5MIN(above FL140)</p> <p>DREAD MHA 5000</p>	<p>MAX 230KIAS(at or below FL140) MAX 240KIAS(above FL140) 1MIN(at or below FL140) 1.5MIN(above FL140)</p> <p>GODIN MHA 8000</p>	
<p>MAX 230KIAS(at or below FL140) MAX 240KIAS(above FL140) 1MIN(at or below FL140) 1.5MIN(above FL140)</p> <p>DENN MHA 4000</p>	<p>MAX 230KIAS(at or below FL140) MAX 240KIAS(above FL140) 1MIN(at or below FL140) 1.5MIN(above FL140)</p> <p>NOVEL MHA 5000</p>	

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY22/23

POLIX 1S ARRIVAL

From POLIX at FL150, to GODIN, to NOVEL at or above 8000FT, to SCREW, to STEAM.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	POLIX	-	-	-7.5	-	-	FL150	-	-	RNAV1
002	TF	GODIN	-	335 (327.2)	-7.5	14.1	-	-	-	-	RNAV1
003	TF	NOVEL	-	264 (256.4)	-7.5	14.0	-	+8000	-	-	RNAV1
004	TF	SCREW	-	203 (195.2)	-7.5	18.8	-	-	-	-	RNAV1
005	TF	STEAM	-	168 (160.4)	-7.5	7.6	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	POLIX	310 (302.3)	-7.5	1.0(-14000) 1.5(+14001)	-	L	11000	-	-230(-14000) -240(+14001)	RNAV1
Hold	GODIN	197 (189.2)	-7.5	1.0(-14000) 1.5(+14001)	-	R	8000	-	-230(-14000) -240(+14001)	RNAV1
Hold	NOVEL	264 (256.4)	-7.5	1.0(-14000) 1.5(+14001)	-	L	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	SCREW	203 (195.2)	-7.5	1.0(-14000) 1.5(+14001)	-	L	4000	-	-230(-14000) -240(+14001)	RNAV1

CHANGE : Restriction on NOVEL

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY22/23

POLIX 1D ARRIVAL

From POLIX at FL150, to GODIN, to NOVEL at or above 8000FT, to DREAD, to DENNY, to DATUM.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	POLIX	-	-	-7.5	-	-	FL150	-	-	RNAV1
002	TF	GODIN	-	335 (327.2)	-7.5	14.1	-	-	-	-	RNAV1
003	TF	NOVEL	-	264 (256.4)	-7.5	14.0	-	+8000	-	-	RNAV1
004	TF	DREAD	-	191 (183.1)	-7.5	17.2	-	-	-	-	RNAV1
005	TF	DENNY	-	167 (159.9)	-7.5	16.5	-	-	-	-	RNAV1
006	TF	DATUM	-	167 (160.0)	-7.5	5.8	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	POLIX	310 (302.3)	-7.5	1.0(-14000) 1.5(+14001)	-	L	11000	-	-230(-14000) -240(+14001)	RNAV1
Hold	GODIN	197 (189.2)	-7.5	1.0(-14000) 1.5(+14001)	-	R	8000	-	-230(-14000) -240(+14001)	RNAV1
Hold	NOVEL	264 (256.4)	-7.5	1.0(-14000) 1.5(+14001)	-	L	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	DREAD	191 (183.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	DENNY	167 (159.9)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
DATUM	354259.6N / 1400824.3E	NOVEL	362106.9N / 1400004.9E
DENNY	354828.8N / 1400556.4E	POLIX	361237.1N / 1402622.5E
DREAD	360359.2N / 1395856.9E	SCREW	360301.2N / 1395400.4E
GODIN	362425.3N / 1401655.9E	STEAM	355553.3N / 1395708.4E

CHANGE : Restriction on NOVEL

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY16L/16R

OSHIMA L ARRIVAL
OSHIMA R ARRIVAL

RNAV 1

Note 1) DME/DME/IRU or GNSS required.

2) RADAR service required.

VAR 8° W(2019)

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

NUMAN
MHA 4000

180°
360°

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

NEURO
MHA 4000

110°
290°

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

ANZAC
MHA 5000

248°
068°

OSHIMA L ARRIVAL
OSHIMA R ARRIVAL

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

SNARE
MHA 4000

717°
297°

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)


SPINE
MHA 4000

168°
348°

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

SHAFT
MHA 4000

150°
330°



MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

OSHIMA(XAC)
MHA 5000

098°
278°

OSHIMA L ARRIVAL
SPINE
SNOKE
SHAFT 9000

OSHIMA R ARRIVAL
NUMAN
210KIAS

OSHIMA L ARRIVAL
NUMAN
210KIAS
13.4
011°
SHAFT 9000
SCOPE 10000

CHANGE : ACCORN, T6L60 abolished. ANZAC, SACHS established.

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY16L/16R

OSHIMA L ARRIVAL

From XAC, to ANZAC, to SOLAR at 13000FT, to SCOUT, to TT250, to TT251, to TT252, to STOCK at 13000FT, to SHAFT at 9000FT, to SNOKE, to SPINE, to SOPPY at or below 7000FT, to SNARE at 6000FT, to SACHS, to SANDY.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	XAC	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	ANZAC	-	068 (060.8)	-7.5	15.9	-	-	-	-	RNAV1
003	TF	SOLAR	-	026 (018.4)	-7.5	9.1	-	13000	230	-	RNAV1
004	TF	SCOUT	-	052 (044.3)	-7.5	10.1	-	-	-	-	RNAV1
005	TF	TT250	-	131 (123.1)	-7.5	9.0	-	-	-	-	RNAV1
006	TF	TT251	-	110 (102.5)	-7.5	7.1	-	-	-	-	RNAV1
007	TF	TT252	-	092 (084.3)	-7.5	7.1	-	-	-	-	RNAV1
008	TF	STOCK	-	071 (063.6)	-7.5	9.0	-	13000	230	-	RNAV1
009	TF	SHAFT	-	330 (322.4)	-7.5	22.5	-	9000		-	RNAV1
010	TF	SNOKE	-	011 (003.4)	-7.5	13.4	-	-	-	-	RNAV1
011	TF	SPINE	-	348 (340.6)	-7.5	6.8	-	-	-	-	RNAV1
012	TF	SOPPY	-	297 (289.2)	-7.5	8.4	-	-7000	-	-	RNAV1
013	TF	SNARE	-	297 (289.1)	-7.5	7.8	-	6000	-	-	RNAV1
014	TF	SACHS	-	297 (289.0)	-7.5	3.4	-	-	-	-	RNAV1
015	TF	SANDY	-	288 (280.0)	-7.5	3.8	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	XAC	098 (090.3)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	ANZAC	068 (060.8)	-7.5	1.0(-14000) 1.5(+14001)	-	L	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	SHAFT	330 (322.4)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	SPINE	348 (340.6)	-7.5	1.0(-14000) 1.5(+14001)	-	L	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	SNARE	297 (289.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1

CHANGE : ACCORN, T6L60 abolished. ANZAC, SACHS established.

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY16L/16R

OSHIMA R ARRIVAL

From XAC, to ANZAC, to SOLAR, to SCOUT, to SCOPE at 10000FT, to T6R70, to NUMAN at 9000FT, to NORIK, to T6R71, to T6R72, to NURSE at 9000FT, to NEURO at 6000FT, to NIGEL at 6000FT, to NATTY.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	XAC	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	ANZAC	-	068 (060.8)	-7.5	15.9	-	-	-	-	RNAV1
003	TF	SOLAR	-	026 (018.4)	-7.5	9.1	-	-	230	-	RNAV1
004	TF	SCOUT	-	052 (044.3)	-7.5	10.1	-	-	-	-	RNAV1
005	TF	SCOPE	-	036 (028.5)	-7.5	20.0	-	10000	-	-	RNAV1
006	TF	T6R70	-	036 (028.6)	-7.5	14.0	-	-	-	-	RNAV1
007	TF	NUMAN	-	360 (352.5)	-7.5	11.1	-	9000	210	-	RNAV1
008	TF	NORIK	-	360 (352.5)	-7.5	7.3	-	-	-	-	RNAV1
009	TF	T6R71	-	006 (358.9)	-7.5	6.5	-	-	-	-	RNAV1
010	TF	T6R72	-	342 (334.4)	-7.5	5.0	-	-	-	-	RNAV1
011	TF	NURSE	-	317 (309.8)	-7.5	6.5	-	9000	210	-	RNAV1
012	TF	NEURO	-	213 (205.5)	-7.5	13.5	-	6000	-	-	RNAV1
013	TF	NIGEL	-	252 (244.1)	-7.5	3.1	-	6000	-	-	RNAV1
014	TF	NATTY	-	252 (244.1)	-7.5	5.2	-	-	-	-	RNAV1

CHANGE : ACCORN abolished. ANZAC established.

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	XAC	098 (090.3)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	ANZAC	068 (060.8)	-7.5	1.0(-14000) 1.5(+14001)	-	L	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	NUMAN	360 (352.5)	-7.5	1.0(-14000) 1.5(+14001)	-	L	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	NEURO	290 (282.9)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY16L/16R

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
ANZAC	345028.8N / 1394146.7E	SNOKE	353551.6N / 1401411.7E
NATTY	355350.9N / 1394531.3E	SOLAR	345909.2N / 1394518.5E
NEURO	355727.6N / 1395441.3E	SOPPY	354458.8N / 1400140.3E
NIGEL	355607.5N / 1395117.8E	SPINE	354213.5N / 1401125.8E
NORIK	355428.9N / 1401054.5E	STOCK	350438.7N / 1403002.9E
NUMAN	354714.4N / 1401204.9E	T6R70	353614.4N / 1401351.4E
NURSE	360939.3N / 1400153.3E	T6R71	360059.5N / 1401045.1E
SACHS	354838.2N / 1394838.4E	T6R72	360530.2N / 1400804.3E
SANDY	354917.5N / 1394402.8E	TT250	350129.7N / 1400308.5E
SCOPE	352358.4N / 1400538.3E	TT251	345957.7N / 1401136.0E
SCOUT	350624.1N / 1395356.8E	TT252	350039.9N / 1402013.0E
SHAFT	352227.4N / 1401313.3E	XAC	344244.1N / 1392450.5E
SNARE	354731.1N / 1395238.1E		

CHANGE : ACCORN, T6L60 abolished. ANZAC, SACHS established.

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY16L/16R

AKSEL L ARRIVAL
AKSEL R ARRIVAL


RNAV 1

Note 1) DME/DME/IRU or GNSS required.

2) RADAR service required.

VAR 8° W(2019)

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)




MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)



VOR/DME
HANEDA
112.2 HME
CH-59X
35°33'44"N/139°45'40"E
100FT



MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

SNARE
MHA 4000



MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

SPINE
MHA 4000



MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

SHAFT
MHA 4000

CHANGE : T6L60 abolished. SACHS established.

AKSEL R ARRIVAL

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

AKSEL L ARRIVAL

SPINE
SNOKE
SHAFT
STOWE
SCOPE
TT253
TT254
TT255
SALLY
AKSEL

AKSEL L ARRIVAL

NUMAN (9000)
210KIAS
T6R70
SCOPE (10000)

Civil Aviation Bureau,Japan (EFF:2 DEC 2021)

7/10/21

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY16L/16R

AKSEL L ARRIVAL

From AKSEL, to SALLY at 12000FT, to TT253, to TT254, to TT255, to STOWE at 12000FT, to SHAFT at 9000FT, to SNOKE, to SPINE, to SOPPY at or below 7000FT, to SNARE at 6000FT, to SACHS, to SANDY.

Critical DME	—	
DME GAP	—	
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1	

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AKSEL	—	—	-7.5	—	—	—	—	—	RNAV1
002	TF	SALLY	—	023 (015.0)	-7.5	13.4	—	12000	230	—	RNAV1
003	TF	TT253	—	048 (040.5)	-7.5	8.5	—	—	—	—	RNAV1
004	TF	TT254	—	109 (102.0)	-7.5	7.6	—	—	—	—	RNAV1
005	TF	TT255	—	092 (084.4)	-7.5	7.6	—	—	—	—	RNAV1
006	TF	STOWE	—	071 (063.6)	-7.5	9.6	—	12000	230	—	RNAV1
007	TF	SHAFT	—	330 (322.4)	-7.5	24.0	—	9000	—	—	RNAV1
008	TF	SNOKE	—	011 (003.4)	-7.5	13.4	—	—	—	—	RNAV1
009	TF	SPINE	—	348 (340.6)	-7.5	6.8	—	—	—	—	RNAV1
010	TF	SOPPY	—	297 (289.2)	-7.5	8.4	—	-7000	—	—	RNAV1
011	TF	SNARE	—	297 (289.1)	-7.5	7.8	—	6000	—	—	RNAV1
012	TF	SACHS	—	297 (289.0)	-7.5	3.4	—	—	—	—	RNAV1
013	TF	SANDY	—	288 (280.0)	-7.5	3.8	—	—	—	—	RNAV1

CHANGE : T6L60 abolished, SACHS established.

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	AKSEL	039 (031.2)	-7.5	1.0(-14000) 1.5(+14001)	—	R	5000	—	-230(-14000) -240(+14001)	RNAV1
Hold	SHAFT	330 (322.4)	-7.5	1.0(-14000) 1.5(+14001)	—	R	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	SPINE	348 (340.6)	-7.5	1.0(-14000) 1.5(+14001)	—	L	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	SNARE	297 (289.1)	-7.5	1.0(-14000) 1.5(+14001)	—	R	4000	—	-230(-14000) -240(+14001)	RNAV1

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY16L/16R

AKSEL R ARRIVAL

From AKSEL, to SALLY, to SCOUT, to SCOPE at 10000FT, to T6R70, to NUMAN at 9000FT, to NORIK, to T6R71, to T6R72, to NURSE at 9000FT, to NEURO at 6000FT, to NIGEL at 6000FT, to NATTY.

Critical DME	—
DME GAP	—
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AKSEL	—	—	-7.5	—	—	—	—	—	RNAV1
002	TF	SALLY	—	023 (015.0)	-7.5	13.4	—	—	230	—	RNAV1
003	TF	SCOUT	—	001 (353.7)	-7.5	12.9	—	—	—	—	RNAV1
004	TF	SCOPE	—	036 (028.5)	-7.5	20.0	—	10000	—	—	RNAV1
005	TF	T6R70	—	036 (028.6)	-7.5	14.0	—	—	—	—	RNAV1
006	TF	NUMAN	—	360 (352.5)	-7.5	11.1	—	9000	210	—	RNAV1
007	TF	NORIK	—	360 (352.5)	-7.5	7.3	—	—	—	—	RNAV1
008	TF	T6R71	—	006 (358.9)	-7.5	6.5	—	—	—	—	RNAV1
009	TF	T6R72	—	342 (334.4)	-7.5	5.0	—	—	—	—	RNAV1
010	TF	NURSE	—	317 (309.8)	-7.5	6.5	—	9000	210	—	RNAV1
011	TF	NEURO	—	213 (205.5)	-7.5	13.5	—	6000	—	—	RNAV1
012	TF	NIGEL	—	252 (244.1)	-7.5	3.1	—	6000	—	—	RNAV1
013	TF	NATTY	—	252 (244.1)	-7.5	5.2	—	—	—	—	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	AKSEL	039 (031.2)	-7.5	1.0(-14000) 1.5(+14001)	—	R	5000	—	-230(-14000) -240(+14001)	RNAV1
Hold	NUMAN	360 (352.5)	-7.5	1.0(-14000) 1.5(+14001)	—	L	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	NEURO	290 (282.9)	-7.5	1.0(-14000) 1.5(+14001)	—	R	4000	—	-230(-14000) -240(+14001)	RNAV1

CHANGE : New PROC

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY16L/16R

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
AKSEL	344039.5N / 1395126.9E	SHAFT	352227.4N / 1401313.3E
NATTY	355350.9N / 1394531.3E	SNARE	354731.1N / 1395238.1E
NEURO	355727.6N / 1395441.3E	SNOKE	353551.6N / 1401411.7E
NIGEL	355607.5N / 1395117.8E	SOPPY	354458.8N / 1400140.3E
NORIK	355428.9N / 1401054.5E	SPINE	354213.5N / 1401125.8E
NUMAN	354714.4N / 1401204.9E	STOWE	350325.9N / 1403111.4E
NURSE	360939.3N / 1400153.3E	T6R70	353614.4N / 1401351.4E
SACHS	354838.2N / 1394838.4E	T6R71	360059.5N / 1401045.1E
SALLY	345333.9N / 1395540.1E	T6R72	360530.2N / 1400804.3E
SANDY	354917.5N / 1394402.8E	TT253	350001.4N / 1400224.6E
SCOPE	352358.4N / 1400538.3E	TT254	345826.5N / 1401129.4E
SCOUT	350624.1N / 1395356.8E	TT255	345910.9N / 1402041.4E

CHANGE : T6L60 abolished. SACHS established.

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY16L/16R

AROSA L ARRIVAL
AROSA R ARRIVAL

RNAV 1

- Note 1) DME/DME/IRU or GNSS required.
2) RADAR service required.

VAR 8° W(2019)

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

NUMAN
MHA 4000

081°
096°
108°

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

NEURO
MHA 4000

110°
290°

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

SNARE
MHA 4000

717°
297°

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

SPINE
MHA 4000

89°
84°
83°


AROSA L ARRIVAL

SPINE
SNOKE
SHAFT
9000
13.4
011°
84°
83°
89°

AROSA R ARRIVAL

NUMAN
9000
210KIAS
096°
111°
T6R70
14°
036°
SCOPE
10000

VOR/DME
HANEDA
112.2 HME
CH-59X
35°33'44"N/139°45'40"E
100FT



MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

SHAFT
MHA 4000

150°
330°

MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

AVEEY
MHA 5000

134°
314°

CHANGE : T6L60 abolished. SACHS established.

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY16L/16R

AROSA L ARRIVAL

From AROSA, to AVEEY at 11000FT, to ALDEN at 11000FT, to TT256, to TT257, to SLICK at 11000FT, to SHAFT at 9000FT, to SNOKE, to SPINE, to SOPPY at or below 7000FT, to SNARE at 6000FT, to SACHS, to SANDY.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AROSA	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	AVEEY	-	277 (269.8)	-7.5	16.4	-	11000	230	-	RNAV1
003	TF	ALDEN	-	337 (330.0)	-7.5	11.3	-	11000	230	-	RNAV1
004	TF	TT256	-	337 (329.9)	-7.5	6.1	-	-	-	-	RNAV1
005	TF	TT257	-	290 (282.4)	-7.5	8.1	-	-	-	-	RNAV1
006	TF	SLICK	-	311 (303.1)	-7.5	10.2	-	11000	230	-	RNAV1
007	TF	SHAFT	-	052 (044.3)	-7.5	25.6	-	9000	-	-	RNAV1
008	TF	SNOKE	-	011 (003.4)	-7.5	13.4	-	-	-	-	RNAV1
009	TF	SPINE	-	348 (340.6)	-7.5	6.8	-	-	-	-	RNAV1
010	TF	SOPPY	-	297 (289.2)	-7.5	8.4	-	-7000	-	-	RNAV1
011	TF	SNARE	-	297 (289.1)	-7.5	7.8	-	6000	-	-	RNAV1
012	TF	SACHS	-	297 (289.0)	-7.5	3.4	-	-	-	-	RNAV1
013	TF	SANDY	-	288 (280.0)	-7.5	3.8	-	-	-	-	RNAV1

CHANGE : T6L60 abolished. SACHS established.

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	AVEEY	314 (306.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	SHAFT	330 (322.4)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	SPINE	348 (340.6)	-7.5	1.0(-14000) 1.5(+14001)	-	L	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	SNARE	297 (289.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY16L/16R

AROSA R ARRIVAL

From AROSA, to AVEEY at 11000FT, to ALDEN at 11000FT, to TT256, to TT257, to SCOUT, to SCOPE at 10000FT, to T6R70, to NUMAN at 9000FT, to NORIK, to T6R71, to T6R72, to NURSE at 9000FT, to NEURO at 6000FT, to NIGEL at 6000FT, to NATTY.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AROSA	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	AVEEY	-	277 (269.8)	-7.5	16.4	-	11000	230	-	RNAV1
003	TF	ALDEN	-	337 (330.0)	-7.5	11.3	-	11000	230	-	RNAV1
004	TF	TT256	-	337 (329.9)	-7.5	6.1	-	-	-	-	RNAV1
005	TF	TT257	-	290 (282.4)	-7.5	8.1	-	-	-	-	RNAV1
006	TF	SCOUT	-	328 (320.5)	-7.5	10.1	-	-	-	-	RNAV1
007	TF	SCOPE	-	036 (028.5)	-7.5	20.0	-	10000	-	-	RNAV1
008	TF	T6R70	-	036 (028.6)	-7.5	14.0	-	-	-	-	RNAV1
009	TF	NUMAN	-	360 (352.5)	-7.5	11.1	-	9000	210	-	RNAV1
010	TF	NORIK	-	360 (352.5)	-7.5	7.3	-	-	-	-	RNAV1
011	TF	T6R71	-	006 (358.9)	-7.5	6.5	-	-	-	-	RNAV1
012	TF	T6R72	-	342 (334.4)	-7.5	5.0	-	-	-	-	RNAV1
013	TF	NURSE	-	317 (309.8)	-7.5	6.5	-	9000	210	-	RNAV1
014	TF	NEURO	-	213 (205.5)	-7.5	13.5	-	6000	-	-	RNAV1
015	TF	NIGEL	-	252 (244.1)	-7.5	3.1	-	6000	-	-	RNAV1
016	TF	NATTY	-	252 (244.1)	-7.5	5.2	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	AVEEY	314 (306.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	NUMAN	360 (352.5)	-7.5	1.0(-14000) 1.5(+14001)	-	L	4000	-	-230(-14000) -240(+14001)	RNAV1
Hold	NEURO	290 (282.9)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1

CHANGE : New PROC

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY16L/16R

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
ALDEN	345141.1N / 1401505.3E	SCOUT	350624.1N / 1395356.8E
AROSA	344201.7N / 1404157.3E	SHAFT	352227.4N / 1401313.3E
AVEEY	344155.9N / 1402158.0E	SLICK	350412.7N / 1395120.0E
NATTY	355350.9N / 1394531.3E	SNARE	354731.1N / 1395238.1E
NEURO	355727.6N / 1395441.3E	SNOKE	353551.6N / 1401411.7E
NIGEL	355607.5N / 1395117.8E	SOPPY	354458.8N / 1400140.3E
NORIK	355428.9N / 1401054.5E	SPINE	354213.5N / 1401125.8E
NUMAN	354714.4N / 1401204.9E	T6R70	353614.4N / 1401351.4E
NURSE	360939.3N / 1400153.3E	T6R71	360059.5N / 1401045.1E
SACHS	354838.2N / 1394838.4E	T6R72	360530.2N / 1400804.3E
SANDY	354917.5N / 1394402.8E	TT256	345655.4N / 1401122.9E
SCOPE	352358.4N / 1400538.3E	TT257	345838.5N / 1400146.6E

CHANGE : T6L60 abolished. SACHS established.

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL


GODIN L ARRIVAL
GODIN R ARRIVAL

RNAV STAR RWY16L/16R

RNAV 1

- Note 1) DME/DME/IRU or GNSS required.
2) RADAR service required.

VAR 8° W(2019)



MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)



NOVEL
MHA 5000

264°
084°


MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)
1MIN(at or below FL140)
1.5MIN(above FL140)

017°
197°


GODIN
MHA 8000



GODIN R ARRIVAL



GODIN L ARRIVAL



CHANGE : T6L60 abolished, SACHS established.

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY16L/16R

GODIN L ARRIVAL

From GODIN, to NOVEL at 8000FT, to NAMCO, to TT680, to TT681, to NILUS at 8000FT, to SNARE at 6000FT, to SACHS, to SANDY.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	GODIN	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	NOVEL	-	264 (256.4)	-7.5	14.0	-	8000	210	-	RNAV1
003	TF	NAMCO	-	177 (169.8)	-7.5	10.7	-	-	-	-	RNAV1
004	TF	TT680	-	137 (129.7)	-7.5	7.0	-	-	-	-	RNAV1
005	TF	TT681	-	162 (154.3)	-7.5	5.4	-	-	-	-	RNAV1
006	TF	NILUS	-	186 (178.9)	-7.5	7.0	-	8000	210	-	RNAV1
007	TF	SNARE	-	255 (247.0)	-7.5	17.2	-	6000	-	-	RNAV1
008	TF	SACHS	-	297 (289.0)	-7.5	3.4	-	-	-	-	RNAV1
009	TF	SANDY	-	288 (280.0)	-7.5	3.8	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	GODIN	197 (189.2)	-7.5	1.0(-14000) 1.5(+14001)	-	R	8000	-	-230(-14000) -240(+14001)	RNAV1
Hold	NOVEL	264 (256.4)	-7.5	1.0(-14000) 1.5(+14001)	-	L	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	SNARE	297 (289.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1

CHANGE : T6L60 abolished. SACHS established.

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY16L/16R

GODIN R ARRIVAL

From GODIN, to NOVEL at 8000FT, to NAMCO, to TT680, to TT681, to NILUS at 8000FT, to NEURO at 6000FT, to NIGEL at 6000FT, to NATTY.

Critical DME	–
DME GAP	–
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	GODIN	–	–	-7.5	–	–	–	–	–	RNAV1
002	TF	NOVEL	–	264 (256.4)	-7.5	14.0	–	8000	210	–	RNAV1
003	TF	NAMCO	–	177 (169.8)	-7.5	10.7	–	–	–	–	RNAV1
004	TF	TT680	–	137 (129.7)	-7.5	7.0	–	–	–	–	RNAV1
005	TF	TT681	–	162 (154.3)	-7.5	5.4	–	–	–	–	RNAV1
006	TF	NILUS	–	186 (178.9)	-7.5	7.0	–	8000	210	–	RNAV1
007	TF	NEURO	–	290 (282.9)	-7.5	14.5	–	6000	–	–	RNAV1
008	TF	NIGEL	–	252 (244.1)	-7.5	3.1	–	6000	–	–	RNAV1
009	TF	NATTY	–	252 (244.1)	-7.5	5.2	–	–	–	–	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	GODIN	197 (189.2)	-7.5	1.0(-14000) 1.5(+14001)	–	R	8000	–	-230(-14000) -240(+14001)	RNAV1
Hold	NOVEL	264 (256.4)	-7.5	1.0(-14000) 1.5(+14001)	–	L	5000	–	-230(-14000) -240(+14001)	RNAV1
Hold	NEURO	290 (282.9)	-7.5	1.0(-14000) 1.5(+14001)	–	R	4000	–	-230(-14000) -240(+14001)	RNAV1

CHANGE : New PROC

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY16L/16R


Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
GODIN	362425.3N / 1401655.9E	NOVEL	362106.9N / 1400004.9E
NAMCO	361035.1N / 1400226.3E	SACHS	354838.2N / 1394838.4E
NATTY	355350.9N / 1394531.3E	SANDY	354917.5N / 1394402.8E
NEURO	355727.6N / 1395441.3E	SNARE	354731.1N / 1395238.1E
NIGEL	355607.5N / 1395117.8E	TT680	360608.2N / 1400904.0E
NILUS	355415.2N / 1401208.8E	TT681	360113.8N / 1401158.7E

CHANGE : T6L60 abolished. SACHS established.

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL



STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY16L/16R

POLIX L ARRIVAL

From POLIX at FL150, to GODIN, to NOVEL at 8000FT, to NAMCO, to TT680, to TT681, to NILUS at 8000FT, to SNARE at 6000FT, to SACHS, to SANDY.

Critical DME	—
DME GAP	—
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	POLIX	—	—	-7.5	—	—	FL150	—	—	RNAV1
002	TF	GODIN	—	335 (327.2)	-7.5	14.1	—	—	—	—	RNAV1
003	TF	NOVEL	—	264 (256.4)	-7.5	14.0	—	8000	210	—	RNAV1
004	TF	NAMCO	—	177 (169.8)	-7.5	10.7	—	—	—	—	RNAV1
005	TF	TT680	—	137 (129.7)	-7.5	7.0	—	—	—	—	RNAV1
006	TF	TT681	—	162 (154.3)	-7.5	5.4	—	—	—	—	RNAV1
007	TF	NILUS	—	186 (178.9)	-7.5	7.0	—	8000	210	—	RNAV1
008	TF	SNARE	—	255 (247.0)	-7.5	17.2	—	6000	—	—	RNAV1
009	TF	SACHS	—	297 (289.0)	-7.5	3.4	—	—	—	—	RNAV1
010	TF	SANDY	—	288 (280.0)	-7.5	3.8	—	—	—	—	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	POLIX	310 (302.3)	-7.5	1.0(-14000) 1.5(+14001)	—	L	11000	—	-230(-14000) -240(+14001)	RNAV1
Hold	GODIN	197 (189.2)	-7.5	1.0(-14000) 1.5(+14001)	—	R	8000	—	-230(-14000) -240(+14001)	RNAV1
Hold	NOVEL	264 (256.4)	-7.5	1.0(-14000) 1.5(+14001)	—	L	5000	—	-230(-14000) -240(+14001)	RNAV1
Hold	SNARE	297 (289.1)	-7.5	1.0(-14000) 1.5(+14001)	—	R	4000	—	-230(-14000) -240(+14001)	RNAV1

CHANGE : T6L60 abolished. SACHS established.

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY16L/16R

POLIX R ARRIVAL

From POLIX at FL150, to GODIN, to NOVEL at 8000FT, to NAMCO, to TT680, to TT681, to NILUS at 8000FT, to NEURO at 6000FT, to NIGEL at 6000FT, to NATTY.

Critical DME	—
DME GAP	—
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	POLIX	—	—	-7.5	—	—	FL150	—	—	RNAV1
002	TF	GODIN	—	335 (327.2)	-7.5	14.1	—	—	—	—	RNAV1
003	TF	NOVEL	—	264 (256.4)	-7.5	14.0	—	8000	210	—	RNAV1
004	TF	NAMCO	—	177 (169.8)	-7.5	10.7	—	—	—	—	RNAV1
005	TF	TT680	—	137 (129.7)	-7.5	7.0	—	—	—	—	RNAV1
006	TF	TT681	—	162 (154.3)	-7.5	5.4	—	—	—	—	RNAV1
007	TF	NILUS	—	186 (178.9)	-7.5	7.0	—	8000	210	—	RNAV1
008	TF	NEURO	—	290 (282.9)	-7.5	14.5	—	6000	—	—	RNAV1
009	TF	NIGEL	—	252 (244.1)	-7.5	3.1	—	6000	—	—	RNAV1
010	TF	NATTY	—	252 (244.1)	-7.5	5.2	—	—	—	—	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	POLIX	310 (302.3)	-7.5	1.0(-14000) 1.5(+14001)	—	L	11000	—	-230(-14000) -240(+14001)	RNAV1
Hold	GODIN	197 (189.2)	-7.5	1.0(-14000) 1.5(+14001)	—	R	8000	—	-230(-14000) -240(+14001)	RNAV1
Hold	NOVEL	264 (256.4)	-7.5	1.0(-14000) 1.5(+14001)	—	L	5000	—	-230(-14000) -240(+14001)	RNAV1
Hold	NEURO	290 (282.9)	-7.5	1.0(-14000) 1.5(+14001)	—	R	4000	—	-230(-14000) -240(+14001)	RNAV1

CHANGE : New PROC

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR RWY16L/16R

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
GODIN	362425.3N / 1401655.9E	POLIX	361237.1N / 1402622.5E
NAMCO	361035.1N / 1400226.3E	SACHS	354838.2N / 1394838.4E
NATTY	355350.9N / 1394531.3E	SANDY	354917.5N / 1394402.8E
NEURO	355727.6N / 1395441.3E	SNARE	354731.1N / 1395238.1E
NIGEL	355607.5N / 1395117.8E	TT680	360608.2N / 1400904.0E
NILUS	355415.2N / 1401208.8E	TT681	360113.8N / 1401158.7E
NOVEL	362106.9N / 1400004.9E		

CHANGE : T6L60 abolished. SACHS established.

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR

OSHIMA NIGHT ARRIVAL

From XAC, to UTIBO, to UMUKI at or above 6000FT, to KAIHO.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	XAC	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	UTIBO	-	067 (059.2)	-7.5	27.6	-	-	-	-	RNAV1
003	TF	UMUKI	-	353 (345.5)	-7.5	16.1	-	+6000	-	-	RNAV1
004	TF	KAIHO	-	353 (345.5)	-7.5	6.9	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	XAC	098 (090.3)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	KAIHO	353 (345.5)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR

AKSEL NIGHT ARRIVAL

From AKSEL, to UTIBO, to UMUKI at or above 6000FT, to KAIHO.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AKSEL	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	UTIBO	-	014 (006.6)	-7.5	16.2	-	-	-	-	RNAV1
003	TF	UMUKI	-	353 (345.5)	-7.5	16.1	-	+6000	-	-	RNAV1
004	TF	KAIHO	-	353 (345.5)	-7.5	6.9	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	AKSEL	039 (031.2)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	KAIHO	353 (345.5)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR

AROSA NIGHT ARRIVAL

From AROSA, to AVEEY, to UTIBO, to UMUKI at or above 6000FT, to KAIHO.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AROSA	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	AVEEY	-	277 (269.8)	-7.5	16.4	-	-	-	-	RNAV1
003	TF	UTIBO	-	310 (302.8)	-7.5	27.5	-	-	-	-	RNAV1
004	TF	UMUKI	-	353 (345.5)	-7.5	16.1	-	+6000	-	-	RNAV1
005	TF	KAIHO	-	353 (345.5)	-7.5	6.9	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	AVEEY	314 (306.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	KAIHO	353 (345.5)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR

MESSE NIGHT ARRIVAL

From MESSE, to UTIBO, to UMUKI at or above 6000FT, to KAIHO.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	MESSE	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	UTIBO	-	246 (238.8)	-7.5	27.4	-	-	-	-	RNAV1
003	TF	UMUKI	-	353 (345.5)	-7.5	16.1	-	+6000	-	-	RNAV1
004	TF	KAIHO	-	353 (345.5)	-7.5	6.9	-	-	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	MESSE	246 (238.8)	-7.5	1.0(-14000) 1.5(+14001)	-	L	6000	-	-230(-14000) -240(+14001)	RNAV1
Hold	KAIHO	353 (345.5)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1

Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
AKSEL	344039.5N / 1395126.9E	MESSE	351100.8N / 1402214.7E
AROSA	344201.7N / 1404157.3E	UMUKI	351219.1N / 1394849.2E
AVEEY	344155.9N / 1402158.0E	UTIBO	345647.0N / 1395343.9E
KAIHO	351857.8N / 1394642.4E	XAC	344244.1N / 1392450.5E

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR


**OSHIMA V ARRIVAL / AKSEL V ARRIVAL
AROSA V ARRIVAL / MESSE V ARRIVAL**

RNAV 1

Note 1) DME/DME/IRU or GNSS required.

2) RADAR service required.

VAR 8° W(2019)



STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR

OSHIMA V ARRIVAL

From XAC, to UTIBO, to UMUKI at or above 6000FT, to KAIHO at or above 4000FT, to LD225, to LD224, to DARKS at or above 1800FT.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	XAC	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	UTIBO	-	067 (059.2)	-7.5	27.6	-	-	-	-	RNAV1
003	TF	UMUKI	-	353 (345.5)	-7.5	16.1	-	+6000	-	-	RNAV1
004	TF	KAIHO	-	353 (345.5)	-7.5	6.9	-	+4000	-	-	RNAV1
005	TF	LD225	-	046 (038.9)	-7.5	9.3	-	-	-220	-	RNAV1
006	TF	LD224	-	052 (044.9)	-7.5	9.4	-	-	-	-	RNAV1
007	TF	DARKS	-	307 (299.7)	-7.5	2.8	-	+1800	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	XAC	098 (090.3)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	KAIHO	353 (345.5)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR

AKSEL V ARRIVAL

From AKSEL, to UTIBO, to UMUKI at or above 6000FT, to KAIHO at or above 4000FT, to LD225, to LD224, to DARKS at or above 1800FT.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course 'M('T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AKSEL	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	UTIBO	-	014 (006.6)	-7.5	16.2	-	-	-	-	RNAV1
003	TF	UMUKI	-	353 (345.5)	-7.5	16.1	-	+6000	-	-	RNAV1
004	TF	KAIHO	-	353 (345.5)	-7.5	6.9	-	+4000	-	-	RNAV1
005	TF	LD225	-	046 (038.9)	-7.5	9.3	-	-	-220	-	RNAV1
006	TF	LD224	-	052 (044.9)	-7.5	9.4	-	-	-	-	RNAV1
007	TF	DARKS	-	307 (299.7)	-7.5	2.8	-	+1800	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course 'M('T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	AKSEL	039 (031.2)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	KAIHO	353 (345.5)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR

AROSA V ARRIVAL

From AROSA, to AVEEY, to UTIBO, to UMUKI at or above 6000FT, to KAIHO at or above 4000FT, to LD225, to LD224, to DARKS at or above 1800FT.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AROSA	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	AVEEY	-	277 (269.8)	-7.5	16.4	-	-	-	-	RNAV1
003	TF	UTIBO	-	310 (302.8)	-7.5	27.5	-	-	-	-	RNAV1
004	TF	UMUKI	-	353 (345.5)	-7.5	16.1	-	+6000	-	-	RNAV1
005	TF	KAIHO	-	353 (345.5)	-7.5	6.9	-	+4000	-	-	RNAV1
006	TF	LD225	-	046 (038.9)	-7.5	9.3	-	-	-220	-	RNAV1
007	TF	LD224	-	052 (044.9)	-7.5	9.4	-	-	-	-	RNAV1
008	TF	DARKS	-	307 (299.7)	-7.5	2.8	-	+1800	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	AVEEY	314 (306.1)	-7.5	1.0(-14000) 1.5(+14001)	-	R	5000	-	-230(-14000) -240(+14001)	RNAV1
Hold	KAIHO	353 (345.5)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1

STANDARD ARRIVAL CHART-INSTRUMENT

RJTT / TOKYO INTL

RNAV STAR

MESSE V ARRIVAL

From MESSE, to UTIBO, to UMUKI at or above 6000FT, to KAIHO at or above 4000FT, to LD225, to LD224, to DARKS at or above 1800FT.

Critical DME	-
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1


Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	MESSE	-	-	-7.5	-	-	-	-	-	RNAV1
002	TF	UTIBO	-	246 (238.8)	-7.5	27.4	-	-	-	-	RNAV1
003	TF	UMUKI	-	353 (345.5)	-7.5	16.1	-	+6000	-	-	RNAV1
004	TF	KAIHO	-	353 (345.5)	-7.5	6.9	-	+4000	-	-	RNAV1
005	TF	LD225	-	046 (038.9)	-7.5	9.3	-	-	-220	-	RNAV1
006	TF	LD224	-	052 (044.9)	-7.5	9.4	-	-	-	-	RNAV1
007	TF	DARKS	-	307 (299.7)	-7.5	2.8	-	+1800	-	-	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	MESSE	246 (238.8)	-7.5	1.0(-14000) 1.5(+14001)	-	L	6000	-	-230(-14000) -240(+14001)	RNAV1
Hold	KAIHO	353 (345.5)	-7.5	1.0(-14000) 1.5(+14001)	-	R	4000	-	-230(-14000) -240(+14001)	RNAV1


Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
AKSEL	344039.5N / 1395126.9E	LD225	352614.1N / 1395353.4E
AROSA	344201.7N / 1404157.3E	MESSE	351100.8N / 1402214.7E
AVEEY	344155.9N / 1402158.0E	UMUKI	351219.1N / 1394849.2E
DARKS	353414.8N / 1395902.9E	UTIBO	345647.0N / 1395343.9E
KAIHO	351857.8N / 1394642.4E	XAC	344244.1N / 1392450.5E
LD224	353252.5N / 1400200.0E		


INSTRUMENT APPROACH CHART



INSTRUMENT APPROACH CHART




INSTRUMENT APPROACH CHART



INSTRUMENT APPROACH CHART

RJTT / TOKYO INTL


LOC Y RWY34L



INSTRUMENT APPROACH CHART

RJTT / TOKYO INTL


ILS X RWY34L



INSTRUMENT APPROACH CHART

RJTT / TOKYO INTL

TOKYO APP 119.1 - 119.4 - 119.7 126.5 - 236.8 - 261.2	ILS - LOC 111.7 IHA CH-54X	TOKYO TOWER 118.1 - 124.35 - 118.575 118.725 - 118.8	RADAR AVBL ATIS 128.8
---	-------------------------------	--	--------------------------



MISSED APPROACH

Climb on HDG 337° to HME 3.0DME,
turn right HDG 060° to intercept and
proceed via HME R015/SYE R196 to
KASGA and hold at 4000FT.
Contact TOKYO APP

Timing not authorized for defining the MAPt.

Missed APCH climb gradient MNM 3.0%

MINIMA		THR elev. 18		AD elev. 21
CAT	LOC		CIRCLING	
	MDA(H)	RVR/ CMV	MDA(H)	VIS
A	560 (539)	1000	730 (709)	1600
B		1200		2400
C				3200
D		1600		


MINIMA with Missed APCH climb gradient of 2.5% are not established.

Circling is not authorized during the night time, except counterclockwise circling to RWY16R/16L/34R.

INSTRUMENT APPROACH CHART

RJTT / TOKYO INTL


VOR RWY34L



INSTRUMENT APPROACH CHART

RJTT / TOKYO INTL


ILS Z RWY34R (CAT II & III)



INSTRUMENT APPROACH CHART

RJTT / TOKYO INTL


LOC Z RWY34R



INSTRUMENT APPROACH CHART


RJTT / TOKYO INTL

ILS Y RWY34R (CAT II & III)



MISSED APPROACH

Climb on HDG337° to 800FT, turn right climb to 3000FT via HME R091 to CHIBA and hold. Contact TOKYO APP.

DME to ITC
NM to THR

0.2 0.4 4.6 6.6

0 0.2 4.4 6.4

Missed APCH climb gradient MNM 5.0%

MINIMA THR elev. 20


AD elev. 21

CHANGE: MINIMA(CAT IIIA, IIIB → CAT III).

INSTRUMENT APPROACH CHART

RJTT / TOKYO INTL

LOC Y RWY34R




MISSSED APPROACH

Turn right, climb to 3000FT via HME R091 to CHIBA and hold.
Contact TOKYO APP.

Timing not authorized for defining the MAPt.
No turn before MAPt.

HME




DME to ITC	0.2	0.6	2.1	3.0	3.7	8.7
NM to THR	0	0.5	1.9	2.8	3.5	8.5

MINIMA		THR elev. 20	AD elev. 21	
CAT	LOC	CIRCLING		
	MDA(H)	RVR/ CMV	MDA(H)	VIS
A		1200		
B		1400		1600
C	700 (679)		730 (709)	2400
D		1800		3200

Circling is not authorized during the night time, except counterclockwise circling to RWY 16R/16L and clockwise circling to RWY 34L.


INSTRUMENT APPROACH CHART



INSTRUMENT APPROACH CHART

RJTT / TOKYO INTL


LOC RWY22



MISSSED APPROACH

Turn right, climb to 4000FT via HME
R015 /SYE R196 to KASGA and hold.
Contact TOKYO APP.

Timing not authorized for defining the MAPt.
No turn before MAPt.



Missed APCH climb gradient MNM 4.0%

MINIMA THR elev. 35 AD elev. 21

CAT	LOC		CIRCLING	
	MDA(H)	RVR/ CMV	MDA(H)	VIS
A	1000			1600
B	600 (579)	1200	730 (709)	2400
C				3200
D	1600			


MINIMA with Missed APCH climb gradient of 2.5% are not established.

Circling is not authorized during the night time, except counterclockwise circling to RWY16R/16L and clockwise circling to RWY23,RWY34R/34L.

INSTRUMENT APPROACH CHART

RJTT / TOKYO INTL


LDA Z RWY22



MISSSED APPROACH

At MAPt, turn right climb to 4000FT via HME R015 / SYE R196 to KASGA and hold.
Contact TOKYO APP.

Timing not authorized for defining the MAPt.



Missed APCH climb gradient MNM 4.0%

MINIMA	THR elev. 35	AD elev. 21
CAT	MDA(H)	VIS
A		
B		
C	1000 (979)	6000
D		

**Do Not turn left
until D1.1 IKL**

**SO AS NOT TO MISUNDERSTAND
THE RUNWAY**

MINIMA with Missed APCH climb gradient of 2.5% are not established.
MINIMA APPLICATION CRITERIA in AD1.1.6.10.1.4 are not applicable.

INSTRUMENT APPROACH CHART


RJTT / TOKYO INTL

LDA Z RWY22

Visual Prescribed Track for LDA Z RWY22

Visual manoeuvre with Prescribed Track (VPT) : VPT stands for visual maneuvering after the MAPt using prescribed track.


Note : Remain on the LDA until passing MAPt so as not to penetrate the NTZ, and to avoid the RWY23 traffic.



In case of GO AROUND, pilot should report ATC as soon as practicable.

Until receiving ATC instructions, aircraft turn right for joining HME R015/SYE R196 and missed approach procedure.

INSTRUMENT APPROACH CHART



CHANGE : Update

INSTRUMENT APPROACH CHART


RJTT / TOKYO INTL

LDA Y RWY22

Visual Prescribed Track for LDA Y RWY22

Visual manoeuvre with Prescribed Track (VPT) : VPT stands for visual maneuvering after the MAPt using prescribed track.


Note : Remain on the LDA until passing MAPt so as not to penetrate the NTZ, and to avoid the RWY23 traffic.



In case of GO AROUND, pilot should report ATC as soon as practicable.

Until receiving ATC instructions, aircraft turn left for joining HME R177 and missed approach procedure.

INSTRUMENT APPROACH CHART



INSTRUMENT APPROACH CHART


RJTT / TOKYO INTL

LDA X RWY22

Visual Prescribed Track for LDA X RWY22

Visual manoeuvre with Prescribed Track (VPT) : VPT stands for visual maneuvering after the MAPt using prescribed track.

Note : Remain on the LDA until passing MAPt so as not to penetrate the NTZ, and to avoid the RWY23 traffic.




In case of GO AROUND, pilot should report ATC as soon as practicable.

Until receiving ATC instructions, aircraft turn right for joining HME R015/SYE R196 and missed approach procedure.

INSTRUMENT APPROACH CHART

RJTT / TOKYO INTL

LDA W RWY22



INSTRUMENT APPROACH CHART


RJTT / TOKYO INTL

LDA W RWY22

Visual Prescribed Track for LDA W RWY22

Visual manoeuvre with Prescribed Track (VPT) : VPT stands for visual maneuvering after the MAPt using prescribed track.


Note : Remain on the LDA until passing MAPt so as not to penetrate the NTZ, and to avoid the RWY23 traffic.



In case of GO AROUND, pilot should report ATC as soon as practicable.

Until receiving ATC instructions, aircraft turn right for joining HME R015/SYE R196 and missed approach procedure.


INSTRUMENT APPROACH CHART



INSTRUMENT APPROACH CHART

RJTT / TOKYO INTL


LOC Z RWY23



INSTRUMENT APPROACH CHART

RJTT / TOKYO INTL


ILS Y or LOC Y RWY23



INSTRUMENT APPROACH CHART

RJTT / TOKYO INTL


LDA Z RWY23



MISSED APPROACH

At MAPt, turn left climb to 4500FT via HME R177 to UTIBO via Uraga and hold. Contact TOKYO APP.

Timing not authorized for defining the MAPt.



MINIMA		THR elev. 55	AD elev. 21
CAT	MDA(H)	VIS	
A			
B			
C			
D	1000 (979)	6000	

MINIMA APPLICATION CRITERIA in AD1.1.6.10.1.4 are not applicable.


INSTRUMENT APPROACH CHART

RJTT / TOKYO INTL

LDA Z RWY23

Visual Prescribed Track for LDA Z RWY23

Visual manoeuvre with Prescribed Track (VPT) : VPT stands for visual maneuvering after the MAPt using prescribed track.



CHANGE : Correction of misdescription (ITL COORD).


In case of GO AROUND, pilot should report ATC as soon as practicable.

Until receiving ATC instructions, aircraft turn left HDG 229° for joining HME R177 and missed approach procedure.

INSTRUMENT APPROACH CHART

RJTT / TOKYO INTL

LDA Y RWY23




MISSED APPROACH

At MAPt, turn left climb to 4500FT via HME R177 to UTIBO via URAGA and hold.
Contact TOKYO APP.

Timing not authorized for defining the MAPt.

HME



MINIMA		THR elev. 55	AD elev. 21
CAT	MDA(H)	VIS	
A			
B			
C			
D	1000 (979)	6000	

MINIMA APPLICATION CRITERIA in AD1.1.6.10.1.4 are not applicable.

CHANGE : Update


INSTRUMENT APPROACH CHART

RJTT / TOKYO INTL

LDA Y RWY23

Visual Prescribed Track for LDA Y RWY23

Visual manoeuvre with Prescribed Track (VPT) : VPT stands for visual maneuvering after the MAPt using prescribed track.




CHANGE : Correction of misdescription (ITL COORD).

In case of GO AROUND, pilot should report ATC as soon as practicable.
Until receiving ATC instructions, aircraft turn left HDG 229° for joining HME R177 and missed approach procedure.

INSTRUMENT APPROACH CHART

RJTT / TOKYO INTL


LDA X RWY23



MISSED APPROACH

At MAPt, turn left climb to 4500FT via HME R177 to UTIBO via Uraga and hold. Contact TOKYO APP.

Timing not authorized for defining the MAPt.



	MINIMA	THR elev. 55	AD elev. 21
CAT	MDA(H)	VIS	
A			
B	1000 (979)	6000	
C			
D			

MINIMA APPLICATION CRITERIA in AD1.1.6.10.1.4 are not applicable.


INSTRUMENT APPROACH CHART

RJTT / TOKYO INTL

LDA X RWY23

Visual Prescribed Track for LDA X RWY23



Visual manoeuvre with Prescribed Track (VPT) : VPT stands for visual maneuvering after the MAPt using prescribed track.



INSTRUMENT APPROACH CHART

RJTT / TOKYO INTL

LDA W RWY23



MINIMA		THR elev. 55	AD elev. 21
CAT	MDA(H)	VIS	
A			
B			
C	1000 (979)	6000	
D			

MINIMA APPLICATION CRITERIA in AD1.1.6.10.1.4 are not applicable.


INSTRUMENT APPROACH CHART

RJTT / TOKYO INTL

LDA W RWY23

Visual Prescribed Track for LDA W RWY23


Visual manoeuvre with Prescribed Track (VPT) : VPT stands for visual maneuvering after the MAPt using prescribed track.



INSTRUMENT APPROACH CHART

RJTT / TOKYO INTL

RNP RWY23(AR)



INSTRUMENT APPROACH CHART

RJTT / TOKYO INTL

RNP RWY23(AR)

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	KAIHO	-	-	-7.2	-	-	+6000	-	-	-
002	TF	TT301	-	046 (038.8)	-7.2	12.2	-	4000	-	-	1.0
003	TF	TT302	-	046 (038.8)	-7.2	0.9	-	3715	-	-3.00	0.3
004	RF Center: TTRF1 r=3.10NM	TT303	-	-	-7.2	7.0	L	1490	-165	-3.00	0.3
005	TF	TT304	-	277 (269.6)	-7.2	1.2	-	1119	-	-3.00	0.3
006	RF Center: TTRF2 r=2.00NM	TT305	-	-	-7.2	1.7	L	585	-	-3.00	0.3
007	TF	RW23	Y	230 (222.5)	-7.2	1.5	-	106	-	-3.00/51	0.3
008	TF	TT306	-	230 (222.5)	-7.2	6.5	-	-	-	-	1.0
009	TF	TT307	-	147 (139.9)	-7.2	4.9	-	-	-	-	1.0
010	TF	UTIBO	-	177 (169.9)	-7.2	27.6	-	4500	-	-	1.0


Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
KAIHO	351857.83N / 1394642.43E	TTRF1	353106.44N / 1395349.88E
TT301	352828.24N / 1395606.98E	TTRF2	353212.62N / 1395225.48E
TT302	352909.99N / 1395647.99E		
TT303	353413.28N / 1395350.00E		
TT304	353412.77N / 1395224.45E		
TT305	353332.98N / 1395034.74E		
RW23	353226.15N / 1394919.61E		
TT306	352740.05N / 1394357.98E		
TT307	352356.01N / 1394749.03E		
UTIBO	345647.02N / 1395343.90E		


CHANGE : PROC renamed.

INSTRUMENT APPROACH CHART


RJTT / TOKYO INTL




INSTRUMENT APPROACH CHART



INSTRUMENT APPROACH CHART





INSTRUMENT APPROACH CHART



INSTRUMENT APPROACH CHART


RJTT / TOKYO INTL

VOR A (for RWY16R/RWY16L)




MINIMA		AD elev. 21	
CAT	CIRCLING		
	MDA(H)	VIS	
A		1600	
B	760 (739)		
C		2400	
D		3200	

INTENTIONALLY LEFT BLANK



RJTT / TOKYO INTL

HLDG PATTERN



CHANGE : SNOKE established

RJTT / TOKYO INTL

RNAV HLDG PATTERN

Note 1) DME/DME/IRU or GNSS required. 2) RADAR service required.		RNAV 1
1. Outbound Time / Distance 2. Speed → See Tabular Description.		
ARLON MHA 4000	BACON MHA 4000	
COACH MHA 4000	CREAM MHA 4000	
DREAD MHA 5000	MESSE MHA 6000	
SCREW MHA 4000	STING MHA 4000	
NUMAN MHA 4000	OSHIMA(XAC) MHA 5000	
NEURO MHA 4000		

CHANGE : ACORN abolished. ANZAC established.

RJTT / TOKYO INTL

RNAV HLDG PATTERN

Path	Waypoint Identifier	Inbound Course °M(T)	Magnetic Variation	Outbound Time (MIN)	Outbound Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	AKSEL	039 (031.2)	-7.5	1.0(-14000) 1.5(+14001)	—	R	5000	—	-230(-14000) -240(+14001)	RNAV1
Hold	ANZAC	068 (060.8)	-7.5	1.0(-14000) 1.5(+14001)	—	L	5000	—	-230(-14000) -240(+14001)	RNAV1
Hold	ARLON	009 (001.6)	-7.5	1.0(-14000) 1.5(+14001)	—	L	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	AVEEY	314 (306.1)	-7.5	1.0(-14000) 1.5(+14001)	—	R	5000	—	-230(-14000) -240(+14001)	RNAV1
Hold	BACON	003 (355.2)	-7.5	1.0(-14000) 1.5(+14001)	—	L	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	CIVIC	345 (337.7)	-7.5	1.0(-14000) 1.5(+14001)	—	R	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	COACH	185 (177.8)	-7.5	1.0(-14000) 1.5(+14001)	—	R	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	COLOR	197 (189.1)	-7.5	1.0(-14000) 1.5(+14001)	—	R	8000	—	-230(-14000) -240(+14001)	RNAV1
Hold	CREAM	291 (283.1)	-7.5	1.0(-14000) 1.5(+14001)	—	R	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	DENNY	167 (159.9)	-7.5	1.0(-14000) 1.5(+14001)	—	R	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	DREAD	191 (183.1)	-7.5	1.0(-14000) 1.5(+14001)	—	R	5000	—	-230(-14000) -240(+14001)	RNAV1
Hold	GODIN	197 (189.2)	-7.5	1.0(-14000) 1.5(+14001)	—	R	8000	—	-230(-14000) -240(+14001)	RNAV1
Hold	KAIHO	353 (345.5)	-7.5	1.0(-14000) 1.5(+14001)	—	R	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	MESSE	246 (238.8)	-7.5	1.0(-14000) 1.5(+14001)	—	L	6000	—	-230(-14000) -240(+14001)	RNAV1
Hold	NEURO	290 (282.9)	-7.5	1.0(-14000) 1.5(+14001)	—	R	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	NOVEL	264 (256.4)	-7.5	1.0(-14000) 1.5(+14001)	—	L	5000	—	-230(-14000) -240(+14001)	RNAV1
Hold	NUMAN	360 (352.5)	-7.5	1.0(-14000) 1.5(+14001)	—	L	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	NYLON	357 (350.0)	-7.5	1.0(-14000) 1.5(+14001)	—	L	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	POLIX	310 (302.3)	-7.5	1.0(-14000) 1.5(+14001)	—	L	11000	—	-230(-14000) -240(+14001)	RNAV1
Hold	SCREW	203 (195.2)	-7.5	1.0(-14000) 1.5(+14001)	—	L	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	SHAFT	330 (322.4)	-7.5	1.0(-14000) 1.5(+14001)	—	R	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	SNARE	297 (289.1)	-7.5	1.0(-14000) 1.5(+14001)	—	R	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	SPINE	348 (340.6)	-7.5	1.0(-14000) 1.5(+14001)	—	L	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	STING	067 (059.6)	-7.5	1.0(-14000) 1.5(+14001)	—	R	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	WEDGE	300 (292.4)	-7.5	1.0(-14000) 1.5(+14001)	—	L	4000	—	-230(-14000) -240(+14001)	RNAV1
Hold	XAC	098 (090.3)	-7.5	1.0(-14000) 1.5(+14001)	—	R	5000	—	-230(-14000) -240(+14001)	RNAV1

CHANGE : ACORN abolished. ANZAC established.

RJTT / TOKYO INTL

RNAV HLDG PATTERN


Waypoint Coordinates

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
AKSEL	344039.5N / 1395126.9E	MESSE	351100.8N / 1402214.7E
ANZAC	345028.8N / 1394146.7E	NEURO	355727.6N / 1395441.3E
ARLON	351525.3N / 1395859.8E	NOVEL	362106.9N / 1400004.9E
AVEEY	344155.9N / 1402158.0E	NUMAN	354714.4N / 1401204.9E
BACON	353155.0N / 1401215.1E	NYLON	354018.5N / 1400919.9E
CIVIC	350840.6N / 1402552.1E	POLIX	361237.1N / 1402622.5E
COACH	353736.0N / 1401231.5E	SCREW	360301.2N / 1395400.4E
COLOR	360116.3N / 1401219.8E	SHAFT	352227.4N / 1401313.3E
CREAM	351743.4N / 1400612.4E	SNARE	354731.1N / 1395238.1E
DENNY	354828.8N / 1400556.4E	SPINE	354213.5N / 1401125.8E
DREAD	360359.2N / 1395856.9E	STING	345157.9N / 1401453.4E
GODIN	362425.3N / 1401655.9E	WEDGE	350900.4N / 1395846.5E
KAIHO	351857.8N / 1394642.4E	XAC	344244.1N / 1392450.5E

CHANGE : ACORN abolished. ANZAC established.

RJTT / TOKYO INTL

Visual REP




※図中に標高を示す数字がある場合、単位はメートル(m)である。The unit of measurement used to express elevation is meter(m).


CHANGE : Map updated. BRG/DIST from ARP.

Call sign	BRG / DIST from ARP	Remarks
渋谷 Shibuya	328°T / 7.4NM	JR駅 JR Station
品川 Shinagawa	336°T / 5.0NM	JR駅 JR Station
洗足 Senzoku	303°T / 5.3NM	池 Pond
丸子橋 Marukobashi	289°T / 5.8NM	橋 Bridge
多摩川大橋 Tamagawaohashi	272°T / 4.2NM	橋 Bridge
新川崎 Shinkawasaki	269°T / 5.4NM	JR駅 JR Station
大師橋 Daishibashi	253°T / 2.0NM	橋 Bridge
六郷橋 Rokugobashi	255°T / 3.7NM	橋 Bridge
扇島 Ogijima	221°T / 5.9NM	扇島の西端 West edge of the island
ベイブリッジ Bay Bridge	221°T / 7.9NM	(首都高速湾岸線)橋 Bridge

RJTT / TOKYO INTL

Minimum Vectoring Altitude CHART



**PAPI:**

RWY16L-3.0°, MEHT 19.9m (65ft)

412m inside from THR.

RWY16L-3.25°, MEHT 19.9m(65ft)

378m inside from THR.

RWY34R-3.0°, MEHT 20.0m (66ft)

416m inside from THR.

RWY16R-3.0°, MEHT 19.9m (65ft)

432m inside from THR.

RWY16R-3.25°, MEHT 19.9m(65ft)

397m inside from THR.

RWY34L-3.0°, MEHT 20.0m (66ft)

449m inside from THR.

RWY04-3.0°, MEHT 18.5m (61ft)

369m inside from THR.

RWY22-3.0°, MEHT 19.5m (63ft)

438m inside from THR.

RWY23-3.0°, MEHT 20.0m (66ft)

452m inside from THR.

RWY Grooving :

RWY16L/34R 3360m X 40m

RWY16R/34L 3000m X 40m

RWY04/22 2500m X 40m

RWY05/23 2500m X 40m

Attachment-1

Local flying restriction of Tokyo INTL AP

Unless otherwise authorized by ATC.

Aircraft other than the arriving at and/or departing from Tokyo International Airport are required not to fly over the Kawasaki Petrochemical Complex area, and even in case of flying over the area, not to fly below an altitude of 3,000 feet.

